

1 (https://www.interviewcake.com/question/javascript/inflight-entertainment)

You've built an in-flight entertainment system with on-demand movie streaming.

Users on longer flights like to start a second movie right when their first one ends, but they complain that the plane usually lands before they can see the ending. **So you're building a feature for choosing two movies whose total runtimes will equal the exact flight length.**

Write a function that takes an integer `flightLength` (in minutes) and an array of integers `movieLengths` (in minutes) and returns a boolean indicating whether there are two numbers in `movieLengths` whose sum equals `flightLength`.

When building your function:

- Assume your users will watch *exactly* two movies
- Don't make your users watch the same movie twice
- Optimize for runtime over memory

Gotchas

We can do this in $O(n)$ time, where n is the length of `movieLengths`.

Remember: your users shouldn't watch the same movie twice. **Are you sure your method won't give a false positive if the array has one element that is half `flightLength`?**

Breakdown

How would we solve this by hand? We know our two movie lengths need to sum to `flightLength`. So for a given `firstMovieLength`, we need a `secondMovieLength` that equals `flightLength - firstMovieLength`.

To do this by hand we might go through `movieLengths` from beginning to end, treating each item as `firstMovieLength`, and for each of those check if there's a `secondMovieLength` equal to `flightLength - firstMovieLength`.

How would we implement this in code? We could nest two loops (the outer choosing `firstMovieLength`, the inner choosing `secondMovieLength`). That'd give us a runtime of $O(n^2)$. We can do better.

To bring our runtime down we'll probably need to replace that inner loop (the one that looks for a matching `secondMovieLength`) with something faster.

We could sort the `movieLengths` first—then we could use binary search to find `secondMovieLength` in $O(\lg n)$ time instead of $O(n)$ time. But sorting would cost $O(n \lg n)$, and we can do even better than that.

Could we check for the existence of our `secondMovieLength` in constant time?

What data structure gives us convenient constant-time lookups?

A set!

So we could throw all of our `movieLengths` into a set first, in $O(n)$ time. Then we could loop through our possible `firstMovieLengths` and replace our inner loop with a simple check in our set. This'll give us $O(n)$ runtime overall!

Of course, we need to add some logic to make sure we're not showing users the same movie twice...

But first, we can tighten this up a bit. Instead of two sequential loops, can we do it all in one loop? (Done carefully, this will give us protection from showing the same movie twice as well.)

Solution

We make one pass through `movieLengths`, treating each item as the `firstMovieLength`. At each iteration, we:

1. See if there's a `matchingSecondMovieLength` we've seen already (stored in our `movieLengthsSeen` set) that is equal to `flightLength - firstMovieLength`. If there is, we short-circuit and return `true`.
2. Keep our `movieLengthsSeen` set up to date by throwing in the current `firstMovieLength`.

```
function canTwoMoviesFillFlight(movieLengths, flightLength) {  
  
    // movie lengths we've seen so far  
    var movieLengthsSeen = new Set();  
  
    for (var i = 0; i < movieLengths.length; i++) {  
        var firstMovieLength = movieLengths[i];  
  
        var matchingSecondMovieLength = flightLength - firstMovieLength;  
        if (movieLengthsSeen.has(matchingSecondMovieLength)) {  
            return true;  
        }  
  
        movieLengthsSeen.add(firstMovieLength);  
    }  
  
    // we never found a match, so return false  
    return false;  
}
```

We know users won't watch the same movie twice because we check `movieLengthsSeen` for `matchingSecondMovieLength` *before* we've put `firstMovieLength` in it!

Complexity

$O(n)$ time, and $O(n)$ space. Note while optimizing runtime we added a bit of space cost.

Bonus

1. What if we wanted the movie lengths to sum to something close to the flight length (say, within 20 minutes)?
2. What if we wanted to fill the flight length as nicely as possible with any number of movies (not just 2)?
3. What if we knew that `movieLengths` was *sorted*? Could we save some space and/or time?

Did you get it right?



Yes, I'm expert on this



Not quite, review later

Like this problem? Pass it on!

Share



Tweet

(https://www.facebook.com/sharer/sharer.php?u=https://www.interviewcake.com/question/javascript/inflight-entertainment)

(https://www.facebook.com/sharer/sharer.php?u=https://www.interviewcake.com/question/javascript/inflight-entertainment)

Type code!

Yo, follow along!

(https://www.facebook.com/interviewcake)

Subscribe to our weekly question email list » (/free-weekly-coding-interview-problem-newsletter)

Programming interview questions by company:

- Google interview questions (/google-interview-questions)
- Facebook interview questions (/facebook-interview-questions)
- Amazon interview questions (/amazon-interview-questions)

Programming interview questions by language:

- Java interview questions (/java-interview-questions)
- Python interview questions (/python-interview-questions)
- Ruby interview questions (/ruby-interview-questions)
- JavaScript interview questions (/javascript-interview-questions)
- **NEW:** Testing and QA interview questions (/testing-and-qa-interview-questions)
- **NEW:** SQL interview questions (/sql-interview-questions)

Copyright © 2016 Cake Labs, Inc. All rights reserved.
 228 Park Ave S #82632, New York, NY US 10003 (804) 876-2253
[Privacy \(/privacy-policy\)](#) | [Terms \(/terms-and-conditions\)](#)