

## AI ASSISTED CODING

NAME : N.JyoshnaSri

HALL.NO:2403A52106

### LAB ASSIGNMENT – 6.4:

#### TASK – 1:

Start a Python class named Student with attributes name, roll\_number, and marks. Prompt GitHub Copilot to complete methods for displaying details and checking if marks are above average

#prompt used here:

write a python program to create a class named student with attributes name of stud,roll\_number and marks

# Code screenshots:

colab.research.google.com/drive/1s-K3HJuTx\_Wwo3oCmk89V2ozLZwaKm0#scrollTo=88bf8161

```
class student:
    def __init__(self, name_of_stud, roll_number, marks):
        self.name_of_stud = name_of_stud
        self.roll_number = roll_number
        self.marks = marks

    def display_student_info(self):
        print(f"Student Name: {self.name_of_stud}")
        print(f"Roll Number: {self.roll_number}")
        print(f"Marks: {self.marks}")

# Example usage of the student class
# Create a student object
student1 = student("Alice", "A101", 85)

# Display student information
student1.display_student_info()
```

Student Name: Alice  
Roll Number: A101  
Marks: 85

give me code explanation

Sure! Here is an explanation of the code you have in your notebook:

The first code cell is empty.

The second code cell defines a Python class called `student`.

- `class student`: This line declares a new class named `student`.
- `def __init__(self, name_of_stud, roll_number, marks)`: This is the constructor method of the class. It's called when you create a new `student` object. It initializes the attributes of the object:
  - `self.name_of_stud`: Stores the name of the student.
  - `self.roll_number`: Stores the student's roll number.
  - `self.marks`: Stores the student's marks.
- `def display_student_info(self)`: This is another method of the class. It's used to print the student's information in a formatted way.
- `student1 = student("Alice", "A101", 85)`: This line creates an instance (an object) of the `student` class. It passes "Alice", "A101", and 85 as arguments to the constructor, which sets the `name_of_stud`, `roll_number`, and `marks` attributes for this specific student object.
- `student1.display_student_info()`: This line calls the `display_student_info` method on the `student1` object, which prints the information for "Alice".

The output shows the information for `student1` as printed by the `display_student_info` method.

What can I help you build?

Gemini can make mistakes so double-check it and use code with caution. [Learn more](#)

colab.research.google.com/drive/106C5gzTciaUp7DWAeMGBuUq6PKGt9YLU#scrollTo=ane0aec

```
class Student:
    def __init__(self, name_of_stud, roll_number, marks):
        self.name_of_stud = name_of_stud
        self.roll_number = roll_number
        self.marks = marks

    def display_details(self):
        print(f"Student Name: {self.name_of_stud}")
        print(f"Roll Number: {self.roll_number}")
        print(f"Marks: {self.marks}")

    def is_passed(self):
        return self.marks >= 40

students = []
num_students = int(input("Enter the number of students: "))

for i in range(num_students):
    print(f"\nEnter details for student {i + 1}:")
    name = input("Enter student name: ")
    roll_number = input("Enter roll number: ")
    marks = int(input("Enter marks: "))
    student = Student(name, roll_number, marks)
    students.append(student)

print("\n--- Student Details ---")
for student in students:
```

Additional methods could be added to the `Student` class, such as calculating the grade based on marks or comparing students.

Please explain this code:

```
<> class Student:
```

This code defines a `Student` class and then uses it to collect, store, and display information for multiple students.

Here's a breakdown:

- `class Student`: This defines a blueprint for creating `Student` objects.
  - `__init__(self, name_of_stud, roll_number, marks)`: This is the constructor method. It's called when you create a new `Student` object. It initializes the object's attributes: `name_of_stud`, `roll_number`, and `marks`.
  - `display_details(self)`: This method prints the student's name, roll number, and marks.
  - `is_passed(self)`: This method checks if the student's `marks` are 40 or greater and returns `True` if they are, and `False` otherwise.
- `students = []`: An empty list called `students` is created to store

What can I help you build?

Gemini can make mistakes, so double-check it and use code with caution. [Learn more](#)

2403e52137-erg/AI-Coding x Untitled11.ipynb - Colab

colab.research.google.com/drive/106C5gzTGiaUp7DWAeMGbeUq8PKGT9YLU#scrollTo=a2ee0aec

Untitled11.ipynb

File Edit View Insert Runtime Tools Help

Q Commands + Code + Text ▶ Run all

```
student = Student(name, roll_number, marks)
students.append(student)

print("\n--- Student Details ---")
for student in students:
    student.display_details()
    if student.is_passed():
        print("Status: Passed")
    else:
        print("Status: Failed")
    print("-" * 20)
```

Enter the number of students: 5

Entering details for student 1:  
Enter student name: nandhu  
Enter roll number: 2086  
Enter marks: 89

Entering details for student 2:  
Enter student name: bhaviha  
Enter roll number: 2099  
Enter marks: 92

Entering details for student 3:  
Enter student name: akshitha  
Enter roll number: 2137  
Enter marks: 45

Entering details for student 4:  
Enter student name: jyoshna  
Enter roll number: 2106  
Enter marks: 55

Gemini

- `is_passed(self)`: This method checks if the student's marks are 40 or greater and returns `True` if they are, and `False` otherwise.
- `students = []`: An empty list called `students` is created to store the `Student` objects.
- `num_students = int(input("Enter the number of students: "))`: The program prompts the user to enter the number of students and stores the input as an integer in the `num_students` variable.
- `for i in range(num_students): ...`: This loop runs `num_students` times to get details for each student.
  - Inside the loop, it prompts the user for the student's name, roll number, and marks.
  - `student = Student(name, roll_number, marks)`: A new `Student` object is created with the entered details.
  - `students.append(student)`: The newly created `Student` object is added to the `students` list.
- `print("\n--- Student Details ---")`: This prints a header before displaying the student details.
- `for student in students: ...`: This loop iterates through each `Student` object in the `students` list.

What can I help you?

Gemini can make mistakes, so double-check it and use code with caution. [Learn more](#)

Variables Terminal

15:45 Python 3

29°C Mostly cloudy

Quick search

ENG IN 01-09-2025

2403e52137-erg/AI-Coding x Untitled11.ipynb - Colab

colab.research.google.com/drive/106C5gzTGiaUp7DWAeMGbeUq8PKGT9YLU#scrollTo=a2ee0aec

Untitled11.ipynb

File Edit View Insert Runtime Tools Help

Q Commands + Code + Text ▶ Run all

```
Enter details for student 4:  
Enter student name: jyoshna  
Enter roll number: 2106  
Enter marks: 55
```

```
Enter details for student 5:  
Enter student name: sreeja  
Enter roll number: 2103  
Enter marks: 67
```

```
--- Student Details ---  
Student Name: nandhu  
Roll Number: 2086  
Marks: 89  
Status: Passed  
-----  
Student Name: bhaviha  
Roll Number: 2099  
Marks: 92  
Status: Passed  
-----  
Student Name: akshitha  
Roll Number: 2137  
Marks: 45  
Status: Passed  
-----  
Student Name: jyoshna  
Roll Number: 2106  
Marks: 55  
Status: Passed  
-----  
Student Name: sreeja  
Roll Number: 2103  
Marks: 67
```

Gemini

- `num_students` times to get details for each student.
  - Inside the loop, it prompts the user for the student's name, roll number, and marks.
  - `student = Student(name, roll_number, marks)`: A new `Student` object is created with the entered details.
  - `students.append(student)`: The newly created `Student` object is added to the `students` list.
- `print("\n--- Student Details ---")`: This prints a header before displaying the student details.
- `for student in students: ...`: This loop iterates through each `Student` object in the `students` list.
  - `student.display_details()`: Calls the display details method for the current student to print their information.
  - `if student.is_passed(): ... else: ...`: This checks if the student passed using the `is_passed` method and prints "Status: Passed" or "Status: Failed" accordingly.
  - `print("-" * 20)`: Prints a separator line after each student's details.

Bad response

What can I help you?

Gemini can make mistakes, so double-check it and use code with caution. [Learn more](#)


Variables Terminal

15:45 Python 3

Breaking news PM Modi at SCO...

Quick search

ENG IN 01-09-2025



## CODE EXPLANATION:

✓ RAM  
Disk

⌵

⌴

Gemini X

J

give me code explanation

✦

Sure! Here is an explanation of the code you have in your notebook:

The first code cell is empty.

The second code cell defines a Python class called `student`.

- `class student:` : This line declares a new class named `student`.
- `def __init__(self, name_of_stud, roll_number, marks):` : This is the constructor method of the class. It's called when you create a new `student` object. It initializes the attributes of the object:
  - `self.name_of_stud` : Stores the name of the student.
  - `self.roll_number` : Stores the student's roll number.
  - `self.marks` : Stores the student's marks.
- `def display_student_info(self):` : This is another method of the class. It's used to print the student's information in a formatted way.
- `student1 = student("Alice", "A101", 85)` : This line creates an instance (an object) of the `student` class. It passes "Alice", "A101", and 85 as arguments to the constructor, which sets the `name_of_stud`, `roll_number`, and `marks` attributes for this specific student object.
- `student1.display_student_info()` : This line calls the `display_student_info` method on the `student1` object, which prints the information for "Alice".

The output shows the information for `student1` as printed by the `display_student_info` method.

👍

🗨

✦

What can I help you build?

⊕ ▶

Gemini can make mistakes so double-check it and use code with caution. [Learn more](#)

✓ 3:20 PM Python 3

ENG  
IN

15:22  
01-09-2025

## TASK-2:

- Write the first two lines of a for loop to iterate through a list of numbers. Use a comment prompt to let Copilot suggest how to calculate and print the square of even numbers only.

# CODE OUTPUT SCREENSHOTS:

The screenshot displays a Google Colab notebook interface. The main code cell contains the following Python code:

```
[2] # Create a list
numbers = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]

# Iterate through the list and calculate the square of even numbers
squared_even_numbers = []
for number in numbers:
    # This is the first line inside the loop (part of the condition)
    if number % 2 == 0:
        # This is the second line inside the loop (calculation and append)
        squared_even_numbers.append(number ** 2)

# Print the results
print("Original list:", numbers)
print("Squared even numbers:", squared_even_numbers)
```

The output of the code is:

```
Original list: [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
Squared even numbers: [4, 16, 36, 64, 100]
```

On the right side, the Gemini AI interface shows a prompt: "Of course! Let's break down the code in the last cell:" followed by a detailed explanation of the code logic, including comments and line numbers. The explanation covers the list creation, the loop structure, the conditional check for even numbers, and the final print statements.

## #prompt used :

Write a python program to create a list and write first 2 lines in loop and calculate the square of even numbers only .

## Code explanation:

J explain the above code

✦ Of course! Let's break down the code in the last cell:

```
# Create a list
numbers = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]

# Iterate through the list and calculate the square of even numbers
squared_even_numbers = []
for number in numbers:
    # This is the first line inside the loop (part of the condition)
    if number % 2 == 0:
        # This is the second line inside the loop (calculation and append)
        squared_even_numbers.append(number ** 2)

# Print the results
print("Original list:", numbers)
print("Squared even numbers:", squared_even_numbers)
```

1. `numbers = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]`: This line creates a list named `numbers` and initializes it with integers from 1 to 10.
2. `squared_even_numbers = []`: This line creates an empty list called `squared_even_numbers`. This list will store the squared values of the even numbers found in the `numbers` list.
3. `for number in numbers:`: This is a `for` loop that iterates through each element in the `numbers` list. In each iteration, the current element is assigned to the variable `number`.
4. `if number % 2 == 0:`: This is an `if` statement inside the loop. It checks if the current `number` is even. The modulo operator (`%`) returns the remainder of a division. If a number divided by 2 has a remainder of 0, it's an even number.
5. `squared_even_numbers.append(number ** 2)`: This line is executed only if the `if`

✦ What can I help you build?

Gemini can make mistakes so double-check it and use code with caution. [Learn more](#)

✓ 3:59 PM Python 3



ENG  
IN



16:02  
01-09-2025

5. `squared_even_numbers.append(number ** 2)`: This line is executed only if the `if` condition (the number is even) is true.
  - `number ** 2` calculates the square of the current even `number`.
  - `.append()` is a list method that adds the calculated square to the `squared_even_numbers` list.
6. `print("Original list:", numbers)`: This line prints the original `numbers` list.
7. `print("Squared even numbers:", squared_even_numbers)`: This line prints the `squared_even_numbers` list, which now contains the squares of all the even numbers from the original list.

In summary, the code iterates through the `numbers` list, checks if each number is even, and if it is, calculates its square and adds it to the `squared_even_numbers` list. Finally, it prints both the original and the new list.



◆ What can I help you build?



### Task-3:

- Create a class called `BankAccount` with attributes `account_holder` and `balance`. Use Copilot to complete methods for `deposit()`, `withdraw()`, and check for insufficient balance.

#prompt used here:

**Write a python program to create a class named bank account with attributes like `account_holder`, `balance`.**

**Write a python program to check `deposit`, `withdraw` and check insufficient balance.**



# Code screenshots:

```
class BankAccount:
    def __init__(self, account_holder, initial_balance=0):
        self.account_holder = account_holder
        self.balance = initial_balance

    def deposit(self, amount):
        if amount > 0:
            self.balance += amount
            print(f"Deposited: ${amount}. New balance: ${self.balance}")
        else:
            print("Deposit amount must be positive.")



    def withdraw(self, amount):
        if amount > 0:
            if self.balance >= amount:
                self.balance -= amount
                print(f"Withdrew: ${amount}. New balance: ${self.balance}")
            else:
                print("Insufficient balance.")
        else:
            print("Withdrawal amount must be positive.")


    def check_balance(self):
        print(f"Account balance for {self.account_holder}: ${self.balance}")

# Example usage:
account1 = BankAccount("Alice Smith", 1000)
account1.check_balance()
account1.deposit(500)
account1.withdraw(200)
account1.withdraw(1500) # This should result in an insufficient balance message
account1.check_balance()
```




```
Account balance for Alice Smith: $1000
Deposited: $500. New balance: $1500
Withdrew: $200. New balance: $1300
Insufficient balance.
Account balance for Alice Smith: $1300
```

## Code explanation:


✓ RAM  Disk 








Gemini X 

- `class BankAccount:` : This line defines a new class named `BankAccount`. This is a blueprint for creating bank account objects.
- `def __init__(self, account_holder, initial_balance=0):` : This is the constructor method. It's automatically called when you create a new `BankAccount` object.
  - `self` : Refers to the instance of the class being created.
  - `account_holder` : This parameter takes the name of the account holder.
  - `initial_balance=0` : This parameter takes the initial balance for the account. It has a default value of 0 if no initial balance is provided.
  - `self.account_holder = account_holder` and `self.balance = initial_balance` : These lines initialize the `account_holder` and `balance` attributes for the new object.
- `def deposit(self, amount):` : This method handles depositing money into the account.
  - `if amount > 0:` : It checks if the deposit amount is positive.
  - `self.balance += amount` : If the amount is positive, it's added to the `balance`.
  - `print(...)` : It prints a confirmation message with the deposited amount and the new balance.
  - `else:` : If the amount is not positive, it prints an error message.
- `def withdraw(self, amount):` : This method handles withdrawing money from the account.
  - `if amount > 0:` : It checks if the withdrawal amount is positive.
  - `if self.balance >= amount:` : If the amount is positive, it then checks if there are sufficient funds in the account.
  - `self.balance -= amount` : If there are sufficient funds, the amount is subtracted from the `balance`.
  - `print(...)` : It prints a confirmation message with the withdrawn amount and the new balance.
  - `else:` : If there are insufficient funds, it prints an "Insufficient balance" message.

 What can I help you build?  

Gemini can make mistakes so double-check it and use code with caution. [Learn more](#)

✓ 4:10 PM  Python 3

    ENG IN    16:15  
01-09-2025

Disk

Gemini X

- `if amount > 0:` : It checks if the withdrawal amount is positive.
- `if self.balance >= amount:` : If the amount is positive, it then checks if there are sufficient funds in the account.
- `self.balance -= amount` : If there are sufficient funds, the amount is subtracted from the `balance`.
- `print(...)` : It prints a confirmation message with the withdrawn amount and the new balance.
- `else:` : If there are insufficient funds, it prints an "Insufficient balance" message.
- The outer `else:` handles cases where the withdrawal amount is not positive.

5. `def check_balance(self):` : This method simply prints the current balance for the account holder.

6. **Example Usage:** The lines outside the class demonstrate how to use the `BankAccount` class:

- `account1 = BankAccount("Alice Smith", 1000)` : Creates a new `BankAccount` object named `account1` for "Alice Smith" with an initial balance of 1000.
- `account1.check_balance()` : Calls the `check_balance` method on `account1`.
- `account1.deposit(500)` : Calls the `deposit` method to add 500 to the balance.
- `account1.withdraw(200)` : Calls the `withdraw` method to subtract 200 from the balance.
- `account1.withdraw(1500)` : Calls the `withdraw` method to try and subtract 1500, which will trigger the "Insufficient balance" message because the current balance is 1300.
- `account1.check_balance()` : Calls `check_balance` again to show the final balance.

This program provides a basic simulation of a bank account using object-oriented programming in Python.

What can I help you build?

## Task-4:

- Define a list of student dictionaries with keys name and score. Ask Copilot to write a while loop to print the names of students who scored more than 75

## #PROMPT USED:

Define a list of student dictionaries with keys name and score and to write a while loop to print the names of students who scored more than 75.

## CODE SCREENSHOTS:

The screenshot displays a Google Colab notebook environment. The main code cell contains a list of student dictionaries and a while loop to print names of students with scores above 75. The output shows the names Alice, Charlie, and Eve. To the right, the Gemini AI chat interface is open, showing a conversation where the user asks for an explanation of the code, and Gemini provides a detailed, step-by-step breakdown of the code's logic.

```
[1] students = [
    {'name': 'Alice', 'score': 80},
    {'name': 'Bob', 'score': 70},
    {'name': 'Charlie', 'score': 90},
    {'name': 'David', 'score': 65},
    {'name': 'Eve', 'score': 85}
]

i = 0
print("Students who scored more than 75:")
while i < len(students):
    if students[i]['score'] > 75:
        print(students[i]['name'])
    i += 1
```

Students who scored more than 75:  
Alice  
Charlie  
Eve

**Gemini Chat:**

1 Define a list of student dictionaries with keys name and score and to write a while loop to print the names of students who scored more than 75.

✦ Certainly! I'll create a list of student dictionaries and then write a while loop to print the names of students who scored more than 75.

The request has been satisfied. Would you like to explore other ways to achieve the same result, perhaps using a for loop or list comprehension? I could also show you how to store this data in a Pandas DataFrame for more complex analysis.

✦ explain the above code

✦ No problem, I can explain the code.

1. **Defining the data:** The code starts by creating a list of dictionaries called `students`. Each dictionary in the list represents a student and has two key-value pairs: `name` (the student's name) and `score` (the student's score).
2. **Initializing a counter:** A variable `i` is initialized to 0. This variable will be used as a counter to iterate through the `students` list.
3. **Printing a header:** The code prints a message "Students who scored more than 75:" to the console to indicate the output that follows.
4. **Starting a while loop:** A `while` loop is used to iterate through the `students` list. The loop continues as long as the value of `i` is less than the length of the `students` list.
5. **Checking the score:** Inside the loop, for each student (accessed using `students[i]`), the code checks if their `'score'` is greater than 75 using an `if` statement.
6. **Printing the name:** If the student's score is greater than 75, the code prints the student's `'name'`.
7. **Incrementing the counter:** After checking the score (or not, if the score is not greater than 75), the value of `i` is incremented by 1 (`i += 1`). This moves the loop to the next student.

✦ What can I help you build?

Gemini can make mistakes so double-check it and use code with caution. [Learn more](#)

## CODE EXPLANATION:



Gemini X



**J** explain the above code

✦ No problem, I can explain the code.

1. **Defining the data:** The code starts by creating a list of dictionaries called `students`. Each dictionary in the list represents a student and has two key-value pairs: `name` (the student's name) and `score` (the student's score).
2. **Initializing a counter:** A variable `i` is initialized to 0. This variable will be used as a counter to iterate through the `students` list.
3. **Printing a header:** The code prints a message "Students who scored more than 75:" to the console to indicate the output that follows.
4. **Starting a while loop:** A `while` loop is used to iterate through the `students` list. The loop continues as long as the value of `i` is less than the length of the `students` list.
5. **Checking the score:** Inside the loop, for each student (accessed using `students[i]`), the code checks if their `'score'` is greater than 75 using an `if` statement.
6. **Printing the name:** If the student's score is greater than 75, the code prints the student's `'name'`.
7. **Incrementing the counter:** After checking the score (or not, if the score is not greater than 75), the value of `i` is incremented by 1 (`i += 1`). This moves the loop to the next student in the list.

The loop continues until all students in the list have been checked. The output shows the names of the students whose scores were greater than 75.



✦ What can I help you build?



Gemini can make mistakes so double-check it and use code with caution. [Learn more](#)

✓ 9:10 PM Python 3

## **TASK-5:**

- **Begin writing a class ShoppingCart with an empty items list. Prompt Copilot to generate methods to add\_item, remove\_item, and use a loop to calculate the total bill using conditional discounts.**

### **#PROMPT USED:**

**Begin writing a class ShoppingCart with an empty items list to generate methods to add\_item, remove\_item, and use a loop to calculate the total bill using conditional discounts.**

### **CODE SCREENSHOTS:**

colab.research.google.com/drive/1PSrKqmFgloNTEm4t4ty9b3JsP9fB5T#scrollTo=626db598

Untitled5.ipynb

```
class ShoppingCart:
    def __init__(self):
        self.items = []

    def add_item(self, name, price, quantity=1):
        """Adds an item to the shopping cart."""
        for item in self.items:
            if item['name'] == name:
                item['quantity'] += quantity
                print(f"Updated quantity for {name}. New quantity: {item['quantity']}")
                return
        self.items.append({'name': name, 'price': price, 'quantity': quantity})
        print(f"Added {quantity} x {name} to the cart.")

    def remove_item(self, name, quantity=1):
        """Removes an item or a specific quantity of an item from the shopping cart."""
        for item in self.items:
            if item['name'] == name:
                if item['quantity'] > quantity:
                    item['quantity'] -= quantity
                    print(f"Removed {quantity} x {name}. Remaining quantity: {item['quantity']}")
                elif item['quantity'] == quantity:
                    self.items.remove(item)
                    print(f"Removed all {name} from the cart.")
                else:
                    print(f"Cannot remove {quantity} x {name}. Only {item['quantity']} in cart.")
                    return
        print(f"{name} not found in the cart.")

    def calculate_total(self):
        """Calculates the total bill with conditional discounts."""
        total = 0
        for item in self.items:
            item_total = item['price'] * item['quantity']
            # Example conditional discount: 10% off if item quantity is 5 or more
            if item['quantity'] >= 5:
                discount = item_total * 0.10
                item_total -= discount
                print(f"Applied 10% discount on {item['name']}.")
            total += item_total
        return total

    def display_cart(self):
        """Displays the current items in the shopping cart."""
        if not self.items:
            print("Your shopping cart is empty.")
        else:
            print("Shopping Cart:")
            for item in self.items:
                print(f"- {item['name']} (Price: ${item['price']:.2f}, Quantity: {item['quantity']})")
            print(f"Total: ${self.calculate_total():.2f}")
```

Gemini

Sure! I can help you with that. I'll create a `ShoppingCart` class with the requested methods to manage items, remove them, and calculate the total with discounts.

The `ShoppingCart` class has been created with the requested methods. Would you like to:

1. Create an instance of the `ShoppingCart` class and add some items to it?
2. Test the `remove_item` method?
3. See how the `calculate_total` method works with and without discounts?
4. Add more complex discount logic to the `calculate_total` method?

What can I help you build?

Rain warning  
In effect

9:24 PM Python 3

colab.research.google.com/drive/1PSrKqmFgloNTEm4t4ty9b3JsP9fB5T#scrollTo=626db598

Untitled5.ipynb

```
class ShoppingCart:
    def __init__(self):
        self.items = []

    def add_item(self, name, price, quantity=1):
        """Adds an item to the shopping cart."""
        for item in self.items:
            if item['name'] == name:
                item['quantity'] += quantity
                print(f"Updated quantity for {name}. New quantity: {item['quantity']}")
                return
        self.items.append({'name': name, 'price': price, 'quantity': quantity})
        print(f"Added {quantity} x {name} to the cart.")

    def remove_item(self, name, quantity=1):
        """Removes an item or a specific quantity of an item from the shopping cart."""
        for item in self.items:
            if item['name'] == name:
                if item['quantity'] > quantity:
                    item['quantity'] -= quantity
                    print(f"Removed {quantity} x {name}. Remaining quantity: {item['quantity']}")
                elif item['quantity'] == quantity:
                    self.items.remove(item)
                    print(f"Removed all {name} from the cart.")
                else:
                    print(f"Cannot remove {quantity} x {name}. Only {item['quantity']} in cart.")
                    return
        print(f"{name} not found in the cart.")

    def calculate_total(self):
        """Calculates the total bill with conditional discounts."""
        total = 0
        for item in self.items:
            item_total = item['price'] * item['quantity']
            # Example conditional discount: 10% off if item quantity is 5 or more
            if item['quantity'] >= 5:
                discount = item_total * 0.10
                item_total -= discount
                print(f"Applied 10% discount on {item['name']}.")
            total += item_total
        return total

    def display_cart(self):
        """Displays the current items in the shopping cart."""
        if not self.items:
            print("Your shopping cart is empty.")
        else:
            print("Shopping Cart:")
            for item in self.items:
                print(f"- {item['name']} (Price: ${item['price']:.2f}, Quantity: {item['quantity']})")
            print(f"Total: ${self.calculate_total():.2f}")
```

Gemini

Sure! I can help you with that. I'll create a `ShoppingCart` class with the requested methods to manage items, remove them, and calculate the total with discounts.

The `ShoppingCart` class has been created with the requested methods. Would you like to:

1. Create an instance of the `ShoppingCart` class and add some items to it?
2. Test the `remove_item` method?
3. See how the `calculate_total` method works with and without discounts?
4. Add more complex discount logic to the `calculate_total` method?

What can I help you build?

Rain warning  
In effect

9:24 PM Python 3

Snipping Tool

Screenshot copied to clipboard  
Automatically saved to screenshots folder.

Markup and share

### CODE EXPLANATION:

Gemini X

**J** GIVE ME EXPLANATION FOR THE ABOVE CODE

★ Certainly! I can explain the `ShoppingCart` class code for you.

This code defines a Python class called `ShoppingCart` that simulates a simple online shopping cart. Here's a breakdown of its components:

1. `__init__(self)`: This is the constructor method. It's called when you create a new `ShoppingCart` object. It initializes an empty list called `self.items` which will store the items added to the cart. Each item in this list will be a dictionary containing the item's name, price, and quantity.
2. `add_item(self, name, price, quantity=1)`: This method allows you to add items to the cart.
  - It takes the `name`, `price`, and optional `quantity` of the item as arguments. The default quantity is 1.
  - It iterates through the existing items in `self.items`.
  - If an item with the same name is already in the cart, it updates the quantity of that item.
  - If the item is not found, it appends a new dictionary representing the item to the `self.items` list.
  - It prints a message indicating whether the item was added or the quantity was updated.
3. `remove_item(self, name, quantity=1)`: This method allows you to remove items or a specific quantity of items from the cart.
  - It takes the `name` and optional `quantity` of the item to remove. The default quantity is 1.
  - It iterates through the items in `self.items`.
  - If the item with the given name is found:
    - If the quantity to remove is less than the current quantity in the cart, it

What can I help you build?

Gemini can make mistakes so double-check it and use code with caution. [Learn more](#)





Disk



Gemini X



- If the quantity to remove is equal to the current quantity, it removes the entire item from the `self.items` list.
  - If the quantity to remove is greater than the current quantity, it prints a message indicating that the quantity cannot be removed.
  - If the item is not found in the cart, it prints a message.
4. `calculate_total(self)`: This method calculates the total cost of all items in the cart, including conditional discounts.
- It initializes a `total` variable to 0.
  - It iterates through each `item` in the `self.items` list.
  - For each item, it calculates the `item_total` by multiplying the `price` and `quantity`.
  - It then checks if the `item['quantity']` is 5 or more. If it is, it applies a 10% discount to the `item_total`.
  - The discounted (or original) `item_total` is added to the overall `total`.
  - Finally, it returns the calculated `total`.
5. `display_cart(self)`: This method prints the current contents of the shopping cart and the total bill.
- It checks if the `self.items` list is empty. If it is, it prints "Your shopping cart is empty."
  - If the cart is not empty, it prints a "Shopping Cart:" header.
  - It then iterates through each item in `self.items` and prints the item's name, price, and quantity.
  - Finally, it calls the `calculate_total()` method and prints the total bill.

This class provides a basic framework for managing a shopping cart with the ability to add and remove items, and calculate a total with a simple discount rule.



What can I help you build?

