

# SQL Server

TEST OF SQL SERVER

JYOT HATHI

## Index

<b>A. Given Reference Table Creation and Data Insertion .....</b>	<b>3</b>
1. Employee Table:.....	3
2. Department Table (To Normalize Employee Table): .....	4
3. Incentive Table:.....	4
<b>B. Execution of Give Queries:.....</b>	<b>5</b>
1. Get First_Name from employee table using alias name “Employee Name” .....	5
2. Get position of 'o' in name 'John' from employee table .....	5
3. Get FIRST_NAME ,Joining year,Joining Month and Joining Date from employee table .....	5
4. Get all employee details from the employee table order by First_Name Ascending and Salary descending.....	6
5. Get employee details from employee table whose employee name are not “John” and “Roy”.....	6
6. Get employee details from employee table whose first name ends with 'n'. .....	6
7. Get employee details from employee table whose first name ends with 'n' and name contains 4 letters.....	7
8. Get employee details from employee table whose Salary less than 800000 .....	7
9. Get employee details from employee table who joined before January 1st 2013 .....	7
10. Get difference between JOINING_DATE and INCENTIVE_DATE from employee and incentives table.....	8
11. Print database date. ....	8
12. Get department,total salary with respect to a department from employee table. ....	8
13. Get department,no of employees in a department,total salary with respect to a department from employee table order by total salary descending .....	9
14. Select no of employees joined with respect to year and month from employee table. ....	9
15. Update incentive table with employee's Incentive_amount as '12000' where employee name is 'John' .....	9
16. Select TOP 2 salary from employee table .....	10
17. Select 2nd Highest salary from employee table .....	10
18. Write. What is the difference between UNION and UNION ALL? .....	10
19. Write a syntax for CREATE Employee Table. ....	10
20. Write a syntax for truncate all data from Employee Table. ....	11
21. Write a syntax for CREATE Procedure to display the Employee details by passing the “Employee Id” in the procedure.....	11
22. Write a syntax for CREATE SQL function, which accept three number as argument and return the highest number.....	11
23. Write a syntax for Update the Employee's salary whose department is “Insurance”..	12

24. State the difference between varchar and nvarchar..... 12
25. Write a query that insert the data into Employee table, data as mentioned. {First name : 'Critiano' , Last name : 'Ronaldo' , Salary : '30000' , Joining Date : '01-FEB-13 12.00.00 AM' , Department : 'Banking' } ..... 13

## A. Given Reference Table Creation and Data Insertion

### 1. Employee Table:

```
/*Creation of Table tblEmployee*/
create table tblEmployee
(
    Employee_Id int identity(1,1) primary key,
    First_Name varchar(50) not null,
    Last_Name varchar(50) not null,
    Salary int not null,
    Joining_Date datetime not null,
    Department_Id int,
    constraint check_Salary_Employee check(Salary >= 0),
    constraint fk_tblDepartment_tblEmployee
        foreign key(Department_Id) references tblDepartment(Deptid)
);
Insert Into tblEmployee
(First_Name,Last_Name,Salary,Joining_Date,Department_Id)
values('John','Abraham',1000000,'01-JAN-13 12:00:00 AM',1);

Insert Into tblEmployee
(First_Name,Last_Name,Salary,Joining_Date,Department_Id)
values('Michael','Clarke',800000,'01-JAN-13 12:00:00 AM',2);

Insert Into tblEmployee
(First_Name,Last_Name,Salary,Joining_Date,Department_Id)
values('Roy','Thomas',700000,'01-FEB-13 12:00:00 AM',1);

Insert Into tblEmployee
(First_Name,Last_Name,Salary,Joining_Date,Department_Id)
values('Tom','Jose',600000,'01-FEB-13 12:00:00 AM',2);

Insert Into tblEmployee
(First_Name,Last_Name,Salary,Joining_Date,Department_Id)
values('Jerry','Pinto',650000,'01-FEB-13 12:00:00 AM',2);

Insert Into tblEmployee
(First_Name,Last_Name,Salary,Joining_Date,Department_Id)
values('Philip','Mathew',750000,'01-JAN-13 12:00:00 AM',3);

Insert Into tblEmployee
(First_Name,Last_Name,Salary,Joining_Date,Department_Id)
values('TestName1','123',650000,'01-JAN-13 12:00:00 AM',3);

Insert Into tblEmployee
(First_Name,Last_Name,Salary,Joining_Date,Department_Id)
values('TestName2','Lname%',600000,'01-FEB-13 12:00:00 AM',2);
```

**2. Department Table (To Normalize Employee Table):**

```
create table tblDepartment
(
    Deptid int identity(1,1) primary key,
    Department varchar(20) not null
)
/*As Initial Data is Available so Inserting data in tblDepartment*/
Insert into tblDepartment values('Banking');
Insert into tblDepartment values('Insurance');
Insert into tblDepartment values('Services');
```

**3. Incentive Table:**

```
create table tblIncentives
(
    Incentive_Id int Identity(1,1) primary key,
    Employee_ref_id int,
    Incentive_date date not null,
    Incentive_amount int not null,
    constraint fk_tblEmployee_tblIncentives
        foreign key(Employee_ref_id) references tblEmployee(Employee_Id),
    constraint check_Incentive_amount_Incentives check(Incentive_amount >= 0),
);
/*As Initial Data is Available so Inserting data in tblIncentives*/
Insert into tblIncentives
(Employee_ref_id, Incentive_date, Incentive_amount)
values(1, '01-FEB-13', 5000);

Insert into tblIncentives
(Employee_ref_id, Incentive_date, Incentive_amount)
values(2, '01-FEB-13', 3000);

Insert into tblIncentives
(Employee_ref_id, Incentive_date, Incentive_amount)
values(3, '01-FEB-13', 4000);

Insert into tblIncentives
(Employee_ref_id, Incentive_date, Incentive_amount)
values(1, '01-JAN-13', 4500);

Insert into tblIncentives
(Employee_ref_id, Incentive_date, Incentive_amount)
values(2, '01-JAN-13', 3500);
```

## B. Execution of Give Queries:

### 1. Get First\_Name from employee table using alias name "Employee Name"

```
/*Query 1: Get First_Name from employee table using alias name "Employee Name" */  
select First_Name as [Employee Name] from tblEmployee;
```

	Employee Name
1	John
2	Michael
3	Roy
4	Tom
5	Jerry
6	Philip
7	TestName1
8	TestName2

### 2. Get position of 'o' in name 'John' from employee table

```
/*Query 2: Get position of 'o' in name 'John' from employee table */  
select CHARINDEX('o',First_Name) as Position from tblEmployee where First_Name='John';
```

	Position
1	2

### 3. Get FIRST\_NAME ,Joining year,Joining Month and Joining Date from employee table

```
/*Query 3: Get FIRST_NAME ,Joining year,Joining Month and Joining Date from employee table */  
select  
First_Name,DATENAME(YEAR,Joining_Date) as [Joining year],  
DATENAME(Month,Joining_Date) as [Joining Month],  
DATENAME(day,Joining_Date) as [Joining Date]  
from tblEmployee;
```

	First_Name	Joining year	Joining Month	Joining Date
1	John	2013	January	1
2	Michael	2013	January	1
3	Roy	2013	February	1
4	Tom	2013	February	1
5	Jerry	2013	February	1
6	Philip	2013	January	1
7	TestName1	2013	January	1
8	TestName2	2013	February	1

#### 4. Get all employee details from the employee table order by First\_Name Ascending and Salary descending.

```
/*Query 4: Get all employee details from the employee table order by First_Name Ascending and Salary descending */
select First_Name,Last_Name,Salary,Convert(varchar,Joining_Date,0)as Joining_Date,Department from
tblEmployee
inner join
tblDepartment on tblDepartment.Deptid=tblEmployee.Department_Id
order by First_Name,Salary DESC
```

	First_Name	Last_Name	Salary	Joining_Date	Department
1	Jerry	Pinto	650000	Feb 1 2013 12:00AM	Insurance
2	John	Abraham	1000000	Jan 1 2013 12:00AM	Banking
3	Michael	Clarke	800000	Jan 1 2013 12:00AM	Insurance
4	Philip	Mathew	750000	Jan 1 2013 12:00AM	Services
5	Roy	Thomas	700000	Feb 1 2013 12:00AM	Banking
6	TestName1	123	650000	Jan 1 2013 12:00AM	Services
7	TestName2	Lname%	600000	Feb 1 2013 12:00AM	Insurance
8	Tom	Jose	600000	Feb 1 2013 12:00AM	Insurance

#### 5. Get employee details from employee table whose employee name are not "John" and "Roy".

```
/*Query 5: Get employee details from employee table whose employee name are not "John" and "Roy" */
select First_Name,Last_Name,Salary,Convert(varchar,Joining_Date,0)as Joining_Date,Department from
tblEmployee
inner join
tblDepartment on tblDepartment.Deptid=tblEmployee.Department_Id
where First_Name NOT IN ('John','Roy');
```

	First_Name	Last_Name	Salary	Joining_Date	Department
1	Michael	Clarke	800000	Jan 1 2013 12:00AM	Insurance
2	Tom	Jose	600000	Feb 1 2013 12:00AM	Insurance
3	Jerry	Pinto	650000	Feb 1 2013 12:00AM	Insurance
4	Philip	Mathew	750000	Jan 1 2013 12:00AM	Services
5	TestName1	123	650000	Jan 1 2013 12:00AM	Services
6	TestName2	Lname%	600000	Feb 1 2013 12:00AM	Insurance

#### 6. Get employee details from employee table whose first name ends with 'n'.

```
/*Query 6: Get employee details from employee table whose first name ends with 'n' */
select First_Name,Last_Name,Salary,Convert(varchar,Joining_Date,0) as Joining_Date,Department from
tblEmployee
inner join
tblDepartment on tblDepartment.Deptid=tblEmployee.Department_Id
where First_Name LIKE '%n';
```

	First_Name	Last_Name	Salary	Joining_Date	Department
1	John	Abraham	1000000	Jan 1 2013 12:00AM	Banking

**7. Get employee details from employee table whose first name ends with 'n' and name contains 4 letters.**

```
/*Query 7: Get employee details from employee table whose first name ends with 'n' and letters.*/
select First_Name,Last_Name,Salary,Convert(varchar,Joining_Date,0) as Joining_Date,Department from
tblEmployee
inner join
tblDepartment on tblDepartment.Deptid=tblEmployee.Department_Id
where First_Name LIKE '__n'
```

	First_Name	Last_Name	Salary	Joining_Date	Department
1	John	Abraham	1000000	Jan 1 2013 12:00AM	Banking

**8. Get employee details from employee table whose Salary less than 800000**

```
/*Query 8: Get employee details from employee table whose Salary less than 800000 */
select First_Name,Last_Name,Salary,Convert(varchar,Joining_Date,0) as Joining_Date,Department from
tblEmployee
inner join
tblDepartment on tblDepartment.Deptid=tblEmployee.Department_Id
where Salary < 800000;
```

	First_Name	Last_Name	Salary	Joining_Date	Department
1	Roy	Thomas	700000	Feb 1 2013 12:00AM	Banking
2	Tom	Jose	600000	Feb 1 2013 12:00AM	Insurance
3	Jerry	Pinto	650000	Feb 1 2013 12:00AM	Insurance
4	Philip	Mathew	750000	Jan 1 2013 12:00AM	Services
5	TestName1	123	650000	Jan 1 2013 12:00AM	Services
6	TestName2	Lname%	600000	Feb 1 2013 12:00AM	Insurance

**9. Get employee details from employee table who joined before January 1st 2013**

```
/*Query 9: Get employee details from employee table who joined before January 1st 2013 */
select First_Name,Last_Name,Salary,Convert(varchar,Joining_Date,0) as Joining_Date,Department from
tblEmployee
inner join
tblDepartment on tblDepartment.Deptid=tblEmployee.Department_Id
where Joining_Date < CAST('01-JAN-13' as datetime);
```

	First_Name	Last_Name	Salary	Joining_Date	Department
--	------------	-----------	--------	--------------	------------



### 10. Get difference between JOINING\_DATE and INCENTIVE\_DATE from employee and incentives table

```
/*Query 10: Get difference between JOINING_DATE and INCENTIVE_DATE from employee and incentives table */
select First_Name+SPACE(1)+Last_Name as Employee_Name,
DATEDIFF(day,Joining_Date,Incentive_date) as [Incentive_Date - Joining_Date (In Days)]
from tblEmployee inner join tblIncentives
on tblEmployee.Employee_Id=tblIncentives.Employee_ref_id
order by Employee_Name,[Incentive_Date - Joining_Date (In Days)]
```

	Employee_Name	Incentive_Date - Joining_Date (In Days)
1	John Abraham	0
2	John Abraham	31
3	Michael Clarke	0
4	Michael Clarke	31
5	Roy Thomas	0

### 11. Print database date.

```
/*Query 11: Print database date. */
print GETDATE();
```

Editor	Messages
	Feb 20 2021 12:07PM
	Completion time: 2021-02-20T12:07:07.8177857+05:30

### 12. Get department,total salary with respect to a department from employee table.

```
/*Query 12: Get department,total salary with respect to a department from employee table. */
select Department,SUM(Salary) as [Total Salary] from
tblEmployee
inner join
tblDepartment on tblDepartment.Deptid=tblEmployee.Department_Id
group by Department
```

	Department	Total Salary
1	Banking	1700000
2	Insurance	2650000
3	Services	1400000

**13. Get department, no of employees in a department, total salary with respect to a department from employee table order by total salary descending .**

```

/*Query 13: Get department, no of employees in a department, total salary with respect to a department
from employee table order by total salary descending . */
select Department, Count(Employee_Id) as [Total Employee], SUM(Salary) as [Total Salary] from
tblEmployee
inner join
tblDepartment on tblDepartment.Deptid=tblEmployee.Department_Id
group by Department
order by [Total Salary] DESC

```

	Department	Total Employee	Total Salary
1	Insurance	4	2650000
2	Banking	2	1700000
3	Services	2	1400000

**14. Select no of employees joined with respect to year and month from employee table.**

```

/*Query 14: Select no of employees joined with respect to year and month from employee table */
select
ISNULL([Joining Year], 'ALL') as [Joining Year],
ISNULL([Joining Month], 'ALL') as [Joining Month] ,
COUNT(Employee_Id) as [Number of Employee] from
(select
Employee_Id,
DATENAME(YEAR, Joining_Date) as [Joining Year],
DATENAME(MONTH, Joining_Date) as [Joining Month]
from tblEmployee
)
as tblYearlyRecuritemnt
group by ROLLUP([Joining Year], [Joining Month])
order by [Joining Year] ASC, [Joining Month] DESC

```

	Joining Year	Joining Month	Number of Employee
1	2013	January	4
2	2013	February	4
3	2013	ALL	8
4	ALL	ALL	8

**15. Update incentive table with employee's Incentive\_amount as '12000' where employee name is 'John'**

```

/*Query 15: 15. Update incentive table with employee's Incentive_amount as '12000'
where employee name is 'John' */
update tblIncentives
set Incentive_amount=12000
where
Employee_ref_id=(select Employee_Id from tblEmployee where First_Name='John')

select First_Name, Incentive_amount from
tblEmployee join tblIncentives on tblIncentives.Employee_ref_id = tblEmployee.Employee_Id

```

	First_Name	Incentive_amount
1	John	12000
2	Michael	3000
3	Roy	4000
4	John	12000
5	Michael	3500

#### 16. Select TOP 2 salary from employee table

```
/*Query 16: Select TOP 2 salary from employee table */
select top 2 Salary from tblEmployee;
```

	Salary
1	1000000
2	800000

#### 17. Select 2nd Highest salary from employee table

```
/*Query 17: Select 2nd Highest salary from employee table */
select top 1 Salary from
(select top 2 Salary from tblEmployee order by Salary DESC) as tbltempEmployee
order by Salary;
```

	Salary
1	800000

#### 18. Write. What is the difference between UNION and UNION ALL?

Ans:

1. Union All Not Remove the Duplication of Records
2. Whereas UNION First Remove Duplication and Then Display Data.

#### 19. Write a syntax for CREATE Employee Table.

Ans:

Create table tblEmployee

(

EmployeeId int Identity(1,1) primary key,

First\_Name varchar(50) not null,

```
Last Name varchar(50) not null,  
Salary int not null,  
Joining_Date datetime not null,  
Department varchar(50),  
Constraint ck_Salary_tblEmployee CHECK(Salary >=0)  
);
```

**Note:** Here We Can Normalize the table By Create Department Table and then have to set reference of that to employee table instead of Department Manually.

**20. Write a syntax for truncate all data from Employee Table.**

Ans.

```
TRUNCATE table tblEmployee;
```

**21. Write a syntax for CREATE Procedure to display the Employee details by passing the “Employee Id” in the procedure.**

Ans.

```
Create proc sp_tblEmployee  
@EmployeeId int =0  
As  
Begin  
    Select * from tblEmployee where [Employee Id] = @ EmployeeId;  
End
```

**22. Write a syntax for CREATE SQL function, which accept three number as argument and return the highest number.**

Ans.

```
Create function fc_HighestNumber(@number1 int, @number2 int  
,@number3 int)  
Returns int  
As  
Begin  
    Declare @highest int;
```

```
    If @number1 > @number2 AND @number1 > @number3
        Set @highest= @number1;
    Else if @number2 > @number3
        Set @highest= @number2;
    Else
        Set @highest= @number3;
    Return @highest;
End
```

**23. Write a syntax for Update the Employee's salary whose department is "Insurance".**

Ans:

1. If Employee Is Not Normalized by creating Separate Department table

```
Update tblEmployee
Set Salary=<new Salary>
Where Department = 'Insurance'
```

2. If Employee Is Normalized by creating Separate Department table

```
Update tblEmployee
Set Salary=<new Salary>
Where DepartmentId = (select DeptId from tblDepartment where
Department = 'Insurance');
```

**24. State the difference between varchar and nvarchar.**

Ans:

1. varchar store data as 8-bit representation so it requires less size to store
2. nvarchar store data as Unicode Format (16-Bit Representation) so It Take More Amount of storage in compare of varchar.

**25. Write a query that insert the data into Employee table, data as mentioned.  
{First name : 'Critiano' , Last name : 'Ronaldo' , Salary : '30000' , Joining Date : '01-FEB-13 12.00.00 AM' , Department : 'Banking' }**

Ans:

1. If Employee Is Not Normalized by creating Separate Department table

Insert into tblEmployee

(First\_Name,Last\_Name,Salary,Joining\_Date,Department)

Values('Critiano', 'Ronaldo', 30000, '01-FEB-13 12:00:00 AM',  
'Banking');

2. If Employee Is Normalized by creating Separate Department table

Insert into tblEmployee

(First\_Name,Last\_Name,Salary,Joining\_Date,Department\_Id)

Values('Critiano', 'Ronaldo', 30000, '01-FEB-13 12:00:00 AM',1);

**Note:** Here 1 is Department id from tblDepartment whose Department Value is Banking