

Terminal Host 1 +

Name: statefulset-controller-token-d5pfl
Namespace: kube-system
Labels: <none>
Annotations: kubernetes.io/service-account.name: statefulset-controller
kubernetes.io/service-account.uid: f952da99-8b1d-11eb-96c2-0242ac1

10067

Type: kubernetes.io/service-account-token

Data
====
ca.crt: 1025 bytes
namespace: 11 bytes
token: eyJhbGciOiJSUzI1NiIsImtpZCI6IiJ9.eyJpc3MiOiJrdWJlcm5ldGVzL3NlcnZpY2VhY2NvdW50Iiwia3ViZXJuZXRlcy5pby9zZXJ2aWNlYWNjb3VudC9uYW1lc3BhY2UiOiJrdWJlLXN5c3RlbSI6Imt1YmVybmV0ZXMuaW8vc2VydmljZWFjY291bnQvc2VjcmV0Lm5hbWUiOiJzdGF0ZWZ1bHNldC1jb250cm9sbGVyLXRva2VuLWQ1cGZsIiwia3ViZXJuZXRlcy5pby9zZXJ2aWNlYWNjb3VudC9zZXJ2aWNlLWVjY291bnQubmFtZSI6InN0YXRLZnVsc2V0LWNvbnRyb2xsZXIiLCJrdWJlcm5ldGVzLmlvL3NlcnZpY2VhY2NvdW50L3NlcnZpY2UtYWNjb3VudC51aWQiOiJmOTUyZGE5OS04YjFkLTExZWItOTZjMi0wMjQvYVVMxMTAwNjIiLCJzdWIiOiJzeXN0ZW06c2Vudml1ZWVjY291bnQ6a3ViZXN0ZW06c3RhZGVmdWx

Terminal Host 2

Your Interactive Bash Terminal. A safe place to learn and execute commands.

```
node01 $ kubeadm join --discovery-token-unsafe-skip-ca-verification --token=102952.1a7dd4cc8d1f4cc5 172.17.0.103:6443
[preflight] Running pre-flight checks
docker ps | grep docker-http-server
[preflight] Reading configuration from the cluster...
[preflight] FYI: You can look at this config file with 'kubectl -n kube-system get cm kubeadm-config -oyaml'
[kubelet-start] Downloading configuration for the kubelet from the "kubelet-config-1.14" ConfigMap in the kube-system namespace
[kubelet-start] Writing kubelet configuration to file "/var/lib/kubelet/config.yaml"
[kubelet-start] Writing kubelet environment file with flags to file "/var/lib/kubelet/kubeadm-flags.env"
[kubelet-start] Activating the kubelet service
[kubelet-start] Waiting for the kubelet to perform the TLS Bootstrap...
[kubelet-check] Initial timeout of 40s passed.

This node has joined the cluster:
* Certificate signing request was sent to apiserver and a response was received.
* The Kubelet was informed of the new secure connection details.

Run 'kubectl get nodes' on the control-plane to see this node join the cluster.
```

+

```
Type:    kubernetes.io/service-account-token
```

[illegible]

```
node01 $ kubeadm join --discovery-token-unsafe-skip-ca-verification --token=102952.1a7dd4cc8d1f4cc5 172.17.0.103:6443
[preflight] Running pre-flight checks
docker ps | grep docker-http-server
[preflight] Reading configuration from the cluster...
[preflight] FYI: You can look at this config file with 'kubectl -n kube-system get cm kubeadm-config -oyaml'
[kubelet-start] Downloading configuration for the kubelet from the "kubelet-config-1.14" ConfigMap in the kube-system namespace
[kubelet-start] Writing kubelet configuration to file "/var/lib/kubelet/config.yaml"
[kubelet-start] Writing kubelet environment file with flags to file "/var/lib/kubelet/kubeadm-flags.env"
[kubelet-start] Activating the kubelet service
[kubelet-start] Waiting for the kubelet to perform the TLS Bootstrap...
[kubelet-check] Initial timeout of 40s passed.
```

```
This node has joined the cluster:
* Certificate signing request was sent to apiserver and a response was received.
* The Kubelet was informed of the new secure connection details.
```

Run 'kubectl get nodes' on the control-plane to see this node join the cluster.

Terminal Host 1 +

```
Name:          ttl-controller-token-wlc9l
Namespace:     kube-system
Labels:        <none>
Annotations:   kubernetes.io/service-account.name: ttl-controller
                kubernetes.io/service-account.uid: fcb834cb-8b1d-11eb-96c2-0242ac1
10067
```

Type: kubernetes.io/service-account-token

Data
=====

```
namespace: 11 bytes
token:      eyJhbGciOiJSUzI1NiIsImtpZCI6IiJ9.eyJpc3MiOiJrdWJlcm5ldGVzL3NlcnZpY2VhY2NvdW50Iiwia3ViZXJuZXRlcy5pby9zZXJ2aWNlYWNjb3VudC9uYW1lc3BhY2UiOiJrdWJlLXN5c3RlbSIsImt1YmVybmV0ZXMuaW8vc2VydmljZWFjY291bnQvc2VjcmV0Lm5hbWUiOiJ0dGwtY29udHJvbGxlcii10b2t1bi13bGM5bCIsImt1YmVybmV0ZXMuaW8vc2VydmljZWFjY291bnQvc2VydmljZS1hY2NvdW50Lm5hbWUiOiJ0dGwtY29udHJvbGxlcii1YmVybmV0ZXMuaW8vc2VydmljZWFjY291bnQvc2VydmljZS1hY2NvdW50LnVpZCI6ImZjYjgzNGNiLThtbWQtMTFlYi05NmMyLTAYNDJhYzExMDA2NyIsInN1YiI6InN5c3RlbTpzZXJ2aWNlYWNjb3VudDprdwJlLXN5c3RlbTp0dGwtY29udHJvbGxlciiJ9.UjuGq2P5Xa2iAY3mILRmGVOFTFXTh4iT2HPvDYaY9hASaGOz.IXt7KhVOaHltfgxOP Tw0hH38O.IKt.x5tObOkat73W
```

Terminal Host 2

Your Interactive Bash Terminal. A safe place to learn and execute commands.

```
node01 $ kubeadm join --discovery-token-unsafe-skip-ca-verification --token=102952.1a7dd4cc8d1f4cc5 172.17.0.103:6443
[preflight] Running pre-flight checks
docker ps | grep docker-http-server
[preflight] Reading configuration from the cluster...
[preflight] FYI: You can look at this config file with 'kubectl -n kube-system get cm kubeadm-config -oyaml'
[kubelet-start] Downloading configuration for the kubelet from the "kubelet-config-1.14" ConfigMap in the kube-system namespace
[kubelet-start] Writing kubelet configuration to file "/var/lib/kubelet/config.yaml"
[kubelet-start] Writing kubelet environment file with flags to file "/var/lib/kubelet/kubeadm-flags.env"
[kubelet-start] Activating the kubelet service
[kubelet-start] Waiting for the kubelet to perform the TLS Bootstrap...
[kubelet-check] Initial timeout of 40s passed.
```

This node has joined the cluster:

- * Certificate signing request was sent to apiserver and a response was received.
- * The Kubelet was informed of the new secure connection details.

Run 'kubectl get nodes' on the control-plane to see this node join the cluster.

Terminal Host 1



Name: bootstrap-token-102952
Namespace: kube-system
Labels: <none>
Annotations: <none>

Type: bootstrap.kubernetes.io/token

Data
=====

auth-extra-groups: 47 bytes
description: 56 bytes
expiration: 20 bytes
token-id: 6 bytes
token-secret: 16 bytes
usage-bootstrap-authentication: 4 bytes
usage-bootstrap-signing: 4 bytes

Name: certificate-controller-token-tncdj
Namespace: kube-system

Terminal Host 2

Your Interactive Bash Terminal. A safe place to learn and execute commands.

```
node01 $ kubeadm join --discovery-token-unsafe-skip-ca-verification --token=102952.1a7dd4cc8d1f4cc5 172.17.0.103:6443
[preflight] Running pre-flight checks
docker ps | grep docker-http-server
[preflight] Reading configuration from the cluster...
[preflight] FYI: You can look at this config file with 'kubectl -n kube-system get cm kubeadm-config -oyaml'
[kubelet-start] Downloading configuration for the kubelet from the "kubelet-config-1.14" ConfigMap in the kube-system namespace
[kubelet-start] Writing kubelet configuration to file "/var/lib/kubelet/config.yaml"
[kubelet-start] Writing kubelet environment file with flags to file "/var/lib/kubelet/kubeadm-flags.env"
[kubelet-start] Activating the kubelet service
[kubelet-start] Waiting for the kubelet to perform the TLS Bootstrap...
[kubelet-check] Initial timeout of 40s passed.

This node has joined the cluster:
* Certificate signing request was sent to apiserver and a response was received.
* The Kubelet was informed of the new secure connection details.

Run 'kubectl get nodes' on the control-plane to see this node join the cluster.
```


Terminal Host 1 + 🔔 ⌵ ⚙

```
ca.crt:      1025 bytes
namespace:   11 bytes

Name:        cronjob-controller-token-4lsgj
Namespace:   kube-system
Labels:      <none>
Annotations: kubernetes.io/service-account.name: cronjob-controller
             kubernetes.io/service-account.uid: fbf78f44-8b1d-11eb-96c2-0242ac1
10067

Type: kubernetes.io/service-account-token
```

Data
====

```
ca.crt:      1025 bytes
namespace:   11 bytes
token:       eyJhbGciOiJSUzI1NiIsImtpZCI6IiJ9.eyJpc3MiOiJrdWJlcm5ldGVzL3N1cnZpY2VhY2NvdW50Iiwia3ViZXJuZXRlcy5pby9zZXJ2aWNlYWNjb3VudC9uYW1lc3BhY2UiOiJrdWJlLXN5c3RlbSIsImt1YmVybmljZWFjY291bnQvc2VjcmV0Lm5hbWUiOiJjc9uam9iLWNvbnRvb2xsZXItZG9rZW4tNGx2Z2oiLCJrdWJlcm5ldGVzLm1vL3N1cnZpY2VhY2NvdW50L3N1cnZpY2UtYWN
```

Terminal Host 2

Your Interactive Bash Terminal. A safe place to learn and execute commands.

```
node01 $ kubeadm join --discovery-token-unsafe-skip-ca-verification --token=102952.1a7dd4cc8d1f4cc5 172.17.0.103:6443
[preflight] Running pre-flight checks
docker ps | grep docker-http-server
[preflight] Reading configuration from the cluster...
[preflight] FYI: You can look at this config file with 'kubectl -n kube-system get cm kubeadm-config -oyaml'
[kubelet-start] Downloading configuration for the kubelet from the "kubelet-config-1.14" ConfigMap in the kube-system namespace
[kubelet-start] Writing kubelet configuration to file "/var/lib/kubelet/config.yaml"
[kubelet-start] Writing kubelet environment file with flags to file "/var/lib/kubelet/kubeadm-flags.env"
[kubelet-start] Activating the kubelet service
[kubelet-start] Waiting for the kubelet to perform the TLS Bootstrap...
[kubelet-check] Initial timeout of 40s passed.

This node has joined the cluster:
* Certificate signing request was sent to apiserver and a response was received.
* The Kubelet was informed of the new secure connection details.

Run 'kubectl get nodes' on the control-plane to see this node join the cluster.
```

Terminal Host 1 +

Name: daemon-set-controller-token-ctmgc
Namespace: kube-system
Labels: <none>
Annotations: kubernetes.io/service-account.name: daemon-set-controller
kubernetes.io/service-account.uid: fc58f598-8b1d-11eb-96c2-0242ac110067

Type: kubernetes.io/service-account-token

Data
====

ca.crt: 1025 bytes
namespace: 11 bytes
token: eyJhbGciOiJSUzI1NiIsImtpZCI6IiJ9.eyJpc3MiOiJrdWJlcm5ldGVzL3N1cnZpY2VhY2NvdW50Iiwia3ViZXJuZXRlcy5pby9zZXJ2aWNlYWNjb3VudC9uYW1lc3BhY2UiOiJrdWJlLXN5c3RlbSI6Imt1YmVybmV0ZXMuaW8vc2VydmljZWFjY291bnQvc2VjcmV0Lm5hbWUiOiJkYWVtb24tc2V0LWNvb3R5b2xsZXItZG9rZW4tY3RtZ2MiLCJrdWJlcm5ldGVzLmlvL3N1cnZpY2VhY2NvdW50L3N1cnZpY2UyYWNjb3VudC5uYW1lIjoizGF1bW9uLXNldC1jb250cm9sbGVyIiwia3ViZXJuZXRlcy5pby9zZXJ2aWNlYWNjb3VudC9zZXJ2aWNlLWFjY291bnQudWlkIjoizmM1OGY1OTgtOGIxZC0xMWVlLTk2YzItMDIOMmFiMTFFwMDY3Iiwic3ViIjoic3lzdGVtOnN1cnZpY2VhY2NvdW50Omt1YmUta3lzdGVtOmRhZW1vbi1zZXQ

Terminal Host 2

Your Interactive Bash Terminal. A safe place to learn and execute commands.

```
node01 $ kubeadm join --discovery-token-unsafe-skip-ca-verification --token=102952.1a7dd4cc8d1f4cc5 172.17.0.103:6443
[preflight] Running pre-flight checks
docker ps | grep docker-http-server
[preflight] Reading configuration from the cluster...
[preflight] FYI: You can look at this config file with 'kubectl -n kube-system get cm kubeadm-config -oyaml'
[kubelet-start] Downloading configuration for the kubelet from the "kubelet-config-1.14" ConfigMap in the kube-system namespace
[kubelet-start] Writing kubelet configuration to file "/var/lib/kubelet/config.yaml"
[kubelet-start] Writing kubelet environment file with flags to file "/var/lib/kubelet/kubeadm-flags.env"
[kubelet-start] Activating the kubelet service
[kubelet-start] Waiting for the kubelet to perform the TLS Bootstrap...
[kubelet-check] Initial timeout of 40s passed.
```

This node has joined the cluster:
* Certificate signing request was sent to apiserver and a response was received.
* The Kubelet was informed of the new secure connection details.

Run 'kubectl get nodes' on the control-plane to see this node join the cluster.

+

```
Type:    kubernetes.io/service-account-token
```

```
ca.crt:      1025 bytes
namespace:   11 bytes
token:       eyJhbGciOiJSUzI1NiIsImtpZCI6IiJ9.eyJpc3MiOiJrdWJlcm5ldGVzL3NlcnZpY2VhY2NvdW50Iiwia3ViZXJuZXRlcy5pby9zZXJ2aWNlYWNjb3VudC9uYW1lc3BhY2UiOiJrdWJlLXN5c3RlbSIsImt1YmVybmV0ZXMuaW8vc2VydmljZSWEjY291bnQvc2VjcmV0Lm5hbWUiOiJkZWZhdWx0LXRva2VhY2V5OWJnIiwia3ViZXJuZXRlcy5pby9zZXJ2aWNlYWNjb3VudC9zZXJ2aWNlLWFfY291bnQubmFtZSI6ImRlZmF1bGhQIiLCJrdWJlcm5ldGVzLmlvL3NlcnZpY2VhY2NvdW50L3NlcnZpY2UyYWNjb3VudC51aWQ1OiJlZmZDA0YjczMS04YjFkLTExZWI0OTZjMi0wMjQyYWNmMTA0NjYjLjCjZdWi0iOiJzeXN0ZW06c2VydmljZSWEjY291bnQ6a3ViZS1zeXN0ZW06ZGVmYXVudCj9.e062J0DM_jC6ONdxZwTu220haV_Bhi5h4V1wnc
```

```
node01 $ kubeadm join --discovery-token-unsafe-skip-ca-verification --token=102952.1a7dd4cc8d1f4cc5 172.17.0.103:6443
[preflight] Running pre-flight checks
docker ps | grep docker-http-server
[preflight] Reading configuration from the cluster...
[preflight] FYI: You can look at this config file with 'kubectl -n kube-system get cm kubeadm-config -oyaml'
[kubelet-start] Downloading configuration for the kubelet from the "kubelet-config-1.14" ConfigMap in the kube-system namespace
[kubelet-start] Writing kubelet configuration to file "/var/lib/kubelet/config.yaml"
[kubelet-start] Writing kubelet environment file with flags to file "/var/lib/kubelet/kubeadm-flags.env"
[kubelet-start] Activating the kubelet service
[kubelet-start] Waiting for the kubelet to perform the TLS Bootstrap...
[kubelet-check] Initial timeout of 40s passed.
```

```
This node has joined the cluster:
```

```
* Certificate signing request was sent to apiserver and a response was received.
* The Kubelet was informed of the new secure connection details.
```

Run 'kubectl get nodes' on the control-plane to see this node join the cluster.

Terminal Host 1



```
Name: deployment-controller-token-glq8l
Namespace: kube-system
Labels: <none>
Annotations: kubernetes.io/service-account.name: deployment-controller
              kubernetes.io/service-account.uid: f92de96e-8b1d-11eb-96c2-0242ac1
10067
```

Type: kubernetes.io/service-account-token

```
Data
====
ca.crt: 1025 bytes
namespace: 11 bytes
token: eyJhbGciOiJSUzI1NiIsImtpZCI6IiJ9.eyJpc3MiOiJrdWJlcm5ldGVzL3N1cnZpY2VhY2NvdW50Iiwia3ViZXJuZXRlcy5pby9zZXJ2aWNlYWNjb3VudC9uYW1lc3BhY2UiOiJrdWJlLXN5c3RlbSIsImt1YmVybmV0ZXMuaW8vc2VydmljZWFjY291bnQvc2VjcmV0Lm5hbWUiOiJkZXBs3ltZW50LWNvb3R5b2xsZXItZG9rZW4tZ2Z2OGwiLCJrdWJlcm5ldGVzLm1vL3N1cnZpY2VhY2NvdW50L3N1cnZpY2UyYWNjb3VudC5uYW1lIjoizGVwbG95bWVudC1jb250cm9sbGVyIiwia3ViZXJuZXRlcy5pby9zZXJ2aWNlYWNjb3VudC9zZXJ2aWNlLWFjY291bnQudWlkIjoizjkyZGU5NmUtOGIxZC0xMWVlLTk2YzItMDIOMmFiMTFFwMDY3Iiwic3ViIjoic3lzdGVtOnN1cnZpY2VhY2NvdW50Omt1YmUta3lzdGVtOmRlcGxveW11bnQ
```

Terminal Host 2

Your Interactive Bash Terminal. A safe place to learn and execute commands.

```
node01 $ kubeadm join --discovery-token-unsafe-skip-ca-verification --token=102952.1a7dd4cc8d1f4cc5 172.17.0.103:6443
[preflight] Running pre-flight checks
docker ps | grep docker-http-server
[preflight] Reading configuration from the cluster...
[preflight] FYI: You can look at this config file with 'kubectl -n kube-system get cm kubeadm-config -oyaml'
[kubelet-start] Downloading configuration for the kubelet from the "kubelet-config-1.14" ConfigMap in the kube-system namespace
[kubelet-start] Writing kubelet configuration to file "/var/lib/kubelet/config.yaml"
[kubelet-start] Writing kubelet environment file with flags to file "/var/lib/kubelet/kubeadm-flags.env"
[kubelet-start] Activating the kubelet service
[kubelet-start] Waiting for the kubelet to perform the TLS Bootstrap...
[kubelet-check] Initial timeout of 40s passed.

This node has joined the cluster:
* Certificate signing request was sent to apiserver and a response was received.
* The Kubelet was informed of the new secure connection details.

Run 'kubectl get nodes' on the control-plane to see this node join the cluster.
```


+

```
Type:    kubernetes.io/service-account-token
```

[illegible]

```
node01 $ kubeadm join --discovery-token-unsafe-skip-ca-verification --token=102952.1a7dd4cc8d1f4cc5 172.17.0.103:6443
[preflight] Running pre-flight checks
docker ps | grep docker-http-server
[preflight] Reading configuration from the cluster...
[preflight] FYI: You can look at this config file with 'kubectl -n kube-system get cm kubeadm-config -oyaml'
[kubelet-start] Downloading configuration for the kubelet from the "kubelet-config-1.14" ConfigMap in the kube-system namespace
[kubelet-start] Writing kubelet configuration to file "/var/lib/kubelet/config.yaml"
[kubelet-start] Writing kubelet environment file with flags to file "/var/lib/kubelet/kubeadm-flags.env"
[kubelet-start] Activating the kubelet service
[kubelet-start] Waiting for the kubelet to perform the TLS Bootstrap...
[kubelet-check] Initial timeout of 40s passed.
```

```
This node has joined the cluster:
```

```
* Certificate signing request was sent to apiserver and a response was received.
* The Kubelet was informed of the new secure connection details.
```

Run 'kubectl get nodes' on the control-plane to see this node join the cluster.

Terminal Host 1

Name: expand-controller-token-9pp2l
Namespace: kube-system
Labels: <none>
Annotations: kubernetes.io/service-account.name: expand-controller
kubernetes.io/service-account.uid: fc476c0d-8b1d-11eb-96c2-0242ac1
10067

Type: kubernetes.io/service-account-token

Data
====

token: eyJhbGciOiJSUzI1NiIsImtpZCI6IiJ9.eyJpc3MiOiJrdWJlcm5ldGVzL3NlcnZpY2VhY2NvdW50Iiwia3ViZXJuZXRlcy5pby9zZXJ2aWNlYWNjb3VudC9uYW1lc3BhY2UiOiJrdWJlLXN5c3RlbSIsImt1YmVybmV0ZXMuaW8vc2VydmljZWFjY291bnQvc2VjcmV0Lm5hbWUiOiJleHBhbmQtY29udHJvbGxlc10b2t1bi05cHAYbCIIsImt1YmVybmV0ZXMuaW8vc2VydmljZWFjY291bnQvc2VydmljZS1hY2NvdW50Lm5hbWUiOiJleHBhbmQtY29udHJvbGxlc1IsImt1YmVybmV0ZXMuaW8vc2VydmljZWFjY291bnQvc2VydmljZS1hY2NvdW50LnVpZCI6ImZjNDc2YzBkLThtbWQtMTFlYi05NmMyLTAYNDJhYzExMDA2NyIsInN1YiI6InN5c3RlbTprZXJ2aWNlYWNjb3VudDprdWJlLXN5c3RlbTpleHBhbmQtY29udHJvbGxlc1J9.k5wXa6FBP6hhIJuNdSHUCbkα3AizRazI 5HF-xFXI,z9X-α10L0mα02TXM1-6Ci-3zYHFCb7mα8wαFn

Terminal Host 2

Your Interactive Bash Terminal. A safe place to learn and execute commands.

```
node01 $ kubeadm join --discovery-token-unsafe-skip-ca-verification --token=102952.1a7dd4cc8d1f4cc5 172.17.0.103:6443
[preflight] Running pre-flight checks
docker ps | grep docker-http-server
[preflight] Reading configuration from the cluster...
[preflight] FYI: You can look at this config file with 'kubectl -n kube-system get cm kubeadm-config -oyaml'
[kubelet-start] Downloading configuration for the kubelet from the "kubelet-config-1.14" ConfigMap in the kube-system namespace
[kubelet-start] Writing kubelet configuration to file "/var/lib/kubelet/config.yaml"
[kubelet-start] Writing kubelet environment file with flags to file "/var/lib/kubelet/kubeadm-flags.env"
[kubelet-start] Activating the kubelet service
[kubelet-start] Waiting for the kubelet to perform the TLS Bootstrap...
[kubelet-check] Initial timeout of 40s passed.

This node has joined the cluster:
* Certificate signing request was sent to apiserer and a response was received.
* The Kubelet was informed of the new secure connection details.

Run 'kubectl get nodes' on the control-plane to see this node join the cluster.
```

Terminal Host 1 +

namespace: 11 bytes

Name: generic-garbage-collector-token-7s8cl
Namespace: kube-system
Labels: <none>
Annotations: kubernetes.io/service-account.name: generic-garbage-collector
kubernetes.io/service-account.uid: fc6430af-8b1d-11eb-96c2-0242ac1

10067

Type: kubernetes.io/service-account-token

Data
====
ca.crt: 1025 bytes
namespace: 11 bytes
token: eyJhbGciOiJSUzI1NiIsImtpZCI6IiJ9.eyJpc3MiOiJrdWJlcm5ldGVzL3NlcnZpY2VhY2NvdW50Iiwia3ViZXJuZXRlcy5pby9zZXJ2aWNlYWNjb3VudC9uYW1lc3BhY2UiOiJrdWJlLXN5c3RlbSIsImt1YmVybWV0ZXMuaW8vc2Vydm1jZWFiY291bnQvc2VjcmV0Lm5hbWUiOiJnZW5lcmljLWdhcmJhZ2UtY29sbGVjdG9yLXRva2VuLTdzOGNsIiwia3ViZXJuZXRlcy5pby9zZXJ2aWNlYWNjb3VudC9zZXJ2aWNlIiwiaWF0IjY291bnQubmFtZSI6ImludHBMVuaWMTz2FvYmFnZS1ib2xsZWNN0h3TilCJrdWJlcm5ldGVzLm1

Terminal Host 2

Your Interactive Bash Terminal. A safe place to learn and execute commands.

```
node01 $ kubeadm join --discovery-token-unsafe-skip-ca-verification --token=102952.1a7dd4cc8d1f4cc5 172.17.0.103:6443
[preflight] Running pre-flight checks
docker ps | grep docker-http-server
[preflight] Reading configuration from the cluster...
[preflight] FYI: You can look at this config file with 'kubectl -n kube-system get cm kubeadm-config -oyaml'
[kubelet-start] Downloading configuration for the kubelet from the "kubelet-config-1.14" ConfigMap in the kube-system namespace
[kubelet-start] Writing kubelet configuration to file "/var/lib/kubelet/config.yaml"
[kubelet-start] Writing kubelet environment file with flags to file "/var/lib/kubelet/kubeadm-flags.env"
[kubelet-start] Activating the kubelet service
[kubelet-start] Waiting for the kubelet to perform the TLS Bootstrap...
[kubelet-check] Initial timeout of 40s passed.
```

This node has joined the cluster:

- * Certificate signing request was sent to apiserver and a response was received.
- * The Kubelet was informed of the new secure connection details.

Run 'kubectl get nodes' on the control-plane to see this node join the cluster.

Terminal Host 1 + 🔊 ⌵ ⚙

```
2jAY3qpLRqnqYQfTFXTh4jT2HPyDYgY9hASaGQzJXt7KhVOaHltfgxOP_Tw0hH38OJKLx5tQbQkqI73W
FEzyAE1FbXmRE8S8NcnzdpfIl3leuwQMAh_ow6pKLAPIYkNUEFPuc4QBU3VmgKrPG4VfdJM7xFxibsBG
KzitmOSlnY6cIpyFvjHXFyhHvBLDAYx3JMA-J1zNorBEHutJenl0KwepZadV0WYzaJYi11PGk4ZlbWK1
XYAFm3L8Sf8bWRusa9d36flUCfbw34sIbHArIHuDWS_5L-6sr1B2aecCp4jZvLuDJFjd9Bdfx8npzfnd
o7yTsYy2xpXA
```

```
Name:          weave-net-token-b8tvb
Namespace:     kube-system
Labels:        <none>
Annotations:   kubernetes.io/service-account.name: weave-net
                kubernetes.io/service-account.uid: faabb32d-8b1d-11eb-96c2-0242ac1
```

10067

Type: kubernetes.io/service-account-token

Data

====

```
ca.crt:      1025 bytes
namespace:   11 bytes
token:       eyJhbGciOiJSUzI1NiIsImtpZCI6Ij9_levJnc3MiOiJrdWJlcm5ldGVzL3N1cnZpeY2V
```

Terminal Host 2

Your Interactive Bash Terminal. A safe place to learn and execute commands.

```
node01 $ kubeadm join --discovery-token-unsafe-skip-ca-verification --token=102952.1a7dd4cc8d1f4cc5 172.17.0.103:6443
[preflight] Running pre-flight checks
docker ps | grep docker-http-server
[preflight] Reading configuration from the cluster...
[preflight] FYI: You can look at this config file with 'kubectl -n kube-system get cm kubeadm-config -oyaml'
[kubelet-start] Downloading configuration for the kubelet from the "kubelet-config-1.14" ConfigMap in the kube-system namespace
[kubelet-start] Writing kubelet configuration to file "/var/lib/kubelet/config.yaml"
[kubelet-start] Writing kubelet environment file with flags to file "/var/lib/kubelet/kubeadm-flags.env"
[kubelet-start] Activating the kubelet service
[kubelet-start] Waiting for the kubelet to perform the TLS Bootstrap...
[kubelet-check] Initial timeout of 40s passed.
```

This node has joined the cluster:

- * Certificate signing request was sent to apiserver and a response was received.
- * The Kubelet was informed of the new secure connection details.

Run 'kubectl get nodes' on the control-plane to see this node join the cluster.