

Summary

- Parsed 44 public tables from Supabase migrations.
- All parsed tables show RLS enabled in migration SQL: True.
- Important referenced objects not found in parsed table migrations: oems, search_queries, api_logs.

bikeai_booking_charges | RLS: Yes

Purpose	BikeAI platform charge records.
Read pages	src/dealer/DealerRevenueWidgets.tsx
Write pages	No current frontend write found
Used by	src/dealer/DealerRevenueWidgets.tsx
Security risk	contains financial data.

booking_timeline | RLS: Yes

Purpose	Stores booking timeline records; key columns include id, booking_id, status, message, actor_id, actor_name, created_at.
Read pages	No current frontend read found
Write pages	No current frontend write found
Used by	Migration/schema only in current scan
Security risk	review effective policies for broad authenticated access.

crm_booking_links | RLS: Yes

Purpose	Stores crm booking links records; key columns include id, token, customer_id, vehicle_id, service_center_id, service_type, due_date, due_km.
Read pages	/dealer/crm, /my/book-service or /admin/bookings/new
Write pages	/dealer/crm, /my/book-service or /admin/bookings/new
Used by	/dealer/crm, /my/book-service or /admin/bookings/new
Security risk	contains PII/location/secret fields.

crm_campaigns | RLS: Yes

Purpose	Stores crm campaigns records; key columns include id, name, campaign_type, target_type, template_id, message_body, target_count, sent_count.
Read pages	No current frontend read found
Write pages	No current frontend write found
Used by	Migration/schema only in current scan
Security risk	contains PII/location/secret fields.

crm_followups | RLS: Yes

Purpose	Stores crm followups records; key columns include id, customer_id, service_center_id, title, follow_up_type, lead_status, scheduled_at, completed_at.
Read pages	/admin/customers/:id, /dealer/crm
Write pages	/dealer/crm
Used by	/admin/customers/:id, /dealer/crm
Security risk	review effective policies for broad authenticated access.

crm_interaction_events | RLS: Yes

Purpose	Stores crm interaction events records; key columns include id, customer_id, vehicle_id, service_center_id, event_type, title, body, entity_type.
Read pages	/dealer/crm
Write pages	/dealer/crm, /dealer/queue or /dealer/service-manager, shared AI chat
Used by	/dealer/crm, /dealer/queue or /dealer/service-manager, shared AI chat
Security risk	review effective policies for broad authenticated access.

crm_retention_feedback | RLS: Yes

Purpose	Stores crm retention feedback records; key columns include id, customer_id, vehicle_id, service_center_id, reason, details, competitor_name, status.
Read pages	/dealer/crm
Write pages	/dealer/crm
Used by	/dealer/crm
Security risk	review effective policies for broad authenticated access.

crm_service_interval_rules | RLS: Yes

Purpose	Stores crm service interval rules records; key columns include id, service_center_id, name, rule_type, service_type, interval_days, interval_km, trigger_mode.
Read pages	/dealer/crm
Write pages	/dealer/crm
Used by	/dealer/crm
Security risk	review effective policies for broad authenticated access.

csv_imports | RLS: Yes

Purpose	Stores csv imports records; key columns include id, import_type, file_name, total_rows, imported_rows, skipped_rows, duplicate_rows, error_rows.
Read pages	No current frontend read found
Write pages	No current frontend write found
Used by	Migration/schema only in current scan
Security risk	review effective policies for broad authenticated access.

customer_bookings | RLS: Yes

Purpose	Customer portal booking, pickup/drop, status, cost, tracking, and OTP records.
Read pages	/dealer/crm, /dealer/queue or /dealer/service-manager, /my/book-service or /admin/bookings/new, /my/bookings or /admin/bookings, /my/bookings/:id, /my/dashboard, supabase/functions/twilio-send/index.ts
Write pages	/dealer/queue or /dealer/service-manager, /my/book-service or /admin/bookings/new, /my/bookings/:id
Used by	/dealer/crm, /dealer/queue or /dealer/service-manager, /my/book-service or /admin/bookings/new, /my/bookings or /admin/bookings, /my/bookings/:id, /my/dashboard, supabase/functions/twilio-send/index.ts
Security risk	contains PII/location/secret fields; contains financial data.

customer_documents | RLS: Yes

Purpose	Stores customer documents records; key columns include id, customer_id, vehicle_id, document_type, document_name, file_url, expiry_date, is_verified.
Read pages	No current frontend read found
Write pages	No current frontend write found
Used by	Migration/schema only in current scan
Security risk	contains PII/location/secret fields.

customer_otp_sessions | RLS: Yes

Purpose	Stores customer otp sessions records; key columns include id, phone, otp_code, channel, is_verified, expires_at, created_at.
Read pages	No current frontend read found
Write pages	No current frontend write found
Used by	Migration/schema only in current scan
Security risk	contains PII/location/secret fields.

customer_reviews | RLS: Yes

Purpose	Stores customer reviews records; key columns include id, customer_id, booking_id, service_center_id, rating, review_text, created_at.
Read pages	No current frontend read found
Write pages	/my/bookings/:id
Used by	/my/bookings/:id
Security risk	review effective policies for broad authenticated access.

customer_vehicles | RLS: Yes

Purpose	Customer garage vehicles and service metadata.
Read pages	/admin/customers, /admin/customers/:id, /dealer/crm, /my/book-service or /admin/bookings/new, /my/dashboard, /my/garage
Write pages	/dealer/crm, /my/add-vehicle, /my/garage
Used by	/admin/customers, /admin/customers/:id, /dealer/crm, /my/add-vehicle, /my/book-service or /admin/bookings/new, /my/dashboard, /my/garage
Security risk	review effective policies for broad authenticated access.

dealer_wallet_transactions | RLS: Yes

Purpose	Dealer wallet transaction ledger.
Read pages	src/dealer/DealerRevenueWidgets.tsx
Write pages	No current frontend write found
Used by	src/dealer/DealerRevenueWidgets.tsx
Security risk	contains financial data.

dealer_wallets | RLS: Yes

Purpose	Dealer wallet balance and status.
Read pages	src/dealer/DealerRevenueWidgets.tsx
Write pages	No current frontend write found
Used by	src/dealer/DealerRevenueWidgets.tsx
Security risk	contains financial data.

geofence_events | RLS: Yes

Purpose	Stores geofence events records; key columns include id, rider_id, job_id, event_type, triggered_at, lat, lng, auto_action.
Read pages	No current frontend read found
Write pages	No current frontend write found
Used by	Migration/schema only in current scan
Security risk	contains PII/location/secret fields.

live_notifications | RLS: Yes

Purpose	Stores live notifications records; key columns include id, recipient_id, job_id, rsa_id, event_type, title, body, channel.
Read pages	No current frontend read found
Write pages	No current frontend write found
Used by	Migration/schema only in current scan
Security risk	review effective policies for broad authenticated access.

message_templates | RLS: Yes

Purpose	CRM/ops message template definitions.
Read pages	/dealer/crm
Write pages	/dealer/crm
Used by	/dealer/crm
Security risk	contains PII/location/secret fields.

notification_queue | RLS: Yes

Purpose	Queued outbound customer/dealer notifications.
Read pages	/dealer/crm
Write pages	/dealer/crm, /dealer/queue or /dealer/service-manager
Used by	/dealer/crm, /dealer/queue or /dealer/service-manager
Security risk	review effective policies for broad authenticated access.

otp_verifications | RLS: Yes

Purpose	Stores otp verifications records; key columns include id, job_id, phone, otp_code, purpose, channel, is_verified, verified_at.
Read pages	No current frontend read found
Write pages	No current frontend write found
Used by	Migration/schema only in current scan

Security risk contains PII/location/secret fields.

pickup_deliveries | RLS: Yes

Purpose Pickup/delivery jobs and rider tracking.

Read pages /admin/live-ops, /admin/live-ops/job/:id, /admin/live-ops/new-job

Write pages /admin/live-ops, /admin/live-ops/job/:id, /admin/live-ops/new-job

Used by /admin/live-ops, /admin/live-ops/job/:id, /admin/live-ops/new-job

Security risk contains PII/location/secret fields.

profiles | RLS: Yes

Purpose User profile, contact, and role records.

Read pages /admin/customers, /admin/customers/:id, /admin/customers/new, /admin/dashboard, /admin/live-ops/new-job, /admin/rsa, /admin/users, /dealer/crm, /my/book-service or /admin/bookings/new, /my/settings, src/hooks/useAuth.ts, src/hooks/useCustomerAuth.ts, src/hooks/useDealerAuth.ts, src/pages/SettingsPage.tsx, supabase/functions/ai-chat/index.ts, supabase/functions/twilio-send/index.ts

Write pages /admin/customers/new, /admin/rsa, /admin/users, /dealer/crm, /my/settings, src/pages/SettingsPage.tsx

Used by /admin/customers, /admin/customers/:id, /admin/customers/new, /admin/dashboard, /admin/live-ops/new-job, /admin/rsa, /admin/users, /dealer/crm, /my/book-service or /admin/bookings/new, /my/settings, src/hooks/useAuth.ts, src/hooks/useCustomerAuth.ts, src/hooks/useDealerAuth.ts, src/lib/supabase.ts, src/pages/SettingsPage.tsx, supabase/functions/ai-chat/index.ts, supabase/functions/twilio-send/index.ts

Security risk contains PII/location/secret fields; role changes must be protected.

rider_location_pings | RLS: Yes

Purpose Stores rider location pings records; key columns include id, rider_id, job_id, lat, lng, speed_kmph, heading, accuracy_m.

Read pages No current frontend read found

Write pages No current frontend write found

Used by Migration/schema only in current scan

Security risk contains PII/location/secret fields.

riders | RLS: Yes

Purpose Pickup, delivery, and RSA rider records.

Read pages /admin/live-ops, /admin/live-ops/job/:id, /admin/live-ops/new-job, /admin/rsa, /dealer/queue or /dealer/service-manager

Write pages /admin/live-ops, /admin/live-ops/job/:id, /admin/live-ops/new-job, /admin/rsa, /dealer/queue or /dealer/service-manager

Used by /admin/live-ops, /admin/live-ops/job/:id, /admin/live-ops/new-job, /admin/rsa, /dealer/queue or /dealer/service-manager, src/App.tsx

Security risk contains PII/location/secret fields.

rsa_requests | RLS: Yes

Purpose Roadside assistance requests.

Read pages /admin/live-ops, /admin/rsa

Write pages /admin/live-ops, /admin/rsa

Used by /admin/live-ops, /admin/rsa

Security risk contains PII/location/secret fields.

service_approval_requests | RLS: Yes

Purpose Customer approval requests for additional service work.

Read pages /dealer/queue or /dealer/service-manager

Write pages /dealer/queue or /dealer/service-manager

Used by /dealer/queue or /dealer/service-manager

Security risk contains financial data.

service_bookings | RLS: Yes

Purpose Legacy/admin service booking records.

Read pages /admin/customers/:id, /admin/dashboard, /admin/dealers/:id, /admin/live-ops/new-job, /my/book-service or /admin/bookings/new, /my/bookings or /admin/bookings, supabase/functions/twilio-send/index.ts

Write pages /admin/dealers/:id, /my/book-service or /admin/bookings/new, /my/bookings or /admin/bookings

Used by /admin/customers/:id, /admin/dashboard, /admin/dealers/:id, /admin/live-ops/new-job, /my/book-service or /admin/bookings/new, /my/bookings or /admin/bookings, src/lib/supabase.ts, supabase/functions/twilio-send/index.ts

Security risk review effective policies for broad authenticated access.

service_centers | RLS: Yes

Purpose Dealer/workshop profile, owner, address, status, capacity, and location.

Read pages /admin/dashboard, /admin/dealers, /admin/dealers/:id, /dealer/crm, /dealer/queue or /dealer/service-manager, /my/book-service or /admin/bookings/new, src/components/DealerModal.tsx, supabase/functions/dealer-search/index.ts, supabase/functions/twilio-send/index.ts

Write pages /admin/dealers, /admin/dealers/:id, src/components/DealerModal.tsx

Used by /admin/dashboard, /admin/dealers, /admin/dealers/:id, /dealer/crm, /dealer/queue or /dealer/service-manager, /my/book-service or /admin/bookings/new, src/components/DealerModal.tsx, src/lib/supabase.ts, supabase/functions/dealer-search/index.ts, supabase/functions/twilio-send/index.ts

Security risk contains PII/location/secret fields.

service_chat_memory | RLS: Yes

Purpose	CRM/service chat memory and AI context.
Read pages	/dealer/crm, /dealer/queue or /dealer/service-manager
Write pages	/dealer/crm, /dealer/queue or /dealer/service-manager, shared AI chat
Used by	/dealer/crm, /dealer/queue or /dealer/service-manager, shared AI chat
Security risk	review effective policies for broad authenticated access.

service_customer_tokens | RLS: Yes

Purpose	Stores service customer tokens records; key columns include id, token, token_type, customer_id, booking_id, job_card_id, approval_id, service_center_id.
Read pages	No current frontend read found
Write pages	/dealer/queue or /dealer/service-manager
Used by	/dealer/queue or /dealer/service-manager
Security risk	contains PII/location/secret fields.

service_feedback_responses | RLS: Yes

Purpose	Stores service feedback responses records; key columns include id, token_id, customer_id, booking_id, job_card_id, service_center_id, rating, comments.
Read pages	/dealer/crm
Write pages	No current frontend write found
Used by	/dealer/crm
Security risk	contains PII/location/secret fields.

service_inspections | RLS: Yes

Purpose	Vehicle inspection checklists, photos, notes, and acknowledgements.
Read pages	/dealer/queue or /dealer/service-manager
Write pages	/dealer/queue or /dealer/service-manager
Used by	/dealer/queue or /dealer/service-manager
Security risk	contains PII/location/secret fields.

service_intervals | RLS: Yes

Purpose	Catalog service interval rules.
Read pages	No current frontend read found
Write pages	No current frontend write found
Used by	Migration/schema only in current scan
Security risk	review effective policies for broad authenticated access.

service_job_cards | RLS: Yes

Purpose	Dealer service operations job cards.
Read pages	/dealer/queue or /dealer/service-manager, shared AI chat, supabase/functions/twilio-send/index.ts
Write pages	/dealer/queue or /dealer/service-manager, shared AI chat
Used by	/dealer/queue or /dealer/service-manager, shared AI chat, supabase/functions/twilio-send/index.ts
Security risk	contains financial data.

service_job_timeline | RLS: Yes

Purpose	Timeline/status events for job cards.
Read pages	/dealer/queue or /dealer/service-manager
Write pages	/dealer/queue or /dealer/service-manager
Used by	/dealer/queue or /dealer/service-manager
Security risk	review effective policies for broad authenticated access.

service_technicians | RLS: Yes

Purpose	Dealer technician staff records.
Read pages	/dealer/queue or /dealer/service-manager
Write pages	No current frontend write found
Used by	/dealer/queue or /dealer/service-manager
Security risk	contains PII/location/secret fields; role changes must be protected.

sms_messages | RLS: Yes

Purpose	Stores sms messages records; key columns include id, to_phone, message_type, body_preview, twilio_sid, status, customer_id, booking_id.
Read pages	No current frontend read found
Write pages	supabase/functions/twilio-send/index.ts

Used by	supabase/functions/twilio-send/index.ts
Security risk	contains PII/location/secret fields.

vehicle_condition_reports | RLS: Yes

Purpose	Stores vehicle condition reports records; key columns include id, job_id, booking_id, report_type, photos, scratch_map, fuel_level, odometer_km.
Read pages	/admin/live-ops/job/:id
Write pages	/admin/live-ops/job/:id
Used by	/admin/live-ops/job/:id
Security risk	contains PII/location/secret fields.

vehicle_documents | RLS: Yes

Purpose	Stores vehicle documents records; key columns include id, vehicle_id, customer_id, doc_type, doc_name, doc_url, expiry_date, is_verified.
Read pages	/admin/customers/:id
Write pages	No current frontend write found
Used by	/admin/customers/:id
Security risk	contains PII/location/secret fields.

vehicle_models | RLS: Yes

Purpose	Vehicle model catalog linked to OEMs.
Read pages	/admin/vehicles, /dealer/crm, /my/add-vehicle, shared vehicle search API, shared vehicle selector
Write pages	/my/add-vehicle
Used by	/admin/vehicles, /dealer/crm, /my/add-vehicle, shared vehicle search API, shared vehicle selector
Security risk	catalog writes should be admin-only.

vehicle_oems | RLS: Yes

Purpose	Vehicle OEM/brand catalog.
Read pages	/admin/vehicles, /dealer/crm, /my/add-vehicle, shared vehicle selector
Write pages	No current frontend write found
Used by	/admin/vehicles, /dealer/crm, /my/add-vehicle, shared vehicle selector
Security risk	catalog writes should be admin-only.

vehicle_specs | RLS: Yes

Purpose	Stores vehicle specs records; key columns include id, model_id, engine_cc, power_bhp, torque_nm, compression_ratio, engine_type, fuel_tank_litres.
Read pages	No current frontend read found
Write pages	No current frontend write found
Used by	Migration/schema only in current scan
Security risk	catalog writes should be admin-only.

vehicle_variants | RLS: Yes

Purpose	Vehicle variant catalog linked to models.
Read pages	No current frontend read found
Write pages	No current frontend write found
Used by	Migration/schema only in current scan
Security risk	catalog writes should be admin-only.