```
Case Study 1: Online Course Registration System
```

© Objective:

Table Structure:

Allow students to register/unregister for courses and view course details.

```
CREATE DATABASE course_db;

USE course_db;

CREATE TABLE courses (

course_id INT PRIMARY KEY,

course_name VARCHAR(100),
```

faculty VARCHAR(100),

JDBC Operations:

• INSERT: Add new courses.

credits INT);

- SELECT: List available courses.
- UPDATE: Modify faculty or credit values.
- DELETE: Remove obsolete courses.

```
package Jdbccasestudy;
import java.sql.Connection;
import java.sql.DriverManager;
import java.sql.PreparedStatement;
import java.sql.ResultSet;
import java.sql.Statement;
import java.util.Scanner;

public class CourseRegistrationSystem {
    static final String DB_URL = "jdbc:mysql://localhost:3306/course_db";
    static final String USER = "root";
    static final String PASS = "root"; // Replace with your DB password
```

```
public static void main(String[] args) {
  Scanner <u>sc</u> = new Scanner(System.in);
  try (
    Connection conn = DriverManager.getConnection(DB_URL, USER, PASS);
    Statement stmt = conn.createStatement();
  ) {
    while (true) {
      System.out.println("\n--- Course Registration System ---");
      System.out.println("1. Add Course");
      System.out.println("2. View Courses");
      System.out.println("3. Update Course");
      System.out.println("4. Delete Course");
      System.out.println("5. Exit");
      System.out.print("Choose: ");
      int choice = sc.nextInt();
      sc.nextLine();
      if (choice == 1) {
         System.out.print("Course ID: ");
         int id = sc.nextInt();
         sc.nextLine();
         System.out.print("Course Name: ");
         String name = sc.nextLine();
         System.out.print("Faculty: ");
         String faculty = sc.nextLine();
         System.out.print("Credits: ");
         int credits = sc.nextInt();
         String sql = "INSERT INTO courses VALUES (?, ?, ?, ?)";
```

```
PreparedStatement ps = conn.prepareStatement(sql);
  ps.setInt(1, id);
  ps.setString(2, name);
  ps.setString(3, faculty);
  ps.setInt(4, credits);
  ps.executeUpdate();
  System.out.println("Course added!");
} else if (choice == 2) {
  ResultSet rs = stmt.executeQuery("SELECT * FROM courses");
  System.out.println("\nCourses:");
  while (rs.next()) {
    System.out.println(rs.getInt(1) + " | " + rs.getString(2) +
         " | " + rs.getString(3) + " | Credits: " + rs.getInt(4));
  }
} else if (choice == 3) {
  System.out.print("Enter Course ID to Update: ");
  int id = sc.nextInt();
  sc.nextLine();
  System.out.print("New Faculty: ");
  String faculty = sc.nextLine();
  System.out.print("New Credits: ");
  int credits = sc.nextInt();
  String sql = "UPDATE courses SET faculty = ?, credits = ? WHERE course_id = ?";
  PreparedStatement ps = conn.prepareStatement(sql);
  ps.setString(1, faculty);
  ps.setInt(2, credits);
  ps.setInt(3, id);
  ps.executeUpdate();
```

```
} else if (choice == 4) {
           System.out.print("Enter Course ID to Delete: ");
           int id = sc.nextInt();
           String sql = "DELETE FROM courses WHERE course_id = ?";
           PreparedStatement ps = conn.prepareStatement(sql);
           ps.setInt(1, id);
           ps.executeUpdate();
           System.out.println("Course deleted!");
         } else if (choice == 5) {
           break;
         } else {
           System.out.println("Invalid choice");
         }
      }
    } catch (Exception e) {
      e.printStackTrace();
    }
  }
}
```

System.out.println("Course updated!");

Case Study 2: Product Inventory System

© Objective:

Track product stock in a retail store.

Table Structure:C

CREATE DATABASE inventory_db;

```
USE inventory_db;
CREATE TABLE products (
        product_id INT PRIMARY KEY,
        product_name VARCHAR(100),
        quantity INT,
        price DECIMAL(10,2)
);
JDBC Operations:
• INSERT: Add new products to inventory.
• SELECT: View stock levels and prices.
• UPDATE: Update quantity after sale/purchase.
• DELETE: Remove discontinued products
package Jdbccasestudy;
import java.sql.Connection;
import java.sql.DriverManager;
import java.sql.PreparedStatement;
import java.sql.ResultSet;
import java.util.Scanner;
import java.sql.Statement;
public class ProductInventorySystem {
        static final String DB_URL = "jdbc:mysql://localhost:3306/inventory_db";
  static final String USER = "root";
  static final String PASS ="root"; // Replace with your DB password
  public static void main(String[] args) {
    Scanner <u>sc</u> = new Scanner(System.in);
```

```
try (
  Connection conn = DriverManager.getConnection(DB_URL, USER, PASS);
  Statement stmt = conn.createStatement();
) {
  while (true) {
    System.out.println("\n--- Product Inventory ---");
    System.out.println("1. Add Product");
    System.out.println("2. View Products");
    System.out.println("3. Update Quantity");
    System.out.println("4. Delete Product");
    System.out.println("5. Exit");
    System.out.print("Choose: ");
    int choice = sc.nextInt();
    sc.nextLine();
    if (choice == 1) {
      System.out.print("Product ID: ");
      int id = sc.nextInt();
      sc.nextLine();
      System.out.print("Product Name: ");
      String name = sc.nextLine();
      System.out.print("Quantity: ");
      int qty = sc.nextInt();
      System.out.print("Price: ");
      double price = sc.nextDouble();
      String sql = "INSERT INTO products VALUES (?, ?, ?, ?)";
      PreparedStatement ps = conn.prepareStatement(sql);
      ps.setInt(1, id);
      ps.setString(2, name);
      ps.setInt(3, qty);
```

```
ps.setDouble(4, price);
  ps.executeUpdate();
  System.out.println("Product added!");
} else if (choice == 2) {
  ResultSet rs = stmt.executeQuery("SELECT * FROM products");
  System.out.println("\nInventory:");
  while (rs.next()) {
    System.out.println(rs.getInt(1) + " | " + rs.getString(2) +
         " | Qty: " + rs.getInt(3) + " | " + rs.getDouble(4));
  }
} else if (choice == 3) {
  System.out.print("Enter Product ID: ");
  int id = sc.nextInt();
  System.out.print("New Quantity: ");
  int qty = sc.nextInt();
  String sql = "UPDATE products SET quantity = ? WHERE product_id = ?";
  PreparedStatement ps = conn.prepareStatement(sql);
  ps.setInt(1, qty);
  ps.setInt(2, id);
  ps.executeUpdate();
  System.out.println("Quantity updated!");
} else if (choice == 4) {
  System.out.print("Enter Product ID to Delete: ");
  int id = sc.nextInt();
  String sql = "DELETE FROM products WHERE product_id = ?";
  PreparedStatement ps = conn.prepareStatement(sql);
  ps.setInt(1, id);
```

```
ps.executeUpdate();
    System.out.println("Product deleted!");
} else if (choice == 5) {
    break;
} else {
    System.out.println("Invalid choice");
}
} catch (Exception e) {
    e.printStackTrace();
}
}
```