

Min Max With Alpha Beta for Tic Tac Toe

Name: Iyoti Sharma

Class: BE IT

Roll No: 60

Batch: I3

Sub: ISLAB

DOP

DOC

Marks

Sign

## \* Min Max with Alpha Beta for Tic Tac Toe :

- The goal of Tic-Tac-Toe is to be the first player to get three in a row on 3x3 grid.
- 'x' always goes first.
- Players alternate placing 'xs' and 'Os' on board until either :

(i) one player has three in a row horizontally, vertically or diagonally.

(ii) All nine squares are filled

- Programmer created in 'Winning States' named set containing a list of all possible.

Win conditions inside 'properties.py', if a player places 'xs' or 'Os' in any of the list, they are declared winner.

The winning states are:

Winning States =  $([0, 1, 2], [3, 4, 5], [6, 7, 8], [0, 3, 6], [1, 4, 7], [2, 5, 8], [0, 4, 8], [2, 7, 6])$

- Programmer has created a dummy bot which chooses positions randomly as DummyBot.py. The GameBoard initializes the free spaces to None. (List of Nones).

- Programmers also created a minmax bot which uses MinMax Algorithm with AlphaBeta pruning to decide the best move.



- The main.py starts by initialization of two objects of MinMaxBot and DummyBot. The code then creates a variable Judge which is called TrTac Toe Judge, to which both objects are passed.
- Programmer also created a Helper method, Helper.py which gets the opponent's position to bot and gets the available moves to play and imports properties by mentioned earlier.

\* Inputs :- No inputs from user.  
(both the bots, DummyBot and MinMaxBot play the game)

\* Output :- (i) Winner Name which can be :  
(a) Bot one (MinMax Bot)  
(b) Bot Two (Dummy Bot)  
(c) Draw (when all positions are filled with no winner)

The winner is decided if the bot's position is in the set of list of Winning States()

\* Analysis of claim by programmer that it uses MinMax with alpha beta Pruning

(i) This claim comes from the Best move() method in MinMax.py as it uses recursion to find the next best move.

(ii) It starts by getting the winner() state and checks if the game already ended by comparing the winner variable with self.char, self.opponent or Draw state and returns 1, -1, 0 respectively.

(iii) The method then starts for loop which iterates through all possible moves in the gameboard.

(iv) After every move, the Bestmove() calls itself recursively to figure out next best move by the MinMax Bot.

(v) The Bot then places the marker on best move and updates the Alpha, Beta variables.

(vi) The Alpha, Beta variables are checked with Value and are updated accordingly. If Value is greater than Alpha, Alpha is assigned to Value & if it's lower than Beta, Beta's value is updated to Value.

Thus, the claim by programmer that it uses MinMax with Alpha Beta pruning is correct.



## Outputs

(i) Bot one

'x'	'o'	'x'
'o'	'o'	None
'x'	'o'	'x'

(ii) Bot one

'o'	'x'	'x'
'o'	None	None
'o'	None	'x'

(iii) Bot Two

'o'	'x'	None
'o'	'x'	'x'
'o'	'o'	'x'

(iv) Bot Two

'x'	'x'	'x'
'x'	'o'	'o'
'o'	'x'	'o'

(v) Bot One

'x'	'o'	None
'o'	'x'	None
'x'	'o'	'x'

(vi) Bot One

'o'	'x'	x
x	o	None
x	o	o

(vii) Bot one

'o'	'x'	None
None	'x'	'o'
None	'x'	None

(viii) Draw

'o'	'x'	'x'
'x'	'o'	'o'
'x'	'o'	'x'

(ix) Bot two

'o'	'x'	'x'
'x'	'x'	'o'
'x'	'o'	'o'

(x) Draw

'x'	'o'	'x'
'o'	'o'	'x'
'x'	'x'	'o'