

Social network Graph Link Prediction - Facebook Challenge

```
In [1]: #Importing Libraries
# please do go through this python notebook:
import warnings
warnings.filterwarnings("ignore")

import csv
import pandas as pd#pandas to create small dataframes
import datetime #Convert to unix time
import time #Convert to unix time
# if numpy is not installed already : pip3 install numpy
import numpy as np#Do arithmetic operations on arrays
# matplotlib: used to plot graphs
import matplotlib
import matplotlib.pyplot as plt
import seaborn as sns#Plots
from matplotlib import rcParams#Size of plots
from sklearn.cluster import MiniBatchKMeans, KMeans#Clustering
import math
import pickle
import os
# to install xgboost: pip3 install xgboost
import xgboost as xgb

import warnings
import networkx as nx
import pdb
import pickle
from pandas import HDFStore,DataFrame
from pandas import read_hdf
from scipy.sparse.linalg import svds, eigs
import gc
from tqdm import tqdm
```

1. Reading Data

```
In [2]: if os.path.isfile('data/after_eda/train_pos_after_eda.csv'):
        train_graph=nx.read_edgelist('data/after_eda/train_pos_after_eda.csv',delimiter=',',create_using=nx.DiGraph(),nodetype=int)
        print(nx.info(train_graph))
    else:
        print("please run the FB_EDA.ipynb or download the files from drive")
```

```
Name:
Type: DiGraph
Number of nodes: 1780722
Number of edges: 7550015
Average in degree: 4.2399
Average out degree: 4.2399
```

```
In [3]: train_graph.in_degree(1), train_graph.out_degree(1)
```

```
Out[3]: (3, 2)
```

2. Similarity measures

2.1 Jaccard Distance:

<http://www.statisticshowto.com/jaccard-index/> (<http://www.statisticshowto.com/jaccard-index/>)

$$j = \frac{|X \cap Y|}{|X \cup Y|}$$

```
In [4]: #for followees
def jaccard_for_followees(a,b):
    try:
        if len(set(train_graph.successors(a))) == 0 | len(set(train_graph.successors(b))) == 0:
            return 0
        sim = (len(set(train_graph.successors(a)).intersection(set(train_graph.successors(b))))) /\
                (len(set(train_graph.successors(a)).union(set(train_graph.successors(b)
))))))
    except:
        return 0
    return sim
```

```
In [5]: #one test case
print(jaccard_for_followees(273084,1505602))

0.0
```

```
In [6]: #node 1635354 not in graph
print(jaccard_for_followees(273084,1635354))

0
```

```
In [7]: #for followers
def jaccard_for_followers(a,b):
    try:
        if len(set(train_graph.predecessors(a))) == 0 | len(set(g.predecessors(b))) == 0:
            return 0
        sim = (len(set(train_graph.predecessors(a)).intersection(set(train_graph.predecessors(b))))) /\
                (len(set(train_graph.predecessors(a)).union(set(train_graph.predecessors(b)
))))))
    except:
        return 0
    return sim
```

```
In [8]: print(jaccard_for_followers(273084,470294))

0
```

```
In [9]: #node 1635354 not in graph
print(jaccard_for_followees(669354,1635354))
```

0

2.2 Cosine distance

$$\text{CosineDistance} = \frac{|X \cap Y|}{|X| \cdot |Y|}$$

```
In [10]: #for followees
def cosine_for_followees(a,b):
    try:
        if len(set(train_graph.successors(a))) == 0 | len(set(train_graph.successors(b))) == 0:
            return 0
        sim = (len(set(train_graph.successors(a)).intersection(set(train_graph.successors(b))))) / \
              (math.sqrt(len(set(train_graph.successors(a)))*len((set(train_graph.succe
ssors(b)))))
        return sim
    except:
        return 0
```

```
In [11]: print(cosine_for_followees(273084,1505602))
```

0.0

```
In [12]: print(cosine_for_followees(273084,1635354))
```

0

```
In [13]: def cosine_for_followers(a,b):
        try:

            if len(set(train_graph.predecessors(a))) == 0 | len(set(train_graph.predecessors(b))) == 0:
                return 0
            sim = (len(set(train_graph.predecessors(a)).intersection(set(train_graph.predecessors(b))))) / \
                (math.sqrt(len(set(train_graph.predecessors(a)))) * (len(set(train_graph.p
redecessors(b)))))
            return sim
        except:
            return 0
```

```
In [14]: print(cosine_for_followers(2,470294))
```

```
0.02886751345948129
```

```
In [15]: print(cosine_for_followers(669354,1635354))
```

```
0
```

3. Ranking Measures

https://networkx.github.io/documentation/networkx-1.10/reference/generated/networkx.algorithms.link_analysis.pagerank_alg.pagerank.html
[\(https://networkx.github.io/documentation/networkx-1.10/reference/generated/networkx.algorithms.link_analysis.pagerank_alg.pagerank.html\)](https://networkx.github.io/documentation/networkx-1.10/reference/generated/networkx.algorithms.link_analysis.pagerank_alg.pagerank.html)

PageRank computes a ranking of the nodes in the graph G based on the structure of the incoming links.



Mathematical PageRanks for a simple network, expressed as percentages. (Google uses a logarithmic scale.) Page C has a higher PageRank than Page E, even though there are fewer links to C; the one link to C comes from an important page and hence is of high value. If web surfers who start on a random page have an 85% likelihood of choosing a random link from the page they are currently visiting, and a 15% likelihood of jumping to a page chosen at random from the entire web, they will reach Page E 8.1% of the time. **(The 15% likelihood of jumping to an arbitrary page corresponds to a damping factor of 85%.) Without damping, all web surfers would eventually end up on Pages A, B, or C, and all other pages would have PageRank zero. In the presence of damping, Page A effectively links to all pages in the web, even though it has no outgoing links of its own.**

3.1 Page Ranking

<https://en.wikipedia.org/wiki/PageRank> (<https://en.wikipedia.org/wiki/PageRank>)

```
In [16]: if not os.path.isfile('data/fea_sample/page_rank.p'):
         pr = nx.pagerank(train_graph, alpha=0.85)
         pickle.dump(pr, open('data/fea_sample/page_rank.p', 'wb'))
         else:
         pr = pickle.load(open('data/fea_sample/page_rank.p', 'rb'))
```

```
In [17]: print('min', pr[min(pr, key=pr.get)])
         print('max', pr[max(pr, key=pr.get)])
         print('mean', float(sum(pr.values())) / len(pr))
```

```
min 1.6556497245737814e-07
max 2.7098251341935827e-05
mean 5.615699699389075e-07
```

```
In [18]: #for imputing to nodes which are not there in Train data
         mean_pr = float(sum(pr.values())) / len(pr)
         print(mean_pr)
```

```
5.615699699389075e-07
```

```
In [ ]:
```

4. Other Graph Features

4.1 Shortest path:

Getting Shortest path between two nodes, if nodes have direct path i.e directly connected then we are removing that edge and calculating path.

```
In [19]: #if has direct edge then deleting that edge and calculating shortest path
def compute_shortest_path_length(a,b):
    p=-1
    try:
        if train_graph.has_edge(a,b):
            train_graph.remove_edge(a,b)
            p= nx.shortest_path_length(train_graph,source=a,target=b)
            train_graph.add_edge(a,b)
        else:
            p= nx.shortest_path_length(train_graph,source=a,target=b)
    return p
    except:
        return -1
```

```
In [20]: #testing
compute_shortest_path_length(77697, 826021)
```

Out[20]: 10

```
In [21]: #testing
compute_shortest_path_length(669354,1635354)
```

Out[21]: -1

4.2 Checking for same community

```
In [22]: #getting weekly connected edges from graph
wcc=list(nx.weakly_connected_components(train_graph))
def belongs_to_same_wcc(a,b):
    index = []
    if train_graph.has_edge(b,a):
        return 1
    if train_graph.has_edge(a,b):
        for i in wcc:
            if a in i:
                index= i
                break
        if (b in index):
            train_graph.remove_edge(a,b)
            if compute_shortest_path_length(a,b)==-1:
                train_graph.add_edge(a,b)
                return 0
            else:
                train_graph.add_edge(a,b)
                return 1
        else:
            return 0
    else:
        for i in wcc:
            if a in i:
                index= i
                break
        if(b in index):
            return 1
        else:
            return 0
```

```
In [23]: belongs_to_same_wcc(861, 1659750)
```

```
Out[23]: 0
```

```
In [24]: belongs_to_same_wcc(669354,1635354)
```

```
Out[24]: 0
```


4.3 Adamic/Adar Index:

Adamic/Adar measures is defined as inverted sum of degrees of common neighbours for given two vertices.

$$A(x, y) = \sum_{u \in N(x) \cap N(y)} \frac{1}{\log(|N(u)|)}$$

```
In [25]: #adar index
def calc_adar_in(a,b):
    sum=0
    try:
        n=list(set(train_graph.successors(a)).intersection(set(train_graph.successors(b))))
        if len(n)!=0:
            for i in n:
                sum=sum+(1/np.log10(len(list(train_graph.predecessors(i)))))
            return sum
        else:
            return 0
    except:
        return 0
```

```
In [26]: calc_adar_in(1,189226)
```

```
Out[26]: 0
```

```
In [27]: calc_adar_in(669354,1635354)
```

```
Out[27]: 0
```

4.4 Is persion was following back:

```
In [28]: def follows_back(a,b):
          if train_graph.has_edge(b,a):
              return 1
          else:
              return 0
```

```
In [29]: follows_back(1,189226)
```

```
Out[29]: 1
```

```
In [30]: follows_back(669354,1635354)
```

```
Out[30]: 0
```

4.5 Katz Centrality:

https://en.wikipedia.org/wiki/Katz_centrality (https://en.wikipedia.org/wiki/Katz_centrality)

<https://www.geeksforgeeks.org/katz-centrality-centrality-measure/> (<https://www.geeksforgeeks.org/katz-centrality-centrality-measure/>) Katz centrality computes the centrality for a node based on the centrality of its neighbors. It is a generalization of the eigenvector centrality. The Katz centrality for node i is

$$x_i = \alpha \sum_j A_{ij} x_j + \beta,$$

where A is the adjacency matrix of the graph G with eigenvalues

$$\lambda$$

.

The parameter

$$\beta$$

controls the initial centrality and

$$\alpha < \frac{1}{\lambda_{max}}.$$

```
In [31]: if not os.path.isfile('data/fea_sample/katz.p'):
          katz = nx.katz.katz_centrality(train_graph,alpha=0.005,beta=1)
          pickle.dump(katz,open('data/fea_sample/katz.p','wb'))
        else:
          katz = pickle.load(open('data/fea_sample/katz.p','rb'))
```

```
In [32]: print('min',katz[min(katz, key=katz.get)])
          print('max',katz[max(katz, key=katz.get)])
          print('mean',float(sum(katz.values())) / len(katz))
```

```
min 0.0007313532484065916
max 0.003394554981699122
mean 0.0007483800935562018
```

```
In [33]: mean_katz = float(sum(katz.values())) / len(katz)
          print(mean_katz)
```

```
0.0007483800935562018
```

4.6 Hits Score

The HITS algorithm computes two numbers for a node. Authorities estimates the node value based on the incoming links. Hubs estimates the node value based on outgoing links.

https://en.wikipedia.org/wiki/HITS_algorithm (https://en.wikipedia.org/wiki/HITS_algorithm)

```
In [34]: if not os.path.isfile('data/fea_sample/hits.p'):
          hits = nx.hits(train_graph, max_iter=100, tol=1e-08, nstart=None, normalized=True)
          pickle.dump(hits,open('data/fea_sample/hits.p','wb'))
        else:
          hits = pickle.load(open('data/fea_sample/hits.p','rb'))
```

```
In [35]: print('min',hits[0][min(hits[0], key=hits[0].get)])  
print('max',hits[0][max(hits[0], key=hits[0].get)])  
print('mean',float(sum(hits[0].values())) / len(hits[0]))
```

```
min 0.0  
max 0.004868653378780953  
mean 5.615699699344123e-07
```

```
In [ ]:
```

5. Featurization

5. 1 Reading a sample of Data from both train and test

```
In [36]: import random  
if os.path.isfile('data/after_eda/train_after_eda.csv'):  
    filename = "data/after_eda/train_after_eda.csv"  
    # you uncomment this line, if you dont know the lentgh of the file name  
    # here we have hardcoded the number of lines as 1510030  
    # n_train = sum(1 for line in open(filename)) #number of records in file (excludes header)  
    n_train = 1510028  
    s = 100000 #desired sample size  
    skip_train = sorted(random.sample(range(1,n_train+1),n_train-s))  
    #https://stackoverflow.com/a/22259008/4084039
```

```
In [37]: if os.path.isfile('data/after_eda/test_after_eda.csv'): # changed train to test  
    filename = "data/after_eda/test_after_eda.csv"  
    # you uncomment this line, if you dont know the lentgh of the file name  
    # here we have hardcoded the number of lines as 3775008  
    # n_test = sum(1 for line in open(filename)) #number of records in file (excludes header)  
    n_test = 3775006  
    s = 50000 #desired sample size  
    skip_test = sorted(random.sample(range(1,n_test+1),n_test-s))  
    #https://stackoverflow.com/a/22259008/4084039
```

```
In [38]: print("Number of rows in the train data file:", n_train)
print("Number of rows we are going to eliminate in train data are", len(skip_train))
print("Number of rows in the test data file:", n_test)
print("Number of rows we are going to eliminate in test data are", len(skip_test))
```

Number of rows in the train data file: 15100028
 Number of rows we are going to eliminate in train data are 15000028
 Number of rows in the test data file: 3775006
 Number of rows we are going to eliminate in test data are 3725006

```
In [39]: df_final_train = pd.read_csv('data/after_eda/train_after_eda.csv', skiprows=skip_train, names=['source_node',
'destination_node'])
df_final_train['indicator_link'] = pd.read_csv('data/train_y.csv', skiprows=skip_train, names=['indicator_link'])
print("Our train matrix size ", df_final_train.shape)
df_final_train.head(2)
```

Our train matrix size (100002, 3)

Out[39]:

	source_node	destination_node	indicator_link
0	273084	1505602	1
1	912810	1678443	1

```
In [40]: df_final_test = pd.read_csv('data/after_eda/test_after_eda.csv', skiprows=skip_test, names=['source_node', 'destination_node'])
df_final_test['indicator_link'] = pd.read_csv('data/test_y.csv', skiprows=skip_test, names=['indicator_link'])
print("Our test matrix size ", df_final_test.shape)
df_final_test.head(2)
```

Our test matrix size (50002, 3)

Out[40]:

	source_node	destination_node	indicator_link
0	848424	784690	1
1	1703183	1755993	1

In []:

5.2 Adding a set of features

we will create these each of these features for both train and test data points

1. jaccard_followers
2. jaccard_followees
3. cosine_followers
4. cosine_followees
5. num_followers_s
6. num_followees_s
7. num_followers_d
8. num_followees_d
9. inter_followers
10. inter_followees

```
In [41]: if not os.path.isfile('data/fea_sample/storage_sample_stage1.h5'):
    #mapping jaccrd followers to train and test data
    df_final_train['jaccard_followers'] = df_final_train.apply(lambda row:
                                                                jaccard_for_followers(row['source_node'],row['destination_node']
                                                                )),axis=1)
    df_final_test['jaccard_followers'] = df_final_test.apply(lambda row:
                                                             jaccard_for_followers(row['source_node'],row['destination_node']
                                                             )),axis=1)

    #mapping jaccrd followees to train and test data
    df_final_train['jaccard_followees'] = df_final_train.apply(lambda row:
                                                                jaccard_for_followees(row['source_node'],row['destination_node']
                                                                )),axis=1)
    df_final_test['jaccard_followees'] = df_final_test.apply(lambda row:
                                                             jaccard_for_followees(row['source_node'],row['destination_node']
                                                             )),axis=1)

    #mapping jaccrd followers to train and test data
    df_final_train['cosine_followers'] = df_final_train.apply(lambda row:
                                                                cosine_for_followers(row['source_node'],row['destination_node']),
                                                                axis=1)
    df_final_test['cosine_followers'] = df_final_test.apply(lambda row:
                                                             cosine_for_followers(row['source_node'],row['destination_node']),
                                                             axis=1)

    #mapping jaccrd followees to train and test data
    df_final_train['cosine_followees'] = df_final_train.apply(lambda row:
                                                                cosine_for_followees(row['source_node'],row['destination_node']),
                                                                axis=1)
    df_final_test['cosine_followees'] = df_final_test.apply(lambda row:
                                                             cosine_for_followees(row['source_node'],row['destination_node']),
                                                             axis=1)
```

```
In [42]: def compute_features_stage1(df_final):  
    #calculating no of followers followees for source and destination  
    #calculating intersection of followers and followees for source and destination  
    num_followers_s=[]  
    num_followees_s=[]  
    num_followers_d=[]  
    num_followees_d=[]  
    inter_followers=[]  
    inter_followees=[]  
    for i,row in df_final.iterrows():  
        try:  
            s1=set(train_graph.predecessors(row['source_node']))  
            s2=set(train_graph.successors(row['source_node']))  
        except:  
            s1 = set()  
            s2 = set()  
        try:  
            d1=set(train_graph.predecessors(row['destination_node']))  
            d2=set(train_graph.successors(row['destination_node']))  
        except:  
            d1 = set()  
            d2 = set()  
        num_followers_s.append(len(s1))  
        num_followees_s.append(len(s2))  
  
        num_followers_d.append(len(d1))  
        num_followees_d.append(len(d2))  
  
        inter_followers.append(len(s1.intersection(d1)))  
        inter_followees.append(len(s2.intersection(d2)))  
  
    return num_followers_s, num_followers_d, num_followees_s, num_followees_d, inter_followers, inter_followees
```



```
In [43]: if not os.path.isfile('data/fea_sample/storage_sample_stage1.h5'):
    df_final_train['num_followers_s'], df_final_train['num_followers_d'], \
    df_final_train['num_followees_s'], df_final_train['num_followees_d'], \
    df_final_train['inter_followers'], df_final_train['inter_followees'] = compute_features_stage1(df_final_train)

    df_final_test['num_followers_s'], df_final_test['num_followers_d'], \
    df_final_test['num_followees_s'], df_final_test['num_followees_d'], \
    df_final_test['inter_followers'], df_final_test['inter_followees'] = compute_features_stage1(df_final_test)

    hdf = HDFStore('data/fea_sample/storage_sample_stage1.h5')
    hdf.put('train_df', df_final_train, format='table', data_columns=True)
    hdf.put('test_df', df_final_test, format='table', data_columns=True)
    hdf.close()
else:
    df_final_train = read_hdf('data/fea_sample/storage_sample_stage1.h5', 'train_df', mode='r')
    df_final_test = read_hdf('data/fea_sample/storage_sample_stage1.h5', 'test_df', mode='r')
```

5.3 Adding new set of features

we will create these each of these features for both train and test data points

1. adar index
2. is following back
3. belongs to same weakly connect components
4. shortest path between source and destination

```

In [44]: if not os.path.isfile('data/fea_sample/storage_sample_stage2.h5'):
    #mapping adar index on train
    df_final_train['adar_index'] = df_final_train.apply(lambda row: calc_adar_in(row['source_node'],row['destination_node']),axis=1)
    #mapping adar index on test
    df_final_test['adar_index'] = df_final_test.apply(lambda row: calc_adar_in(row['source_node'],row['destination_node']),axis=1)

    #-----
    #mapping followback or not on train
    df_final_train['follows_back'] = df_final_train.apply(lambda row: follows_back(row['source_node'],row['destination_node']),axis=1)

    #mapping followback or not on test
    df_final_test['follows_back'] = df_final_test.apply(lambda row: follows_back(row['source_node'],row['destination_node']),axis=1)

    #-----
    #mapping same component of wcc or not on train
    df_final_train['same_comp'] = df_final_train.apply(lambda row: belongs_to_same_wcc(row['source_node'],row['destination_node']),axis=1)

    ##mapping same component of wcc or not on test
    df_final_test['same_comp'] = df_final_test.apply(lambda row: belongs_to_same_wcc(row['source_node'],row['destination_node']),axis=1)

    #-----
    #mapping shortest path on train
    df_final_train['shortest_path'] = df_final_train.apply(lambda row: compute_shortest_path_length(row['source_node'],row['destination_node']),axis=1)
    #mapping shortest path on test
    df_final_test['shortest_path'] = df_final_test.apply(lambda row: compute_shortest_path_length(row['source_node'],row['destination_node']),axis=1)

    hdf = HDFStore('data/fea_sample/storage_sample_stage2.h5')
    hdf.put('train_df',df_final_train, format='table', data_columns=True)
    hdf.put('test_df',df_final_test, format='table', data_columns=True)
    hdf.close()
else:
    df_final_train = read_hdf('data/fea_sample/storage_sample_stage2.h5', 'train_df',mode='r')
    df_final_test = read_hdf('data/fea_sample/storage_sample_stage2.h5', 'test_df',mode='r')

```

5.4 Adding new set of features

we will create these each of these features for both train and test data points

1. Weight Features

- weight of incoming edges
- weight of outgoing edges
- weight of incoming edges + weight of outgoing edges
- weight of incoming edges * weight of outgoing edges
- 2*weight of incoming edges + weight of outgoing edges
- weight of incoming edges + 2*weight of outgoing edges

2. Page Ranking of source

3. Page Ranking of dest

4. katz of source

5. katz of dest

6. hubs of source

7. hubs of dest

8. authorities_s of source

9. authorities_s of dest

Weight Features

In order to determine the similarity of nodes, an edge weight value was calculated between nodes. Edge weight decreases as the neighbor count goes up. Intuitively, consider one million people following a celebrity on a social network then chances are most of them never met each other or the celebrity. On the other hand, if a user has 30 contacts in his/her social network, the chances are higher that many of them know each other. credit - Graph-based Features for Supervised Link Prediction William Cukierski, Benjamin Hamner, Bo Yang

$$W = \frac{1}{\sqrt{1 + |X|}}$$

it is directed graph so calculated Weighted in and Weighted out differently

```
In [45]: #source and destination of each link
Weight_in = {}
Weight_out = {}
for i in tqdm(train_graph.nodes()):
    s1=set(train_graph.predecessors(i))
    w_in = 1.0/(np.sqrt(1+len(s1)))
    Weight_in[i]=w_in

    s2=set(train_graph.successors(i))
    w_out = 1.0/(np.sqrt(1+len(s2)))
    Weight_out[i]=w_out

#for imputing with mean
mean_weight_in = np.mean(list(Weight_in.values()))
mean_weight_out = np.mean(list(Weight_out.values()))
```

```
100%|██████████████████████████████████████████████████████████████████████████| 1780722/1780722 [00:47<00:00, 373  
59.73it/s]
```

```
In [46]: if not os.path.isfile('data/fea_sample/storage_sample_stage3.h5'):
    #mapping to pandas train
    df_final_train['weight_in'] = df_final_train.destination_node.apply(lambda x: Weight_in.get(x,mean_weight_in))
    df_final_train['weight_out'] = df_final_train.source_node.apply(lambda x: Weight_out.get(x,mean_weight_out))

    #mapping to pandas test
    df_final_test['weight_in'] = df_final_test.destination_node.apply(lambda x: Weight_in.get(x,mean_weight_in))
    df_final_test['weight_out'] = df_final_test.source_node.apply(lambda x: Weight_out.get(x,mean_weight_out))

    #some features engineerings on the in and out weights
    df_final_train['weight_f1'] = df_final_train.weight_in + df_final_train.weight_out
    df_final_train['weight_f2'] = df_final_train.weight_in * df_final_train.weight_out
    df_final_train['weight_f3'] = (2*df_final_train.weight_in + 1*df_final_train.weight_out)
    df_final_train['weight_f4'] = (1*df_final_train.weight_in + 2*df_final_train.weight_out)

    #some features engineerings on the in and out weights
    df_final_test['weight_f1'] = df_final_test.weight_in + df_final_test.weight_out
    df_final_test['weight_f2'] = df_final_test.weight_in * df_final_test.weight_out
    df_final_test['weight_f3'] = (2*df_final_test.weight_in + 1*df_final_test.weight_out)
    df_final_test['weight_f4'] = (1*df_final_test.weight_in + 2*df_final_test.weight_out)
```

```

In [47]: if not os.path.isfile('data/fea_sample/storage_sample_stage3.h5'):

    #page rank for source and destination in Train and Test
    #if anything not there in train graph then adding mean page rank
    df_final_train['page_rank_s'] = df_final_train.source_node.apply(lambda x: pr.get(x, mean_pr))
    df_final_train['page_rank_d'] = df_final_train.destination_node.apply(lambda x: pr.get(x, mean_pr))

    df_final_test['page_rank_s'] = df_final_test.source_node.apply(lambda x: pr.get(x, mean_pr))
    df_final_test['page_rank_d'] = df_final_test.destination_node.apply(lambda x: pr.get(x, mean_pr))
    #=====

    #Katz centrality score for source and destination in Train and test
    #if anything not there in train graph then adding mean katz score
    df_final_train['katz_s'] = df_final_train.source_node.apply(lambda x: katz.get(x, mean_katz))
    df_final_train['katz_d'] = df_final_train.destination_node.apply(lambda x: katz.get(x, mean_katz))

    df_final_test['katz_s'] = df_final_test.source_node.apply(lambda x: katz.get(x, mean_katz))
    df_final_test['katz_d'] = df_final_test.destination_node.apply(lambda x: katz.get(x, mean_katz))
    #=====

    #Hits algorithm score for source and destination in Train and test
    #if anything not there in train graph then adding 0
    df_final_train['hubs_s'] = df_final_train.source_node.apply(lambda x: hits[0].get(x, 0))
    df_final_train['hubs_d'] = df_final_train.destination_node.apply(lambda x: hits[0].get(x, 0))

    df_final_test['hubs_s'] = df_final_test.source_node.apply(lambda x: hits[0].get(x, 0))
    df_final_test['hubs_d'] = df_final_test.destination_node.apply(lambda x: hits[0].get(x, 0))
    #=====

    #Hits algorithm score for source and destination in Train and Test
    #if anything not there in train graph then adding 0
    df_final_train['authorities_s'] = df_final_train.source_node.apply(lambda x: hits[1].get(x, 0))
    df_final_train['authorities_d'] = df_final_train.destination_node.apply(lambda x: hits[1].get(x, 0))

    df_final_test['authorities_s'] = df_final_test.source_node.apply(lambda x: hits[1].get(x, 0))
    df_final_test['authorities_d'] = df_final_test.destination_node.apply(lambda x: hits[1].get(x, 0))
    #=====

    hdf = HDFStore('data/fea_sample/storage_sample_stage3.h5')
    hdf.put('train_df', df_final_train, format='table', data_columns=True)
    hdf.put('test_df', df_final_test, format='table', data_columns=True)
    hdf.close()

```

```

else:
    df_final_train = read_hdf('data/fea_sample/storage_sample_stage3.h5', 'train_df', mode='r')
    df_final_test = read_hdf('data/fea_sample/storage_sample_stage3.h5', 'test_df', mode='r')

```

5.5 Adding new set of features

we will create these each of these features for both train and test data points

1. SVD features for both source and destination

```

In [48]: def svd(x, S):
        try:
            z = sadj_dict[x]
            return S[z]
        except:
            return [0,0,0,0,0,0]

```

```

In [49]: #for svd features to get feature vector creating a dict node val and inedx in svd vector
sadj_col = sorted(train_graph.nodes())
sadj_dict = { val:idx for idx,val in enumerate(sadj_col)}

```

```

In [50]: Adj = nx.adjacency_matrix(train_graph,nodelist=sorted(train_graph.nodes())).asfptype()

```

```

In [51]: U, s, V = svds(Adj, k = 6)
print('Adjacency matrix Shape',Adj.shape)
print('U Shape',U.shape)
print('V Shape',V.shape)
print('s Shape',s.shape)

```

```

Adjacency matrix Shape (1780722, 1780722)
U Shape (1780722, 6)
V Shape (6, 1780722)
s Shape (6,)

```

```

In [52]: U[0,:]

```

```

Out[52]: array([-2.06310635e-15,  4.86280649e-12,  4.32863831e-13,  6.34827009e-14,
                1.18652791e-14,  1.85734069e-16])

```



```
In [58]: df_final_train['svd_dot_source']
```

```
Out[58]: 0      1.114951e-11
          1      3.192812e-03
          2      4.874439e-35
          3      4.710691e-20
          4      7.775088e-14
          ...
          99997    1.096571e-25
          99998    3.139539e-32
          99999    4.158490e-22
          100000   -5.695261e-30
          100001    8.712146e-27
          Name: svd dot source, Length: 100002, dtype: float64
```

```
In [59]: svd_dot_train_destination = []  
         for v in tqdm(train_nodes):  
             s, d = v  
             svd_dot_train_destination.append(np.dot(svd(s,V.T),np.array(svd(d,V.T)).T)) # svd(s, V) will return svd f  
         or source node of V**** svd(d,V.T).T => is destination node for V  
         svd_dot_train_destination = np.array(svd_dot_train_destination)  
  
100%|██████████████████████████████████████████████████████████████████████████████| 100002/100002 [00:00<00:00, 1401  
61.65it/s]
```

```
In [60]: df_final_train['svd dot destination'] = svd_dot_train_destination
```

```
In [61]: df_final_train['svd dot destination']
```

```
Out[61]: 0      2.238777e-12
          1      9.068719e-04
          2      7.436984e-36
          3      3.159735e-18
          4      3.708786e-16
          ...
          99997    0.000000e+00
          99998    0.000000e+00
          99999    0.000000e+00
         100000    6.252742e-26
         100001    1.639378e-15
          Name: svd dot destination, Length: 100002, dtype: float64
```



```
In [74]: def pa_score_followers(x,y):
        if x in train_graph:
            x_degree = train_graph.in_degree(x)
        else:
            x_degree=0

        if y in train_graph:
            y_degree = train_graph.in_degree(y)
        else:
            y_degree=0
#     print(x_degree, y_degree) # for testing purpose
        return np.abs(np.sqrt(x_degree))*np.abs(np.sqrt(y_degree))

def pa_score_followee(x,y):
    if x in train_graph:
        x_degree = train_graph.out_degree(x)
    else:
        x_degree=0

    if y in train_graph:
        y_degree = train_graph.out_degree(y)
    else:
        y_degree=0
#     print(x_degree, y_degree) # for testing purpose
    return np.abs(np.sqrt(x_degree))*np.abs(np.sqrt(y_degree))
```

```
In [89]: pa_score_followers(27,130) # Preferential attachment score of node no: 27, 30 of our training graph
```

```
Out[89]: 2.449489742783178
```

```
In [90]: pa_score_followee(27, 130)
```

```
Out[90]: 0.0
```

```
In [ ]:
```

```
In [91]: train_nodes = list(zip(df_final_train.source_node,df_final_train.destination_node))
```

```
In [92]: test_nodes = list(zip(df_final_test.source_node, df_final_test.destination_node))
```

```
In [93]: from tqdm import tqdm
```

```
In [94]: train_pref_attach_score_followers = []

for v in tqdm(train_nodes):
    i,j = v
    train_pref_attach_score_followers.append(pa_score_followers(i,j))

train_pref_attach_score_followers = np.array(train_pref_attach_score_followers)

100%|████████████████████████████████████████████████████████████████████████████████| 100002/100002 [00:02<00:00, 385
81.88it/s]
```

```
In [95]: df_final_train['pa_score_followers']= train_pref_attach_score_followers
```

```
In [96]: train_pref_attach_score_followee = []

for v in tqdm(train_nodes):
    i,j = v
    train_pref_attach_score_followee.append(pa_score_followee(i,j))

train_pref_attach_score_followee = np.array(train_pref_attach_score_followee)

100%|████████████████████████████████████████████████████████████████████████████████| 100002/100002 [00:01<00:00, 710
13.54it/s]
```

```
In [97]: df_final_train['pa_score_followee'] = train_pref_attach_score_followee
```

```
In [ ]:
```



```
In [104]: df_final_test.columns
```

```
Out[104]: Index(['source_node', 'destination_node', 'indicator_link',  
                'jaccard_followers', 'jaccard_followees', 'cosine_followers',  
                'cosine_followees', 'num_followers_s', 'num_followees_s',  
                'num_followees_d', 'inter_followers', 'inter_followees', 'adar_index',  
                'follows_back', 'same_comp', 'shortest_path', 'weight_in', 'weight_out',  
                'weight_f1', 'weight_f2', 'weight_f3', 'weight_f4', 'page_rank_s',  
                'page_rank_d', 'katz_s', 'katz_d', 'hubs_s', 'hubs_d', 'authorities_s',  
                'authorities_d', 'svd_dot_source', 'svd_dot_destination',  
                'pa_score_followers', 'pa_score_followee'],  
               dtype='object')
```

```

In [106]: if not os.path.isfile('data/fea_sample/assignment_storage_sample_stage4.h5'):
#=====

df_final_train[['svd_u_s_1', 'svd_u_s_2', 'svd_u_s_3', 'svd_u_s_4', 'svd_u_s_5', 'svd_u_s_6']] = \
df_final_train.source_node.apply(lambda x: svd(x, U)).apply(pd.Series)

df_final_train[['svd_u_d_1', 'svd_u_d_2', 'svd_u_d_3', 'svd_u_d_4', 'svd_u_d_5', 'svd_u_d_6']] = \
df_final_train.destination_node.apply(lambda x: svd(x, U)).apply(pd.Series)
#=====

df_final_train[['svd_v_s_1', 'svd_v_s_2', 'svd_v_s_3', 'svd_v_s_4', 'svd_v_s_5', 'svd_v_s_6',]] = \
df_final_train.source_node.apply(lambda x: svd(x, V.T)).apply(pd.Series)

df_final_train[['svd_v_d_1', 'svd_v_d_2', 'svd_v_d_3', 'svd_v_d_4', 'svd_v_d_5', 'svd_v_d_6']] = \
df_final_train.destination_node.apply(lambda x: svd(x, V.T)).apply(pd.Series)
#=====

df_final_test[['svd_u_s_1', 'svd_u_s_2', 'svd_u_s_3', 'svd_u_s_4', 'svd_u_s_5', 'svd_u_s_6']] = \
df_final_test.source_node.apply(lambda x: svd(x, U)).apply(pd.Series)

df_final_test[['svd_u_d_1', 'svd_u_d_2', 'svd_u_d_3', 'svd_u_d_4', 'svd_u_d_5', 'svd_u_d_6']] = \
df_final_test.destination_node.apply(lambda x: svd(x, U)).apply(pd.Series)

#=====

df_final_test[['svd_v_s_1', 'svd_v_s_2', 'svd_v_s_3', 'svd_v_s_4', 'svd_v_s_5', 'svd_v_s_6',]] = \
df_final_test.source_node.apply(lambda x: svd(x, V.T)).apply(pd.Series)

df_final_test[['svd_v_d_1', 'svd_v_d_2', 'svd_v_d_3', 'svd_v_d_4', 'svd_v_d_5', 'svd_v_d_6']] = \
df_final_test.destination_node.apply(lambda x: svd(x, V.T)).apply(pd.Series)
#=====

hdf = HDFStore('data/fea_sample/assignment_storage_sample_stage4.h5')
hdf.put('train_df_assignment', df_final_train, format='table', data_columns=True)
hdf.put('test_df_assignment', df_final_test, format='table', data_columns=True)
hdf.close()

```

```

In [ ]: # prepared and stored the data from machine learning models
# pelase check the FB_Models.ipynb

```