

Solution to Introduction to the Theory of Computation

Lwins_Lights

Contents

1	Regular Languages	2
2	Context-Free Languages	3
3	The Church–Turing Thesis	4
4	Decidability	5
5	Reducibility	6
6	Advanced Topics in Computability Theory	8

1 Regular Languages

2 Context-Free Languages

3 The Church–Turing Thesis

4 Decidability

- 4.10 *Refer to the textbook.*
- 4.11 By the pumping lemma, $L(M)$ is an infinite language $\iff L(M)$ includes a string of length p . Since $R = \Sigma^p \Sigma^*$ is a regular language, it is easy to design a PDA P recognizing $L(M) \cap R$. Then use E_{PDA} 's decider to decide whether $L(M) \cap R = \emptyset$.
- 4.12 *Refer to the textbook.*
- 4.13 $L(R) \subseteq L(S) \iff L(R) \cup L(S) = L(S)$, which can be decided by EQ_{DFA} 's decider.
- 4.14 *Refer to the textbook.*
- *4.15 By the pumping lemma, $1^k \in L(G) \implies 1^{k+p!} \in L(G)$ for every $k \geq p$. Therefore $1^* \subseteq L(G) \iff \{1^k \mid k \leq p + p!\} \subseteq L(G)$, which can be easily checked by a TM in finite time.
- 4.16 Since $A = \{\langle R \rangle \mid R \text{ is a regular expression, } R \cap \Sigma^* 111 \Sigma^* \neq \emptyset\}$, we only need an E_{DFA} 's decider.
- 4.17 Suppose we have two DFAs D_1 and D_2 . Let D be a DFA recognizing $L(D_1) \oplus L(D_2)$, where \oplus means symmetric difference. By the pumping lemma, $L(D) \cap (\Sigma \cup \epsilon)^p = \emptyset \implies L(D) = \emptyset$, thus p can be the required length.
- *4.18 \Leftarrow : It is enough to design a TM, which recognizes C by checking whether $\langle x, y \rangle \in D$ for all possible y one by one.
 \Rightarrow : Suppose TM M recognizes C . Let $D = \{\langle x, y \rangle \mid x \in C \text{ and } y \text{ is the computation history of } M \text{ on input } x\}$, which is obviously decidable.
- *4.19 Let C be a recognizable but undecidable language, e.g., A_{TM} . Construct D provided by Problem 4.18. Letting homomorphism f satisfy $f(\langle x, y \rangle) = x$ for every x, y we obtain $f(D) = C$.
- 4.20 Let M be a TM which runs both \bar{A} 's recognizer and \bar{B} 's recognizer on its own input. M accepts when \bar{B} 's recognizer accepts and rejects when \bar{A} 's recognizer accepts. Clearly $C = L(M)$ separates A and B .
- 4.21 M is a DFA that accepts $w^{\mathcal{R}}$ whenever it accepts $w \iff L(M) = L(M)^{\mathcal{R}}$, which can be decided by EQ_{DFA} 's decider.
- 4.22 In order to determine whether $L(R)$ is prefix-free, it suffices to check whether the DFA recognizing $L(R)$ has the property that from a reachable accept state we could arrive an accept state again by several transitions.
- *4.23 *Refer to the textbook.*
- 4.24 A PDA $P = (Q, \Sigma, \Gamma, \delta, q_0, F)$ has an useless state $q \in Q$ if and only if PDA $P' = (Q, \Sigma, \Gamma, \delta, q_0, \{q\})$ recognizes \emptyset . Therefore we can use E_{PDA} 's decider to solve it.
- *4.25 *Refer to the textbook.*
- *4.26 M is a DFA that accepts some palindrome $\iff \text{CFL } \{w \mid w = w^{\mathcal{R}}\} \cap L(M) \text{ is not empty, which can be decided by } E_{\text{PDA}} \text{'s decider.}$
- *4.27 Refer to the solution to Problem 4.26.
- 4.28 x is a substring of some $y \in L(G) \iff L(G) \cap \Sigma^* x \Sigma^* \neq \emptyset$, which can be decided by E_{PDA} 's decider.
- 4.29 *Need a solution.*
- 4.30 *Need a solution.*
- 4.31 *Need a solution.*
- 4.32 *Need a solution.*

5 Reducibility

- 5.9 Reduce from A_{TM} . To determine whether TM M accepts w , construct TM N which always accepts 01 but accepts 10 if and only if M accepts w .
- 5.10 *Refer to the textbook.*
- 5.11 *Refer to the textbook.*
- 5.12 Reduce from E_{TM} . To determine whether TM M accepts nothing, construct TM N which simulates M on N 's own input w but never writes a blank symbol over a nonblank symbol unless when M accepts.
- 5.13 Reduce from E_{TM} . To determine whether TM M accepts nothing, construct TM N which simulates M on N 's own input w and obviously has no useless state except the one q_{accept} .
- 5.14 *Need a solution.*
- 5.15 Let M' be M after modifying all its transitions $\delta(q_i, a) = (q_{\text{accept}}, b, X)$ to $\delta(q_i, a) = (q_{\text{reject}}, b, X)$, and then modifying all $\delta(q_i, a) = (q_j, b, L)$ to $\delta(q_i, a) = (q_{\text{accept}}, b, R)$. The problem is now reduced to checking whether M' , as a *TM with stay put instead of left* described in Problem 3.13, accepts w . It is easy since $L(M')$ is regular by the solution to Problem 3.13.
- 5.16 Suppose for the sake of contradiction that BB is computable. Then obviously there exists a TM M having k states, which writes $BB(n) + 1$ 1s on the tape, when given input $\langle n \rangle$. Further, using M we can construct a series of TMs M_n having exactly $k + n/2$ states, which writes $BB(n) + 1$ 1s on the tape when started with a blank tape. However, then M_{2k} , as a $2k$ -state TM, would write $BB(2k) + 1$ 1s. Absurd.
- 5.17 *Need a solution.*
- 5.18 *Need a solution.*
- 5.19 *Need a solution.*
- 5.20 *Need a solution.*
- 5.21 The hint in the textbook is sufficient.
- 5.22 \Leftarrow : Trivial.
 \Rightarrow : Let $f(x) = \langle M, x \rangle$, where TM M is A 's recognizer.
- 5.23 \Leftarrow : Trivial, since 0^*1^* is surely decidable.
 \Rightarrow : Suppose there is an A 's decider, then f defined as follows is computable.
- $$f(x) = \begin{cases} 01, & x \in A \\ 10, & x \notin A \end{cases}$$
- 5.24 *Need a solution.*
- 5.25 $\overline{E_{\text{TM}}} \leq_m A_{\text{TM}}$ by Problem 5.22 and it is well known that $A_{\text{TM}} \leq_m E_{\text{TM}}$. By the way, it is not difficult to construct an undecidable language B such that $B =_m \overline{B}$.
- 5.26 *Need a solution.*
- 5.27 *Need a solution.*
- *5.28 *Refer to the textbook.*
- 5.29 The case P is not nontrivial is trivial. As for the second condition, let $P = \{\langle M \rangle \mid \text{TM } M \text{ has 100 states}\}$.
- 5.30 Trivial.

- 5.31 Let M be a TM which on input $\langle x \rangle$ ($x \in \mathbb{Z}^+$) calculates $x, f(x), f(f(x)), \dots$ until it finds some $f^{(n)}(x) = 1$, and then accepts. Let N be a TM uses H to calculate whether $\langle M, x \rangle \in A_{\text{TM}}$ for $x = 1, 2, \dots$ in order, until it finds some $\langle M, x \rangle \notin A_{\text{TM}}$, and then accepts. We have the positive answer to the $3x + 1$ problem if and only if $\langle N, 0 \rangle \notin A_{\text{TM}}$.
- 5.32 a. As hinted, reduce from PCP .
 b. Reduce from $OVERLAP_{\text{CFG}}$ by constructing a grammar whose rules are G 's and H 's rules and $S \rightarrow S_G\$ \mid S_H\$\$, where S_G and S_H are G 's and H 's start variables.$
- 5.33 *Need a solution.*
- 5.34 *Need a solution.*
- 5.35 *Need a solution.*
- *5.36 See <https://csttheory.stackexchange.com/q/39407/46760> for two different solutions.

6 Advanced Topics in Computability Theory

6.6 Let $M = P_{\langle N \rangle}$ and N print $\langle M \rangle = q(\langle N \rangle)$.

6.7 A TM that always loops.

*6.8 Suppose for the sake of contradiction that f is a reduction from EQ_{TM} to $\overline{EQ_{\text{TM}}}$. It is easy to generalize the fixed-point version of the recursion theorem to find $f(\langle M, N \rangle) = \langle M', N' \rangle$ such that M, N simulate M', N' respectively. Then $\langle M, N \rangle \in EQ_{\text{TM}} \iff \langle M', N' \rangle \in \overline{EQ_{\text{TM}}} \iff \langle M, N \rangle \in \overline{EQ_{\text{TM}}}$. Absurd.

6.9 Refer to the textbook.

6.10 Refer to the textbook.

*6.11 $(\mathbb{R}, =, <)$.

6.12 Refer to the textbook.

6.13 Since \mathbb{Z}_m is finite, any sentence in the language of \mathcal{F}_m can be decided by brute-force checking.

6.14 Let $J = 0A \cup 1B$.

6.15 Let $B = A_{\text{TM}}^A = \{\langle M^A, w \rangle \mid M^A \text{ accepts } w\}$. Then apply any classical method used in proving undecidability of A_{TM} .

*6.16 *Need a solution.*

*6.17 Let

$$\begin{aligned} A &= \{\langle M, w \rangle \mid \text{TM } M \text{ on input } w \text{ halts with 0 on its tape}\} \\ B &= \{\langle M, w \rangle \mid \text{TM } M \text{ on input } w \text{ halts with 1 on its tape}\} \end{aligned}$$

If there is a C 's decider N , we can construct TM M which on input w first run N on $\langle M, w \rangle$ to know that M would not halt with $x \in \{0, 1\}$ on M 's tape, and then violates it.

6.18 *Need a solution.*

6.19 $|\{L(M^A) \mid M^A \text{ is an oracle TM}\}| \leq |\{M^A \mid M^A \text{ is an oracle TM}\}| \leq \aleph_0 < 2^{\aleph_0} = |\{L \mid L \text{ is a language}\}|$.

6.20 *Need a solution.*

6.21 *Need a solution.*

6.22 *Need a solution.*

6.23 Reduce from Problem 6.24.

6.24 Reduce from Problem 6.25.

6.25 *Need a solution.*

*6.26 Suppose for the sake of contradiction that $K(xy) \leq K(x) + K(y) + c$ always holds. Define

$$f_n = \sum_{|x|=n} 2^{-K(x)}.$$

Then $K(xy) \leq K(x) + K(y) + c \implies f_{n+m} \geq 2^{-c} f_n f_m \implies f_{kn} \geq (2^{-c} f_n)^k$. On the other hand, Corollary 6.30 implies $f_n \leq n + 1$. Therefore,

$$f_n \leq 2^c \sqrt[k]{f_{kn}} \leq 2^c \sqrt[k]{kn + 1}.$$

Letting $k \rightarrow +\infty$ we obtain that $f_n \leq 2^c$ for all n . However, there is a TM M which on input $\langle p, q \rangle$ ($p, q \in \mathbb{N}$ and $q < 2^{2^p}$) halts with $r(p, q)$, a 2^p -bits binary representation of q , on its tape. So $K(r(p, q)) \leq 2 \log_2 p + \log_2 q + d$ with some constant d . Then, if $n = 2^p$ for some large p ,

$$f_n = \sum_{|x|=n} 2^{-K(x)} \geq \sum_{q < 2^n} 2^{-K(r(p, q))} \geq 2^{-2 \log_2 p - d} \sum_{q < 2^n} \frac{1}{q} \geq \frac{n}{2^d (\log n)^2},$$

which apparently contradicts with $f_n \leq 2^c$.

6.27 *Need a solution.*

- 6.28 a. $x = 0 \iff \forall y, x + y = y$
 b. $x = 1 \iff \forall y, y = 0 \wedge x + y = 1$
 c. $x = y \iff \forall z, z = 0 \wedge x + z = y$
 d. $x < y \iff \exists z, \neg(z = 0) \wedge x + z = y$