

# Biomedical Engineering

```
#load the libraries as usual
import matplotlib.pyplot as plt
import numpy as np
```

**(1) Type in the following commands, see what happens and interpret them**

```
data = np.random.random(size=(4, 6))
plt.imshow(data, interpolation='nearest')
plt.show()
print(data)
```

```
data = np.random.random(size=(11, 11))
data2 = np.round(data)
plt.imshow(data2, interpolation='nearest')
plt.show()
print(data2)
```

```
n = 11
data = np.zeros((n,n))

# (a) what is the effect of the following three lines
data[1,1] = 1
data[2,3] = 1
data[3,5] = 1
# (b) again what do the following two lines do?
data[5,1:n-1] = 1
data[n-2,:] = 1

print(data)
plt.imshow(data, interpolation='nearest')
plt.show()
```

```
# Here we practise 'for' loops
n = 11
data = np.zeros((n,n))


# (a) What is the effect of this 'for' loop?
for i in range(0,n):
    data[i,3] = 1

# (b) And this 'for' loop?
col = (n-1) // 2
for i in range(0,n,2):
    data[i,col] = 1


print(data)
plt.imshow(data, interpolation='nearest')
plt.show()
```

**(2) Let us switch gears. You are asked to reproduce the following images by replacing the ... dots with your own Python commands. Take advantage of the examples above.**


```
n = 11
data = np.zeros((n,n))
...
plt.imshow(data, interpolation='nearest')
plt.show()
```




```
n = 11
data = np.zeros((n,n))
...
plt.imshow(data, interpolation='nearest')
plt.show()
```




```
n = 11
data = np.zeros((n,n))
...
plt.imshow(data, interpolation='nearest')
plt.show()
```




```
n = 11
data = np.zeros((n,n))
...
plt.imshow(data, interpolation='nearest')
plt.show()
```




```
n = 11
data = np.zeros((n,n))
...
plt.imshow(data, interpolation='nearest')
plt.show()
```



```
n = 11
data = np.zeros((n,n))
...
plt.imshow(data, interpolation='nearest')
plt.show()
```



```
n = 501
r = n/2.0
data = np.zeros((n,n))
...
plt.imshow(data, interpolation='nearest')
plt.show()
```




**(3) Finally we want to load and display an external data set that contains Earth's elevation and pessimetry data of grid of longitude and latitude points**

```
#The following command will fail if you do not have the 'topography_180x360_grid.txt'
#file in current folder
H = np.loadtxt('topography_180x360_grid.txt')
print(H)
print(H.shape)
```

```
# Now you should simply be in awe
plt.imshow(H, interpolation='nearest')
plt.show()
```


**(3a) Insert one commnd and cover the continent of Australia with a yellow rectangle. Set the values in the rectangle to -10000.**

```
H2 = H
...
plt.imshow(H2, interpolation='nearest')
plt.show()
```



**(3b) Insert one command and cover the continent of South American with a blue rectangle. Set the values in the rectangle to +10000.**


```
H3 = H
...
plt.imshow(H3, interpolation='nearest')
plt.show()
```



```
#Try the following commands. The result will be very odd. What happened to the H array?
H4 = H
plt.imshow(H4, interpolation='nearest')
plt.show()
```


**(3c) Load the 'topography180x360grid.txt' file again. For all points with elevations above 2000 m, set the elevation to 10000 m. For all points with a pessimetry of more then 2000 m, set the elevation to -10000 m.**

```
H4 = np.loadtxt('topography_180x360_grid.txt')
...
plt.imshow(H4, interpolation='nearest')
plt.show()
```




**(3d) In addition to the modifications in (3c), now also change the elevation to zero if the original elevation was betweenb -2000 and +2000 m.**

```
H4 = np.loadtxt('topography_180x360_grid.txt')
...
plt.imshow(H4, interpolation='nearest')
plt.show()
```



**(3e) From the movie "Black Panther", we learn that Wakanda is the center of the modern world. Now shift our map in east-west direction so that Africa appears in the map's center as shown below.**

```
#Accommodating Wakanda
H5 = np.copy(H4);
...
plt.imshow(H5, interpolation='nearest')
plt.show()
```



**(3f) Let us practise the np.append command. Just type in the commands to see what happens.**

```
H = np.loadtxt('topography_180x360_grid.txt')
HH = np.append(H,H,axis=0)
plt.imshow(HH, interpolation='nearest')
plt.show()
```

```
H = np.loadtxt('topography_180x360_grid.txt')
HH = np.append(H,H,axis=1)
HHHH = np.append(HH,HH,axis=1)
plt.imshow(HHHH, interpolation='nearest')
plt.show()
```

```
H = np.loadtxt('topography_180x360_grid.txt')
nx = H.shape[0]
ny = H.shape[1]
print(nx,ny)
Extra = np.zeros([100,ny])
HExtra = np.append(H,Extra,axis=0)
plt.imshow(HExtra, interpolation='nearest')
plt.show()
```