

Complete Payment API Integration Guide (PHP)

This document explains how to integrate the Create Order and Check Order Status APIs from:

<https://cash.free.jzstore.in>

1. CREATE ORDER API (PHP Integration)

URL:

<https://cash.free.jzstore.in/api/create-order>

Sample PHP Code:

```
<?php
define('PAY_API_URL', 'https://cash.free.jzstore.in/api/create-order');
define('USER_TOKEN', '509ffd178aff24dc09640796da90fc22');

$customer_mobile = '8145344963';
$order_id = time() . rand(1000, 9999);
$amount = '1.00';
$redirect_url = 'https://yourdomain.com/payment/success.php';
$remark1 = 'testremark';
$remark2 = 'testremark2';

$data = [
    'customer_mobile' => $customer_mobile,
    'user_token'      => USER_TOKEN,
    'amount'          => $amount,
    'order_id'        => $order_id,
    'redirect_url'     => $redirect_url,
    'remark1'         => $remark1,
    'remark2'         => $remark2
];
```

```

$ch = curl_init(PAY_API_URL);
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
curl_setopt($ch, CURLOPT_POST, true);
curl_setopt($ch, CURLOPT_POSTFIELDS, http_build_query($data));

$response = curl_exec($ch);
curl_close($ch);

$result = json_decode($response, true);

if ($result['status'] === true) {
    echo "<h3>Order Created Successfully</h3>";
    echo "Order ID: " . htmlspecialchars($result['result']['orderId']) . "<br>";
    echo "<a href=\"" . htmlspecialchars($result['result']['payment_url']) . "\" target='_blank'>Pay Now</a>";
} else {
    echo "<h3>Failed: " . htmlspecialchars($result['message']) . "</h3>";
}
?>

```

--- 2. CHECK ORDER STATUS API (PHP Integration) ---

URL:

<https://cash.free.jzstore.in/api/check-order-status>

Sample PHP Code:

```

<?php
define('PAY_STATUS_URL', 'https://cash.free.jzstore.in/api/check-order-status');
define('USER_TOKEN', '509ffd178aff24dc09640796da90fc22');

$order_id = '8787772321800';

```

```

$data = [
    'user_token' => USER_TOKEN,
    'order_id' => $order_id
];

$ch = curl_init(PAY_STATUS_URL);
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
curl_setopt($ch, CURLOPT_POST, true);
curl_setopt($ch, CURLOPT_POSTFIELDS, http_build_query($data));

$response = curl_exec($ch);
curl_close($ch);

$result = json_decode($response, true);

if (!empty($result['status']) && $result['status'] === true) {
    echo "<h3>Order Found</h3>";
    echo "<pre>" . print_r($result, true) . "</pre>";
} else {
    echo "<h3>Failed: " . htmlspecialchars($result['message'] ?? 'Unknown error') . "</h3>";
}

?>

```

NOTES:

- Order Timeout: 30 minutes (auto-fails if unpaid).
- Always generate unique order_id for each transaction.
- Use HTTPS URLs in redirect_url.
- Sanitize responses before displaying them.
- Store order details in your database before redirecting to payment page.

