

What Are Agents? And How Do They Work?


From language modeling to systems that act in the world

Carnegie Mellon University
Language Technologies Institute

Daniel Fried · Graham Neubig

11-768: AI Agents


How capable are current agents?




Sixteen agents built a 100,000-line C compiler in two weeks—able to compile the Linux kernel.

Building a C compiler with a team of parallel Claudes · Carlini, Anthropic 2026 ↗

How capable are current agents?





Summer Yue (@summeryue0) · X, February 2026 ↗


How capable are current agents?

What should an agent be allowed to do autonomously?


Autonomous · Ask first · Never

Diagnose why the online store's checkout started failing UNCLASSIFIED	**Draft and send a product-launch email to 50,000 customers** UNCLASSIFIED	**Collect your tax forms, and prepare and file your 2025 tax return** UNCLASSIFIED
Migrate a payments API from Python to Rust without breaking mobile checkout UNCLASSIFIED	**Buy concert tickets to my favorite band if they set up a show in my area** UNCLASSIFIED	**Adjust an insulin dose after a week of glucose readings** UNCLASSIFIED





Jing Yu Koh · multimodal GUI-agent demo · 2024



Graham Neubig · OpenHands visual debugging

Meet the teaching team

Instructors



Daniel Fried



Graham Neubig

TAs




Aditya Soni



Andy Liu



Apurva Gandhi



Demi Wang




Jiarui Liu



Saujas Vaduguru



Weiwei Sun



Yueqi Song

Compute sponsors

Thanks to these sponsors for providing compute for the assignments and project!








What is an agent?

An agent is anything that can be viewed as perceiving its environment through sensors and acting upon that environment through actuators.

Russell & Norvig, *Artificial Intelligence: A Modern Approach*



- **Environment:** a repository, website, application, or workflow
- **State/Observations:** messages, file contents, webpages, screenshots, and tool results
- **Actions:** replies, file edits, shell commands, API calls, and mouse or keyboard events
- **Reward:** passing test cases, satisfying LLM-as-a-judge rubrics, positive user feedback


Recap: language models

Next-token prediction

- At each step, predict a distribution over the next token.
- Append the generated token to the prefix and predict again.

Chain of thought

- Generate intermediate reasoning tokens before the answer.
- Those tokens become context for later predictions.



Tool definition

A typed interface exposed to the model.

- Name and description
- JSON Schema for arguments
- The chat template renders it as text

```
{
  "name": "read_file",
  "description": "Read a UTF-8 file.",
  "parameters": {
    "type": "object",
    "properties": { "path": { "type": "string" } },
    "required": ["path"]
  }
}
```

Example after `apply_chat_template`

```
<tools>
{"name":"read_file","description":"Read a UTF-8 file.",
 "parameters":{"type":"object","properties":{"path":{"type":"string"}},
 "required":["path"]}}
</tools>
```

Tool calls and results

Tool call

```
{"role":"assistant","tool_calls":[{
  "id":"call_7",
  "name":"read_file",
  "arguments":{"path":"test.py"}
}]}
```

After `apply_chat_template`

```
<tool_call>
{"name":"read_file","arguments":{"path":"test.py"}}
</tool_call>
```

Tool result

```
{"role":"tool",
 "tool_call_id":"call_7",
 "name":"read_file",
 "content":"def add(a, b): …"}
```

After `apply_chat_template`

```
<tool_response>
def add(a, b): …
</tool_response>
```


From LLMs to agents: actions as tokens

Language model

- A tool call is another token sequence the model can predict.
- The sequence names a tool and supplies its arguments.


Harness

- Parses, validates, and executes the call.
- Returns the result as observation tokens.



Toolformer · Schick et al., NeurIPS 2023 ↗

An agent is a model in a loop



ReAct · Yao et al., ICLR 2023 ↗

A minimal ReAct loop

mini-swe-agent

Browse the full source: Loop → Templates →

```python
def run(self, task: str = "", **kwargs) -> dict:
    self.messages = []
    self.add_messages(
        self.model.format_message(role="system", content=self._render_template(self.config.system_template)),
        self.model.format_message(role="user", content=self._render_template(self.config.instance_template)),
    )

    while True:
        self.step()

def step(self) -> list[dict]:
    return self.execute_actions(self.query())


def query(self) -> dict:
    message = self.model.query(self.messages)
    self.add_messages(message)
    return message

def execute_actions(self, message: dict) -> list[dict]:
    """Execute actions in message, add observation messages, return them."""
```

Assignment 1: implement and extend a similar controller; create and call your own tools; apply it to software tasks.

Example agent trajectory

swebench.com ↗



Agent capabilities

1. **Accurate tool calling**
2. **Coherence over long context**
3. **Customizability**
4. **Complex task management**
5. **Environment understanding**
6. **Safety**


Two ways to build these capabilities

LLM training

- Change the model's behavior through pretraining, SFT, or RL.
- Teach reusable patterns for reasoning, tool use, and recovery.
- Capabilities become part of the learned policy.

Harness engineering

- Change the system around the model: prompts, tools, memory, and control flow.
- Provide context, validation, retries, and safety boundaries.
- Capabilities emerge from the model–harness combination.



How agent behavior is trained

01

Pretraining

Text, code, multimodal data
Broad representations and regularities

02

Mid-training / SFT

Instructions, traces, tool calls
Formats and demonstrations

03

RL

Rewards or preferences
Trajectory-level behavior

Accurate tool calling

Harness engineering

- Grammar-constrained decoding.

LLM training

- **SFT:** train on tool-calling traces.




Coherence over long context

Harness engineering

- Context compression/compaction.
- Dynamic memory lookup.
- Sub-agent delegation.

LLM training

- **SFT:** long-context training.



Customizability

Harness engineering

- Agent memory.
- Skills.
- Custom tools.

LLM training

- **RL:** learning from user feedback.




Complex task management

Harness engineering

- Provide planning/decomposition tools.
- Sub-agent delegation.

LLM training

- **RL:** train on complex, long-horizon tasks.



Environment understanding

Harness engineering

- Learn skills corresponding to domain knowledge.

LLM training

- **SFT:** train on data w/ expected observation shape.
- **RL:** train in domain-specific environments.




Safety

Harness engineering


- Sandboxing tools.
- Limit access to credentials.
- Monitor trajectories.

LLM training

- **RL:** safety-aware RL.



Agents are systems, not just models




Harness engineering

Shared functionality

- Manage state, tools, memory, and control flow
- Validate actions and handle errors
- Enforce permissions and safety boundaries

Example software:

- **Coding agents:** CC, Codex, OpenHands, OpenCode, Pi
- **Orchestrators:** LangChain, CrewAI




Sandbox

Shared functionality

- Isolate code and tool execution
- Limit compute, network, and filesystem access
- Create reproducible environments

Example software:

- Docker / Apptainer
- Modal / Sail




LM inference

Shared functionality

- Serve model generations reliably
- Batch requests and reuse the KV cache
- Manage streaming, parallelism, and throughput

Example software:

- vLLM
- SGLang




Training systems

Shared functionality

- Prepare data and collect rollouts
- Coordinate distributed workers
- Checkpoint, evaluate, and reproduce runs

Example software:

- SkyRL
- Miles



Observability and monitoring

Shared functionality

- Capture traces and metrics
- Track quality, cost, and failures
- Compare trajectories and evaluations

Example software:

- Laminar
- MLFlow



What you should be able to do

1. Implement an agent from scratch on top of an open-source LLM.
2. Design evaluations for multi-step tasks.
3. Train agents to improve their capabilities.
4. Reason about safety and reliability tradeoffs.
5. Pursue an open research question in agents.



06 · ASSIGNMENTS

Learn by building and measuring

A1 · Harness

TENTATIVE DUE: THU, SEP 10

Build the basic infrastructure and establish a reproducible baseline.

A2 · Evaluation

TENTATIVE DUE: THU, SEP 24

Measure behavior, report failure cases, and distinguish demos from evidence.

A3 · Training

TENTATIVE DUE: THU, OCT 22

Train or adapt a component; analyze behavior, cost, and robustness.

Project

Integrate the ideas around a scoped task, environment, and evaluation.

Semester schedule

Aug 25 – Sep 8

Agent capabilities
what is an agent · tools · context · memory · planning

Sep 10 – Sep 15

Domains
coding · GUI

Sep 17 – Oct 1

Training + domains
SFT · RL basics · deep research · advanced RL

Oct 6 – Oct 22

Frameworks + safety
sandboxes · OpenHands · LangGraph
Fall break: Oct 12–16

Oct 27 – Nov 5

Interaction + projects
people · multi-agent · project hours

Nov 10 – Dec 3

Advanced topics + presentations
future of work · search · posters
Thanksgiving: Nov 25–27

Before we begin: prerequisites

- This course requires prior serious experience training a language model.
- We'll share a link to a Google form on Piazza. Submit the form by **Thursday, Aug 27** so that we can finalize enrollment.
- In the form, tell us about a university course with an LM-training assignment: the course, assignment link, term, and grade.
- If you lack the formal prerequisite, explain comparable experience—such as pre/post-training work or published research training 4–7B+ language models.
- We will enforce the prerequisite strictly; students who cannot meet it will be asked to drop the course.

How course work adds up

- **Assignments 1–3:** 40% total, completed individually.
- **Lecture highlights:** 10% total, completed individually; due within 24 hours after each lecture, starting Thursday.
- **Research project:** 50% total, in teams of 2–3.
- Proposal 5% · check-in 5% · presentation 10% · final report 30%.
- Assignment descriptions and Canvas provide the authoritative requirements and deadlines.




Using Agents in This Class?

- We acknowledge that you use agents day-to-day, but we also want you to learn how to build, evaluate, and reason about them yourself.
- AI tools are generally permitted unless a specific assignment or project writeup says otherwise.
- Lecture highlights must be written by you, not generated by AI.
- You are responsible for every submitted claim, citation, result, and line of code—and will be quizzed on it.

Deadlines, submission, and slack

- Assignments 1–3 each include two 24-hour slack days.
- Slack days are attached to each assignment: they cannot be transferred or shared.
- After slack days are used, the penalty is 5% of the assignment score per additional day or part-day.
- Project proposal and report each have two slack days; the presentation has none.





Thank you, Questions?

Next Class: Agent Capabilities 1 — Tool Use