

LABORATORY PROGRAM – 5

Implement Wordcount program on Hadoop framework

OBSERVATION

CODE, COMMAND WITH OUTPUT

Driver Code

```
// Importing libraries
import java.io.IOException;
import org.apache.hadoop.conf.Configured;
import org.apache.hadoop.fs.Path;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapred.FileInputFormat;
import org.apache.hadoop.mapred.FileOutputFormat;
import org.apache.hadoop.mapred.JobClient;
import org.apache.hadoop.mapred.JobConf;
import org.apache.hadoop.util.Tool;
import org.apache.hadoop.util.ToolRunner;

public class WCDriver extends Configured implements Tool {

    public int run(String[] args) throws IOException {
        if (args.length < 2) {
            System.out.println("Please give valid inputs");
            return -1;
        }

        JobConf conf = new JobConf(WCDriver.class);
        conf.setJobName("WordCount");

        FileInputFormat.setInputPaths(conf, new Path(args[0]));
        FileOutputFormat.setOutputPath(conf, new Path(args[1]));

        conf.setMapperClass(WCMapper.class);
        conf.setReducerClass(WCReducer.class);

        conf.setMapOutputKeyClass(Text.class);
        conf.setMapOutputValueClass(IntWritable.class);

        conf.setOutputKeyClass(Text.class);
        conf.setOutputValueClass(IntWritable.class);

        JobClient.runJob(conf);
        return 0;
    }

    // Main Method
    public static void main(String[] args) throws Exception {
        int exitCode = ToolRunner.run(new WCDriver(), args);
        System.out.println("Job Exit Code: " + exitCode);
    }
}
```

Mapper Code

```
// Importing libraries
import java.io.IOException;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.LongWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapred.MapReduceBase;
import org.apache.hadoop.mapred.Mapper;
```

```

import org.apache.hadoop.mapred.OutputCollector;
import org.apache.hadoop.mapred.Reporter;

public class WCMapper extends MapReduceBase implements Mapper<LongWritable, Text, Text, IntWritable> {

    // Map function
    public void map(LongWritable key, Text value, OutputCollector<Text, IntWritable> output, Reporter reporter)
        throws IOException {
        String line = value.toString();

        // Splitting the line on whitespace
        for (String word : line.split("\\s+")) {
            if (word.length() > 0) {
                output.collect(new Text(word), new IntWritable(1));
            }
        }
    }
}

```

Reducer Code

```

// Importing libraries
import java.io.IOException;
import java.util.Iterator;

import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapred.MapReduceBase;
import org.apache.hadoop.mapred.OutputCollector;
import org.apache.hadoop.mapred.Reducer;
import org.apache.hadoop.mapred.Reporter;


public class WCReducer extends MapReduceBase implements Reducer<Text, IntWritable, Text, IntWritable> {

    // Reduce function
    public void reduce(Text key, Iterator<IntWritable> values,
        OutputCollector<Text, IntWritable> output,
        Reporter reporter) throws IOException {
        int count = 0;

        // Counting the frequency of each word
        while (values.hasNext()) {
            count += values.next().get();
        }

        output.collect(key, new IntWritable(count));
    }
}

```



```

hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~$ cd ./Desktop/
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ start-all.sh
WARNING: Attempting to start all Apache Hadoop daemons as hadoop in 10 seconds.
WARNING: This is not a recommended production deployment configuration.
WARNING: Use CTRL-C to abort.
Starting namenodes on [localhost]
Starting datanodes
Starting secondary namenodes [bmscecse-HP-Elite-Tower-800-G9-Desktop-PC]
Starting resourcemanager
Starting nodemanagers
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hdfs dfs -mkdir /Lab06
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hadoop fs -ls /Lab06

```

```

hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ jps
7360 DataNode
7928 ResourceManager
8681 Jps
7178 NameNode
8091 NodeManager
7644 SecondaryNameNode
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ cd ..
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~$ cd ./Desktop/
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ nano file1.txt

```

```

hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hadoop fs -copyFromLocal -f /home/hadoop/Desktop/file1.txt /rgs/test.txt
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hadoop jar /home/hadoop/Desktop/WordCount.jar wordcount.WordCount /rgs/test.txt /output
JAR does not exist or is not a normal file: /home/hadoop/Desktop/WordCount.jar
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hadoop jar /home/hadoop/Desktop/Word_Count.jar wordcount.WordCount /rgs/test.txt /output
Exception in thread "main" java.lang.ClassNotFoundException: wordcount.WordCount
    at java.base/java.net.URLClassLoader.findClass(URLClassLoader.java:476)
    at java.base/java.lang.ClassLoader.loadClass(ClassLoader.java:594)
    at java.base/java.lang.ClassLoader.loadClass(ClassLoader.java:527)
    at java.base/java.lang.Class.forName0(Native Method)
    at java.base/java.lang.Class.forName(Class.java:398)
    at org.apache.hadoop.util.RunJar.run(RunJar.java:321)
    at org.apache.hadoop.util.RunJar.main(RunJar.java:241)
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hadoop fs -cat /output/part-00000
are 1
brother 1
family 1
hi 1
how 5
is 4
job 1
sister 1
you 1
your 4
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hadoop fs -ls /output
Found 2 items
-rw-r--r-- 1 hadoop supergroup 0 2024-05-21 15:21 /output/_SUCCESS
-rw-r--r-- 1 hadoop supergroup 69 2024-05-21 15:21 /output/part-00000

```