

Lecture 2: Neuron models and basic learning rules

Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-1

Contents of this lecture


- After this lecture, you should know
 - How a neuron works?
 - Some basic neuron models.
 - Basic steps for using a neural network.
 - General learning rule for one neuron.
 - Learning of discrete neuron.
 - Learning of continuous neuron.
 - Learning of single layer NNs with discrete neurons.
 - Learning of single layer NNs with continuous neurons.

Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-2

How "large" is a human brain ?

- A neuron is the basic element in a biological brain.
- There are approximately 100,000,000,000 neurons in a human brain.
- One neuron is connected with approximately 10,000 other neurons.
- The human brain is very large and very complex system.
- Although each neuron is slow, un-reliable, and non-intelligent, the whole brain can make decisions very quickly, in a relatively reliable and intelligent way.




Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-3

What is a bio-neuron?

- A B-neuron contains
 - a cell body for signal processing,
 - many dendrites to receive signals,
 - an axon for outputting the result, and
 - a synapse between the axon and each dendrite.




From Wikipedia

Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-4

A neuron works as follows

- Signals (impulses) come into the dendrites through the synapses.
- All signals from all dendrites are summed up in the cell body.
- When the sum is larger than a threshold, the neuron fires, and sends out an impulse signal to other neurons through the axon.




From Wikipedia

Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-5

The McCulloch-Pitts neuron model

- Proposed by McCulloch and Pitts in 1943.
- A processor (system) with multiple input and a single output.
- Effective input: weighted sum of all inputs.
- Bias or threshold: if the effective input is larger than the bias, the neuron outputs a one, otherwise, it outputs a zero.



Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-6

Some terminologies

- The parameters used to scale the inputs are called the **weights**.
- The **effective input** is the weighted sum of the inputs.
- The parameter to measure the switching level is the **threshold** or bias.
- The function for producing the final output is called the **activation function**, which is the step function in the McCulloch-Pitts model.

$$o = f\left(\sum_{i=1}^n w_i x_i - T\right)$$

$$f(u) = \begin{cases} 1 & \text{if } u \geq 0 \\ 0 & \text{otherwise} \end{cases}$$

Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-7


Generalization of the neuron model

- In general, there are many different kinds of activation functions.
- The step function used in the McCulloch-Pitts model is simply one of them.
- Because the activation function takes only two values, this model is called **discrete neuron**.
- To make the neuron learnable, some kind of continuous function is often used as the activation function. This kind of neurons are called **continuous neurons**.
- Typical functions used in an artificial neuron are sigmoid functions, radial basis function, sinusoidal functions, etc.

Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-8

Activation function of continuous neuron: sigmoid function




(Fig. 2.5 in the textbook written by Prof. Zurada)

Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-9


A neuron model with augmented input



Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-10

Single layer neural network and multi-layer neural network



Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-11


Basic steps for using a neural network

- **Learning:** to store the information into the network.
 - Supervised and unsupervised learning.
 - On-line learning and off-line learning.
- **Recall:** to retrieve information stored in the network.
 - Auto-association and hetero-association.
 - Classification and/or recognition.

Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-12

Basic Diagram of Learning



Teacher signal available: supervised learning

Teacher signal un-available: un-supervised learning

Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-13

Basic diagram of recall



Auto-association: The output is the same pattern as the input.

Hetero-association: The output is a different representation of the input pattern.

Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-14

General learning rule for one neuron

$$W^{k+1} = W^k + crx$$

- c is a learning constant.
- r is the learning signal, which is a function of
 - W : the current weight vector
 - x : the input vector

Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-15

Perceptron learning rule

$$W^{k+1} = W^k + crx$$

c : learning constant in $[0,1]$

$$r = d - f(u)$$

d : given teacher signal

$$u = \langle W^k, x \rangle$$

$$f(u) = \begin{cases} 1 & \text{if } u > 0 \\ -1 & \text{if } u < 0 \end{cases}$$

W^0 : Given at random

This is a supervised learning rule because teacher signals are required

Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-16

Delta learning rule

$$W^{k+1} = W^k + crx$$

c : learning constant in $[0,1]$

$$r = [d - f(u)]f'(u)$$

d : given teacher signal

$$u = \langle W^k, x \rangle$$

$f(u)$: sigmoid function


W^0 : Given at random

This is also a supervised learning rule because teacher signals are required

Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-17


Program for perceptron learning



Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-18

Program for delta rule




Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-19

Example 1

- There are four training examples shown in the left figure:
 - $(1,1), (1,-1), (-1,1)$ and $(-1,-1)$
- The teacher signals are
 - $-1, 1, 1,$ and -1
- That is, we want to divide the data into two groups using a line




Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-20

How to classify the data using one neuron?

$$\forall x = [x_1, x_2, -1]^T$$

if $(w_1 x_1 + w_2 x_2 - w_3 \geq 0)$ $o = 1$
else $o = -1$



1. The input is augmented with an extra element fixed to -1.
2. If effective input is larger than or equal to zero, the input belongs to group 1.
3. Otherwise, the input is in group 2.

Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-21


Results of perceptron learning

The initial weights:
(0.811319 0.102490 0.100490)

The error in the 1st learning cycle is 2.000000
The connection weights of the neurons are
(-0.188681 1.102490 -0.899510)

The error in the 2nd learning cycle is 4.000000
The connection weights of the neurons are
(1.811319 1.102490 -0.899510)

The error in the 3rd learning cycle is 0.000000
The connection weights of the neurons are
(1.811319 1.102490 -0.899510)




Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-22

Results of delta learning

Error in the 161-th learning cycle=0.010610
Error in the 162-th learning cycle=0.010541
Error in the 163-th learning cycle=0.010472
Error in the 164-th learning cycle=0.010405
Error in the 165-th learning cycle=0.010338
Error in the 166-th learning cycle=0.010273
Error in the 167-th learning cycle=0.010208
Error in the 168-th learning cycle=0.010144
Error in the 169-th learning cycle=0.010081
Error in the 170-th learning cycle=0.010018
Error in the 171-th learning cycle=0.009956

The connection weights of the neurons:
3.165432 3.167550 -3.163318




Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-23

Single layer neural network for solving multi-class problems

- There are J inputs and K outputs.
- The last input is fixed to -1 (dummy input).
- For a given input vector y
 - The effective input of the k-th neuron is net_k
 - The actual output of the k-th neuron is o_k
 - The desired output of the k-th neuron is d_k
 - The error to be minimized is E.



Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-24

Learning of single layer network


- The learning of a single layer network can be performed by adopting the perceptron learning rule or the delta learning rule separately to each neuron.
- The only thing to do is to add one more LOOP in the program.

Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-25

Example 2

- Find a single layer neural network with two discrete neurons.
- One is to realize the AND gate, and another is to realize the OR gate.



Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-26

Numerical results for the example

The initial condition:

$W[0]: 0.248875 \ 0.165883 \ 0.093191$

$W[1]: 0.111389 \ 0.443656 \ 0.543946$

For the 1-th learning cycle:

The error is 6.000000

$W[0]: 1.248875 \ 1.165883 \ -0.906809$


$W[1]: 0.111389 \ 0.443656 \ 0.543946$

For the 2-th learning cycle:

The error is 0.000000

$W[0]: 1.248875 \ 1.165883 \ -0.906809$

$W[1]: 0.111389 \ 0.443656 \ 0.543946$



Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-27

Team Project I: Part 1

- Write a computer program to realize the perceptron learning rule and the delta learning rule.
- Train a neuron using your program to realize the AND gate. The input pattern and their teacher signals are given as follows:
 - Data: (0,0,-1); (0,1,-1); (1,0,-1); (1,1,-1)
 - Teacher signals: -1, -1, -1, 1
- Program outputs:
 - Weights of the neuron, and
 - Neuron output for each input pattern.

Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-28

Remarks

- The program given in the web page is for delta learning rule only. You should extend this program for this homework.
- The learning process is iterative. You should provide the data one by one, and start from the first datum again when all data are used once.
- One learning cycle is called an epoch.
- The total errors for all data is used as the terminating condition.
- From this experiment we can see that a neuron can be used to realize an AND gate.

Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-29

Team Project I: Part 2

- Extend the program written in the first step to learning of single layer neural networks.
- The program should be able to design
 - Case 1: A single layer neural network with discrete neurons.
 - Case 2: A single layer neural network with continuous neurons.
- Test your program using the following data
 - Inputs: (10,2,-1), (2,-5,-1), (-5,5,-1).
 - Teacher signals: (1,-1,-1), (-1,1,-1), and (-1,-1,1)

Produced by Qiangfu Zhao (Sine 1997), All rights reserved ©

Lecture 2-30