


1.Create A new component which have news title(should print as h2), news detail(), published date, source create this component using sling model. NewsModel.java @Model(adaptables = Resource.class, defaultInjectionStrategy = DefaultInjectionStrategy.*OPTIONAL*) public class NewsModel { @Inject private String text; @Inject private String newsDetail; @Inject private Calendar publishedDate; // FIXED: Changed to Calendar type public String getText() { return text; } public String getNewsDetail() { return newsDetail; } public String getFormattedPublishedDate() { if (publishedDate != null) { SimpleDateFormat sdf = new SimpleDateFormat("dd MMM yyyy"); return sdf.format(publishedDate.getTime()); // FIXED: Now works with Calendar return "N/A"; News.html <h2 class="cmp-news title">News Component</h2>

Text:

Published Date:







2.Create multi field component(multiple news) using sling model fields: title of new and source of news




3. Create clientlibs for news component

```
✓ inews
> inews
> ineq_dialog
✓ inex
```


```
.cmp-news__title {
    color: green;
}
.cmp-news__label {
    color: yellow;
}
.cmp-news__output {
    color: black;
}
```

4.Apply Green colour to the heading(h2) and yellow colour to news detail(<p) and date should be black in colour.



5.Add Component style to add custom style name (cop-news-component) in news component

content.xml



Component Path: /apps/news/components/basepage

basepage.html

7.Create custom page properties saying Global properties and 3 fields should be there as og:title, og:description and og:image path.

dialog.xml

```
<jcr:root xmlns:jcr="http://www.jcp.org/jcr/1.0"
xmlns:sling="http://sling.apache.org/jcr/sling/1.0"
jcr:primaryType="cq:Dialog"
cq:dialogMode="floating">
<content jcr:primaryType="nt:unstructured">
<items jcr:primaryType="nt:unstructured">
<ogTitle
jcr:primaryType="nt:unstructured"
sling:resourceType="granite/ui/components/coral/foundation/form/textfield"
fieldLabel="OG Title"</pre>
```

```
name="./ogTitle"/>
<ogDescription
jcr:primaryType="nt:unstructured"
sling:resourceType="granite/ui/components/coral/foundation/form/textarea"
fieldLabel="OG Description"
name="./ogDescription"/>
<ogImage
jcr:primaryType="nt:unstructured"
sling:resourceType="granite/ui/components/coral/foundation/form/textfield
```

8. What is extraclientlib add it this multi field component

The extraclientlib property adds additional client libraries (CSS, JS) to the multi-field component, allowing custom styling and JavaScript logic.

Why Use extraClientLibs?

- Helps extend functionality without modifying core component clientlibs.
- Useful for adding custom JavaScript or styles specific to a component.
- Allows separation of concerns, keeping core and additional scripts/styles modular.
- Makes debugging and maintenance easier by loading external scripts as needed