RideShare Botswana: getting it running

You only need this if you are running the app on your own phone. The back end (Supabase) and the Google keys already live in the cloud, so you do NOT deploy anything.

Steps

1. Install **Node.js (LTS)** from https://nodejs.org
2. Install **Expo Go** on your phone and use the same Wi-Fi as your computer.
3. Put `setup.bat` (Windows) or `setup.sh` (Mac/Linux) in the project folder, the one with `package.json`.
4. Double-click `setup.bat`, or run `bash setup.sh`. It installs the packages, checks the two sign-in packages (`npx expo install @react-native-async-storage/async-storage react-native-url-polyfill`, then `npm ls` on both), and asks for the Supabase URL and anon key to make your `.env`. At the end it asks about deploying the Edge Functions. Everyone except the Supabase owner answers **n**.
5. Start the app: `npx expo start -c`, then scan the QR code with Expo Go.
6. Sign up inside the app with your own email. Test with two accounts: one driver, one passenger.

If something goes wrong

- **"You need to be signed in to Expo Go and Expo CLI"** (iPhone): sign in to the same Expo account in Expo Go, and on the computer set an `EXPO_TOKEN` (made at expo.dev, Account settings, Access tokens). `npx expo login` can crash in the Windows terminal, so the token is the safer way.
- **App can't load or shows old code:** stop it, then `npx expo start -c`.
- **Sign-in or data errors:** check `.env` has no spaces or quotes, then restart with `-c`.
- **Phone can't find the computer:** same Wi-Fi, and allow Node through the Windows firewall.
- **"Function not found in schema cache"** after new SQL: whoever owns Supabase runs `notify pgrst, 'reload schema';` in the SQL Editor.

Keep private

- Never commit `.env` or share the Supabase `service_role` key.
- Only the Supabase owner needs the deploy commands and the SQL files. The script runs them if you answer **y**:

```
```

```
npx supabase functions deploy search-places --use-api --project-ref lagqmieiuhpguuqydtzp
npx supabase functions deploy compute-route --use-api --project-ref lagqmieiuhpguuqydtzp
npx supabase functions deploy find-matches --use-api --project-ref lagqmieiuhpguuqydtzp
```

The Google key is a Supabase secret (`GOOGLE_ROUTES_API_KEY`, dashboard > Edge Functions > Secrets), not a file.