




All devices

Filter

- ATM switch
- cisco7200
- Cloud
- Ethernet hub
- Ethernet switch
- Frame Relay switch
- NAT
- VPCS

+ New template

SSH Login:



Topology Summary

Node	Console
R1	telnet localhost:5010
R2	telnet localhost:5000

Servers Summary

Sowmith CPU 21.2%, RAM 62.1%

Console

GNS3 management console.
Running GNS3 version 2.2.61 on Windows (64-bit) with Python 3.13.14 Qt 6.10.0 and PyQt 6.10.2.
Copyright (c) 2006-2026 GNS3 Technologies.
Use Help -> GNS3 Doctor to detect common issues.

=>

Wireshark · Packet 14 · Standard input

▶ Frame 14: Packet, 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface -, id 0

▶ Ethernet II, Src: ca:02:66:8c:00:1c (ca:02:66:8c:00:1c), Dst: ca:01:a2:ec:00:1c (ca:01:a2:ec:00:1c)

▶ Internet Protocol Version 4, Src: 192.168.1.2, Dst: 192.168.1.1

▼ Transmission Control Protocol, Src Port: 45176, Dst Port: 22, Seq: 0, Len: 0

Source Port: 45176

Destination Port: 22

[Stream index: 0]

[Stream Packet Number: 1]

▶ [Conversation completeness: Incomplete, DATA (15)]

[TCP Segment Len: 0]

Sequence Number: 0 (relative sequence number)

Sequence Number (raw): 3894714846

[Next Sequence Number: 1 (relative sequence number)]

Acknowledgment Number: 0

Acknowledgment number (raw): 0

0110 = Header Length: 24 bytes (6)

▼ Flags: 0x002 (SYN)

000. = Reserved: Not set

...0 = Accurate ECN: Not set

.... 0... = Congestion Window Reduced: Not set

.... .0.. = ECN-Echo: Not set

.... ..0. = Urgent: Not set

.... ...0 = Acknowledgment: Not set

.... 0... = Push: Not set

....0.. = Reset: Not set

▶1. = Syn: Set

....0 = Fin: Not set

[TCP Flags:S.]

0000 ca 01 a2 ec 00 1c ca 02 66 8c 00 1c 08 00 45 c0 f.....E.

0010 00 2c 3f ba 00 00 ff 06 f7 fd c0 a8 01 02 c0 a8 .,?.....

0020 01 01 b0 78 00 16 e8 24 a1 de 00 00 00 00 60 02 ...x--\$.....

0030 10 20 ca 20 00 00 02 04 05 b4 00 00

No.: 14 · Time: 52.662085 · Source: 192.168.1.2 · Destination: 192.168.1.1 · Protocol: TCP · Length: 60 · Info: 45176 → 22 [SYN] Seq=0 Win=4128 Len=0 MSS=1460

✓ Show packet bytes

Layout: Vertical (Stacked)

Frame 15: Packet, 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface -, id 0
Ethernet II, Src: ca:01:a2:ec:00:1c (ca:01:a2:ec:00:1c), Dst: ca:02:66:8c:00:1c (ca:02:66:8c:00:1c)
Internet Protocol Version 4, Src: 192.168.1.1, Dst: 192.168.1.2
Transmission Control Protocol, Src Port: 22, Dst Port: 45176, Seq: 0, Ack: 1, Len: 0

Syn-ack

Source Port: 22
Destination Port: 45176
[Stream index: 0]
[Stream Packet Number: 2]
[Conversation completeness: Incomplete, DATA (15)]
[TCP Segment Len: 0]
Sequence Number: 0 (relative sequence number)
Sequence Number (raw): 802103529
[Next Sequence Number: 1 (relative sequence number)]
Acknowledgment Number: 1 (relative ack number)
Acknowledgment number (raw): 3894714847
0110 = Header Length: 24 bytes (6)
Flags: 0x012 (SYN, ACK)
000. = Reserved: Not set
...0 = Accurate ECN: Not set
.... 0... = Congestion Window Reduced: Not set
.... .0.. = ECN-Echo: Not set
.... ..0. = Urgent: Not set
.... ...1 = Acknowledgment: Set
....0 = Push: Not set
....0.. = Reset: Not set
....1. = Syn: Set
....0 = Fin: Not set
[TCP Flags:A..S.]

0000	ca 02 66 8c 00 1c ca 01 a2 ec 00 1c 08 00 45 c0	..f.....E.
0010	00 2c c1 f4 00 00 ff 06 75 c3 c0 a8 01 01 c0 a8	.,.....u.....
0020	01 02 00 16 b0 78 2f cf 20 e9 e8 24 a1 df 60 12	x/-..\$.~.
0030	10 20 79 57 00 00 02 04 05 b4 00 00	.yW.....

No.: 15 · Time: 52.677997 · Source: 192.168.1.1 · Destination: 192.168.1.2 · Protocol: TCP · Length: 60 · Info: 22 → 45176 [SYN, ACK] Seq=0 Ack=1 Win=4128 Len=0 MSS=1460

☒ Show packet bytes Layout: Vertical (Stacked) ▼

- ▶ Frame 16: Packet, 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface -, id 0
- ▶ Ethernet II, Src: ca:02:66:8c:00:1c (ca:02:66:8c:00:1c), Dst: ca:01:a2:ec:00:1c (ca:01:a2:ec:00:1c)
- ▶ Internet Protocol Version 4, Src: 192.168.1.2, Dst: 192.168.1.1
- ▼ Transmission Control Protocol, Src Port: 45176, Dst Port: 22, Seq: 1, Ack: 1, Len: 0

Source Port: 45176

Destination Port: 22

[Stream index: 0]

[Stream Packet Number: 3]

- ▶ [Conversation completeness: Complete, WITH_DATA (31)]

[TCP Segment Len: 0]

Sequence Number: 1 (relative sequence number)

Sequence Number (raw): 3894714847

[Next Sequence Number: 1 (relative sequence number)]

Acknowledgment Number: 1 (relative ack number)

Acknowledgment number (raw): 802103530

0101 = Header Length: 20 bytes (5)

- ▼ Flags: 0x010 (ACK)

000. = Reserved: Not set

...0 = Accurate ECN: Not set

.... 0... = Congestion Window Reduced: Not set

.... .0.. = ECN-Echo: Not set

.... ..0. = Urgent: Not set

.... ...1 = Acknowledgment: Set

.... 0... = Push: Not set

....0.. = Reset: Not set

....0. = Syn: Not set

....0 = Fin: Not set

[TCP Flags:A....]

syn-ack-syn

```
0000  ca 01 a2 ec 00 1c ca 02 66 8c 00 1c 08 00 45 c0  .....f....E.
0010  00 28 3f bb 00 00 ff 06 f8 00 c0 a8 01 02 c0 a8  -(?.....
0020  01 01 b0 78 00 16 e8 24 a1 df 2f cf 20 ea 50 10  ...x...$../-P-
0030  10 20 91 14 00 00 00 00 00 00 00 00  .....

```

No.: 16 · Time: 52.693983 · Source: 192.168.1.2 · Destination: 192.168.1.1 · Protocol: TCP · Length: 60 · Info: 45176 → 22 [ACK] Seq=1 Ack=1 Win=4128 Len=0

☒ Show packet bytes

Layout: Vertical (Stacked)

SSH Login commands:

Config

Interface g1/0

Ip address 192.168.1.1 255.255.255.0

No shutdown

Exit

hostname "name"

Exit

Writ memory-to save

To know arp table =show arp if it is config do show arp

Ip domain-name 'namenetworks '

Crypto key generate rsa

1024

Ssh enabled –to know ssh enabled or not

Do show ssh-if it is conf

Username "name"password "1234"

Line vty 0 4 or any number

Transport input ssh

Transport output ssh

Login local –to login remotely

end

route2

Config

Interface g1/0

Ip address 192.168.1.2 255.255.255.0

No shutdown

Exit

hostname "name"

Exit

Writ memory-to save

to remotely login

ssh?

ssh – L "name" 192.168.1.1

pass 1234 after this we login remotely.