



Discriminative Model Features

Making features from text for discriminative NLP models

Christopher Manning



Features

- In these slides and most maxent work: *features* f are elementary pieces of evidence that link aspects of what we observe d with a category c that we want to predict
- A feature is a function with a bounded real value: $f: C \times D \rightarrow \mathbb{R}$



Features

- In these slides and most maxent work: *features* f are elementary pieces of evidence that link aspects of what we observe d with a category c that we want to predict
- A feature is a function with a bounded real value



Example features

- $f_1(c, d) \equiv [c = \text{LOCATION} \wedge w_{-1} = \text{"in"} \wedge \text{isCapitalized}(w)]$
- $f_2(c, d) \equiv [c = \text{LOCATION} \wedge \text{hasAccentedLatinChar}(w)]$
- $f_3(c, d) \equiv [c = \text{DRUG} \wedge \text{ends}(w, \text{"c"})]$



- Models will assign to each feature a *weight*:
 - A positive weight votes that this configuration is likely correct
 - A negative weight votes that this configuration is likely incorrect



Example features

- $f_1(c, d) \equiv [c = \text{LOCATION} \wedge w_{-1} = \text{"in"} \wedge \text{isCapitalized}(w)]$
- $f_2(c, d) \equiv [c = \text{LOCATION} \wedge \text{hasAccentedLatinChar}(w)]$
- $f_3(c, d) \equiv [c = \text{DRUG} \wedge \text{ends}(w, \text{"c"})]$

LOCATION
in Arcadia

LOCATION
in Québec

DRUG
taking Zantac

PERSON
saw Sue

- Models will assign to each feature a *weight*:
 - A positive weight votes that this configuration is likely correct
 - A negative weight votes that this configuration is likely incorrect



Feature Expectations

- We will crucially make use of two *expectations*
 - actual or predicted counts of a feature firing:

- Empirical count (expectation) of a feature:

$$\text{empirical } E(f_i) = \sum_{(c,d) \in \text{observed}(C,D)} f_i(c,d)$$

- Model expectation of a feature:

$$E(f_i) = \sum_{(c,d) \in (C,D)} P(c,d) f_i(c,d)$$



Features

- In NLP uses, usually a feature specifies (1) an indicator function – a yes/no boolean matching function – of properties of the input and (2) a particular class
 - $f_i(c, d) \equiv [\Phi(d) \wedge c = c_j]$ [Value is 0 or 1]
 - They pick out a data subset and suggest a label for it.
- We will say that $\Phi(d)$ is a feature of the data d , when, for each c_j , the conjunction $\Phi(d) \wedge c = c_j$ is a feature of the data-class pair (c, d)



Features

- In NLP uses, usually a feature specifies
 1. an indicator function – a yes/no boolean matching function – of properties of the input and
 2. a particular class

$$f_i(c, d) \equiv [\Phi(d) \wedge c = c_j] \quad \text{[Value is 0 or 1]}$$

- Each feature picks out a data subset and suggests a label for it



Feature-Based Models

- The decision about a data point is based only on the **features** active at that point.

Data BUSINESS: Stocks hit a yearly low ...
Label: BUSINESS Features {..., stocks, hit, a, yearly, low, ...}

Text
Categorization

Data ... to restructure bank:MONEY debt.
Label: MONEY Features {..., w_{-1} =restructure, w_{+1} =debt, $L=12$, ...}

Word-Sense
Disambiguation

Data DT JJ NN ... The previous fall ...
Label: NN Features { w =fall, t_{-1} =JJ w_{-1} =previous}

POS Tagging



Example: Text Categorization

(Zhang and Oles 2001)

- Features are presence of each **word** in a document and the document **class** (they do feature selection to use reliable indicator words)
- Tests on classic Reuters data set (and others)
 - Naïve Bayes: 77.0% F_1
 - Linear regression: 86.0%
 - **Logistic regression: 86.4%**
 - Support vector machine: 86.5%
- Paper emphasizes the importance of *regularization* (smoothing) for successful use of discriminative methods (not used in much early NLP/IR work)



Other Maxent Classifier Examples

- You can use a maxent classifier whenever you want to assign data points to one of a number of classes:
 - Sentence boundary detection (Mikheev 2000)
 - Is a period end of sentence or abbreviation?
 - Sentiment analysis (Pang and Lee 2002)
 - Word unigrams, bigrams, POS counts, ...
 - PP attachment (Ratnaparkhi 1998)
 - Attach to verb or noun? Features of head noun, preposition, etc.
 - Parsing decisions in general (Ratnaparkhi 1997; Johnson et al. 1999, etc.)



Discriminative Model Features

Making features from text for discriminative NLP models

Christopher Manning