



Maximum entropy sequence models

Maximum entropy Markov models (MEMMs) or Conditional Markov models



Sequence problems

- Many problems in NLP have data which is a sequence of characters, words, phrases, lines, or sentences ...
- We can think of our task as one of labeling each item

VBG	NN	IN	DT	NN	IN	NN
Chasing	opportunity	in	an	age	of	upheaval

POS tagging

PERS	O	O	O	ORG	ORG
Murdoch	discusses	future	of	News	Corp.

Named entity recognition

B	B	I	I	B	I	B	I	B	B
而	相	对	于	这	些	品	牌	的	价

Word segmentation

Q
A
Q
A
A
A
Q
A

Text segmentation




MEMM inference in systems

- For a Conditional Markov Model (CMM) a.k.a. a Maximum Entropy Markov Model (MEMM), the classifier makes a single decision at a time, conditioned on evidence from observations **and previous decisions**
- A larger space of sequences is usually explored via search

Local Context

-3	-2	-1	0	+1
DT	NNP	VBD	???	???
The	Dow	fell	22.6	%

Decision Point



Features

W_0	22.6
W_{+1}	%
W_{-1}	fell
T_{-1}	VBD
$T_{-1}-T_{-2}$	NNP-VBD
hasDigit?	true
...	...

(Ratnaparkhi 1996; Toutanova et al. 2003, etc.)




Example: POS Tagging

- Scoring individual labeling decisions is no more complex than standard classification decisions
 - We have some assumed labels to use for prior positions
 - We use features of those and the observed data (which can include current, previous, and next words) to predict the current label

Local Context

-3	-2	-1	0	+1
DT	NNP	VBD	???	???
The	Dow	fell	22.6	%

Decision Point



Features

W_0	22.6
W_{+1}	%
W_{-1}	fell
T_{-1}	VBD
$T_{-1}-T_{-2}$	NNP-VBD
hasDigit?	true
...	...

(Ratnaparkhi 1996; Toutanova et al. 2003, etc.)




Example: POS Tagging

- POS tagging Features can include:
 - Current, previous, next words in isolation or together.
 - Previous one, two, three tags.
 - Word-internal features: word types, suffixes, dashes, etc.

Local Context

-3	-2	-1	0	+1
DT	NNP	VBD	???	???
The	Dow	fell	22.6	%

Decision Point




Features

W_0	22.6
W_{+1}	%
W_{-1}	fell
T_{-1}	VBD
$T_{-1}-T_{-2}$	NNP-VBD
hasDigit?	true
...	...

(Ratnaparkhi 1996; Toutanova et al. 2003, etc.)




Inference in Systems






Greedy Inference



- Greedy inference:
 - We just start at the left, and use our classifier at each position to assign a label
 - The classifier can depend on previous labeling decisions as well as observed data
- Advantages:
 - Fast, no extra memory requirements
 - Very easy to implement
 - With rich features including observations to the right, it may perform quite well
- Disadvantage:
 - Greedy. We make commit errors we cannot recover from




Beam Inference



- Beam inference:
 - At each position keep the top k complete sequences.
 - Extend each sequence in each local way.
 - The extensions compete for the k slots at the next position.
- Advantages:
 - Fast; beam sizes of 3–5 are almost as good as exact inference in many cases.
 - Easy to implement (no dynamic programming required).
- Disadvantage:
 - Inexact: the globally best sequence can fall off the beam.



Viterbi Inference



- Viterbi inference:
 - Dynamic programming or memoization.
 - Requires small window of state influence (e.g., past two states are relevant).
- Advantage:
 - Exact: the global best sequence is returned.
- Disadvantage:
 - Harder to implement long-distance state-state interactions (but beam inference tends not to allow long-distance resurrection of sequences anyway).



CRFs [Lafferty, Pereira, and McCallum 2001]

- Another sequence model: Conditional Random Fields (CRFs)
- A whole-sequence conditional model rather than a chaining of local models.

$$P(c \mid d, \lambda) = \frac{\exp \sum_i \lambda_i f_i(c, d)}{\sum_{c'} \exp \sum_i \lambda_i f_i(c', d)}$$

- The space of c 's is now the space of sequences
 - But if the features f_i remain local, the conditional sequence likelihood can be calculated exactly using dynamic programming
- Training is slower, but CRFs avoid causal-competition biases
- These (or a variant using a max margin criterion) are seen as the state-of-the-art these days ... but in practice usually work much the same as MEMMs.



Maximum entropy sequence models

Maximum entropy Markov models (MEMMs) or Conditional Markov models