

PrimeBond+

PrimeBond+ is specially formulated acrylic emulsion for modifying Cementitious compositions, Cement Primers, Crack Filling, Anchor & Grout, Waterproofing and Damp Proofing. Mortar prepared with PrimeBond+ is durable and tough and ideal use for thin section application. It has excellent adhesion to various substrates like wood, concrete, brick and metal.

- Application / Advantages
- Bonding Agent, Cementitious Waterproofing
- Good workability at reduced water cement ratio
- Offers good flexural and compressive built-up
- Good bonding and adhesion to substrate
- Excellent Water Impermeability

Product Specification

Properties	Specification
Appearance	Milky White Emulsion
Emulsifying System	Anionic
Total Solids (%)	54% \pm 1
pH at 25°C	8 to 10
Brookfield Viscosity RVT (SP.2 620RPM at 30°C)	17
Specific Gravity	1.025 \pm 0.02
Dilutability with water	Dilutable
Compatibility	Compatible with Cement and Concrete mixture.

Storage

Store between temperature of 5°C and 40°C. Keep containers closed with not in use.

Shelf-Life

Shelf-Life is 18 Months from date of manufacturing provided stored under shade, away from direct heat and sunlight and well protected from freezing.

Packaging

200kg to 20kg HDPE Drums

CONSTRUCTION



BEAUTIFY