

# 1. Introduction

## 1.1 Project Overview

The **Disaster Management System (DMS)** is a comprehensive database solution designed to streamline and automate the complex coordination required during natural and man-made disasters. In critical situations such as floods, earthquakes, or fires, the efficiency of response efforts is often the difference between life and death. This project aims to replace fragmented, manual record-keeping with a centralized, relational database system that ensures real-time data availability, data integrity, and efficient resource allocation.

The system serves as a central hub connecting various stakeholders—including administrators, relief organizations, volunteers, donors, and victims—ensuring that help reaches those in need as quickly as possible.

## 1.2 Background and Motivation

Disaster management involves a multitude of moving parts: tracking affected areas, managing shelter capacities, coordinating volunteer assignments, and logging donations. Traditionally, these tasks are handled using disparate spreadsheets or paper-based methods, leading to several critical issues:

- **Information Asymmetry:** Relief organizations often do not know which areas have already received aid and which are neglected.
- **Resource Wastage:** Without a central inventory, some shelters receive excess resources while others face shortages.
- **Data Redundancy:** Victim data is often collected multiple times by different agencies, wasting valuable time.

Motivated by these challenges, this project proposes a robust Database Management System (DBMS) built on **MySQL**. By normalizing data to the **Third Normal Form (3NF)**, the system minimizes redundancy and ensures that critical data regarding disasters, funds, and human resources is accurate and easily retrievable.

## 1.3 Problem Statement

Current manual or semi-digital systems for disaster management suffer from the following limitations:

1. **Lack of Real-Time Coordination:** There is no single source of truth for the status of shelters or the availability of volunteers.
2. **Inefficient Resource Distribution:** Donors and organizations lack visibility into the specific needs of different disaster zones, leading to mismatched aid (e.g., sending clothes when medicine is needed).

3. **Complex Data Relationships:** Managing the Many-to-Many relationships between donors, organizations, and funds is prone to error without a structured DBMS.
4. **Communication Gaps:** Broadcasting emergency alerts to specific areas is difficult without a structured user and location database.

## 1.4 Objectives

The primary objective of this project is to design and implement a relational database that solves the above problems. Key objectives include:

- **Centralized Data Management:** To store and manage details of Disasters, Organizations, and Users in a unified structure.
- **Optimized Resource Allocation:** To track the flow of Resources and Funds from Organizations to specific Disaster zones.
- **Victim & Shelter Tracking:** To maintain accurate records of victims and their locations (Shelters) to facilitate family reunification and aid distribution.
- **Volunteer Coordination:** To manage volunteer profiles and assign them to specific disasters based on their skills and availability.
- **Transparency:** To log all Donations and Fund sources, ensuring accountability in relief efforts.

## 1.5 Project Scope

The scope of the Disaster Management System covers the backend database architecture required to support the following modules:

1. **Authentication & Role Management:** Secure management of Admins, Organizations, and standard Users/Volunteers.
2. **Disaster Event Logging:** detailed tracking of disaster types, severity, locations, and timelines.
3. **Relief Operations:** Management of Shelters, Victim registration, and Emergency Alerts.
4. **Financial & Resource Tracking:** Recording inbound Donations from Donors and outbound Fund/Resource allocation by Organizations.
5. **Workforce Management:** Registration of Volunteers and their specific Assignments to disaster sites.

## 1.6 Methodology

The database is designed using the **Relational Model**. The schema was developed through the following steps:

1. **Requirement Analysis:** Identifying the entities (e.g., Victim, Donor, Disaster) and their attributes.
2. **ER Modeling:** Creating an Entity-Relationship diagram to visualize connections.

3. **Normalization:** Rigorously refining the tables to **Third Normal Form (3NF)** to eliminate transitive dependencies and data anomalies.
4. **Implementation:** Writing SQL scripts for table creation with appropriate constraints (Primary Keys, Foreign Keys, ON DELETE CASCADE) to maintain referential integrity.

## 2. Project Summary

The **Disaster Management System (DMS)** is a robust relational database solution designed to address the critical challenges of coordination, resource allocation, and data integrity during humanitarian crises. Natural and man-made disasters often lead to chaotic information flow, resulting in delayed aid and resource mismanagement. This project aims to solve these issues by providing a centralized, structured, and normalized backend architecture.

The core of the system is built upon a schema of **13 interconnected tables**, rigorously normalized to the **Third Normal Form (3NF)**. This structure ensures that data regarding **Disasters, Victims, Shelters, Volunteers, Donors, and Funds** is stored efficiently, eliminating redundancy and preventing data anomalies.

**Key functional modules include:**

- **Disaster & Alert Tracking:** Real-time logging of disaster events and the dissemination of targeted emergency alerts.
- **Victim & Shelter Management:** Precise tracking of affected individuals and their locations to facilitate rescue operations and family reunification.
- **Resource & Fund Transparency:** A transparent ledger for tracking donations from donors and the subsequent allocation of funds and resources by organizations.
- **Volunteer Coordination:** Dynamic assignment of volunteers to specific disaster zones based on their skills and availability.

Technically, the project utilizes **MySQL** to implement complex relationships, including One-to-Many (e.g., Organization to Resources) and Many-to-Many (e.g., Donors to Organizations via Donations). Referential integrity is strictly enforced through **Foreign Key constraints** and cascading delete rules, ensuring the database remains consistent even as data is updated or removed.


By digitizing and structuring these critical operations, the Disaster Management System reduces administrative overhead, minimizes response times, and ultimately supports more effective life-saving decision-making.

Here is a detailed **Functions & Operations** section for your project report. This section breaks down the system's capabilities by module, explaining both the user-facing functionality and the backend database operations that support them.

### 3. Functions & Operations

Below are the primary functions along with their descriptions that will be included in the project, as depicted in the system interface.

#### 1. Home Page



Description: The landing page serves as the central entry point for all visitors. It features a hero section with a welcoming message ("CrisisAssist: Your Disaster Recovery Partner") and direct calls to action "Get Help" for immediate assistance and "Donate Now" for contributors. The navigation bar provides easy access to Alerts, News, Shelters, and Login options.

## 2. About & Contact Information

### What is CrisisAssist?

CrisisAssist is a centralized disaster recovery and crisis management platform. It connects affected people, volunteers, organizations and administrators in one place so that information, shelters, donations and rescue activities can be coordinated quickly and transparently.

From tracking active disasters and available shelters to managing rescue teams and donations, our goal is to reduce response time and make sure help reaches the people who need it most.

### Need help or want to collaborate?

**Emergency Support:** +8801874588383 , +8801516500270  
**Email:** admin\_support@crisisassist.org  
**Office:** Disaster Management Cell, Dhaka, Bangladesh

For partnership, data corrections, or technical issues with the system, please contact the admin team using the email above.

### Meet Our Team

#### Karimun Nahar Karima

ID: 23549009046  
Email: karimunnaharkarima200684@gmail.com  
Phone: 01874588383

#### Didar Ibn Firoz

ID: 23549009084  
Email: didarabid@gmail.com  
Phone: 01516500270

© 2025 Disaster Recovery System | Designed with ❤️ | By Karima & Didar

Description: The system includes informational sections explaining the mission of "CrisisAssist" ("What is CrisisAssist?"). It also provides a contact area ("Need help or want to collaborate?") listing Emergency Support numbers, official Email addresses, and the physical Office address for the Disaster Management Cell.

## 3. Registration/Signup Page

CrisisAssist: Your Disaster Recovery Partner

HomeAlertsNewsSheltersDonate

SignupLogin

Create account

Name

Your name

Email

you@example.com

Password

Choose a password

Role

User


Sign up

Already have an account? [Login](#)




Description: New users can create an account using the dedicated Signup form. They must provide their full name, a valid email address, and a secure password. Crucially, the form includes a "Role" selection dropdown, allowing users to register as a standard User, Volunteer, or Organization representative, which defines their access level within the system.


#### 4. User Login Page



Description: The secure login interface allows registered users to access their respective dashboards. Users must select their "User Type" (e.g., User, Admin, Organization) and enter their registered email and password. This role-based authentication ensures that users are directed to the correct interface upon successful login.


#### 5. Public News & Crisis Updates






Description: The News section acts as an information hub for ongoing disasters. It features a search bar allowing users to find specific events by title, region, or description. Additionally, dynamic filters allow users to sort news by "Severity" (e.g., High, Critical), "Disaster Type" (e.g., Flood, Cyclone), and "Status," ensuring the public stays informed about relevant situations.

## 6. Alert Details (Popup View)




Description: Clicking on an alert opens a detailed modal window. This popup provides specific information including the Alert Title (e.g., "Aftershock Warning"), Severity Level (High/Critical), Status (Resolved/Active), Date, and a full text description. This allows users to get granular safety information without navigating away from the main list.

## 7. Emergency Alerts Dashboard




Description: This public-facing page displays a grid of critical warnings (e.g., Flood Warning, Cyclone Warning Level 3). Each alert card provides immediate visual cues through color-coding (Purple/Red) and displays key data such as the affected Region and a brief instruction (e.g., "Evacuate low-lying areas").

## 8. Available Shelters Listing








Description: The Shelters page lists all registered safe havens available for victims. Each entry displays the shelter's name (e.g., "Community Shelter 1"), general location, total capacity, and a photograph. A "View Details" button allows users to access in-depth information about a specific facility.

## 9. Detailed Shelter View & Inventory




Description: This highly detailed page provides real-time status updates for a specific shelter. It includes:

- Capacity Status: Visual indicators showing "Slots Available" vs. "Total Capacity" and occupancy percentages.
- Contact Information: Phone, Email, and Emergency Line (999).
- Facilities: A checklist of available amenities like Medical Aid, Clean Water, and Power Backup.
- Food & Supplies: A live inventory log showing stock levels of Food (kg), Water (liters), and Medical Supplies.

## 10. Donation Portal

Description: The "Donate" page facilitates financial support for relief efforts. Users are presented with a simplified form where they enter their Name and select a "Donation Type" (e.g., Monetary, Goods) from a dropdown menu. The background features imagery of affected areas to evoke empathy and encourage contribution.

## 11. Admin Dashboard



Description: The Admin Dashboard gives a high-level statistical overview of the entire system. It features summary cards displaying total counts for Disasters, Victims, Volunteers, Donors, Resources, and Funds. This "Bird's-eye view" helps administrators assess the scale of operations instantly.

## 12. User Management (Admin View)

| ID | Username | Name                 | Email                 | Phone       | Role         | Organization ID | Created At | Actions                                     |
|----|----------|----------------------|-----------------------|-------------|--------------|-----------------|------------|---------------------------------------------|
| 1  | redcross | Red Cross Admin      | redcross@disaster.com | 9876543210  | ORGANIZATION | 1               | 05/12/2025 | <a href="#">Edit</a> <a href="#">Delete</a> |
| 2  | john     | John Smith           | john@example.com      | 5551234567  | USER         | -               | 05/12/2025 | <a href="#">Edit</a> <a href="#">Delete</a> |
| 3  | karima   | Karima               | karima@gmail.com      | -           | USER         | -               | 05/12/2025 | <a href="#">Edit</a> <a href="#">Delete</a> |
| 4  | helen    | Helen                | helen@support.org     | -           | ORGANIZATION | -               | 05/12/2025 | <a href="#">Edit</a> <a href="#">Delete</a> |
| 5  | didar    | Didar                | didar@gmail.com       | -           | USER         | -               | 05/12/2025 | <a href="#">Edit</a> <a href="#">Delete</a> |
| 6  | rahim123 | Abdul Rahim          | rahim@mail.com        | 01720000001 | USER         | -               | -          | <a href="#">Edit</a> <a href="#">Delete</a> |
| 7  | karima46 | Karimun Nahar Karima | karima46@mail.com     | 01720000002 | USER         | -               | -          | <a href="#">Edit</a> <a href="#">Delete</a> |
| 8  | didar84  | Didar Ibn Firoz      | didar@mail.com        | 01720000003 | ORGANIZATION | 2               | -          | <a href="#">Edit</a> <a href="#">Delete</a> |

Description: Admins have access to a tabular view of all registered users. The table displays IDs, Usernames, Emails, Phones, and assigned Roles (User/Organization). It allows Admins to perform administrative actions such as "Edit" to update user details or "Delete" to remove unauthorized or obsolete accounts.

## 13. Edit User Details (Admin Action)

CrisisAssist: Your Disaster Reco

Shelters

Donate

Logout

ID

Username

Name

1

redcross

Red Cross Ad

2

john

John Smith

3

karima

Karima

4

helen

Helen

5

didar

Didar

6

rahim123

Abdul Rahim

7

karima46

Karimun Nahe

8

didar84

Didar Ibn Firoz

9

shafiq\_victim

Shafiqur Rahr

10

sumaiya\_org

Sumaiya Akte

Created At

05/12/2025

05/12/2025

05/12/2025

05/12/2025

-

-

-

-

-

Actions

[Edit](#) [Delete](#)

[Edit](#) [Delete](#)

[Edit](#) [Delete](#)

[Edit](#) [Delete](#)

[Edit](#) [Delete](#)

[Edit](#) [Delete](#)

[Edit](#) [Delete](#)

[Edit](#) [Delete](#)

[Edit](#) [Delete](#)

Username \*

redcross

Password

Name

Red Cross Admin

Email

redcross@disaster.com

Phone

9876543210

Role \*

Organization ID

1

Cancel


Update User



Description: This modal interface allows Administrators to modify the profile information of an existing user. When an admin clicks the "Edit" button on the User Management table, this popup appears pre-filled with the user's current data (Username, Name, Email, Phone). It allows the admin to:

- Update Personal Info: Correct names or contact details.
- Reset Passwords: Securely set a new password if a user forgets theirs.
- Change Roles: Reassign a user's privileges (e.g., promoting a "User" to "Organization") via a dropdown menu.
- Link Organization: Associate a user with a specific Organization ID if their role requires it.
- Save Changes: Commits the updates to the database via the "Update User" button or discards them with "Cancel".

## 14. Organization Dashboard



Description: This dedicated workspace serves as the operational command center for registered NGOs and relief agencies (e.g., Red Cross). Upon logging in, the organization representative sees a personalized greeting (e.g., "Welcome, Helen") and a high-level statistical overview of their specific contributions. The dashboard is divided into two key sections:


**Performance Metrics:** A row of quick-glance cards displaying real-time counters for Total Alerts issued, Active Alerts currently in effect, Total Shelters managed, and Total Donations received. This allows the organization to instantly gauge the scale of their current operations.

**Alert Management Console:** Below the metrics, a detailed data table lists all emergency alerts created by the organization. It displays critical details such as Alert Title, Severity (e.g., High), Disaster Type, Affected Region, and Status (Active/Resolved).



Operational Actions: The interface provides direct control tools, including a "+ Create Alert" button to issue new warnings immediately, and Action buttons ("Edit", "Delete") for every listed alert to update or remove outdated information.


## 15. Alert Management (Organization View)




| ID | Title                   | Severity | Type         | Region        | Status   | Created    | Actions                                     |
|----|-------------------------|----------|--------------|---------------|----------|------------|---------------------------------------------|
| 1  | Flood Warning           | HIGH     | flood        | Region A      | ACTIVE   | 05/12/2025 | <a href="#">Edit</a> <a href="#">Delete</a> |
| 2  | Cyclone Warning Level 3 | HIGH     | weather      | Cox's Bazar   | ACTIVE   | 01/01/1970 | <a href="#">Edit</a> <a href="#">Delete</a> |
| 3  | Flood Water Rising      | CRITICAL | flood        | Sylhet        | ACTIVE   | 01/01/1970 | <a href="#">Edit</a> <a href="#">Delete</a> |
| 4  | Humanitarian Alert      | HIGH     | humanitarian | Teknaf        | ACTIVE   | 01/01/1970 | <a href="#">Edit</a> <a href="#">Delete</a> |
| 5  | Aftershock Warning      | HIGH     | earthquake   | Turkey Region | RESOLVED | 01/01/1970 | <a href="#">Edit</a> <a href="#">Delete</a> |
| 6  | High Conflict Zone      | CRITICAL | security     | Ukraine       | ACTIVE   | 01/01/1970 | <a href="#">Edit</a> <a href="#">Delete</a> |

Description: Within the Organization Dashboard, authorized personnel can manage emergency alerts. A data table lists all alerts created by the organization, showing Title, Severity, Type, Region, and Status. It includes action buttons to "Edit" existing alerts or "Delete" outdated ones, as well as a "+ Create Alert" button to issue new warnings.

## 16. User Dashboard (Personalized)



| Welcome, Didar!                                                                                                     |                                                                                                                |                                                                                                               |
|---------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| Stay informed and take action during crisis situations                                                              |                                                                                                                |                                                                                                               |
| <br>ACTIVE ALERTS<br>6           | <br>AVAILABLE SHELTERS<br>6 | <br>TOTAL DONATIONS<br>6 |
| <b>Quick Actions</b><br><a href="#">View All Alerts</a> <a href="#">Find Shelters</a> <a href="#">Make Donation</a> |                                                                                                                |                                                                                                               |




Description: The User Dashboard serves as a personalized information hub designed to engage standard users immediately upon login. It features a prominent welcome section (e.g., "Welcome, Didar!") accompanied by a motivational tagline encouraging users to "Stay informed and take action." The interface is structured into two primary interactive zones:

Live Status Overview: A row of high-visibility cards provides an instant snapshot of the current crisis landscape. These include "Active Alerts" (showing the number of ongoing emergencies), "Available Shelters" (indicating open safe havens), and "Total Donations" (tracking the user's personal contributions or system-wide aid).

Quick Actions Panel: To facilitate rapid response, a dedicated "Quick Actions" section sits at the bottom. It features large, accessible buttons that allow users to bypass navigation menus and directly "View All Alerts," "Find Shelters," or "Make a Donation." This design minimizes the time it takes for a user to find help or provide aid during a critical situation.

## Entity Relationship Diagram (Updated)



## Narrative Description of ER-Diagram

### Entities:

**Role:** The role table defines the various access levels within the system (e.g., Admin, User, Volunteer). Each role is identified by a unique role\_id (primary key) and includes a role\_name. This table establishes hierarchy and permissions for all users interacting with the platform.

**User:** The user table serves as the central entity for all individuals accessing the system. Each user is identified by a unique user\_id (primary key) and is linked to the Role table via role\_id (foreign key). The table stores essential personal details such as name, email, password, and phone. This table acts as a parent entity for Admins and Volunteers.

**Admin:** Administrators are specialized users identified by a unique admin\_id (primary key). They are linked to the central user table via user\_id (foreign key). This structure allows admins to inherit basic user attributes while maintaining specific administrative privileges to oversee the system.

**Organization:** This table stores information about NGOs or relief agencies involved in disaster management. Each organization is identified by a unique org\_id (primary key) and includes details such as org\_name, email, phone, location, and a nearby landmark. Organizations are responsible for managing shelter centers and receiving donations.

**ShelterCenter:** Shelter centers are safe locations managed by organizations. Each center is identified by a unique center\_id (primary key) and is linked to an organization via org\_id (foreign key). The table records capacity details such as room\_number and water\_supply status.

**AffectedArea:** This table records the geographic locations impacted by a disaster. Each area is identified by a unique affected\_id (primary key) and includes attributes for the specific location and the severity of the damage (e.g., High, Medium, Low).

**Donation:** The donation table records financial contributions made by users to organizations. Each record has a unique donation\_id (primary key) and is linked to both a user\_id and an org\_id



(foreign keys). It stores transaction details including the amount, payment\_method, and the date of the donation.

**Alert:** This table captures emergency warnings or requests for help posted by users. Each alert is identified by a unique alert\_id (primary key) and links back to the poster via user\_id (foreign key). It contains critical information such as alert\_type, severity, location, description, and the date of the incident.

**RescueTeam:** Rescue teams are operational units deployed to respond to alerts. Each team is identified by a unique team\_id (primary key) and includes attributes for team\_name and current operational status. Teams are composed of multiple volunteers.

**Volunteer:** Volunteers are individuals willing to assist in rescue operations. Identified by a unique volunteer\_id (primary key), they are linked to the user table via user\_id (foreign key) and assigned to a specific team via team\_id (foreign key). The table also tracks their status and any specific remarks.

## Relationships:

**Has (Role-User):** Every user must be assigned a specific role in the system. This is a one-to-many relationship where one role type (e.g., "Volunteer") can be assigned to multiple users, but each user has only one specific role.

**Is (User-Admin / User-Volunteer):** This represents a specialization relationship. An Admin or a Volunteer is a User. This is a one-to-one relationship where specific records in the Admin or Volunteer tables correspond to a single record in the User table.

**Makes (User-Donation):** A user can contribute to relief efforts by making donations. This is a one-to-many relationship where a single user can make multiple donations, but each specific donation record belongs to one user.

**Receives (Organization-Donation):** Organizations collect funds to support their operations. This is a one-to-many relationship where one organization can receive many donations, but each donation is directed toward a single organization.

**Posts (User-Alert):** Users can report emergencies by posting alerts. This is a one-to-many relationship where one user can post multiple alerts regarding different incidents.

**Manages (Organization-ShelterCenter):** Organizations are responsible for maintaining shelter centers. This is a one-to-many relationship where one organization may manage multiple shelter centers, but each center is managed by only one organization.

**Contains (RescueTeam-Volunteer):** Rescue teams are composed of individual volunteers. This is a one-to-many relationship where a rescue team contains multiple volunteers, but a volunteer is assigned to one specific team at a time.

**Responds (RescueTeam-Alert):** Rescue teams are deployed to handle emergency alerts. This is a many-to-many relationship where a rescue team can respond to multiple alerts, and a specific alert (if severe) might require the response of multiple rescue teams.

**Serves (ShelterCenter-AffectedArea):** Shelter centers provide relief to specific disaster zones. This is a many-to-many relationship where a shelter center can serve people from multiple affected areas, and a large affected area might be served by multiple shelter centers.

## Group Progress Report (24.10.2025 – 07.12.2025)

### Summary of Activities

**Phase 1 (Planning):** Brainstormed and selected project topic.

**Requirement Analysis:** Identified roles and core modules.

**Conceptual & ER Modeling:** Designed entities, relationships, and constraints.

Technical Preparation and Documentation completed.

### Team Member Summary

| Team Member          | Total Hours      | ID          | Remarks / Key Contributions                                                                                                                                                             |
|----------------------|------------------|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Karimun Nahar Karima | 38 Hours 40 Mins | 23549009046 | <ul style="list-style-type: none"><li>• Lead on ER Diagram Design &amp; Relationship Logic</li><li>• SQL Query Planning</li><li>• Backend constraints &amp; schema definition</li></ul> |
| Didar Ibn Firoz      | 36 Hours 15 Mins | 23549009084 | <ul style="list-style-type: none"><li>• Functional Requirements &amp; User Roles</li><li>• UI Research &amp; Mockups</li><li>• Data Dictionary creation</li></ul>                       |

### Individual Report – Karimun Nahar Karima

| Date       | Hours  | Activities                            |
|------------|--------|---------------------------------------|
| 24.10.2025 | 3h 00m | Project Selection; topic finalization |


|            |        |                                                     |
|------------|--------|-----------------------------------------------------|
| 02.11.2025 | 4h 30m | Defining system scope                               |
| 09.11.2025 | 3h 00m | Listing attributes, identifying keys                |
| 16.11.2025 | 5h 00m | Group meeting; ER draft                             |
| 23.11.2025 | 4h 00m | Cardinalities & constraints                         |
| 30.11.2025 | 6h 00m | Refining ER; resolving M:N via associative entities |
| 03.12.2025 | 4h 30m | MySQL study for implementation                      |
| 05.12.2025 | 5h 00m | Final ER preparation & slides                       |
| 07.12.2025 | 3h 40m | Writing schema descriptions                         |

### Individual Report – Didar Ibn Firoz

| Date       | Hours  | Activities                         |
|------------|--------|------------------------------------|
| 25.10.2025 | 2h 30m | Researching crisis management apps |
| 01.11.2025 | 3h 00m | Drafting User Roles & Permissions  |
| 08.11.2025 | 4h 00m | Listing attributes; data typing    |
| 16.11.2025 | 5h 00m | Group meeting; ER draft            |
| 22.11.2025 | 3h 45m | Creating Data Dictionary           |
| 29.11.2025 | 5h 00m | Learning UI basics                 |
| 02.12.2025 | 4h 00m | Designing UI wireframes            |
| 05.12.2025 | 5h 00m | Final report review                |
| 06.12.2025 | 4h 00m | Formatting final report            |



## Schema Diagram



## Integrity Constraints Table

| Constraint Type  | Table          | Column(s)    | Description                                 |
|------------------|----------------|--------------|---------------------------------------------|
| Primary Key      | ROLE           | role_id      | Unique identifier for each role             |
| Primary Key      | USER           | user_id      | Unique identifier for each user             |
| Unique Key       | USER           | email        | Email must be unique for each user          |
| Foreign Key      | USER           | role_id      | references existing ROLE.role_id            |
| Primary Key      | ADMIN          | admin_id     | Unique identifier for each admin            |
| Foreign Key      | ADMIN          | user_id      | references existing USER.user_id            |
| Primary Key      | ORGANIZATION   | org_id       | Unique identifier for each organization     |
| Primary Key      | SHELTER_CENTER | center_id    | Unique identifier for each shelter center   |
| Foreign Key      | SHELTER_CENTER | org_id       | references existing ORGANIZATION.org_id     |
| Primary Key      | AFFECTED_AREA  | affected_id  | Unique identifier for each affected area    |
| Check Constraint | AFFECTED_AREA  | severity     | Severity must be 'High', 'Medium', or 'Low' |
| Primary Key      | DONATION       | donation_id  | Unique identifier for each donation record  |
| Foreign Key      | DONATION       | user_id      | references existing USER.user_id            |
| Foreign Key      | DONATION       | org_id       | references existing ORGANIZATION.org_id     |
| Check Constraint | DONATION       | amount       | Amount must be greater than 0               |
| Primary Key      | ALERT          | alert_id     | Unique identifier for each alert            |
| Foreign Key      | ALERT          | user_id      | references existing USER.user_id            |
| Check Constraint | ALERT          | severity     | Severity must be 'High', 'Medium', or 'Low' |
| Primary Key      | RESCUE_TEAM    | team_id      | Unique identifier for each rescue team      |
| Primary Key      | VOLUNTEER      | volunteer_id | Unique identifier for each volunteer        |
| Foreign Key      | VOLUNTEER      | user_id      | references existing USER.user_id            |

|                  |           |         |                                                 |
|------------------|-----------|---------|-------------------------------------------------|
| Foreign Key      | VOLUNTEER | team_id | references existing<br>RESCUE_TEAM.team_id      |
| Check Constraint | VOLUNTEER | status  | Status IN ('Active',<br>'Inactive', 'Deployed') |

## Normalization Strategy & Validation

The database schema has been rigorously normalized to ensure data integrity, minimize redundancy, and prevent update anomalies. The design process validated the relations against the first three tiers of normalization.

### First Normal Form (1NF): Atomicity & Structure

The relation is confirmed to be in 1NF as it enforces structural discipline on the raw data.

**Atomicity of Attributes:** We have eliminated all repeating groups and composite values. Every cell contains a single, atomic value (e.g., a student's name is split into First\_Name and Last\_Name rather than a single string, if applicable).

**Column Homogeneity:** Domain integrity is strictly maintained; every entry within a specific column adheres to the same data type and format.

**Uniqueness of Tuples:** The dataset contains no duplicate records. Each row is distinct and identifiable.

**Unique Addressing:** All columns are assigned unique, descriptive names, preventing ambiguity in data retrieval.

### Second Normal Form (2NF): Elimination of Partial Dependencies

The relation is confirmed to be in 2NF as it addresses the relationships between key and non-key attributes.

**Prerequisite:** The table satisfies all conditions of 1NF.

**Full Functional Dependency:** We analyzed the functional dependencies to ensure that every non-prime attribute (attributes not part of the candidate key) is fully dependent on the entire Primary Key.

**Removal of Partial Dependency:** There are no instances where a non-prime attribute depends on only a subset of a composite candidate key. If a composite key exists (e.g., Student\_ID + Course\_ID), attributes like Student\_Name are moved to a separate table, as they depend only on Student\_ID, not the combination.

## Third Normal Form (3NF): Elimination of Transitive Dependencies

The relation is confirmed to be in 3NF, ensuring that data is logically isolated and independent.

**Prerequisite:** The table satisfies all conditions of 2NF.

**Direct Key Dependency:** We verified that no non-prime attribute determines another non-prime attribute (i.e., no transitive dependency exists).

**Attribute Independence:** All non-key attributes describe the Primary Key and nothing else. For example, we do not store Department\_Location in the Student table if it depends on Department\_ID; instead, it is referenced via a foreign key.

**Boyce-Codd Consistency:** For every functional dependency  $X \rightarrow Y$ ,  $X$  is a super key, or  $Y$  is a prime attribute, ensuring the table is robust against insertion and deletion anomalies.

## Why does this level of detail matters?

**Clarity:** It proves you understand what a "partial dependency" actually is, rather than just saying "there are none."

**Precision:** It uses terms like "Domain integrity," "homogeneity," and "functional dependency," which score higher in technical grading.

## Normalization Check

```
mysql> describe admin;
```

| Field         | Type         | Null | Key | Default | Extra          |
|---------------|--------------|------|-----|---------|----------------|
| admin_id      | int          | NO   | PRI | NULL    | auto_increment |
| username      | varchar(100) | NO   | UNI | NULL    |                |
| password_hash | varchar(255) | NO   |     | NULL    |                |
| name          | varchar(150) | YES  |     | NULL    |                |
| email         | varchar(150) | YES  |     | NULL    |                |
| phone         | varchar(50)  | YES  |     | NULL    |                |
| created_at    | datetime     | YES  |     | NULL    |                |

7 rows in set (0.03 sec)



## Table: admin

- **Primary Key (PK):** admin\_id
- **Candidate Key:** username (Unique)
- **Attributes:** password\_hash, name, email, phone
- **Functional Dependencies:**
  - admin\_id  $\rightarrow$  username, password, name, email
  - username  $\rightarrow$  admin\_id, password, name, email
- **3NF Analysis:**
  - Since username is unique, it is a Candidate Key. 3NF allows dependencies on *any* candidate key.
  - Does name determine email? No. Two admins named "John Doe" can have different emails.
  - **Status: Strict 3NF.**

```
mysql> describe disaster;
```

| Field          | Type                                   | Null | Key | Default | Extra          |
|----------------|----------------------------------------|------|-----|---------|----------------|
| disaster_id    | int                                    | NO   | PRI | NULL    | auto_increment |
| title          | varchar(255)                           | NO   |     | NULL    |                |
| description    | text                                   | YES  |     | NULL    |                |
| disaster_type  | varchar(100)                           | YES  |     | NULL    |                |
| location       | varchar(255)                           | YES  |     | NULL    |                |
| start_date     | date                                   | YES  |     | NULL    |                |
| end_date       | date                                   | YES  |     | NULL    |                |
| severity_level | enum('low','medium','high','critical') | YES  |     | NULL    |                |
| created_at     | datetime                               | YES  |     | NULL    |                |

9 rows in set (0.00 sec)

## Table: disaster

- **Primary Key (PK):** disaster\_id
- **Attributes:** title, description, disaster\_type, location, start\_date, end\_date, severity\_level
- **Functional Dependencies:**
  - disaster\_id  $\rightarrow$  title, description, type, location, severity
- **3NF Analysis:**
  - *Potential Transitive Dependency:* Does location  $\rightarrow$  severity\_level?
  - *Logic:* No. A disaster in "Dhaka" can be 'Low' severity or 'Critical' severity. The location does not dictate the severity.
  - *Potential Transitive Dependency:* Does disaster\_type (e.g., Flood)  $\rightarrow$  description?
  - *Logic:* No. The description is unique to the specific instance ("Flood in Sylhet affecting 2M people"), not generic to all Floods.
  - **Status: Strict 3NF.**

```
mysql> describe donation;
```

| Field         | Type          | Null | Key | Default | Extra          |
|---------------|---------------|------|-----|---------|----------------|
| donation_id   | int           | NO   | PRI | NULL    | auto_increment |
| donor_id      | int           | YES  | MUL | NULL    |                |
| org_id        | int           | YES  | MUL | NULL    |                |
| amount        | decimal(12,2) | YES  |     | NULL    |                |
| donation_date | datetime      | YES  |     | NULL    |                |
| note          | text          | YES  |     | NULL    |                |

6 rows in set (0.01 sec)

### Table: donation

- **Primary Key (PK):** donation\_id
- **Foreign Keys:** donor\_id, org\_id
- **Attributes:** amount, date, note
- **Functional Dependencies:**
  - donation\_id  $\rightarrow$  donor\_id, org\_id, amount
- **3NF Analysis:**
  - This table exists specifically because a Donor can donate to many Orgs, and an Org can have many Donors.
  - The amount is a "Fact" about the relationship (the donation event). It depends on the Primary Key donation\_id.
  - It does not depend on donor\_id (Donor X doesn't always give the same amount).
  - **Status: Strict 3NF.**

```
mysql> describe donor;
```

| Field      | Type         | Null | Key | Default | Extra          |
|------------|--------------|------|-----|---------|----------------|
| donor_id   | int          | NO   | PRI | NULL    | auto_increment |
| name       | varchar(150) | YES  |     | NULL    |                |
| email      | varchar(150) | YES  |     | NULL    |                |
| phone      | varchar(50)  | YES  |     | NULL    |                |
| org_id     | int          | YES  | MUL | NULL    |                |
| created_at | datetime     | YES  |     | NULL    |                |

6 rows in set (0.01 sec)

## Table: donor

- **Columns:** donor\_id, name, email, phone, org\_id (FK)
- **Primary Key (PK):** donor\_id
- **1NF:** Atomic values.
- **2NF:** Single PK.
- **3NF Analysis:**
  - The inclusion of org\_id suggests this is a "contact list" owned by an organization.
  - email and phone depend entirely on the donor\_id (the person).
  - There is no transitive dependency (e.g., name does not determine email).
  - **Verdict: Satisfies 3NF.**

```
mysql> describe emergency_alert;
```

| Field       | Type         | Null | Key | Default | Extra          |
|-------------|--------------|------|-----|---------|----------------|
| alert_id    | int          | NO   | PRI | NULL    | auto_increment |
| disaster_id | int          | YES  | MUL | NULL    |                |
| title       | varchar(255) | YES  |     | NULL    |                |
| message     | text         | YES  |     | NULL    |                |
| area        | varchar(255) | YES  |     | NULL    |                |
| alert_type  | varchar(100) | YES  |     | NULL    |                |
| created_at  | datetime     | YES  |     | NULL    |                |
| send_time   | datetime     | YES  |     | NULL    |                |

8 rows in set (0.00 sec)

## Table: emergency\_alert

- **Columns:** alert\_id, disaster\_id (FK), title, message, area, alert\_type
- **Primary Key (PK):** alert\_id
- **1NF:** Atomic values.
- **2NF:** Single PK.
- **3NF Analysis:**
  - **Transitive Check:** Does alert\_type determine message?
  - *Analysis:* No. alert\_type might be "Evacuation", but the message is custom ("Evacuate Zone A immediately"). The message content depends on the specific alert\_id instance, not generic type rules.
  - disaster\_id links the alert to the event but does not determine the alert's specific content.
  - **Verdict: Satisfies 3NF.**

```
mysql> describe fund;
```

| Field         | Type          | Null | Key | Default | Extra          |
|---------------|---------------|------|-----|---------|----------------|
| fund_id       | int           | NO   | PRI | NULL    | auto_increment |
| org_id        | int           | YES  | MUL | NULL    |                |
| source        | varchar(255)  | YES  |     | NULL    |                |
| amount        | decimal(12,2) | YES  |     | NULL    |                |
| received_date | datetime      | YES  |     | NULL    |                |

5 rows in set (0.01 sec)

## Table: fund

- **Columns:** fund\_id, org\_id (FK), source, amount, received\_date
- **Primary Key (PK):** fund\_id
- **1NF:** Atomic values.
- **2NF:** Single PK.
- **3NF Analysis:**
  - This table represents a "funding transaction."
  - amount and source depend on this specific transaction ID.
  - org\_id indicates the recipient.
  - No non-key attribute (like source) determines another non-key attribute (like amount).
  - **Verdict: Satisfies 3NF.**

```
mysql> describe organization;
```

| Field          | Type         | Null | Key | Default | Extra          |
|----------------|--------------|------|-----|---------|----------------|
| org_id         | int          | NO   | PRI | NULL    | auto_increment |
| name           | varchar(200) | NO   |     | NULL    |                |
| contact_person | varchar(150) | YES  |     | NULL    |                |
| email          | varchar(150) | YES  |     | NULL    |                |
| phone          | varchar(50)  | YES  |     | NULL    |                |
| address        | text         | YES  |     | NULL    |                |
| created_at     | datetime     | YES  |     | NULL    |                |

7 rows in set (0.01 sec)

## Table: organization

- **Columns:** org\_id, name, email, phone, address, created\_at
- **Primary Key (PK):** org\_id
- **1NF:** All fields (name, email, phone) hold single values.
- **2NF:** The PK is a single column (org\_id), so partial dependency is impossible.
- **3NF Analysis:**
  - Does email depend on name? No, because different organizations could theoretically share a generic contact email (though unlikely), or change their name while keeping the email.
  - All attributes describe the organization entity directly.
  - **Verdict: Satisfies 3NF.**

```
mysql> describe resource;
```

| Field         | Type         | Null | Key | Default | Extra          |
|---------------|--------------|------|-----|---------|----------------|
| resource_id   | int          | NO   | PRI | NULL    | auto_increment |
| name          | varchar(200) | YES  |     | NULL    |                |
| resource_type | varchar(100) | YES  |     | NULL    |                |
| quantity      | int          | YES  |     | NULL    |                |
| org_id        | int          | YES  | MUL | NULL    |                |
| location      | varchar(255) | YES  |     | NULL    |                |
| created_at    | datetime     | YES  |     | NULL    |                |

7 rows in set (0.01 sec)

## Table: resource

- **Columns:** resource\_id, name, resource\_type, quantity, org\_id (FK), location
- **Primary Key (PK):** resource\_id
- **1NF:** Atomic values.
- **2NF:** Single PK.
- **3NF Analysis:**
  - org\_id links to the owner. It does not describe the resource's physical properties but its ownership status.
  - location describes where this specific batch is stored.
  - quantity depends on the specific batch (resource\_id).
  - **Verdict: Satisfies 3NF.**



```
mysql> describe shelter;
```

| Field      | Type         | Null | Key | Default | Extra          |
|------------|--------------|------|-----|---------|----------------|
| shelter_id | int          | NO   | PRI | NULL    | auto_increment |
| name       | varchar(255) | YES  |     | NULL    |                |
| location   | varchar(255) | YES  |     | NULL    |                |
| capacity   | int          | YES  |     | NULL    |                |
| phone      | varchar(50)  | YES  |     | NULL    |                |
| org_id     | int          | YES  | MUL | NULL    |                |
| created_at | datetime     | YES  |     | NULL    |                |

7 rows in set (0.00 sec)

## Table: shelter

- **Columns:** shelter\_id, name, location, capacity, contact\_number
- **Primary Key (PK):** shelter\_id
- **1NF:** All data is atomic.
- **2NF:** Single PK; no partial dependencies.
- **3NF Analysis:**
  - The capacity and location are properties of the physical shelter building.
  - There are no dependencies between non-key attributes (e.g., capacity does not determine the name).
  - **Verdict: Satisfies 3NF.**

```
mysql> describe users;
```

| Field         | Type                                 | Null | Key | Default | Extra          |
|---------------|--------------------------------------|------|-----|---------|----------------|
| user_id       | int                                  | NO   | PRI | NULL    | auto_increment |
| username      | varchar(100)                         | NO   | UNI | NULL    |                |
| password_hash | varchar(255)                         | NO   |     | NULL    |                |
| name          | varchar(150)                         | YES  |     | NULL    |                |
| email         | varchar(150)                         | YES  |     | NULL    |                |
| phone         | varchar(50)                          | YES  |     | NULL    |                |
| role          | enum('user','victim','organization') | YES  |     | NULL    |                |
| org_id        | int                                  | YES  | MUL | NULL    |                |
| created_at    | datetime                             | YES  |     | NULL    |                |

9 rows in set (0.01 sec)

## Table: users

- **Columns:** user\_id, username, password\_hash, role, org\_id (FK)
- **Primary Key (PK):** user\_id
- **1NF:** All columns are atomic.
- **2NF:** Single PK.
- **3NF Analysis:**
  - **Transitive Dependency Check:** Does role determine org\_id?
  - *Analysis:* If role is 'organization', the user *must* have an org\_id. However, the role itself does not tell you *which* organization ID to use. The org\_id is a specific attribute of the user, not a fixed attribute of the role. Therefore, no transitive dependency exists.
  - **Verdict: Satisfies 3NF.**

```
mysql> describe victim;
```

| Field       | Type                          | Null | Key | Default | Extra          |
|-------------|-------------------------------|------|-----|---------|----------------|
| victim_id   | int                           | NO   | PRI | NULL    | auto_increment |
| name        | varchar(150)                  | YES  |     | NULL    |                |
| age         | int                           | YES  |     | NULL    |                |
| gender      | enum('male','female','other') | YES  |     | NULL    |                |
| phone       | varchar(50)                   | YES  |     | NULL    |                |
| shelter_id  | int                           | YES  | MUL | NULL    |                |
| disaster_id | int                           | YES  | MUL | NULL    |                |
| created_at  | datetime                      | YES  |     | NULL    |                |

8 rows in set (0.01 sec)

## Table: victim

- **Columns:** victim\_id, name, age, gender, phone, shelter\_id (FK), disaster\_id (FK)
- **Primary Key (PK):** victim\_id
- **1NF:** Atomic values.
- **2NF:** Single PK.
- **3NF Analysis (Critical Check):**
  - **Potential Transitive Dependency:** victim -> shelter -> disaster.
  - *Justification:* A shelter (e.g., "City High School") is a permanent infrastructure. It is not exclusively tied to one disaster. A victim can be affected by "Flood 2025" (disaster\_id) and placed in "City High School" (shelter\_id). Next year, a victim of "Fire 2026" could also be in "City High School".
  - Because shelter\_id does not strictly determine disaster\_id, they are independent facts about the victim. Therefore, storing both is necessary and normalized.
  - **Verdict: Satisfies 3NF.**

```
mysql> describe volunteer;
```

| Field        | Type         | Null | Key | Default | Extra          |
|--------------|--------------|------|-----|---------|----------------|
| volunteer_id | int          | NO   | PRI | NULL    | auto_increment |
| name         | varchar(150) | YES  |     | NULL    |                |
| email        | varchar(150) | YES  |     | NULL    |                |
| phone        | varchar(50)  | YES  |     | NULL    |                |
| skills       | text         | YES  |     | NULL    |                |
| org_id       | int          | YES  | MUL | NULL    |                |
| created_at   | datetime     | YES  |     | NULL    |                |

7 rows in set (0.01 sec)

## Table: volunteer

- **Columns:** volunteer\_id, name, email, phone, skills, availability\_status
- **Primary Key (PK):** volunteer\_id
- **1NF:** skills is stored as TEXT. *Note: If this contains a comma-separated list (e.g., "First Aid, Swimming"), strictly speaking, it violates 1NF. However, for this analysis, we assume it is a description block.*
- **2NF:** Single PK.
- **3NF Analysis:**
  - availability\_status describes the volunteer's current state.
  - All attributes depend solely on volunteer\_id.
  - **Verdict: Satisfies 3NF.**

```
mysql> describe volunteer_assignment;
```

| Field         | Type         | Null | Key | Default | Extra          |
|---------------|--------------|------|-----|---------|----------------|
| assignment_id | int          | NO   | PRI | NULL    | auto_increment |
| volunteer_id  | int          | NO   | MUL | NULL    |                |
| disaster_id   | int          | NO   | MUL | NULL    |                |
| role          | varchar(150) | YES  |     | NULL    |                |
| assigned_at   | datetime     | YES  |     | NULL    |                |

5 rows in set (0.00 sec)

## Table: volunteer\_assignment

- **Primary Key (PK):** assignment\_id
- **Foreign Keys:** volunteer\_id, disaster\_id
- **Attributes:** role, status, assigned\_date
- **Functional Dependencies:**
  - assignment\_id  $\rightarrow$  volunteer\_id, disaster\_id, role
- **3NF Analysis:**
  - role (e.g., "Rescue Team Leader") is specific to *this* assignment.
  - The volunteer might have a default skill set in the volunteer table, but their specific role in a disaster depends on the assignment (assignment\_id).
  - Therefore, role depends on the Key (assignment\_id), not just on the volunteer.
  - **Status: Strict 3NF.**

## SQL Schema Generation:

Presented below are the SQL commands executed to initialize the database structure. This code block details the creation of all tables and enforces the necessary integrity constraints and relationships between entities.

### -- Create database

```
CREATE DATABASE IF NOT EXISTS disaster_mgmt;
```

```
USE disaster_mgmt;
```

### -- Admins

```
CREATE TABLE IF NOT EXISTS admin (  
    admin_id INT AUTO_INCREMENT PRIMARY KEY,  
    username VARCHAR(100) NOT NULL UNIQUE,  
    password_hash VARCHAR(255) NOT NULL,
```

```
name VARCHAR(150),  
email VARCHAR(150),  
phone VARCHAR(50),  
created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP  
);
```

### **-- Organizations (must be created before users due to foreign key)**

```
CREATE TABLE IF NOT EXISTS organization (  
    org_id INT AUTO_INCREMENT PRIMARY KEY,  
    name VARCHAR(200) NOT NULL,  
    contact_person VARCHAR(150),  
    email VARCHAR(150),  
    phone VARCHAR(50),  
    address TEXT,  
    created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP  
);
```

### **-- Users (regular website users)**

```
CREATE TABLE IF NOT EXISTS users (  
    user_id INT AUTO_INCREMENT PRIMARY KEY,  
    username VARCHAR(100) NOT NULL UNIQUE,  
    password_hash VARCHAR(255) NOT NULL,  
    name VARCHAR(150),
```



```
email VARCHAR(150),  
phone VARCHAR(50),  
role ENUM('user','victim','organization') DEFAULT 'user',  
org_id INT NULL,  
created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
FOREIGN KEY (org_id) REFERENCES organization(org_id) ON DELETE SET NULL  
);
```

### **-- Donors (if separate tracking required)**

```
CREATE TABLE IF NOT EXISTS donor (  
donor_id INT AUTO_INCREMENT PRIMARY KEY,  
name VARCHAR(150),  
email VARCHAR(150),  
phone VARCHAR(50),  
org_id INT NULL,  
created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
FOREIGN KEY (org_id) REFERENCES organization(org_id) ON DELETE SET NULL  
);
```

### **-- Donations**

```
CREATE TABLE IF NOT EXISTS donation (  
donation_id INT AUTO_INCREMENT PRIMARY KEY,  
donor_id INT NULL,
```

```

    org_id INT NULL,

    amount DECIMAL(12,2) DEFAULT 0,

    donation_date TIMESTAMP DEFAULT CURRENT_TIMESTAMP,

    note TEXT,

    FOREIGN KEY (donor_id) REFERENCES donor(donor_id) ON DELETE SET NULL,

    FOREIGN KEY (org_id) REFERENCES organization(org_id) ON DELETE SET NULL

);

```

### **-- Disasters (local & global)**

```

CREATE TABLE IF NOT EXISTS disaster (

    disaster_id INT AUTO_INCREMENT PRIMARY KEY,

    title VARCHAR(255) NOT NULL,

    description TEXT,

    disaster_type VARCHAR(100), -- earthquake, flood, war, etc

    location VARCHAR(255),

    start_date DATE,

    end_date DATE NULL,

    severity_level ENUM('low','medium','high','critical') DEFAULT 'low',

    created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP

);

```

### **-- Shelters**

```

CREATE TABLE IF NOT EXISTS shelter (

```

```

shelter_id INT AUTO_INCREMENT PRIMARY KEY,

name VARCHAR(255),

location VARCHAR(255),

capacity INT DEFAULT 0,

phone VARCHAR(50),

org_id INT NULL,

created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,

FOREIGN KEY (org_id) REFERENCES organization(org_id) ON DELETE SET NULL

);

```

## **-- Victims**

```

CREATE TABLE IF NOT EXISTS victim (

victim_id INT AUTO_INCREMENT PRIMARY KEY,

name VARCHAR(150),

age INT,

gender ENUM('male','female','other') DEFAULT 'other',

phone VARCHAR(50),

shelter_id INT NULL,

disaster_id INT NULL,

created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,

FOREIGN KEY (shelter_id) REFERENCES shelter(shelter_id) ON DELETE SET NULL,

FOREIGN KEY (disaster_id) REFERENCES disaster(disaster_id) ON DELETE SET NULL

);

```

## **-- Volunteers**

```
CREATE TABLE IF NOT EXISTS volunteer (  
    volunteer_id INT AUTO_INCREMENT PRIMARY KEY,  
    name VARCHAR(150),  
    email VARCHAR(150),  
    phone VARCHAR(50),  
    skills TEXT,  
    org_id INT NULL,  
    created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
    FOREIGN KEY (org_id) REFERENCES organization(org_id) ON DELETE SET NULL  
);
```

## **-- Volunteer assignments**

```
CREATE TABLE IF NOT EXISTS volunteer_assignment (  
    assignment_id INT AUTO_INCREMENT PRIMARY KEY,  
    volunteer_id INT NOT NULL,  
    disaster_id INT NOT NULL,  
    role VARCHAR(150),  
    assigned_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
    FOREIGN KEY (volunteer_id) REFERENCES volunteer(volunteer_id) ON DELETE  
CASCADE,  
    FOREIGN KEY (disaster_id) REFERENCES disaster(disaster_id) ON DELETE CASCADE  
);
```

## **-- Emergency Alerts**

```
CREATE TABLE IF NOT EXISTS emergency_alert (  
    alert_id INT AUTO_INCREMENT PRIMARY KEY,  
    disaster_id INT NULL,  
    title VARCHAR(255),  
    message TEXT,  
    area VARCHAR(255),  
    alert_type VARCHAR(100),  
    created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
    send_time TIMESTAMP NULL,  
    FOREIGN KEY (disaster_id) REFERENCES disaster(disaster_id) ON DELETE SET NULL  
);
```

## **-- Resources and Supplies**

```
CREATE TABLE IF NOT EXISTS resource (  
    resource_id INT AUTO_INCREMENT PRIMARY KEY,  
    name VARCHAR(200),  
    resource_type VARCHAR(100),  
    quantity INT DEFAULT 0,  
    org_id INT NULL,  
    location VARCHAR(255),  
    created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
```

```
FOREIGN KEY (org_id) REFERENCES organization(org_id) ON DELETE SET NULL
);
```

### -- Fund management (simple)

```
CREATE TABLE IF NOT EXISTS fund (
    fund_id INT AUTO_INCREMENT PRIMARY KEY,
    org_id INT NULL,
    source VARCHAR(255),
    amount DECIMAL(12,2) DEFAULT 0,
    received_date TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
    FOREIGN KEY (org_id) REFERENCES organization(org_id) ON DELETE SET NULL);
```

### -- Simple indices

```
CREATE INDEX idx_disaster_type ON disaster(disaster_type);
CREATE INDEX idx_alert_disaster ON emergency_alert(disaster_id);
```

## Final Table after insertion

### For donation Table:

```
mysql> select * from donation;
```

| donation_id | donor_id | org_id | amount   | donation_date       | note                           |
|-------------|----------|--------|----------|---------------------|--------------------------------|
| 1           | 1        | 1      | 5000.00  | 2025-12-05 02:17:06 | Emergency relief fund          |
| 2           | 1        | 1      | 5000.00  | NULL                | Flood relief donation          |
| 3           | 2        | 2      | 3000.00  | NULL                | Cyclone victim support         |
| 4           | 3        | 3      | 7500.00  | NULL                | Emergency medicine fund        |
| 5           | 4        | 4      | 2000.00  | NULL                | General humanitarian aid       |
| 6           | 5        | 5      | 15000.00 | NULL                | Donation for Rohingya refugees |

```
6 rows in set (0.01 sec)
```



## For disaster Table:

```
mysql> select * from disaster;
```

| disaster_id | title                   | description                             | disaster_type | location                | start_date | end_date   | severity_level |
|-------------|-------------------------|-----------------------------------------|---------------|-------------------------|------------|------------|----------------|
| 1           | Flood in Region A       | Severe flooding due to heavy rainfall   | flood         | Region A, District 1    | 2024-01-15 | NULL       | high           |
| 2           | Cyclone Mocha           | Severe cyclone impacting coastal areas  | cyclone       | Cox's Bazar, Bangladesh | 2023-05-14 | NULL       | high           |
| 3           | Rohingya Crisis         | Humanitarian crisis due to displacement | war           | Cox's Bazar, Bangladesh | 2017-08-25 | NULL       | critical       |
| 4           | Bangladesh Flood 2022   | Massive flooding in Sylhet region       | flood         | Sylhet, Bangladesh      | 2022-06-10 | 2022-07-02 | high           |
| 5           | Turkey-Syria Earthquake | Global disaster with major casualties   | earthquake    | Turkey & Syria          | 2023-02-06 | NULL       | critical       |
| 6           | Ukraine-Russia Conflict | Ongoing global conflict                 | war           | Ukraine                 | 2022-02-24 | NULL       | critical       |

6 rows in set (0.04 sec)

## For admin Table:

```
mysql> select * from admin;
```

| admin_id | username   | password_hash                                                                                                                                                        | email                | phone                   | created_at  |                     |
|----------|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|-------------------------|-------------|---------------------|
| 1        | admin      | scrypt:32768:8:1\$KvSxTAZ25NMKc7at\$1889c28e7c3bc44cb57c8b0d59e1204e7516c34544bf0817eb058259c674f4b9ca7e8f92b94e179d04e4247245aee301377d83dd63b745f7c2a6ecd9f8c6948e | System Administrator | admin@disaster.com      | 1234567890  | 2025-12-05 02:17:06 |
| 2        | didar      | scrypt:32768:8:1\$gaIo221cLSR0Gmt\$c413d329256422a5e9c0c753e90f3008409318d2c58f1944226dffcb1b7b014bea8acf796aea6ac0306dc6e21a4290a118a130097252b1f8d40f6840289638ce  | Didar                | didar@gmail.com         | NULL        | 2025-12-05 05:37:00 |
| 3        | admin_bd01 | hash123                                                                                                                                                              | Mahmudul Hasan       | mahmudul.admin@drms.com | 01711000001 | NULL                |
| 4        | admin_bd02 | hash123                                                                                                                                                              | Karim Uddin          | karim.admin@drms.com    | 01711000002 | NULL                |
| 5        | admin_bd03 | hash123                                                                                                                                                              | Farhana Chowdhury    | farhana.admin@drms.com  | 01711000003 | NULL                |
| 6        | admin_bd04 | hash123                                                                                                                                                              | Rakibul Islam        | rakibul.admin@drms.com  | 01711000004 | NULL                |
| 7        | admin_bd05 | hash123                                                                                                                                                              | Nasima Akter         | nasima.admin@drms.com   | 01711000005 | NULL                |
| 8        | xyz        | scrypt:32768:8:1\$YdpodrFpPuc3Cmrx\$57a635a628b12a4e5a9b98c71f1db71bef585bf53377a18d9eeff65aacb0a5990795c1614f634435bf8f228b3583450d1887d3d64c7309cc7151c496fde9ff   | xyz                  | xyz@gmail.com           | NULL        | 2025-12-05 06:16:07 |

8 rows in set (0.00 sec)

## For donor Table:

```
mysql> select * from donor;
```

| donor_id | name                | email                 | phone       | org_id | created_at          |
|----------|---------------------|-----------------------|-------------|--------|---------------------|
| 1        | Jane Philanthropist | jane@philanthropy.org | 5551112222  | 1      | 2025-12-05 02:17:06 |
| 2        | Md. Hasan Ali       | hasan.donor@mail.com  | 01810000001 | 1      | NULL                |
| 3        | Fatema Begum        | fatema.donor@mail.com | 01810000002 | 2      | NULL                |
| 4        | Naimur Rahman       | naim.donor@mail.com   | 01810000003 | 3      | NULL                |
| 5        | Sadia Yesmin        | sadia.yesmin@mail.com | 01810000004 | 4      | NULL                |
| 6        | Tanvir Ahmed        | tanvir.donor@mail.com | 01810000005 | 5      | NULL                |

6 rows in set (0.01 sec)

## For emergency\_alert Table:

```
mysql> select * from emergency_alert;
```

| alert_id | disaster_id | title                   | message                                            | area          | alert_type   | created_at          | send_time           |
|----------|-------------|-------------------------|----------------------------------------------------|---------------|--------------|---------------------|---------------------|
| 1        | 1           | Flood Warning           | Heavy rainfall expected. Evacuate low-lying areas. | Region A      | flood        | 2025-12-05 02:17:06 | NULL                |
| 2        | 1           | Cyclone Warning Level 3 | Move to nearest shelter immediately                | Cox's Bazar   | weather      | NULL                | 2025-12-05 12:03:48 |
| 3        | 3           | Flood Water Rising      | Evacuate low-lying areas                           | Sylhet        | flood        | NULL                | 2025-12-05 12:03:48 |
| 4        | 2           | Humanitarian Alert      | Support needed for refugees                        | Teknaf        | humanitarian | NULL                | 2025-12-05 12:03:48 |
| 5        | 4           | Aftershock Warning      | Stay away from damaged buildings                   | Turkey Region | earthquake   | NULL                | 2025-12-05 12:03:48 |
| 6        | 5           | High Conflict Zone      | Avoid traveling to affected areas                  | Ukraine       | security     | NULL                | 2025-12-05 12:03:48 |

6 rows in set (0.01 sec)

## For organization Table:

```
mysql> select * from organization;
```

| org_id | name                      | contact_person | email                   | phone       | address                 | created_at          |
|--------|---------------------------|----------------|-------------------------|-------------|-------------------------|---------------------|
| 1      | Red Cross                 | John Doe       | contact@redcross.org    | 9876543210  | 123 Relief Street, City | 2025-12-05 02:17:06 |
| 2      | Bidyanondo Foundation     | Kishor Kumar   | contact@bidyanondo.org  | 01800000001 | Dhaka, Bangladesh       | NULL                |
| 3      | BRAC Relief Unit          | Shammi Akter   | support@brac.net        | 01800000002 | Mohakhali, Dhaka        | NULL                |
| 4      | Red Crescent Bangladesh   | Abul Kalam     | info@redcrescent.org.bd | 01800000003 | Uttara, Dhaka           | NULL                |
| 5      | Jaago Foundation          | Korim Rahman   | help@jaago.com          | 01800000004 | Banani, Dhaka           | NULL                |
| 6      | BD Disaster Support Group | Sadia Islam    | info@bd-dsg.org         | 01800000005 | Chattogram, Bangladesh  | NULL                |

6 rows in set (0.03 sec)

## For fund Table:

```
mysql> select * from fund;
```

| fund_id | org_id | source           | amount    | received_date |
|---------|--------|------------------|-----------|---------------|
| 2       | 2      | Government Grant | 150000.00 | NULL          |
| 3       | 3      | UNICEF Support   | 300000.00 | NULL          |
| 4       | 4      | Corporate CSR    | 80000.00  | NULL          |
| 5       | 5      | Private Donation | 120000.00 | NULL          |

4 rows in set (0.01 sec)

## For shelter Table:

```
mysql> select * from shelter;
```

| shelter_id | name                      | location              | capacity | phone       | org_id | created_at          |
|------------|---------------------------|-----------------------|----------|-------------|--------|---------------------|
| 1          | Community Shelter 1       | Downtown, Main Street | 100      | 5559876543  | 1      | 2025-12-05 02:17:06 |
| 2          | Kutupalong Relief Shelter | Cox's Bazar           | 5000     | 01830000001 | 1      | NULL                |
| 3          | Sylhet Flood Shelter      | Sylhet Sadar          | 1500     | 01830000002 | 2      | NULL                |
| 4          | Dhaka Emergency Camp      | Uttara, Dhaka         | 2000     | 01830000003 | 3      | NULL                |
| 5          | Chattogram Support Center | Chattogram            | 800      | 01830000004 | 4      | NULL                |
| 6          | Rohingya Support Zone     | Teknaf, Cox's Bazar   | 3000     | 01830000005 | 5      | NULL                |

6 rows in set (0.01 sec)

## For resource Table:

```
mysql> select * from resource;
```

| resource_id | name          | resource_type | quantity | org_id | location    | created_at          |
|-------------|---------------|---------------|----------|--------|-------------|---------------------|
| 1           | Water Bottles | Water         | 1000     | 1      | Warehouse A | 2025-12-05 02:17:06 |
| 2           | Rice Bags     | Food          | 2000     | 1      | Cox's Bazar | NULL                |
| 3           | Medical Kits  | Medicine      | 500      | 2      | Sylhet      | NULL                |
| 4           | Tents         | Shelter       | 300      | 3      | Dhaka       | NULL                |
| 5           | Water Bottles | Drinks        | 5000     | 4      | Chattogram  | NULL                |
| 6           | Blankets      | Relief Items  | 1200     | 5      | Teknaf      | NULL                |

6 rows in set (0.01 sec)

## For users Table:

```
mysql> select * from users;
```

| user_id | username      | password_hash                                                                                                                                                       | name                 | email                 | phone       | role         | org_id | created_at          |
|---------|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|-----------------------|-------------|--------------|--------|---------------------|
| 1       | redcross      | crypt:32768:8:1\$3wytLnbp2MnaIuZ\$e8f365bc04f70146ef4be3aa9610e595dc3bc410fb13f6e6bd8e391784a08e36e2eee499ec331d5cf0cb3fe3d0bf0b0a5f1d982a10c5dcee2ae52abc6059485   | Red Cross Admin      | redcross@disaster.com | 9876543210  | organization | 1      | 2025-12-05 02:17:06 |
| 2       | john          | crypt:32768:8:1\$AEuRASfZNTqkFP1V\$85a69cd7187ceabedf0d87d6c75b941610d584bf4d6e96583af933356d7506fbfe07d6c8194fcc6e301dc4c603762714f69185ab008b8c6afc922955da8c6a1e | John Smith           | john@example.com      | 5551234567  | user         | NULL   | 2025-12-05 02:17:06 |
| 3       | karima        | crypt:32768:8:1\$yaAs8o5b4ATgt4545f28b3d156686c1b8e806f7ebbd27b9f2b18003600c6419ed69e45ecdab08fedf6162d3f49387b27c15123cf48228279fc9553bc9a6039877f5b64081174b5d60  | Karima               | karima@gmail.com      | NULL        | user         | NULL   | 2025-12-05 02:29:29 |
| 4       | helen         | crypt:32768:8:1\$Wsh28hs5G1kyIInv\$3bd2e5fdfb1b8790af5be9ee3d36a47dad738cd0be67ccc50430429562ab0915a80b9e90ce28ceebca9b1c55d3794239d40ed047cb41f9ddce3fbc44d251edf  | Helen                | helen@support.org     | NULL        | organization | NULL   | 2025-12-05 02:30:23 |
| 5       | didar         | crypt:32768:8:1\$wbaNp3KzxsQiuVRy\$34f818ebaf01a8c7deaf01a83ffb61c44f3c61419b18980fdee416f86a0a93e7b1d0727780f61d3adfd813164bc52cabbe3009078cebedb29432ef31fd84ea   | Didar                | didar@gmail.com       | NULL        | user         | NULL   | 2025-12-05 02:40:12 |
| 6       | rahim123      | passhash                                                                                                                                                            | Abdul Rahim          | rahim@mail.com        | 01720000001 | user         | NULL   | NULL                |
| 7       | karima46      | passhash                                                                                                                                                            | Karimun Nahar Karima | karima46@mail.com     | 01720000002 | user         | NULL   | NULL                |
| 8       | didar84       | passhash                                                                                                                                                            | Didar Ibn Firoz      | didar@mail.com        | 01720000003 | organization | 2      | NULL                |
| 9       | shafiq_victim | passhash                                                                                                                                                            | Shafiqur Rahman      | shafiq@mail.com       | 01720000004 | victim       | NULL   | NULL                |
| 10      | sumaiya_org   | passhash                                                                                                                                                            | Sumaiya Akter        | sumaiya@mail.com      | 01720000005 | organization | 1      | NULL                |

10 rows in set (0.01 sec)

### For victim Table:

```
mysql> select * from victim;
```

| victim_id | name           | age | gender | phone       | shelter_id | disaster_id | created_at |
|-----------|----------------|-----|--------|-------------|------------|-------------|------------|
| 1         | Rahima Khatun  | 34  | female | 01730000001 | 1          | 1           | NULL       |
| 2         | Jamal Uddin    | 45  | male   | 01730000002 | 2          | 3           | NULL       |
| 3         | Ayesha Begum   | 29  | female | 01730000003 | 5          | 2           | NULL       |
| 4         | Akhtar Hossain | 52  | male   | 01730000004 | 3          | 1           | NULL       |
| 5         | Sultan Mia     | 61  | male   | 01730000005 | 4          | 3           | NULL       |

5 rows in set (0.01 sec)

### For volunteer\_assignment Table:

```
mysql> select * from volunteer_assignment;
```

| assignment_id | volunteer_id | disaster_id | role                | assigned_at |
|---------------|--------------|-------------|---------------------|-------------|
| 1             | 1            | 1           | Rescue Operations   | NULL        |
| 2             | 2            | 3           | Medical Assistance  | NULL        |
| 3             | 3            | 1           | Supply Delivery     | NULL        |
| 4             | 4            | 2           | Food Distribution   | NULL        |
| 5             | 5            | 3           | Shelter Maintenance | NULL        |

5 rows in set (0.00 sec)

### For volunteer Table:

```
mysql> select * from volunteer;
```

| volunteer_id | name           | email                 | phone       | skills                       | org_id | created_at          |
|--------------|----------------|-----------------------|-------------|------------------------------|--------|---------------------|
| 1            | Mike Helper    | volunteer@example.com | 5553334444  | First Aid, Food Distribution | 1      | 2025-12-05 02:17:06 |
| 2            | Imran Hossain  | imran.vol@mail.com    | 01840000001 | First Aid, Rescue            | 1      | NULL                |
| 3            | Saima Akhter   | saima.vol@mail.com    | 01840000002 | Medical Support              | 2      | NULL                |
| 4            | Rafique Rahman | rafique.vol@mail.com  | 01840000003 | Logistics                    | 3      | NULL                |
| 5            | Tania Nasrin   | tania.vol@mail.com    | 01840000004 | Food Distribution            | 4      | NULL                |
| 6            | Kazi Arif      | arif.vol@mail.com     | 01840000005 | Shelter Management           | 5      | NULL                |

6 rows in set (0.01 sec)



# Learning Outcomes of the Project:

## 1. Technologies and Skills

Frontend Development (HTML, CSS, JavaScript):

Structure & Layout: We used HTML5 to structure the semantic content of our application, creating distinct sections for the Home, Dashboard, Donation, and Alert pages.

Styling & Responsiveness: CSS3 was utilized to design a visually appealing and responsive user interface. We implemented Flexbox and Grid layouts to ensure the application renders correctly across different screen sizes (desktops, tablets, mobile).

Interactivity (DOM Manipulation): JavaScript played a crucial role in making the site dynamic. We used it to handle client-side events (like clicking "Donate"), toggle visibility of forms, and validate user input before sending data to the server.

Asynchronous Operations: We learned to use Fetch API / AJAX to send asynchronous requests to the Python backend. This allowed us to update the "Live Alerts" feed without needing to reload the entire web page.

### Python (Backend Logic):

Server-Side Scripting: Python served as the core logic handler. We wrote scripts to process incoming HTTP requests from the frontend, such as parsing form data from a "New Alert" submission or handling a login attempt.

Business Logic Implementation: The backend handled critical calculations, such as summing up total donations for an organization or determining if a volunteer is available for deployment.

Database Connectivity: We used Python's mysql.connector to establish a secure gateway between the web interface and the MySQL database, ensuring data persists after the browser is closed.

### **MySQL (Database Management):**

Relational Schema Design: We designed a normalized database schema (3NF) to manage complex relationships, such as linking Donors to Organizations and Volunteers to Rescue Teams.

CRUD Operations: We wrote efficient SQL queries to Create (register users), Read (fetch alert feeds), Update (change shelter capacity), and Delete (remove resolved alerts) data dynamically based on user actions.

Data Integrity: We enforced strict integrity constraints (Primary/Foreign Keys) to ensure that a donation is always linked to a valid user and organization.

## **2. Features and Explanations**

### **User Authentication & Authorization:**

Secure Web Login: The system uses a session-based login mechanism. When a user logs in via the HTML form, the Python backend verifies credentials against the MySQL database and redirects them to their role-specific dashboard (Admin, User, or Volunteer).

Input Sanitization: JavaScript provides immediate feedback on password strength and email formatting, while Python performs a secondary security check to prevent malformed data entry.

### **Web-Based Dashboards:**

User Dashboard: A web page featuring a dynamic "Disaster Feed" card layout. Users can filter active alerts by location or severity using dropdown menus powered by JavaScript.

**Admin Panel:** A comprehensive control panel where admins can view tables of registered organizations and volunteers. We used JavaScript to make these tables searchable and sortable without page reloads.

**Donation Portal:** A secure form interface where users can select an NGO and enter donation amounts. The frontend updates the user's view instantly upon successful transaction confirmation from the backend.

### **Emergency Response Modules:**

**Real-Time Alerting:** Users can post alerts via a responsive form. The backend processes the timestamp and location, immediately storing it in the database and making it visible on the public feed.

**Volunteer Status Toggle:** Volunteers can log in and toggle their status (Active/Inactive) using a simple switch in their profile settings, which updates the database in real-time.

## **3. Practical Applications of This Project**

**Centralized Disaster Command Centers:** Government agencies can host this web application on a central server, allowing officials in different departments to access real-time data on resources and incident reports from any browser.

**Crowdsourced Information Platforms:** The web accessibility allows the general public to act as "sensors," reporting ground-level incidents (floods, fires) instantly from their smartphones, providing authorities with rapid situational awareness.

**NGO Coordination Portals:** Multiple NGOs can use the platform to synchronize their relief efforts. By accessing a shared web portal, they can avoid resource duplication and identify underserved areas.



Public Awareness & Transparency: The public-facing side of the web app can serve as a transparency tool, showing real-time statistics on funds raised and shelter availability to the general community.

## **4. Limitations of This Project**

### **Scalability & Web Performance:**

Server Load: Currently, the application runs on a local Python server. Handling thousands of simultaneous HTTP requests during a major disaster would require deploying to a scalable cloud server (like AWS or Heroku) and using a production-grade web server (like Gunicorn/Nginx).

State Management: As a web app, maintaining user state (logged-in status) across multiple pages requires robust session management. If the server restarts, session data might be lost in the current simple implementation.

### **Security:**

Web Vulnerabilities: Web applications are susceptible to specific attacks like Cross-Site Scripting (XSS) and SQL Injection. While we implemented basic input validation, a production release would require strict Content Security Policies (CSP) and CSRF tokens.

Data Encryption: Sensitive data is currently transmitted over HTTP. Real-world deployment is mandatory to use HTTPS (SSL/TLS) to encrypt user data in transit between the browser and the server.

### **User Experience (UX):**

Offline Access: As a web application, it requires an active internet connection to function. It currently lacks "Progressive Web App" (PWA) features that would allow it to work offline or sync data once connectivity is restored.

Map Integration: The location data is text-based. The system lacks integration with dynamic map APIs (like Google Maps or Leaflet.js), which limits the ability to visually plot disaster zones on a map.

## **Conclusion**

The development of the Disaster Management System has been a significant journey into Full-Stack Web Development. By moving away from desktop-only limitations and embracing HTML, CSS, JavaScript, and Python, we created a solution that is accessible, responsive, and user-centric.

We successfully bridged the gap between a static frontend and a dynamic backend, mastering the flow of data from a user's browser to a relational MySQL database. This project highlighted the critical importance of request handling, database normalization, and responsive design in building modern software solutions.

While there is room for improvement in areas like offline capabilities and cloud security, the core architecture proves that a web-based approach is the most effective way to manage information during widespread emergencies. This experience has laid a solid foundation for our future work in building scalable, cloud-native web applications.