prac №6

1.


PC-PT
PC0
Laptop-PT
Laptop0
PC-PT
PC1
Laptop-PT
Laptop1
PC-PT
PC2
Laptop-PT
Laptop2

2.


Switch0
Physical
Config
CLI
Attributes
IOS Command Line Interface
Switch>en
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#vlan 2
Switch(config-vlan)#name programmer
Switch(config-vlan)#int range fa0/1-3
Switch(config-if-range)#switchport mode access
Switch(config-if-range)#switchport access vlan 2
Switch(config-if-range)#exit
Switch(config)#exit
Switch#
%SYS-5-CONFIG_I: Configured from console by console
Switch#show vlan
VLAN Name Status Ports
1 default active Fa0/4, Fa0/5, Fa0/6, Fa0/7
Fa0/8, Fa0/9, Fa0/10, Fa0/11
Fa0/12, Fa0/13, Fa0/14, Fa0/15
Fa0/16, Fa0/17, Fa0/18, Fa0/19
Fa0/20, Fa0/21, Fa0/22, Fa0/23
Fa0/24, Gig0/1, Gig0/2
2 programmer active Fa0/1, Fa0/2, Fa0/3
1002 fddi-default active
1003 token-ring-default active
1004 fddinet-default active
1005 trnet-default active
VLAN Type SAID MTU Parent RingNo BridgeNo Stp BrdgMode Trans1 Trans2
1 enet 100001 1500 - - - - - 0 0
2 enet 100002 1500 - - - - - 0 0
1002 fddi 101002 1500 - - - - - 0 0
1003 tr 101003 1500 - - - - - 0 0
1004 fdnet 101004 1500 - - - ieee - 0 0
--More--
Copy
Top

3.


Physical
Config
Desktop
Programming
Attributes
Command Prompt
Cisco Packet Tracer PC Command Line 1.0
C:\>ping
Cisco Packet Tracer PC Ping
Usage: ping [-n count | -v TOS | -t | target
C:\>ping 192.168.0.2
Pinging 192.168.0.2 with 32 bytes of data:
Reply from 192.168.0.2: bytes=32 time=4ms TTL=128
Reply from 192.168.0.2: bytes=32 time=4ms TTL=128
Reply from 192.168.0.2: bytes=32 time<1ms TTL=128
Reply from 192.168.0.2: bytes=32 time=3ms TTL=128
Ping statistics for 192.168.0.2:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 4ms, Average = 2ms
C:\>
PC-PT PC0
Laptop-PT Laptop0
PC-PT PC1
2960-24TT Switch0
Laptop-PT Laptop1
PC-PT PC2
Laptop-PT Laptop2
Simulation Panel
Event List
Vis.
Time(sec)
Last Device
0.000
0.001
PC1
0.002
Switch0
0.003
PC2
0.004
Switch0
Reset Simulation
Constant Delay
Play Controls
Event List Filters - Visible Events

4.


PC-PT PC0
Laptop-PT Laptop0
PC-PT PC1
Laptop-PT Laptop1
2960-24TT Switch0
Laptop-PT Laptop2
PC-PT PC6
Laptop-PT Laptop3
PC-PT PC7
Switch0
Physical
Config
CLI
Attributes
IOS Command Line Interface
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/9, changed state to up
Switch(config)#vlan 4
Switch(config-vlan)#name directors
Switch(config-vlan)#int range fa0/7-9
Switch(config-if-range)#switchport mode access
Switch(config-if-range)#switchport access vlan 4
Switch(config-if-range)#exit
Switch(config)#exit
Switch#
%SYS-5-CONFIG_I: Configured from console by console
Switch#show vlan
VLAN Name Status Ports
1 default active Fa0/10, Fa0/11, Fa0/12, Fa0/13, Fa0/14, Fa0/15, Fa0/16, Fa0/17, Fa0/18, Fa0/19, Fa0/20, Fa0/21, Fa0/22, Fa0/23, Fa0/24, Gig0/1, Gig0/2
2 programmer active Fa0/1, Fa0/2, Fa0/3
3 buhg active Fa0/4, Fa0/5, Fa0/6
4 directors active Fa0/7, Fa0/8, Fa0/9
1002 fddi-default active
1003 token-ring-default active
1004 fddinet-default active
1005 trnet-default active
VLAN Type SAID MTU Parent RingNo BridgeNo Stp BrdgMode Trans1 Trans2
1 enet 100001 1500 - - - - - 0 0
2 enet 100002 1500 - - - - - 0 0
3 enet 100003 1500 - - - - - 0 0
4 enet 100004 1500 - - - - - 0 0
--More--
Copy
Paste

5.


PC7
Physical
Config
Desktop
Programming
Attributes
Command Prompt
Cisco Packet Tracer PC Command Line 1.0
C:\>ping 192.168.0.9
Pinging 192.168.0.9 with 32 bytes of data:
Reply from 192.168.0.9: bytes=32 time=1ms TTL=128
Reply from 192.168.0.9: bytes=32 time=4ms TTL=128
Reply from 192.168.0.9: bytes=32 time=4ms TTL=128
Reply from 192.168.0.9: bytes=32 time=1ms TTL=128
Ping statistics for 192.168.0.9:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 1ms, Maximum = 4ms, Average = 2ms
C:\>
Top
PC-PT PC1
PC-PT PC2
PC-PT PC6
Laptop-PT Laptop0
Laptop-PT Laptop1
Laptop-PT Laptop2
Laptop-PT Laptop3
PC-PT PC7
Simulation Panel
Event List
Vis.
Time(sec)
Last Device
Reset Simulation
Constant Delay
Play Controls
Edit Filters
Show All/None
Event List
Realtime
Fire
Last Status
Source
Destination
Type
Color
Time(sec)
Periodic
Num
Edit
Delete
Successful
PC7
PC6
ICMP
0.000
N
0
(edit)
(delete)