

# Estimating time of a CAL module execution

Statistic under AI and its application to engineering sciences

Jan Bielecki

*Abstract*— **Abstract ...**

*Keywords*— **Machine learning, BalticLSC ...**

## I. INTRODUCTION

Computation Application Language (CAL) is designed to write large scale application in due to perform big data processing. Each CAL program consists of modules that are separately executed in sequence (with parallelization possibility) on virtual machines and sending the results further to next module of an application. CAL language is a part of the system developed under the Baltic LSC[1] project.

During the data processing within the application run, each module is executed with some input data. It could be different kind of data e.g. data frame or set of images. The execution of a module is invoked on a virtual machine with limited resources (RAM, mCPUs, GPUs). The details of an input data and the execution environment resources will be used to estimate the overall application execution time and price on a concrete cluster.

Baltic Large Scale Computing (BalticLSC[2]) project is using CAL language to perform data processing tasks. Each task is an execution of a CAL application. Each module can be used in many CAL applications. We can say that a single module is a one block (commonly as a docker image) and an application is the schema of executing concrete set of blocks. Figure 1 shows the example application that consists of a few modules to perform some image processing. Some of the modules (*R*, *G* and *B processors*) can be executed in parallel.

The aim of this project is to estimate the module execution time based on input data and limited resources of the execution. The chosen approach is to create machine learning models using historical data of the module executions times.

The WCET<sup>1</sup> execution time is a crucial feature of a real-time systems[3] when response should be guaranteed within a specified timing constraint or system should meet the specified deadline. In this project we do not strictly focus on providing an estimation of maximum execution time (WCET). We will try to estimate the average-case execution time (ACET) which is absolutely enough for this use case requirements.

## II. INTRODUCTION

To predict time of module execution we create a machine learning model for each module. With each execution of the module, within some application, we will get another data point to train our model.

<sup>1</sup>Worst-case execution time - the maximum amount of time that the execution can take.

We will use the following features (explanatory variables)<sup>2</sup> as an input data for the model:

1. mCPU limit - called *mili cores* - the fraction of a physical CPU used to carry out the module execution,
2. total size of an input data,
3. max element size of an input data (if the input data is a set of files type it is the biggest part of data to be processed),
4. avg size of an input element,
5. number of input data elements.

This last three features makes sense only if the input data is a set of files. Otherwise, if the data is just a single file (e.g. data frame), the features set should be reduced to just the first two elements from the list above.

Obviously, our dependent value (that we are going to estimate) is an execution time of a module. The example data frame that will be used to train and validate our models is presented in the table I.

## III. ALGORITHM

As a machine learning algorithm for our project we will use *Epsilon-Support Vector Regression*[10] (SVR) - it is based on Support Vector Machine (SVM, originally named *support-vector networks*[9]).

We will use SVR model with a RBF kernel[8] which is the most known flexible kernel and it could project the features vectors into infinite dimensions. It uses Taylor expansion which is equivalent to use an infinite sum over the polynomial kernels. It allows to model any function that is a sum of unknown degree polynomials.

## IV. CONCLUSIONES

Conclusions ... <https://github.com/rasenjop/Plantilla-Jornadas-Sarteco>.

## THANKS

Thanks for the help and support ...

## REFERENCIAS

- [1] FILL IT, *BalticLSC: main webpage of the project*, FILL IT, 14.03.2021.
- [2] FILL IT, *BalticLSC: BalticLSC Admin Tool Technical Documentation, Design of the Computation Application Language, Design of the BalticLSC Computation Tool* <https://www.balticlsc.eu/wp-content/uploads/2020/03/05.2A-05.3A-05.4ABalticLSC.Software.Design.pdf>, FILL IT, 14.03.2021.
- [3] FILL IT, *Estimation of the execution time in real-time systems*, FILL IT, 22.01.2016.

<sup>2</sup>As a docker container that will be used to execute a module do not use SWAP memory, RAM is not colaterated with execution time. In this program we will not use modules with GPU support. Summarizing, the GPUs and RAM resources limits are not taken into account for modeling.




Fig. 1: The example of an image processing application written in the CAL language.

Tabla I: The example data frame for models training and validations.

Module ID	mCPU	total size [KB]	max size [KB]	average size [KB]	number of elements	time [ms]
1	1.1	12414	1341	871	21	7813
1	0.5	12414	1341	871	21	12406
1	3.6	54001	2190	891	82	9017
...	...	...	...	...	...	...

- [4] Leslie Lamport, *A Document Preparation System: L<sup>A</sup>T<sub>E</sub>X, User's Guide and Reference Manual*, Addison Wesley Publishing Company, 1986.
- [5] Helmut Kopka, *L<sup>A</sup>T<sub>E</sub>X, eine Einführung*, Addison-Wesley, 1989.
- [6] D.K. Knuth, *The T<sub>E</sub>Xbook*, Addison-Wesley, 1989.
- [7] D.E. Knuth, *The METAFont book*, Addison Wesley Publishing Company, 1986.
- [8] Wikipedia, *Radial basis function kernel*, Wikipedia, 03.03.2021.
- [9] Vladimir Vapnik, *Support-Vector Networks by Corinna Cortes*, FILL IT, 1995.
- [10] Dr. Saed Sayad, *Support Vector Regression*, FILL IT, 17.01.2021.