

Experiment (3)

Javascript-part 2

Procedure:

1. Create a folder on the Desktop
Name it **js_part2**
2. Inside that folder, create two files
index.html
script.js
3. Open the folder in VS Code

✚ Write the codes below exactly. In this lecture, you will learn how to connect HTML+JavaScript (JS) in separate files (External Method).

Example 1: Connect HTML with JavaScript


File 1

index.html

```
<!DOCTYPE html>
<html>
<head>
  <title>Week 2 JavaScript</title>
</head>
<body>

  <h1>JavaScript Lecture</h1>

  <script src="script.js"></script>
</body>
</html>
```



What happens?

- When the student opens **index.html**
- The browser reads the HTML file
- Then it loads **script.js**
- Then it shows the alert message

File 2

script.js

```
alert("Hello Student")
```

Example 2: Show message when clicking a button


index.html

```
<!DOCTYPE html>
<html>
<head>
  <title>Button Alert</title>
</head>
<body>

  <h1>Button Example</h1>

  <button onclick="showMessage()">Click Me</button>

  <script src="script.js"></script>
</body>
</html>
```



What happens?

- The button is shown on the page
- When user clicks the button
- JavaScript function `showMessage()` runs
- Then alert appears

script.js

```
function showMessage() {
  alert("Welcome to JavaScript")
}
```

Example 3: Change text inside the page


index.html

```
<!DOCTYPE html>
<html>
<head>
  <title>Change Text</title>
</head>
<body>

  <h1 id="title">Original Text</h1>

  <button onclick="changeText()">Change Text</button>

  <script src="script.js"></script>
</body>
</html>
```



What happens?

- The page first shows Original Text
- When the button is clicked
- JavaScript finds the element with id `title`
- Then it replaces the text with Text Changed

script.js

```
function changeText() {
  document.getElementById("title").innerHTML = "Text Changed"
}
```

Example 4: Show result inside the page


index.html

```
<!DOCTYPE html>
<html>
<head>
  <title>Show Result</title>
</head>
<body>

  <h1 id="result">Result will appear here</h1>

  <button onclick="showSum()">Show Sum</button>

  <script src="script.js"></script>
</body>
</html>
```



What happens?

- The page first shows Result will appear here
- When button is clicked
- JavaScript calculates 5 + 7
- Then puts 12 inside the h1 element

script.js

```
function showSum() {
  let a = 5
  let b = 7
  let sum = a + b

  document.getElementById("result").innerHTML = sum
}
```

Example 5: Take input from user and show alert


index.html

```
<!DOCTYPE html>
<html>
<head>
  <title>User Input</title>
</head>
<body>

  <h1>Enter Your Name</h1>

  <input type="text" id="username">
  <button onclick="sayHello()">Send</button>

  <script src="script.js"></script>
</body>
</html>
```



What happens?

- User writes name in input field
- JavaScript reads the value from the input
- Then alert shows Hello Ali or any entered name

script.js



```
function sayHello() {
  let name = document.getElementById("username").value
  alert("Hello " + name)
}
```

Example 6: Take input and show it inside page

index.html

```
<!DOCTYPE html>
<html>
<head>
  <title>Show Name</title>
</head>
<body>

  <h1>Enter Your Name</h1>

  <input type="text" id="username">
  <button onclick="showName()">Show</button>

  <p id="output">Your name will appear here</p>

  <script src="script.js"></script>
</body>
</html>
```

script.js

```
function showName() {
  let name = document.getElementById("username").value
  document.getElementById("output").innerHTML = "Hello " + name
}
```

- This is more visual, you can see the result directly on the page