

CD4051BM/CD4051BC Single 8-Channel Analog Multiplexer/Demultiplexer **CD4052BM/CD4052BC Dual 4-Channel Analog Multiplexer/Demultiplexer** **CD4053BM/CD4053BC Triple 2-Channel Analog Multiplexer/Demultiplexer**

General Description

These analog multiplexers/demultiplexers are digitally controlled analog switches having low "ON" impedance and very low "OFF" leakage currents. Control of analog signals up to $15V_{p-p}$ can be achieved by digital signal amplitudes of 3–15V. For example, if $V_{DD}=5V$, $V_{SS}=0V$ and $V_{EE}=-5V$, analog signals from $-5V$ to $+5V$ can be controlled by digital inputs of 0–5V. The multiplexer circuits dissipate extremely low quiescent power over the full $V_{DD}-V_{SS}$ and $V_{DD}-V_{EE}$ supply voltage ranges, independent of the logic state of the control signals. When a logical "1" is present at the inhibit input terminal all channels are "OFF".

CD4051BM/CD4051BC is a single 8-channel multiplexer having three binary control inputs, A, B, and C, and an inhibit input. The three binary signals select 1 of 8 channels to be turned "ON" and connect the input to the output.

CD4052BM/CD4052BC is a differential 4-channel multiplexer having two binary control inputs, A and B, and an inhibit input. The two binary input signals select 1 or 4 pairs of channels to be turned on and connect the differential analog inputs to the differential outputs.


CD4053BM/CD4053BC is a triple 2-channel multiplexer having three separate digital control inputs, A, B, and C, and

an inhibit input. Each control input selects one of a pair of channels which are connected in a single-pole double-throw configuration.

Features

- Wide range of digital and analog signal levels: digital 3–15V, analog to $15V_{p-p}$
- Low "ON" resistance: 80Ω (typ.) over entire $15V_{p-p}$ signal-input range for $V_{DD}-V_{EE}=15V$
- High "OFF" resistance: channel leakage of ± 10 pA (typ.) at $V_{DD}-V_{EE}=10V$
- Logic level conversion for digital addressing signals of 3–15V ($V_{DD}-V_{SS}=3-15V$) to switch analog signals to $15V_{p-p}$ ($V_{DD}-V_{EE}=15V$)
- Matched switch characteristics: $\Delta R_{ON}=5\Omega$ (typ.) for $V_{DD}-V_{EE}=15V$
- Very low quiescent power dissipation under all digital-control input and supply conditions: $1\mu W$ (typ.) at $V_{DD}-V_{SS}=V_{DD}-V_{EE}=10V$
- Binary address decoding on chip

Connection Diagrams



Order Number CD4051B, CD4052B, or CD4053B

CD4051BM/CD4051BC, CD4052BM/CD4052BC, CD4053BM/CD4053BC Analog Multiplexer/Demultiplexers

Absolute Maximum Ratings

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

DC Supply Voltage (V_{DD})	$-0.5 V_{DC}$ to $+18 V_{DC}$
Input Voltage (V_{IN})	$-0.5 V_{DC}$ to $V_{DD} + 0.5 V_{DC}$
Storage Temperature Range (T_S)	-65°C to $+150^{\circ}\text{C}$
Power Dissipation (P_D)	
Dual-In-Line	700 mW
Small Outline	500 mW
Lead Temp. (T_L) (soldering, 10 sec.)	260°C

Recommended Operating Conditions

DC Supply Voltage (V_{DD})	$+5 V_{DC}$ to $+15 V_{DC}$
Input Voltage (V_{IN})	0V to $V_{DD} V_{DC}$
Operating Temperature Range (T_A)	
4051BM/4052BM/4053BM	-55°C to $+125^{\circ}\text{C}$
4051BC/4052BC/4053BC	-40°C to $+85^{\circ}\text{C}$

DC Electrical Characteristics (Note 2)

Symbol	Parameter	Conditions		− 55°C		+ 25°			+ 125°C		Units
				Min	Max	Min	Typ	Max	Min	Max	
I _{DD}	Quiescent Device Current	V _{DD} = 5V V _{DD} = 10V V _{DD} = 15V			5 10 20			5 10 20		150 300 600	μA μA μA
Signal Inputs (V _{IS}) and Outputs (V _{OS})											
R _{ON}	“ON” Resistance (Peak for V _{EE} ≤ V _{IS} ≤ V _{DD})	R _L = 10 kΩ (any channel selected)	V _{DD} = 2.5V, V _{EE} = −2.5V or V _{DD} = 5V, V _{EE} = 0V		800		270	1050		1300	Ω
			V _{DD} = 5V V _{EE} = −5V or V _{DD} = 10V, V _{EE} = 0V		310		120	400		550	Ω
			V _{DD} = 7.5V, V _{EE} = −7.5V or V _{DD} = 15V, V _{EE} = 0V		200		80	240		320	Ω
ΔR _{ON}	Δ“ON” Resistance Between Any Two Channels	R _L = 10 kΩ (any channel selected)	V _{DD} = 2.5V, V _{EE} = −2.5V or V _{DD} = 5V, V _{EE} = 0V				10				Ω
			V _{DD} = 5V, V _{EE} = −5V or V _{DD} = 10V, V _{EE} = 0V				10				Ω
			V _{DD} = 7.5V, V _{EE} = −7.5V or V _{DD} = 15V, V _{EE} = 0V				5				Ω
	“OFF” Channel Leakage Current, any channel “OFF”	V _{DD} = 7.5V, V _{EE} = −7.5V O/I = ± 7.5V, I/O = 0V		± 50		± 0.01	± 50		± 500	nA	
	“OFF” Channel Leakage Current, all channels “OFF” (Common OUT/IN)	Inhibit = 7.5V	CD4051		± 200		± 0.08	± 200		± 2000	nA
		V _{DD} = 7.5V, V _{EE} = −7.5V, O/I = 0V,	CD4052		± 200		± 0.04	± 200		± 2000	nA
I/O = ± 7.5V		CD4053		± 200		± 0.02	± 200		± 2000	nA	
Control Inputs A, B, C and Inhibit											
V _{IL}	Low Level Input Voltage	V _{EE} = V _{SS} R _L = 1 kΩ to V _{SS} I _{IS} < 2 μA on all OFF channels V _{IS} = V _{DD} thru 1 kΩ V _{DD} = 5V V _{DD} = 10V V _{DD} = 15V			1.5 3.0 4.0			1.5 3.0 4.0		1.5 3.0 4.0	V V V
V _{IH}	High Level Input Voltage	V _{DD} = 5 V _{DD} = 10 V _{DD} = 15		3.5 7 11		3.5 7 11			3.5 7 11		V V V

Note 1: “Absolute Maximum Ratings” are those values beyond which the safety of the device cannot be guaranteed. Except for “Operating Temperature Range” they are not meant to imply that the devices should be operated at these limits. The table of “Electrical Characteristics” provides conditions for actual device operation.

Note 2: All voltages measured with respect to V_{SS} unless otherwise specified.

DC Electrical Characteristics (Note 2) (Continued)

Symbol	Parameter	Conditions		−40°C		+25°C			+85°C		Units
				Min	Max	Min	Typ	Max	Min	Max	
I _{IN}	Input Current	V _{DD} = 15V, V _{IN} = 0V	V _{EE} = 0V		−0.1		−10 ^{−5}	−0.1		−1.0	μA
		V _{DD} = 15V, V _{IN} = 15V	V _{EE} = 0V		0.1		10 ^{−5}	0.1		1.0	μA
I _{DD}	Quiescent Device Current	V _{DD} = 5V			20			20		150	μA
		V _{DD} = 10V			40			40		300	μA
		V _{DD} = 15V			80			80		600	μA
Signal Inputs (V _{IS}) and Outputs (V _{OS})											
R _{ON}	“ON” Resistance (Peak for V _{EE} ≤ V _{IS} ≤ V _{DD})	R _L = 10 kΩ (any channel selected)	V _{DD} = 2.5V, V _{EE} = −2.5V or V _{DD} = 5V, V _{EE} = 0V		850		270	1050		1200	Ω
			V _{DD} = 5V, V _{EE} = −5V or V _{DD} = 10V, V _{EE} = 0V		330		120	400		520	Ω
			V _{DD} = 7.5V, V _{EE} = −7.5V or V _{DD} = 15V, V _{EE} = 0V		210		80	240		300	Ω
ΔR _{ON}	Δ“ON” Resistance Between Any Two Channels	R _L = 10 kΩ (any channel selected)	V _{DD} = 2.5V, V _{EE} = −2.5V or V _{DD} = 5V, V _{EE} = 0V				10				Ω
			V _{DD} = 5V V _{EE} = −5V or V _{DD} = 10V, V _{EE} = 0V				10				Ω
			V _{DD} = 7.5V, V _{EE} = −7.5V or V _{DD} = 15V, V _{EE} = 0V				5				Ω
	“OFF” Channel Leakage Current, any channel “OFF”	V _{DD} = 7.5V, O/I = ±7.5V, I/O = 0V		±50		±0.01	±50		±500	nA	
	“OFF” Channel Leakage Current, all channels “OFF” (Common OUT/IN)	Inhibit = 7.5V V _{DD} = 7.5V, V _{EE} = −7.5V, O/I = 0V	CD4051 CD4052	±200 ±200		±0.08 ±0.04	±200 ±200		±2000 ±2000	nA nA	
		I/O = ±7.5V CD4053	±200		±0.02	±200		±2000	nA		
Control Inputs A, B, C and Inhibit											
V _{IL}	Low Level Input Voltage	V _{EE} = V _{SS} R _L = 1 kΩ to V _{SS} I _{IS} < 2 μA on all OFF Channels V _{IS} = V _{DD} thru 1 kΩ V _{DD} = 5V V _{DD} = 10V V _{DD} = 15V			1.5 3.0 4.0			1.5 3.0 4.0		1.5 3.0 4.0	V V V
V _{IH}	High Level Input Voltage	V _{DD} = 5 V _{DD} = 10 V _{DD} = 15		3.5 7 11		3.5 7 11			3.5 7 11		V V V
I _{IN}	Input Current	V _{DD} = 15V, V _{IN} = 0V	V _{EE} = 0V		−0.1		−10 ^{−5}	−0.1		−1.0	μA
		V _{DD} = 15V, V _{IN} = 15V	V _{EE} = 0V		0.1		10 ^{−5}	0.1		1.0	μA

Note 1: “Absolute Maximum Ratings” are those values beyond which the safety of the device cannot be guaranteed. Except for “Operating Temperature Range” they are not meant to imply that the devices should be operated at these limits. The table of “Electrical Characteristics” provides conditions for actual device operation.

Note 2: All voltages measured with respect to V_{SS} unless otherwise specified.

AC Electrical Characteristics* $T_A = 25^\circ\text{C}$, $t_r = t_f = 20\text{ ns}$, unless otherwise specified.


Symbol	Parameter	Conditions	V_{DD}	Min	Typ	Max	Units
t_{PZH} , t_{PZL}	Propagation Delay Time from Inhibit to Signal Output (channel turning on)	$V_{EE} = V_{SS} = 0V$ $R_L = 1\text{ k}\Omega$ $C_L = 50\text{ pF}$	5V 10V 15V		600 225 160	1200 450 320	ns ns ns
t_{PHZ} , t_{PLZ}	Propagation Delay Time from Inhibit to Signal Output (channel turning off)	$V_{EE} = V_{SS} = 0V$ $R_L = 1\text{ k}\Omega$ $C_L = 50\text{ pF}$	5V 10V 15V		210 100 75	420 200 150	ns ns ns
C_{IN}	Input Capacitance Control input Signal Input (IN/OUT)				5 10	7.5 15	pF pF
C_{OUT}	Output Capacitance (common OUT/IN)						
	CD4051 CD4052 CD4053	$V_{EE} = V_{SS} = 0V$	10V 10V 10V		30 15 8		pF pF pF
C_{IOS}	Feedthrough Capacitance				0.2		pF
C_{PD}	Power Dissipation Capacitance						
	CD4051 CD4052 CD4053				110 140 70		pF pF pF
Signal Inputs (V_{IS}) and Outputs (V_{OS})							
	Sine Wave Response (Distortion)	$R_L = 10\text{ k}\Omega$ $f_{IS} = 1\text{ kHz}$ $V_{IS} = 5\text{ V}_{p-p}$ $V_{EE} = V_{SI} = 0V$	10V		0.04		%
	Frequency Response, Channel "ON" (Sine Wave Input)	$R_L = 1\text{ k}\Omega$, $V_{EE} = 0V$, $V_{IS} = 5\text{ V}_{p-p}$, $20 \log_{10} V_{OS}/V_{IS} = -3\text{ dB}$	10V		40		MHz
	Feedthrough, Channel "OFF"	$R_L = 1\text{ k}\Omega$, $V_{EE} = V_{SS} = 0V$, $V_{IS} = 5\text{ V}_{p-p}$, $20 \log_{10} V_{OS}/V_{IS} = -40\text{ dB}$	10V		10		MHz
	Crosstalk Between Any Two Channels (frequency at 40 dB)	$R_L = 1\text{ k}\Omega$, $V_{EE} = V_{SS} = 0V$, $V_{IS}(A) = 5\text{ V}_{p-p}$, $20 \log_{10} V_{OS}(B)/V_{IS}(A) = -40\text{ dB}$ (Note 3)	10V		3		MHz
t_{PHL} , t_{PLH}	Propagation Delay Signal Input to Signal Output	$V_{EE} = V_{SS} = 0V$ $C_L = 50\text{ pF}$	5V 10V 15V		25 15 10	55 35 25	ns ns ns
Control Inputs, A, B, C and Inhibit							
	Control Input to Signal Crosstalk	$V_{EE} = V_{SS} = 0V$, $R_L = 10\text{ k}\Omega$ at both ends of channel. Input Square Wave Amplitude = 10V	10V		65		mV (peak)
t_{PHL} , t_{PLH}	Propagation Delay Time from Address to Signal Output (channels "ON" or "OFF")	$V_{EE} = V_{SS} = 0V$ $C_L = 50\text{ pF}$	5V 10V 15V		500 180 120	1000 360 240	ns ns ns

*AC Parameters are guaranteed by DC correlated testing.


Note 3: A, B are two arbitrary channels with A turned "ON" and B "OFF".

Block Diagrams

CD4051BM/CD4051BC




CD4052BM/CD4052BC



TL/F/5662-2

Block Diagrams (Continued)

CD4053BM/CD4053BC









TL/F/5662-3

Truth Table

INPUT STATES				“ON” CHANNELS		
INHIBIT	C	B	A	CD4051B	CD4052B	CD4053B
0	0	0	0	0	0X, 0Y	cx, bx, ax
0	0	0	1	1	1X, 1Y	cx, bx, ay
0	0	1	0	2	2X, 2Y	cx, by, ax
0	0	1	1	3	3X, 3Y	cx, by, ay
0	1	0	0	4		cy, bx, ax
0	1	0	1	5		cy, bx, ay
0	1	1	0	6		cy, by, ax
0	1	1	1	7		cy, by, ay
1	*	*	*	NONE	NONE	NONE

*Don't Care condition.

Switching Time Waveforms



TL/F/5662-4


Special Considerations

In certain applications the external load-resistor current may include both V_{DD} and signal-line components. To avoid drawing V_{DD} current when switch current flows into IN/OUT pin, the voltage drop across the bidirectional switch must


not exceed 0.6V at $T_A \leq 25^\circ\text{C}$, or 0.4V at $T_A > 25^\circ\text{C}$ (calculated from R_{ON} values shown). No V_{DD} current will flow through R_L if the switch current flows into OUT/IN pin.

Typical Performance Characteristics


“ON” Resistance vs Signal Voltage for $T_A = 25^\circ\text{C}$




“ON” Resistance as a Function of Temperature for $V_{DD} - V_{EE} = 15V$



“ON” Resistance as a Function of Temperature for $V_{DD} - V_{EE} = 10V$



“ON” Resistance as a Function of Temperature for $V_{DD} - V_{EE} = 5V$



TL/F/5662-5

Physical Dimensions inches (millimeters)

Diagram illustrating the physical dimensions of the J16A package (Cavity Dual-In-Line Package) in inches (millimeters). The package is shown from top, side, and end views.

Top View Dimensions:

- Overall width: 0.785 [19.94] MAX
- Pin pitch: 0.037 ± 0.005 [0.94 ± 0.13] TYP
- Pin width: 0.055 ± 0.005 [1.40 ± 0.13] TYP
- Pin height: 0.220 - 0.310 [5.59 - 7.87]
- Pin diameter: 0.025 [0.64] R
- Pin spacing: 0.005 [0.13] MIN TYP
- Pin length: 0.200 [5.08] MAX TYP
- Pin thickness: 0.125 - 0.200 [3.18 - 5.08] TYP
- Pin width at base: 0.080 [2.03] MAX BOTH ENDS
- Pin width at base: 0.100 ± 0.010 [2.54 ± 0.25] TYP
- Pin width at base: 0.020 - 0.060 [0.51 - 1.52] TYP
- Pin width at base: 0.150 [3.81] MIN TYP
- Pin width at base: 90° ± 4° TYP
- Pin width at base: 0.018 ± 0.003 [0.46 ± 0.08] TYP

Side View Dimensions:

- Overall height: 0.290 - 0.320 [7.37 - 8.13]
- Pin height: 0.180 [4.57] MAX
- Pin angle: 95° ± 5° TYP
- Pin width at base: 0.310 - 0.410 [7.87 - 10.41]
- Pin width at base: 0.010 ± 0.002 [0.25 ± 0.05] TYP

End View Dimensions:

- Overall width: 0.386 - 0.394 [9.804 - 10.00]
- Pin pitch: 0.028 - 0.024 [5.791 - 6.198]
- Pin height: 0.010 MAX [0.254]
- Pin angle: 30° TYP

Small Outline Package (M) Dimensions:

- Overall width: 0.150 - 0.157 [3.810 - 3.988]
- Pin pitch: 0.010 - 0.020 [0.254 - 0.508] × 45°
- Pin height: 0.008 - 0.010 [0.203 - 0.254] TYP ALL LEADS
- Pin width: 0.004 [0.102] ALL LEAD TIPS
- Pin angle: 8° MAX TYP ALL LEADS
- Pin width: 0.016 - 0.050 [0.406 - 1.270] TYP ALL LEADS

Small Outline Package (M) Dimensions:

- Overall width: 0.053 - 0.069 [1.346 - 1.753]
- Pin pitch: 0.014 [0.356]
- Pin height: 0.050 [1.270] TYP
- Pin width: 0.008 [0.203] TYP
- Pin angle: 0.004 - 0.010 [0.102 - 0.254]
- Pin width: 0.014 - 0.020 [0.355 - 0.508] TYP


Ordering Information:

Order Number CD4051BMJ, CD4051BCJ, CD4052BMJ, CD4052BCJ, CD4053BMJ or CD4053BCJ
NS Package Number J16A

J16A (REV L)

Small Outline Package (M)
Order Number CD4051BCM,
CD4052BCM or CD4053BCM
NS Package Number M16A

Physical Dimensions inches (millimeters) (Continued)



Molded Dual-In-Line Package (N)
Order CD4051BM, CD4051BC,
CD4052BM, CD4052BC, CD4053BM, CD4053BC
NS Package Number N16E

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



National Semiconductor Corporation
1111 West Bardin Road
Arlington, TX 76017
Tel: 1(800) 272-9959
Fax: 1(800) 737-7018

National Semiconductor Europe
Fax: (+49) 0-180-530 85 86
Email: cnjwge@tevm2.nsc.com
Deutsch Tel: (+49) 0-180-530 85 85
English Tel: (+49) 0-180-532 78 32
Français Tel: (+49) 0-180-532 93 58
Italiano Tel: (+49) 0-180-534 16 80

National Semiconductor Hong Kong Ltd.
19th Floor, Straight Block,
Ocean Centre, 5 Canton Rd.
Tsimshatsui, Kowloon
Hong Kong
Tel: (852) 2737-1600
Fax: (852) 2736-9960

National Semiconductor Japan Ltd.
Tel: 81-043-299-2309
Fax: 81-043-299-2408

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.

This datasheet has been downloaded from:

www.DatasheetCatalog.com

Datasheets for electronic components.

National Semiconductor was acquired by Texas Instruments.

http://www.ti.com/corp/docs/investor_relations/pr_09_23_2011_national_semiconductor.html

This file is the datasheet for the following electronic components:

CD4051BCJ - <http://www.ti.com/product/cd4051bcj?HQS=TI-null-null-dscatalog-df-pf-null-ww>

CD4051BCM - <http://www.ti.com/product/cd4051bcm?HQS=TI-null-null-dscatalog-df-pf-null-ww>

CD4051 - <http://www.ti.com/product/cd4051?HQS=TI-null-null-dscatalog-df-pf-null-ww>

CD4051BMJ - <http://www.ti.com/product/cd4051bmj?HQS=TI-null-null-dscatalog-df-pf-null-ww>

CD4052BCJ - <http://www.ti.com/product/cd4052bcj?HQS=TI-null-null-dscatalog-df-pf-null-ww>

CD4052BMJ - <http://www.ti.com/product/cd4052bmj?HQS=TI-null-null-dscatalog-df-pf-null-ww>

CD4053BCJ - <http://www.ti.com/product/cd4053bcj?HQS=TI-null-null-dscatalog-df-pf-null-ww>

CD4053BCM - <http://www.ti.com/product/cd4053bcm?HQS=TI-null-null-dscatalog-df-pf-null-ww>

CD4053BMJ - <http://www.ti.com/product/cd4053bmj?HQS=TI-null-null-dscatalog-df-pf-null-ww>