



IBM Developer
SKILLS NETWORK

Hands-on Lab: Using Views

Estimated time needed: 10 minutes

In this lab, you will learn about using views. In SQL, a view is an alternative way of representing data that exists in one or more tables. Just like a real table, it contains rows and columns. The fields in a view are fields from one or more real tables in the database. Though views can be queried like a table, views are dynamic; only the definition of the view is stored, not the data.

How does the syntax of a CREATE VIEW statement look?

```
CREATE VIEW view_name AS
SELECT column1, column2, ...
FROM table_name
WHERE condition;
```

How does the syntax of a REPLACE VIEW statement look?

```
CREATE OR REPLACE VIEW view_name AS
SELECT column1, column2, ...
FROM table_name
WHERE condition;
```

How does the syntax of a DROP VIEW statement look?

```
DROP VIEW view_name;
```

Software Used in this Lab

In this lab, you will use [IBM Db2 Database](#). Db2 is a Relational Database Management System (RDBMS) from IBM, designed to store, analyze and retrieve the data efficiently.

To complete this lab you will utilize a Db2 database service on IBM Cloud. If you did not already complete this lab task earlier in this module, you will not yet have access to Db2 on IBM Cloud, and you will need to follow the lab below first:

- [Hands-on Lab : Sign up for IBM Cloud, Create Db2 service instance and Get started with the Db2 console](#)

Database Used in this Lab

The database used in this lab is an internal database. You will be working on a sample HR database. This HR database schema consists of 5 tables called **EMPLOYEES**, **JOB_HISTORY**, **JOBS**, **DEPARTMENTS** and **LOCATIONS**. Each table has a few rows of sample data. The following diagram shows the tables for the HR database:

SAMPLE HR DATABASE TABLES

EMPLOYEES

EMP_ID	F_NAME	L_NAME	SSN	B_DATE	SEX	ADDRESS	JOB_ID	SALARY	MANAGER_ID	DEP_ID
E1001	John	Thomas	123456	1976-01-09	M	5631 Rice, OakPark,IL	100	100000	30001	2
E1002	Alice	James	123457	1972-07-31	F	980 Berry Ln, Elgin,IL	200	80000	30002	5
E1003	Steve	Wells	123458	1980-08-10	M	291 Springs, Gary,IL	300	50000	30002	5

JOB_HISTORY

EMPL_ID	START_DATE	JOBS_ID	DEPT_ID
E1001	2000-01-30	100	2
E1002	2010-08-16	200	5
E1003	2016-08-10	300	5

JOBS

JOB_ID	JOB_TITLE	MIN_SALARY	MAX_SALARY
100	Sr. Architect	60000	100000
200	Sr. Software Developer	60000	80000
300	Jr. Software Developer	40000	60000

DEPARTMENTS

DEPT_ID	DEPT_NAME	MANAGER_ID	LOC_ID
2	Architect Group	30001	L0001
5	Software Development	30002	L0002
7	Design Team	30003	L0003
5	Software	30004	L0004

LOCATIONS

LOC_ID	DEPT_ID	LOC
L0001	2	
L0002	5	
L0003	7	

NOTE: This lab requires you to have all 5 of these tables of the HR database populated with sample data on Db2. If you don't have the tables above populated with sample data on Db2, please go through the lab below first:

- [Hands-on Lab : Create tables using SQL scripts and Load data into tables](#)

Objectives

After completing this lab, you will be able to:

- Create a View and show a selection of data for a given table
- Update a View to combine two or more tables in meaningful ways
- Drop a created View

Instructions

When you approach the exercises in this lab, follow the instructions to run the queries on Db2:

- Go to the [Resource List](#) of IBM Cloud by logging in where you can find the Db2 service instance that you created in a previous lab under **Services** section. Click on the **Db2-xx service**. Next, open the Db2 Console by clicking on **Open Console** button. Click on the 3-bar menu icon in the top left corner and go to the **Run SQL** page. The Run SQL tool enables you to run SQL statements.
 - If needed, follow [Hands-on Lab : Sign up for IBM Cloud, Create Db2 service instance and Get started with the Db2 console](#)

Exercise 1: Create a View

In this exercise, you will create a View and show a selection of data for a given table.

1. Let's create a view called **EMPSALARY** to display salary along with some basic sensitive data of employees from the HR database. To create the **EMPSALARY** view from the **EMPLOYEES** table, copy the code below and paste it to the textbox of the **Run SQL** page. Click **Run all**.

```
CREATE VIEW EMPSALARY AS
SELECT EMP_ID, F_NAME, L_NAME, B_DATE, SEX, SALARY
FROM EMPLOYEES;
```

The screenshot shows a SQL IDE interface. On the left, the SQL editor contains the following code:

```
1 CREATE VIEW EMP_SALARY AS
2 SELECT EMP_ID, F_NAME, L_NAME, B_DATE, SEX, SALARY
3 FROM EMPLOYEES;
4
```

On the right, the 'Result' pane shows a successful execution of the 'CREATE VIEW EMP_SALARY AS SELECT EMP_...' statement. The status is 'Success' and 'Affected Rows: 0'. The run time is 0.018 s.

2. Using SELECT, query the **EMP_SALARY** view to retrieve all the records. Copy the code below and paste it to the textbox of the **Run SQL** page. Click **Run all**.

```
SELECT * FROM EMP_SALARY;
```

The screenshot shows the SQL IDE with the query 'SELECT * FROM EMP_SALARY;' executed. The result set is displayed in a table with 10 rows and 6 columns: EMP_ID, F_NAME, L_NAME, B_DATE, SEX, and SALARY.

EMP_ID	F_NAME	L_NAME	B_DATE	SEX	SALARY
E1001	John	Thomas	1976-01-09	M	100000.00
E1002	Alice	James	1972-07-31	F	80000.00
E1003	Steve	Wells	1980-08-10	M	50000.00
E1004	Santosh	Kumar	1985-07-20	M	60000.00
E1005	Ahmed	Hussain	1981-01-04	M	70000.00
E1006	Nancy	Allen	1978-02-06	F	90000.00
E1007	Mary	Thomas	1975-05-05	F	65000.00
E1008	Bharath	Gupta	1985-05-06	M	65000.00
E1009	Andrea	Jones	1990-07-09	F	70000.00
E1010	Ann	Jacob	1982-03-30	F	70000.00

Exercise 2: Update a View

In this exercise, you will update a View to combine two or more tables in meaningful ways.

- It now seems that the **EMP_SALARY** view we created in exercise 1 doesn't contain enough salary information, such as max/min salary and the job title of the employees. Let's update the **EMP_SALARY** view:
 - combining two tables **EMPLOYEES** and **JOBS** so that we can display our desired information from the HR database.
 - including the columns **JOB_TITLE**, **MIN_SALARY**, **MAX_SALARY** of the **JOBS** table as well as excluding the **SALARY** column of the **EMPLOYEES** table.

Copy the code below and paste it to the textbox of the **Run SQL** page. Click **Run all**.

```
CREATE OR REPLACE VIEW EMP_SALARY AS
SELECT EMP_ID, F_NAME, L_NAME, B_DATE, SEX, JOB_TITLE, MIN_SALARY, MAX_SALARY
FROM EMPLOYEES, JOBS
WHERE EMPLOYEES.JOB_ID = JOBS.JOB_ID;
```

NOTE: Don't worry if you don't understand how to combine two tables using implicit inner join. You will learn more about joins later on. For now, just think you are combining the data of two different tables, **EMPLOYEES** and **JOBS** by connecting their respective columns **JOB_ID** and **JOB_ID** since both the columns contain common unique data. You can have a look at the diagram (at the beginning of the lab) showing the tables for the HR database to observe how the **JOB_ID** and **JOB_ID** columns from the **EMPLOYEES** and **JOBS** tables respectively contain common unique data.

```

1 CREATE OR REPLACE VIEW EMP_SALARY AS
2 SELECT EMP_ID, F_NAME, L_NAME, B_DATE, SEX, JOB_TITLE, MIN_SALARY, MAX_SALARY
3 FROM EMPLOYEES, JOBS
4 WHERE EMPLOYEES.JOB_ID = JOBS.JOB_IDENT;
5
6

```

Result - Dec 14, 2020 11...

✓ CREATE OR REPLACE VIEW EMP_SALARY AS ... Run time: 0.022 s

Status: **Success** | Affected Rows: **0**

- Using SELECT, query the updated **EMP_SALARY** view to retrieve all the records. Copy the code below and paste it to the textbox of the **Run SQL** page. Click **Run all**.

```
SELECT * FROM EMP_SALARY;
```

Result set 1

EMP_ID	F_NAME	L_NAME	B_DATE	SEX	JOB_TITLE	MIN_SALARY	MAX_SALARY
E1001	John	Thomas	1976-01-09	M	Sr. Architect	60000.00	100000.00
E1002	Alice	James	1972-07-31	F	Sr. Software Dev	60000.00	80000.00
E1003	Steve	Wells	1980-08-10	M	Jr. Software Dev	40000.00	60000.00
E1004	Santosh	Kumar	1985-07-20	M	Jr. Software Dev	40000.00	60000.00
E1005	Ahmed	Hussain	1981-01-04	M	Jr. Architect	50000.00	70000.00
E1006	Nancy	Allen	1978-02-06	F	Lead Architect	70000.00	100000.00
E1007	Mary	Thomas	1975-05-05	F	Jr. Designer	60000.00	70000.00
E1008	Bharath	Gupta	1985-05-06	M	Jr. Designer	60000.00	70000.00
E1009	Andrea	Jones	1990-07-09	F	Sr. Designer	70000.00	90000.00
E1010	Ann	Jacob	1982-03-30	F	Sr. Designer	70000.00	90000.00

Exercise 3: Drop a View

In this exercise, you will drop a created View.

- Let's delete the created **EMP_SALARY** view. Copy the code below and paste it to the textbox of the **Run SQL** page. Click **Run all**.

```
DROP VIEW EMP_SALARY;
```

```

1 DROP VIEW EMP_SALARY;
2

```

Result - Dec 14, 2020 11...

✓ DROP VIEW EMP_SALARY Run time: 0.010 s

Status: **Success** | Affected Rows: **0**

- Using SELECT, you can verify whether the **EMP_SALARY** view has been deleted or not. Copy the code below and paste it to the textbox of the **Run SQL** page. Click **Run all**.

```
SELECT * FROM EMP_SALARY;
```

The screenshot shows a SQL IDE interface. On the left, a code editor contains the query: `SELECT * FROM EMPLOYEES;`. On the right, a results pane shows the execution status. The title is "Result - Dec 14, 2020 11...". The query is "SELECT * FROM EMPLOYEES" with a run time of 0.008 s. The status is "Failed". The error message is: "ZJH17769.EMPLOYEES" is an undefined name., SQLCODE=-204, SQLSTATE=42704, DRIVER=4.26.14. There is a link to "Learn more about this error".

Congratulations! You have completed this lab, and you are ready for the next topic.

Author(s)

- [Sandip Saha Joy](#)

Other Contributor(s)

-

Changelog

Date	Version	Changed by	Change Description
2020-12-24	1.1	Steve Ryan	ID reviewed
2020-12-14	1.0	Sandip Saha Joy	Created initial version

© IBM Corporation 2020. All rights reserved.