

Contraction Theory Based Control Under Input Saturation—LMI Approach [★]

Myeongseok Ryu ^{*} Kyunghwan Choi ^{*} Sesun You ^{**}

^{*} Korea Advanced Institute of Science and Technology (KAIST),
Daejeon 34051, South Korea (e-mail: {dding_98,kh.choi}@kaist.ac.kr)

^{**} Keimyung University, Daegu 42601, South Korea (e-mail:
yousesun@kmu.ac.kr)

Abstract: Besides the traditional Lyapunov stability theory, contraction theory offers a interesting perspective on the stability of nonlinear systems. It allows us analyze the system stability by examining the convergence of trajectories. The recent development of the contraction theory based control has introduced computational efficient methods for obtaining contraction metrics using linear matrix inequalities (LMIs). In this paper, the contraction theory based control strategy is extended to account for input saturation by incorporating saturation constraints into the LMI framework for contraction metric calculation. The proposed method calculates the contraction metrics while ensuring the satisfaction of input saturation constraints and uses as a feedback mechanism to adjust the control inputs. The proposed method is demonstrated its effectiveness through numerical simulations via [Lorenz system](#).

Keywords: Contraction theory, input saturation, linear matrix inequalities (LMIs)

NOTATION

In this paper, we use the following notation:

- $\cdot :=$ denotes *defined as*.
- $(\cdot)^{\top}$ denotes the transpose of a matrix or a vector.
- $\mathbf{x} := [x_i]_{i \in \{1, \dots, n\}} \in \mathbb{R}^n$ denotes the state vector.
- $\mathbf{A} := [a_{ij}]_{i,j \in \{1, \dots, n\}} \in \mathbb{R}^{n \times n}$ denotes a matrix.
- $\lambda_i(\mathbf{A})$, $i \in \{\max, \min\}$ denotes the maximum and minimum singular value of $\mathbf{A}$, respectively.
- $\mathbf{I}_n$ denotes the identity matrix of size n and $\mathbf{0}_{n \times m}$ denotes the zero matrix of size $n \times m$.
- sym denotes the symmetric part of a matrix, i.e., $\text{sym}(\mathbf{A}) := \frac{1}{2}(\mathbf{A} + \mathbf{A}^{\top})$ (see Tsukamoto et al. (2021b)).

1. INTRODUCTION

1.1 Motivation

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla.

[★] Sponsor and financial support acknowledgment goes here. Paper titles should be written in uppercase and lowercase letters, not all uppercase.

Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor.

Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

- 포화에 대한 사전 연구 더해서 비교
- S.S.Ge의 논문 참고

- Contraction theory introduction
- Limitation 1 (computational cost)
- Recent development (LMI)
- Limitation 2 (input saturation)
 - use penalty term to prevent excessive control input
- saturation handling in LMI

To the best of our knowledge, there has been no previous work that considers the input saturation in LMI frameworks for contraction metrics. Hence, the main objective of this paper is to extend the contraction theory based control strategy to account for input saturation simultaneously in the LMI framework.

1.2 Contributions

The main contributions of this paper are

- The contraction metric is obtained by using linear matrix inequalities (LMIs) which simplifies the calculation of the contraction metric;
- Saturation constraint is incorporated into the LMI framework for contraction metric calculation;
- ...; and
- The effectiveness and the feasibility of the proposed method is validated through numerical simulations via **Lorenz system**.

2. PRELIMINARIES

Before presenting the proposed method, we first review the contraction theory and related theorems.

2.1 Contraction Theory

Consider that we have the following deterministic nonlinear system:

$$\frac{d}{dt}\mathbf{x} = \mathbf{f}(\mathbf{x}, t). \quad (1)$$

The contraction theory commences with the definition of *differential dynamics* of the system (1) using *differential displacement* $\delta\mathbf{x}$ (Kirk, 2004, Chap 4), which is defined as follows:

$$\frac{d}{dt}\delta\mathbf{x} = \frac{\partial \mathbf{f}}{\partial \mathbf{x}}\delta\mathbf{x}. \quad (2)$$

The differential displacement $\delta\mathbf{x}$ is the infinitesimal displacement at *fixed time*.

The contraction property of the system (1) can be analyzed using the Lyapunov function $V := V(\mathbf{x}, t) = \frac{1}{2}\delta\mathbf{x}^\top \mathbf{M}\delta\mathbf{x}$, where $\mathbf{M} := \mathbf{M}(\mathbf{x}, \mathbf{x}_d, t) \in \mathbb{R}^{n \times n}$ the *contraction metric*. The contraction metric $\mathbf{M}$ is symmetric positive definite matrix and satisfies $\bar{m}\mathbf{I}_n \succeq \mathbf{M} \succeq m\mathbf{I}_n$ with $\bar{m}, m \in \mathbb{R}_{>0}$. For the system (1) to be contracting, the following condition must hold:

$$\frac{d}{dt}\mathbf{M} + 2\text{sym}(\mathbf{M}\frac{\partial \mathbf{f}}{\partial \mathbf{x}}) \leq -2\alpha\mathbf{M}, \quad (3)$$

which leads to $\frac{d}{dt}V \leq -\alpha V$ for some $\alpha \in \mathbb{R}_{>0}$. In other words, all solutions of the system (1) are contracting to a unique solution with an exponential rate α .

It is notable that the initial conditions are exponentially forgotten in the contracting system Lohmiller and Slotine (1998). Therefore, the contraction property is independent of the initial conditions.

global?? 하다는것도 쓸까?

2.2 Partial Contraction Theory

On the other hand, the partial contraction theory investigates the contraction of the system using a virtual system. Following theorem details the partial contraction theory.

Theorem 1. (see Wang and Slotine (2004)). Consider a nonlinear system of the form $\frac{d}{dt}\mathbf{x} = \mathbf{f}(\mathbf{x}, \mathbf{x}, t)$ and the virtual system $\frac{d}{dt}\mathbf{q} = \mathbf{f}(\mathbf{q}, \mathbf{x}, t)$ are contracting with respect to $\mathbf{q}$. If a particular solution of virtual system verifies a smooth specific property, then all solutions of the original system verifies this property exponentially.

Example 1. Assume that the possible solutions of the virtual system defined in Theorem 1 are $\xi_1(t)$ and $\xi_2(t)$ which are the solutions of the nonlinear system $\mathbf{x}$.

2.3 Perturbed Contracting System

The following theorem presents the contraction property of the perturbed system by adding a bounded perturbation $\mathbf{d}(\mathbf{x}, t)$ to the system (1):

$$\frac{d}{dt}\mathbf{x} = \mathbf{f}(\mathbf{x}, t) + \mathbf{d}(\mathbf{x}, t). \quad (4)$$

Theorem 2. (Eq. 15 Lohmiller and Slotine (1998)). If the system (1) is contracting with the contraction metric $\mathbf{M}$ which satisfies the condition (3), the path integral $V_l(\mathbf{q}, \delta\mathbf{q}, t) = \int_{\xi_1}^{\xi_2} \|\Theta(\mathbf{q}, t)\delta\mathbf{q}\|$, where ξ_1 and ξ_2 are the solutions of (1) and (4), respectively, and $\mathbf{q}$ is the virtual [MS: ADD!!]

$$\|\xi_1(t) - \xi_2(t)\| \leq \frac{V_l(0)}{\sqrt{m}} \exp(-\alpha t) + \frac{\bar{d}}{\alpha} \sqrt{\frac{m}{m}} (1 - \exp(-\alpha t)), \quad (5)$$

[MS: ADD!!]

Proof. See Theorem 2.4 in Tsukamoto et al. (2021c).

[MS: Any more comments, if needed]

3. PROBLEM FORMULATION

Let us consider the following nonlinear system as follows:

$$\begin{aligned}\frac{d}{dt}\mathbf{x} &= \mathbf{f}(\mathbf{x}, t) + \mathbf{B}(\mathbf{x}, t) \text{sat}(\mathbf{u}) + \mathbf{d}(t) \\ &= \mathbf{f}(\mathbf{x}, t) + \mathbf{B}(\mathbf{x}, t)\mathbf{u} + \boldsymbol{\phi}(\mathbf{u}) + \mathbf{d}(t),\end{aligned}\quad (6)$$

where $\mathbf{x} \in \mathbb{R}^n$ denotes the state variables, $\mathbf{u} \in \mathbb{R}^n$ denotes the control inputs, and $\mathbf{d}(t) \in \mathbb{R}^n$ denotes the external disturbances, and $\mathbf{f} := \mathbf{f}(\mathbf{x}, t)$ and $\mathbf{B} := \mathbf{B}(\mathbf{x}, t)$ denote system functions. The input saturation function is denoted by $\text{sat}(\cdot)$ and is defined as

$$\text{sat}(\mathbf{u}) = \begin{cases} \mathbf{u}, & \text{if } \|\mathbf{u}\| \leq \bar{u} \\ \bar{u} \frac{\mathbf{u}}{\|\mathbf{u}\|}, & \text{otherwise,} \end{cases} \quad (7)$$

where $\bar{u} \in \mathbb{R}_{>0}$ denotes the saturation threshold. The difference between the controller output $\mathbf{u}$ and the saturated control input $\text{sat}(\mathbf{u})$ is denoted by $\boldsymbol{\phi}(\mathbf{u}) = \text{sat}(\mathbf{u}) - \mathbf{u}$.

In the practical perspective, we consider the following assumption:

Assumption 1. **수도인버스로변경** The control input matrix $\mathbf{B}$ is sign-definite, so that the inverse of $\mathbf{B}$ exists.

Motivated by the use of the partial contraction theory in Tsukamoto et al. (2021a), [MS: and more...], we assume that the desired control input $\mathbf{u}_d \in \mathbb{R}^n$ which is designed to achieve the desired trajectory $\mathbf{x}_d \in \mathbb{R}^n$ under ideal conditions, i.e., $\mathbf{d} = 0$ and $\|\mathbf{u}_d\| \leq \bar{u}$, is given as follows:

$$\frac{d}{dt}\mathbf{x}_d = \mathbf{f}_d + \mathbf{B}_d\mathbf{u}_d, \quad (8)$$

where $\mathbf{f}_d := \mathbf{f}(\mathbf{x}_d, t)$ and $\mathbf{B}_d := \mathbf{B}(\mathbf{x}_d, t)$.

Finally, the control objective is to design a control input $\mathbf{u}$ such that the system trajectories of the system (4) and the desired system (8) converges, under the existences of the disturbances $\mathbf{d}$ and input saturation $\text{sat}(\cdot)$.

4. MAIN RESULTS

- 포화에 대한 영향을 강조하기 위한 내용 추가 (리마크)
- hard constraint를 쓰지 않고 LMI에 통합

Following the control design in Tsukamoto et al. (2021a), the state-dependent coefficient (SDC) formulation Dani et al. (2015) is used to simplify the analysis to be understood as in LTV system theory. The SDC $\mathbb{A} := \mathbb{A}(\mathbf{x}, \mathbf{x}_d)$ is defined as follows:

$$\mathbb{A} := \int_0^1 \left[\frac{\partial \bar{\mathbf{f}}}{\partial \mathbf{x}} \right] (c\mathbf{x} + (1-c)\mathbf{x}_d) dc, \quad (9)$$

where $\bar{\mathbf{f}} := \bar{\mathbf{f}}(\mathbf{x}, \mathbf{x}_d) = \mathbf{f} - \mathbf{f}_d + \mathbf{B}\mathbf{u}_d - \mathbf{B}_d\mathbf{u}_d$ and c is a dummy variable for the integration. The existence... blah blah can be found in Dani et al. (2015), [MS: and more...].

Then, the error dynamics can be expressed as:

$$\begin{aligned}\frac{d}{dt}(\mathbf{x} - \mathbf{x}_d) &= \mathbf{f} - \mathbf{f}_d + \mathbf{B}\mathbf{u} - \mathbf{B}_d\mathbf{u}_d + \mathbf{B}\boldsymbol{\phi}(\mathbf{u}) + \mathbf{d} \\ &= \underbrace{\mathbf{f} - \mathbf{f}_d + (\mathbf{B} - \mathbf{B}_d)\mathbf{u}_d}_{=\mathbb{A}(\mathbf{x}, \mathbf{x}_d)(\mathbf{x} - \mathbf{x}_d)} \\ &\quad + \mathbf{B}(\mathbf{u} - \mathbf{u}_d) + \mathbf{B}\boldsymbol{\phi}(\mathbf{u}) + \mathbf{d} \\ &= \mathbb{A}(\mathbf{x} - \mathbf{x}_d) + \mathbf{B}(\mathbf{u} - \mathbf{u}_d) + \mathbf{B}\boldsymbol{\phi}(\mathbf{u}) + \mathbf{d} \\ &= \left(\mathbb{A} - \mathbf{B}\mathbf{R}^{-1}\mathbf{B}^\top \mathbf{M} \right) (\mathbf{x} - \mathbf{x}_d) + \mathbf{B}\boldsymbol{\phi}(\mathbf{u}) + \mathbf{d},\end{aligned}\quad (10)$$

with the control input $\mathbf{u}$ defined as:

$$\mathbf{u} = \mathbf{u}_d - \mathbf{R}^{-1}\mathbf{B}^\top \mathbf{M}(\mathbf{x} - \mathbf{x}_d) \quad (11)$$

where $\mathbf{R} = \mathbf{R}^\top \succ 0$ is a symmetric positive definite matrix.

In the following, we formulate the optimization problem to obtain the contraction metric $\mathbf{M}$ which satisfies the contraction condition (15) and does not violate the input saturation constraint (7).

4.1 Contraction Metric Calculation

Contraction Condition Satisfaction Invoking the partial contraction theory reviewed in Section 2.2, we can define the virtual system as follows:

$$\frac{d}{dt}\mathbf{q} = \frac{d}{dt}\mathbf{x}_d + \left(\mathbb{A} - \mathbf{B}\mathbf{R}^{-1}\mathbf{B}^\top \mathbf{M} \right) (\mathbf{q} - \mathbf{x}_d) + \mathbf{d}_\mu, \quad (12)$$

where $\mathbf{q} \in \mathbb{R}^n$ is the virtual state vector and $\mathbf{d}_\mu := \mathbf{d}_\mu(\mathbf{d}, \mu)$, $\forall \mu \in [0, 1]$, is defined as $\mathbf{0} = \mathbf{d}_\mu(\mathbf{d}, 0)$ and $\mathbf{d} = \mathbf{d}_\mu(\mathbf{d}, 1)$. The differential dynamics is then defined as follows:

$$\frac{d}{dt}\delta\mathbf{q} = \left(\mathbb{A} - \mathbf{B}\mathbf{R}^{-1}\mathbf{B}^\top \mathbf{M} \right) \delta\mathbf{q}. \quad (13)$$

[MS: CHECK FROM HERE] Then according to Theorem 1 and 2, system (12) and the system (8) will converge to the desired trajectory $\mathbf{x}_d$ with steady state error:

$$\mathbf{e}_{ss} = (\sup(\mathbf{B}\boldsymbol{\phi}(\mathbf{u})) + \bar{d}) \frac{1}{\alpha} \sqrt{\frac{m}{m}}, \quad (14)$$

with the following conditions:

$$\frac{d}{dt}\mathbf{M} + 2\text{sym}(\mathbf{M}\mathbb{A}) + 2\mathbf{M}\mathbf{B}\mathbf{R}^{-1}\mathbf{B}^\top \mathbf{M} \leq -2\alpha\mathbf{M}. \quad (15)$$

By multiplying $\mathbf{W} := \mathbf{M}^{-1}$ both sides of (15), we have the following LMI:

$$-\frac{d}{dt}\mathbf{W} + 2\text{sym}(\mathbb{A}\mathbf{W}) - 2\mathbf{B}\mathbf{R}^{-1}\mathbf{B}^\top \leq -2\alpha\mathbf{W}. \quad (16)$$

In [MS: []], Tsukamoto et al. proposed a method to formulate the LMI problem for the contraction metric as follows:

$$\begin{aligned}\min_{\mathbf{W}, X, \mu} \quad & X + \lambda\mu \\ \text{s.t.} \quad & (15)\end{aligned} \quad (17)$$

However, even with the proposed method, the input saturation can still occur by excessive contraction metric leading to potential instability. Therefore, we need to incorporate input constraints into the LMI formulation.

Input Saturation Constraint To address the input saturation function (7), the saturation constraint $\mathbf{u}^\top \mathbf{u} - \bar{u}^2 \leq 0$ is defined as:

$$\begin{bmatrix} \bar{u}^2 & \left(\mathbf{u}_d - \mathbf{R}^{-1}\mathbf{B}^\top \mathbf{M}(\mathbf{x} - \mathbf{x}_d) \right)^\top \\ \star & \mathbf{I} \end{bmatrix} \succeq 0. \quad (18)$$

By multiplying both sides by $[\text{diag}(\mathbf{I}, \mathbf{W}(\mathbf{R}^{-1}\mathbf{B}^\top)^{-1})]$, we have LMIs as follows:

$$\begin{bmatrix} \bar{u}^2 & \left(\mathbf{W}(\mathbf{R}^{-1}\mathbf{B}^\top)^{-1} \mathbf{u}_d - (\mathbf{x} - \mathbf{x}_d) \right)^\top \\ \star & \mathbb{X} \end{bmatrix} \succeq 0, \quad (19)$$

where $\mathbb{X} := \mathbf{W}(\mathbf{R}^{-1}\mathbf{B}^\top)^{-1}(\mathbf{R}^{-1}\mathbf{B}^\top)^{-1\top}\mathbf{W}$ which satisfies

$$\begin{bmatrix} \mathbb{X} & \mathbf{W}((\mathbf{R}^{-1}\mathbf{B}^\top)^{-1})^\top \\ \star & \mathbf{I} \end{bmatrix} \succeq 0. \quad (20)$$

Finally, the contraction metric can be obtained by solving the following LMI problem:

$$\begin{aligned} \min_{\mathbf{W}, \mathbb{X}, \mu} \quad & X + \text{trace}(\mathbb{X}) + \lambda\mu \\ \text{s.t.} \quad & (15), (19) \text{ and } (20) \end{aligned} \quad (21)$$

4.2 Numerical Methods For LMI

- Discretize $\frac{d}{dt}\mathbf{M}$
- LMI solver
- Tuning methods

5. NUMERICAL VALIDATION

5.1 Numerical Validation Set Up

We employed the Lorenz system [MS: REF] to validate the proposed method which is represented as follows:

$$\underbrace{\frac{d}{dt} \begin{pmatrix} x \\ y \\ z \end{pmatrix}}_{=: \xi} = \underbrace{\begin{pmatrix} \sigma(y-x) \\ x(\rho-z)-y \\ xy-\beta z \end{pmatrix}}_{=: f(\xi)} + \underbrace{\begin{pmatrix} u_x \\ u_y \\ u_z \end{pmatrix}}_{=: u} + \underbrace{\begin{pmatrix} d_x \\ d_y \\ d_z \end{pmatrix}}_{=: d}, \quad (22)$$

where $\sigma = 10$, $\rho = 28$, and $\beta = \frac{8}{3}$ are system parameters.

5.2 Numerical Validation Results

- Desired -i black solid
- CMP -i blue dashed
- CMP -i red dashed
- CMP -i cyan dashed

6. CONCLUSION

In this study, ...

ACKNOWLEDGEMENTS

Place acknowledgments here.

REFERENCES

- Dani, A.P., Chung, S.J., and Hutchinson, S. (2015). Observer design for stochastic nonlinear systems via contraction-based incremental stability. *IEEE Transactions on Automatic Control*, 60(3), 700–714. doi:10.1109/TAC.2014.2357671. URL <https://doi.org/10.1109/TAC.2014.2357671>.
- Kirk, D. (2004). *Optimal Control Theory: An Introduction*. Dover Books on Electrical Engineering Series. Dover Publications. doi:10.1002/aic.690170452. URL <https://doi.org/10.1002/aic.690170452>.

- Lohmiller, W. and Slotine, J.J.E. (1998). On contraction analysis for non-linear systems. *Automatica*, 34(6), 683–696. doi: [https://doi.org/10.1016/S0005-1098\(98\)00019-3](https://doi.org/10.1016/S0005-1098(98)00019-3). URL [https://doi.org/10.1016/S0005-1098\(98\)00019-3](https://doi.org/10.1016/S0005-1098(98)00019-3).
- Tsukamoto, H., Chung, S.J., and Slotine, J.J. (2021a). Learning-based adaptive control using contraction theory. In *2021 60th IEEE Conference on Decision and Control (CDC)*, 2533–2538. doi:10.1109/CDC45484.2021.9683435. URL <https://doi.org/10.1109/CDC45484.2021.9683435>.
- Tsukamoto, H., Chung, S.J., and Slotine, J.J.E. (2021b). Neural stochastic contraction metrics for learning-based control and estimation. *IEEE Control Systems Letters*, 5(5), 1825–1830. doi:10.1109/LCSYS.2020.3046529. URL <https://doi.org/10.1109/LCSYS.2020.3046529>.
- Tsukamoto, H., Chung, S.J., and Slotine, J.J.E. (2021c). Contraction theory for nonlinear stability analysis and learning-based control: A tutorial overview. *Annual Reviews in Control*, 52, 135–169. doi: <https://doi.org/10.1016/j.arcontrol.2021.10.001>. URL <https://doi.org/10.1016/j.arcontrol.2021.10.001>.
- Wang, W. and Slotine, J.J.E. (2004). On partial contraction analysis for coupled nonlinear oscillators. *Biological Cybernetics*, 92(1), 38–53. doi:10.1007/s00422-004-0527-x. URL <http://dx.doi.org/10.1007/s00422-004-0527-x>.




Fig. 1. Numerical validation results of (C_1) [—], (C_2) [—], (C_3) [—], (C_4) [—], and desired trajectory x_d [---].




Fig. 2. Numerical validation results of (C_1) [—], (C_2) [—], (C_3) [—], (C_4) [—], and desired trajectory x_d [---].