

Q.1

Configure iptables such that if any computer tries to ping or ssh to your firewall WAN (192.168.74.73) Network card, the ip address will be blocked for 2 min,

Ping to WAN ip. Display the ip is blocked for 2min Access the website and make sure it is not accessible after 2min show ip is unblocked and the website open.

ANS ->

# Reload iptables service

>sudo systemctl reload iptables

# Ensure Apache is running

>sudo vim /var/www/html/index.html

>sudo systemctl start httpd

>sudo systemctl status httpd

# Allow HTTP traffic (port 80) for normal website access

>sudo iptables -I INPUT 1 -p tcp --dport 80 -m conntrack --ctstate NEW -j ACCEPT

# Create ipset with 2-minute timeout

>sudo ipset create bad\_iplist hash:ip timeout 120

# Drop traffic from blocked IPs

>sudo iptables -I INPUT 1 -m set --match-set bad\_iplist src -j DROP

# Rule: Add IPs that attempt SSH to bad\_iplist

>sudo iptables -I INPUT 2 -p tcp --dport 22 -j SET --add-set bad\_iplist src

# Rule: Add IPs that attempt to ping WAN to bad\_iplist

>sudo iptables -I INPUT 2 -p icmp --icmp-type echo-request -j SET --add-set bad\_iplist src

#Try to ping and ssh from your client and website is open for all time

#check your list and blocked ips

>sudo ipset list bad\_iplist