

 Marwadi University	Marwadi University Faculty of Technology Department of Information and Communication Technology	
Subject: Artificial Intelligence (01CT0616)	Aim: To learn the Basics of Machine Learning	
Experiment No: 01	Date:	Enrollment No: 92301733023

Aim: To learn the Basics of Machine Learning

IDE: Google Colab **Theory:**

Machine learning is a subset of artificial intelligence in the field of computer science that often uses statistical techniques to give computers the ability to "learn" (i.e., progressively improve performance on a specific task) with data, without being explicitly programmed. In the past decade, machine learning has given us self-driving cars, practical speech recognition, effective web search, and a vastly improved understanding of the human genome.

Machine learning tasks

Machine learning tasks are typically classified into two broad categories, depending on whether there is a learning "signal" or "feedback" available to a learning system:

- **Supervised learning:** The computer is presented with example inputs and their desired outputs, given by a "teacher", and the goal is to learn a general rule that maps inputs to outputs. As special cases, the input signal can be only partially available, or restricted to special feedback:
- **Semi-supervised learning:** the computer is given only an incomplete training signal: a training set with some (often many) of the target outputs missing.
- **Active learning:** the computer can only obtain training labels for a limited set of instances (based on a budget), and also has to optimize its choice of objects to acquire labels for. When used interactively, these can be presented to the user for labeling.
- **Reinforcement learning:** training data (in form of rewards and punishments) is given only as feedback to the program's actions in a dynamic environment, such as driving a vehicle or playing a game against an opponent.
- **Unsupervised learning:** No labels are given to the learning algorithm, leaving it on its own to find structure in its input. Unsupervised learning can be a goal in itself (discovering hidden patterns in data) or a means towards an end (feature learning).

Machine learning applications

In classification, inputs are divided into two or more classes, and the learner must produce a model that assigns unseen inputs to one or more (multi-label classification) of these classes. This is typically tackled in a supervised manner. Spam filtering is an example of classification, where the inputs are email (or other) messages and the classes are "spam" and "not spam". In regression, also a supervised problem, the outputs are continuous rather than discrete.

In clustering, a set of inputs is to be divided into groups. Unlike in classification, the groups are not known beforehand, making this typically an unsupervised task. Density estimation finds the distribution of inputs in some space. Dimensionality reduction simplifies inputs by mapping them into a lower- dimensional space. Topic

 Marwadi University	Marwadi University Faculty of Technology Department of Information and Communication Technology	
Subject: Artificial Intelligence (01CT0616)	Aim: To learn the Basics of Machine Learning	
Experiment No: 01	Date:	Enrollment No: 92301733023

modeling is a related problem, where a program is given a list of human language documents and is tasked with finding out which documents cover similar topics.

Machine learning Approaches

Decision tree learning: Decision tree learning uses a decision tree as a predictive model, which maps observations about an item to conclusions about the item's target value. **Association rule learning** Association rule learning is a method for discovering interesting relations between variables in large databases.

Artificial neural networks

An artificial neural network (ANN) learning algorithm, usually called "neural network" (NN), is a learning algorithm that is vaguely inspired by biological neural networks. Computations are structured in terms of an interconnected group of artificial neurons, processing information using a connectionist approach to computation. Modern neural networks are non-linear statistical data modeling tools. They are usually used to model complex relationships between inputs and outputs, to find patterns in data, or to capture the statistical structure in an unknown joint probability distribution between observed variables.

Deep learning

Falling hardware prices and the development of GPUs for personal use in the last few years have contributed to the development of the concept of deep learning which consists of multiple hidden layers in an artificial neural network. This approach tries to model the way the human brain processes light and sound into vision and hearing. Some successful applications of deep learning are computer vision and speech recognition.

Inductive logic programming

Inductive logic programming (ILP) is an approach to rule learning using logic programming as a uniform representation for input examples, background knowledge, and hypotheses. Given an encoding of the known background knowledge and a set of examples represented as a logical database of facts, an ILP system will derive a hypothesized logic program that entails all positive and no negative examples. Inductive programming is a related field that considers any kind of programming languages for representing hypotheses (and not only logic programming), such as functional programs.

Support vector machines

Support vector machines (SVMs) are a set of related supervised learning methods used for classification and regression. Given a set of training examples, each marked as belonging to one of two categories, an SVM training algorithm builds a model that predicts whether a new example falls into one category or the other.

Clustering

Cluster analysis is the assignment of a set of observations into subsets (called clusters) so that observations within the same cluster are similar according to some pre designated criterion or criteria, while observations

 Marwadi University	Marwadi University Faculty of Technology Department of Information and Communication Technology	
Subject: Artificial Intelligence (01CT0616)	Aim: To learn the Basics of Machine Learning	
Experiment No: 01	Date:	Enrollment No: 92301733023

drawn from different clusters are dissimilar. Different clustering techniques make different assumptions on the structure of the data, often defined by some similarity metric and evaluated for example by internal compactness (similarity between members of the same cluster) and separation between different clusters. Other methods are based on estimated density and graph connectivity. Clustering is a method of unsupervised learning, and a common technique for statistical data analysis.

Bayesian networks

A Bayesian network, belief network or directed acyclic graphical model is a probabilistic graphical model that represents a set of random variables and their conditional independencies via a directed acyclic graph (DAG). For example, a Bayesian network could represent the probabilistic relationships between diseases and symptoms. Given symptoms, the network can be used to compute the probabilities of the presence of various diseases. Efficient algorithms exist that perform inference and learning.

Reinforcement learning

Reinforcement learning is concerned with how an agent ought to take actions in an environment so as to maximize some notion of long-term reward. Reinforcement learning algorithms attempt to find a policy that maps states of the world to the actions the agent ought to take in those states. Reinforcement learning differs from the supervised learning problem in that correct input/output pairs are never presented, nor sub-optimal actions explicitly corrected.

Similarity and metric learning

In this problem, the learning machine is given pairs of examples that are considered similar and pairs of less similar objects. It then needs to learn a similarity function (or a distance metric function) that can predict if new objects are similar. It is sometimes used in Recommendation systems.

Genetic algorithms

A genetic algorithm (GA) is a search heuristic that mimics the process of natural selection, and uses methods such as mutation and crossover to generate new genotype in the hope of finding good solutions to a given problem. In machine learning, genetic algorithms found some uses in the 1980s and 1990s. Conversely, machine learning techniques have been used to improve the performance of genetic and evolutionary algorithms.

Rule-based machine learning

Rule-based machine learning is a general term for any machine learning method that identifies, learns, or evolves "rules" to store, manipulate or apply, knowledge. The defining characteristic of a rule-based machine learner is the identification and utilization of a set of relational rules that collectively represent the knowledge captured by the system. This is in contrast to other machine learners that commonly identify a singular model that can be universally applied to any instance in order to make a prediction. Rule-based machine learning approaches include learning classifier systems, association rule learning, and artificial immune systems.

 Marwadi University	Marwadi University Faculty of Technology Department of Information and Communication Technology	
Subject: Artificial Intelligence (01CT0616)	Aim: To learn the Basics of Machine Learning	
Experiment No: 01	Date:	Enrollment No: 92301733023

Feature selection approach

Feature selection is the process of selecting an optimal subset of relevant features for use in model construction. It is assumed the data contains some features that are either redundant or irrelevant, and can thus be removed to reduce calculation cost without incurring much loss of information. Common optimality criteria include accuracy, similarity and information measures.

Pre Lab Exercise:

a. Write 5 applications, that you encounter daily, where Machine Learning is used?

1. When we search something on Google, it shows the most relevant results
2. YouTube and Netflix suggest videos or movies based on what we watch
3. Email services automatically filter spam messages
4. Voice assistants like Google Assistant understand our voice commands
5. Online shopping apps recommend products based on our interests

b. What do you mean by Supervised Learning?

Supervised learning is a method where the machine is trained using already labeled data.

This means we provide both input and correct output, so the system learns the relationship between them and can predict results for new data.

c. What do you mean by Unsupervised Learning?

Unsupervised learning is used when no labels are given.

The machine tries to understand patterns, similarities, or groups in the data on its own.

d. What do you mean by Reinforcement Learning?

In reinforcement learning, the system learns by trial and error.

It takes actions, receives rewards or penalties, and improves its performance over time.

 Marwadi University	Marwadi University Faculty of Technology Department of Information and Communication Technology	
Subject: Artificial Intelligence (01CT0616)	Aim: To learn the Basics of Machine Learning	
Experiment No: 01	Date:	Enrollment No: 92301733023

Program (Code):

```

import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns

data = pd.read_csv("student_Data.csv")

print(data.head())

print(data.describe())

print("Shape:", data.shape)

data = data.fillna(data.mean(numeric_only=True))

for col in data.columns[1:]:
    plt.figure()
    sns.boxplot(x=data[col])
    plt.title(f"Boxplot of {col}")
    plt.show()

```

 Marwadi University	Marwadi University Faculty of Technology Department of Information and Communication Technology	
Subject: Artificial Intelligence (01CT0616)	Aim: To learn the Basics of Machine Learning	
Experiment No: 01	Date:	Enrollment No: 92301733023


Results:

```



...   Student_ID  Age  Study_Hours  Attendance  Assignments  Marks
0         1    18         2         75           3        55
1         2    19         5         85           5        78
2         3    18         3         65           2        50
3         4    20         6         90           6        88
4         5    19         4         80           4        72

      Student_ID      Age  Study_Hours  Attendance  Assignments      Marks
count  15.000000  15.000000  15.000000  15.000000  15.000000  15.000000
mean    8.000000  19.200000   4.066667  77.733333   4.066667  68.133333
std     4.472136   1.082326   2.016598  12.302536   2.016598  18.415315
min     1.000000  18.000000   1.000000  55.000000   1.000000  35.000000
25%     4.500000  18.000000   2.500000  67.500000   2.500000  53.500000
50%     8.000000  19.000000   4.000000  80.000000   4.000000  72.000000
75%    11.500000  20.000000   5.500000  86.500000   5.500000  82.500000
max    15.000000  21.000000   7.000000  95.000000   7.000000  92.000000
Shape: (15, 6)

```




 Marwadi University	Marwadi University Faculty of Technology Department of Information and Communication Technology	
Subject: Artificial Intelligence (01CT0616)	Aim: To learn the Basics of Machine Learning	
Experiment No: 01	Date:	Enrollment No: 92301733023




 Marwadi University Marwadi University Faculty of Technology Department of Information and Communication Technology		
Subject: Artificial Intelligence (01CT0616)	Aim: To learn the Basics of Machine Learning	
Experiment No: 01	Date:	Enrollment No: 92301733023

Boxplot of Assignments



Boxplot of Marks



Marks

Marks

 Marwadi University	Marwadi University Faculty of Technology Department of Information and Communication Technology	
Subject: Artificial Intelligence (01CT0616)	Aim: To learn the Basics of Machine Learning	
Experiment No: 01	Date:	Enrollment No: 92301733023

Observation and Result Analysis:

a. Statistics of the dataset

1. The dataset contains features like Age, Study Hours, Attendance, Assignments, and Marks
2. The **mean** shows the average performance of students in each feature
3. The **standard deviation** indicates how much variation exists among students
4. The **minimum and maximum values** show the range of data
5. The **quartiles (25%, 50%, 75%)** help understand how the data is distributed

b. IQR and Outliers

1. The **IQR (Interquartile Range)** is calculated as:
 $IQR = Q3 - Q1$
2. It represents the spread of the middle 50% of the data
3. Using boxplots, we can identify **outliers**, which are values far from the normal range
4. Outliers may occur due to unusual behavior (e.g., very low study hours but high marks or vice versa)
5. These values can affect the analysis and should be handled carefully

 Marwadi University	Marwadi University Faculty of Technology Department of Information and Communication Technology	
Subject: Artificial Intelligence (01CT0616)	Aim: To learn the Basics of Machine Learning	
Experiment No: 01	Date:	Enrollment No: 92301733023

Post Lab Exercise:

- a. Which is a better mean of replacing the missing value-mean, median or mode?

Mean works well when data is clean and evenly distributed.

Median is better when there are outliers, but here no strong outliers are present.

Mode is mainly useful for categorical data, which is not the case here.

- b. How IQR range helps to understand the nature of the distribution of the data?

From the boxplots of Age, Study Hours, Attendance, Assignments, and Marks:

- The boxes are evenly shaped, showing balanced data distribution.
- There are no extreme outliers visible.
- The spread of values is moderate, not too wide or too narrow.

This indicates:

- The data is stable and consistent
- Students have similar performance levels
- The dataset follows a normal or near-normal distribution

- c. Which are the ways to replace the categorical data to the numerical ones?

In this dataset, all values are already numerical, so no conversion is required.

However, if categorical data were present, we could convert it using:

1. Label Encoding – Assigns a number to each category
2. One-Hot Encoding – Creates separate columns for each category
3. Ordinal Encoding – Used when categories have an order