OPERATING SYSTEM - CS23431

EXP 7

IPC USING SHARED MEMORY

NAME: KARTHIKHA SRE M ROLL NO: 230701143

PROGRAM:

Sender.c:

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/shm.h>
#include <string.h>
int main() {
int shmid;
shmid = shmget((key t)2345, 1024, 0666 | IPC CREAT); if (shmid == -1) {
perror("shmget failed"); exit(1);
printf("Key of the shared memory segment: %d\n", shmid);
char *shmaddr = (char *) shmat(shmid, NULL, 0);
if (shmaddr == (char *) -1) {
  perror("shmat failed");
  exit(1);
printf("Process is attached at address %p\n", shmaddr);
sprintf(shmaddr, "Hello world!!");
printf("Content written to shared memory: %s\n", shmaddr);
```

```
if (shmdt(shmaddr) == -1) {
  perror("shmdt failed");
  exit(1);
}
return 0;
}
Receiver.c:
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <string.h>
#include <sys/shm.h>
int main() {
int shmid; char *shmaddr;
shmid = shmget((key t)2345, 1024, 0666);
if (shmid == -1) {
  perror("shmget failed");
  exit(1);
}
printf("Key of the shared memory segment: %d\n", shmid);
shmaddr = (char *) shmat(shmid, NULL, 0);
if (shmaddr == (char *) -1) {
  perror("shmat failed");
  exit(1);
}
printf("Process is attached at address %p\n", shmaddr);
printf("Data read from shared memory: %s\n", shmaddr);
```

```
if (shmdt(shmaddr) == -1) {
   perror("shmdt failed");
   exit(1);
}
return 0;
}
```

OUTPUT:

```
[student@localhost ~]$ vi sender.c
[student@localhost ~]$ gcc sender.c
[student@localhost ~]$ ./a.out
key of the shared memory is 622605
Process is attached at 0xb76ee000
Content written is Hello world!!
[student@localhost ~]$ vi receiver.c
[student@localhost ~]$ gcc receiver.c
[student@localhost ~]$ ./a.out
key of shared memory segment is 622605
process is attached at 0xb7782000
Data read from shared memory is Hello world!!
[student@localhost ~]$ ■
```