

Learning from Videos

Naeemullah Khan

naeemullah.khan@kaust.edu.sa



جامعة الملك عبد الله
للعلوم والتقنية
King Abdullah University of
Science and Technology

KAUST Academy
King Abdullah University of Science and Technology

July 11, 2026

Table of Contents

Why focus on video data?

- ▶ **Ubiquity of video data:** streaming, social media, autonomous systems
- ▶ **Need for temporal understanding:** beyond static images to dynamic events
- ▶ **Generative potential:** create, predict, and simulate future frames
- ▶ **Real-world impact:** surveillance, sports analytics, healthcare, AR/VR, content creation

By the end of this session, you will be able to:

- ▶ Define video data and temporal concepts.
- ▶ Identify challenges in acquiring and processing video.
- ▶ Implement models from single-frame CNNs to spatio-temporal Transformers.
- ▶ Extract motion features and recognize actions.
- ▶ Apply self-supervised video representation learning.
- ▶ Critically assess limitations and propose future research.

Video *generation* is covered in the next lecture; vision–language models (CLIP) are covered in the Vision and Text lecture.

Video Learning & Generation: **Introduction**


- ▶ **Video** is a sequence of images (frames) captured over time.
- ▶ Each frame is a static image, but the sequence captures motion and temporal dynamics.
- ▶ Videos can be continuous (e.g., surveillance footage) or discrete (e.g., video clips).
- ▶ Key components:
 - Frame rate: number of frames per second (FPS).
 - Resolution: dimensions of each frame.
 - Duration: total length of the video.

What is Video Data? (cont.)

Videos are all around us
Span an enormous space of spatial and temporal signals




What is Video Data? (cont.)



What is Video Data? (cont.)

RESOLUTION	AVERAGE DATA USAGE PER HOUR
480P (SD)	360 MB
720P (HD)	900 MB
1080P (FULL HD)	1.5 GB
4K (ULTRA HD)	7.2 GB

A video is a **sequence** of images
4D tensor: $T \times 3 \times H \times W$
(or $3 \times T \times H \times W$)



- ▶ Cameras capture video data with various properties that affect quality and usability.
- ▶ Key properties include:
 - **FPS (Frames per Second):** Determines the temporal resolution of the video; higher FPS captures smoother motion.
 - **Spatial Resolution:** Refers to the pixel dimensions of each frame (e.g., 1920x1080); affects image detail.
 - **Field of View (FOV):** The angular extent of the observable scene captured by the camera; wide FOV covers more area.
 - **Depth Sensors:** Devices like RGB-D cameras and LiDAR provide depth information, enabling 3D scene understanding.

30FPS




15FPS



1 FPS




Camera Properties (cont.)



Camera Properties (cont.)





- ▶ **Single Frame:** Static content; no motion cues.
- ▶ **Short Clip:** Captures motion trajectories.
- ▶ **Temporal Window:** Enables extraction of velocity and acceleration.
- ▶ **Temporal Features:** Techniques such as frame differencing and optical flow capture motion information.

What Does Temporal Mean? (cont.)




Illustration of temporal features in video: single frame, short clip, and motion extraction.

Video Learning & Generation: **Data Acquisition & Challenges**

- ▶ Video data can be acquired from various sources, including:
 - **Cameras:** Digital cameras, smartphones, and webcams.
 - **Drones:** Aerial footage for surveillance or mapping.
 - **Webcams:** Live streaming or recorded video.
 - **Public Datasets:** Pre-recorded videos available for research.
- ▶ Key considerations in data acquisition:
 - Quality of the recording device.
 - Environmental conditions (lighting, weather).
 - Ethical considerations (privacy, consent).

► Modern sources for video data:

- **User-generated content:** Platforms like YouTube and TikTok provide vast amounts of diverse video data.
- **Surveillance & IoT:** Cameras embedded in city infrastructure, public spaces, and smart devices continuously capture video streams.
- **Automotive:** Dashcams and sensors in autonomous vehicles generate large-scale driving and traffic video datasets.

► **Metadata and tags:** Videos are often accompanied by metadata (timestamps, GPS, tags) that facilitate search, retrieval, and organization.

Popular Video Datasets:

- ▶ **UCF101:** 13,000+ video clips covering 101 human action categories.
- ▶ **Kinetics-700:** 650,000 video clips annotated with 700 action classes.
- ▶ **ActivityNet:** Large-scale dataset with untrimmed videos for temporal action localization.
- ▶ **Something-Something v2:** Focuses on fine-grained, object-centric actions.
- ▶ **Ego4D:** Egocentric videos capturing daily activities from a first-person perspective.

space of video $\gg$ space of image $\rightarrow$ lots of training data

“ImageNet”-equivalent dataset for videos?

Massive human labelling efforts



UCF101

YouTube videos
13320 videos, 101 action categories



Kinetics

YouTube videos
650,000 video clips, 600 human
action classes



YouTube-8M

8M video clips, Machine-generated
annotations from 3,862 classes



Sports-1M

YouTube videos
1,133,157 videos, 487 sports labels

Datasets

12,414 machine learning datasets

🔔 Share your dataset with the ML community!

Best match

Filter by Modality (clear)

Videos

3332

Texts

3274

Images

484

Audio

424

Medical

399

Filter by Task

Action Recognition

80

Video Understanding

44

Object Tracking

40

Object Detection

39

Video Question Answering

38

1021 dataset results for Videos

**MS COCO** (Microsoft Common Objects in Context)
The MS COCO (Microsoft Common Objects in Context) dataset is a large-scale object detection, segmentation, key-point detection, and captioning dataset. The dataset consists of 328K...
11,848 PAPERS • 96 BENCHMARKS

**UCF101** (UCF101 Human Actions dataset)
UCF101 dataset is an extension of UCF50 and consists of 13,320 video clips, which are classified into 101 categories. These 101 categories can be classified into 5 types (Body motion, Human...
5,853 PAPERS • 27 BENCHMARKS

**Kinetics** (Kinetics Human Action Video Dataset)
The Kinetics dataset is a large-scale, high-quality dataset for human action recognition in videos. The dataset consists of around 500,000 video clips covering 600 human action classes...
5,337 PAPERS • 31 BENCHMARKS

**HMDB51**
The HMDB51 dataset is a large collection of realistic videos from various sources, including movies and web videos. The dataset is composed of 6,766 video clips from 51 action categories...
837 PAPERS • 12 BENCHMARKS

**ActivityNet**
The ActivityNet dataset contains 200 different types of activities and a total of 849 hours of videos collected from YouTube. ActivityNet is the largest benchmark for temporal activity de...
803 PAPERS • 20 BENCHMARKS

**Human3.6M**
The Human3.6M dataset is one of the largest motion capture datasets, which consists of 3.6

[Source: <https://paperswithcode.com/datasets?mod=videos>]

► Issues Working with Videos:

- **High Storage:** Video files are large, requiring significant storage and bandwidth.
- **Variable FPS & Resolution:** Differences in frame rates and resolutions increase preprocessing complexity.
- **Annotation Cost:** Frame-level labeling is time-consuming and expensive.
- **Data Imbalance:** Rare events or classes are often underrepresented in datasets.



Input video:

$T \times 3 \times H \times W$

Videos are ~30 frames per second (fps)

Size of uncompressed video
(3 bytes per pixel):

SD (640 x 480): **~1.5 GB per minute**

HD (1920 x 1080): **~10 GB per minute**



Input video:
 $T \times 3 \times H \times W$

Videos are ~ 30 frames per second (fps)

Size of uncompressed video
(3 bytes per pixel):

SD (640 x 480): **~ 1.5 GB per minute**

HD (1920 x 1080): **~ 10 GB per minute**

Solution: Train on short **clips**: low
fps and low spatial resolution
e.g. $T = 16$, $H=W=112$
(3.2 seconds at 5 fps, 588 KB)

► Solutions for Video Data:

- **Compression & Sampling:** Techniques like keyframe extraction and frame sampling help reduce storage and computational requirements.
- **Data Augmentation:** Methods such as frame dropout and temporal jittering increase data diversity and robustness.
- **Synthetic Data:** Simulated environments (e.g., CARLA, AirSim) generate realistic video data for training and testing.
- **Weak & Self-Supervision:** Leveraging unlabeled or partially labeled data reduces reliance on expensive manual annotations.

Video Learning & Generation: **Video Understanding Models**

- ▶ Video understanding involves analyzing and interpreting video data to extract meaningful information.
- ▶ Key tasks include:
 - **Action recognition:** Identifying actions or activities in videos.
 - **Object detection:** Locating and classifying objects within video frames.
 - **Scene understanding:** Analyzing the context and environment in which actions occur.
 - **Temporal analysis:** Understanding how actions evolve over time.



Input video:
 $T \times 3 \times H \times W$



Swimming
Running
Jumping
Eating
Standing

- ▶ To understand videos, models need to look at both:
 - What's in each frame (spatial info).
 - How things move or change (temporal info).
- ▶ How do we do this?
 - Use CNNs to spot patterns in images.
 - Use RNNs or LSTMs to follow changes over time.
 - Use 3D CNNs to look at several frames together.
 - Use Transformers to connect information across the whole video.



Images: Recognize **objects**



Dog
Cat
Fish
Truck



Videos: Recognize **actions**



Swimming
Running
Jumping
Eating
Standing

- ▶ These models learn from lots of labeled videos.
- ▶ We check how well they work using accuracy, precision, recall, and F1-score.
- ▶ New research is making models faster, more reliable, and better at handling different types of videos.
- ▶ Where is this useful?
 - Security and surveillance.
 - Self-driving cars.
 - Sports analysis.
 - Healthcare monitoring.
 - Recommending videos online.

- ▶ **Clip Length Selection:** Typically, short clips of 16–64 frames are used to balance computational cost and temporal coverage.
- ▶ **Batch Size vs. Temporal Context:** Increasing clip length provides more temporal context but reduces the possible batch size due to memory constraints.
- ▶ **Pretraining for Transfer Learning:** Models are often pretrained on large-scale video datasets (e.g., Kinetics, Sports-1M) to improve performance on downstream tasks.

Raw video: Long, high FPS



Training: Train model to classify short **clips** with low FPS




Testing: Run model on different clips, average predictions



- ▶ Treat each frame independently
- ▶ Use pretrained ImageNet backbones
- ▶ Ignores temporal context; serves as a baseline

Single-Frame CNN (cont.)




- ▶ **Process frames separately**, then combine their representations.
- ▶ **Fully Connected Fusion**: Concatenate frame features, then use fully connected (FC) layers.
- ▶ **Pooling Fusion**: Apply average or max pooling across time dimension.


Pros: Simple and easy to implement.

Cons: Weak temporal modeling; ignores complex temporal dependencies.

Late Fusion (with FC layers)




Late Fusion (with pooling)



Late Fusion (with pooling) (cont.)

Intuition: Get high-level appearance of each frame, and combine them


Problem: Hard to compare low-level motion between frames



- ▶ **Stack frames as input channels to 2D CNN**
- ▶ Learns short-term motion patterns
- ▶ Limited receptive field along time


Early Fusion: Key Ideas (cont.)

Intuition: Compare frames with very first conv layer, after that normal 2D CNN




Intuition: Compare frames with very first conv layer, after that normal 2D CNN


Problem: One layer of temporal processing may not be enough!




- ▶ **3D Convolutional Networks:** Apply convolutional kernels across both spatial and temporal dimensions.
- ▶ **3D Kernels over Space-Time:** Filters operate on width, height, and time, enabling motion modeling.
- ▶ **Capture Local Spatio-Temporal Features:** Learn patterns that span multiple frames, such as movement or actions.
- ▶ **High Computational Cost:** Increased parameters and operations compared to 2D CNNs, leading to higher resource requirements.

Intuition: Use 3D versions of convolution and pooling to slowly fuse temporal information over the course of the network





3D CNN: Key Ideas (cont.)



- ▶ **3D CNNs** are powerful for video understanding, capturing both spatial and temporal features.
- ▶ They are particularly effective for tasks like action recognition, where understanding motion is crucial.
- ▶ However, they require significant computational resources and large datasets for training.
- ▶ **Applications:**
 - Action recognition in videos.
 - Gesture recognition.
 - Video classification.
 - Sports analysis.


Introduced by Tran et al., ICCV 2015

- ▶ Uses $3 \times 3 \times 3$ convolutions on 16-frame video clips.
- ▶ Demonstrated strong performance on the UCF101 action recognition benchmark.
- ▶ **3D Convolutional Networks:** Apply 3D convolutional kernels to capture spatio-temporal features.
- ▶ **Temporal Context:** C3D captures motion patterns by considering multiple frames simultaneously.
- ▶ **Pooling and Normalization:** Use pooling layers to reduce dimensionality and normalize features.
- ▶ **End-to-End Training:** Trained on large video datasets for tasks like action recognition.

- ▶ 3D CNN that uses all $3 \times 3 \times 3$ convolutions and $2 \times 2 \times 2$ pooling (except Pool1, which is $1 \times 2 \times 2$).
- ▶ Released model pretrained on Sports-1M: widely used as a video feature extractor.
- ▶ **Problem:** $3 \times 3 \times 3$ convolutions are very expensive!
 - AlexNet: 0.7 GFLOP
 - VGG-16: 13.6 GFLOP
 - C3D: 39.5 GFLOP ($2.9 \times$ VGG!)

Layer	Size
Input	$3 \times 16 \times 112 \times 112$
Conv1 ($3 \times 3 \times 3$)	$64 \times 16 \times 112 \times 112$
Pool1 ($1 \times 2 \times 2$)	$64 \times 16 \times 56 \times 56$
Conv2 ($3 \times 3 \times 3$)	$128 \times 16 \times 56 \times 56$
Pool2 ($2 \times 2 \times 2$)	$128 \times 8 \times 28 \times 28$
Conv3a ($3 \times 3 \times 3$)	$256 \times 8 \times 28 \times 28$
Conv3b ($3 \times 3 \times 3$)	$256 \times 8 \times 28 \times 28$
Pool3 ($2 \times 2 \times 2$)	$256 \times 4 \times 14 \times 14$
Conv4a ($3 \times 3 \times 3$)	$512 \times 4 \times 14 \times 14$
Conv4b ($3 \times 3 \times 3$)	$512 \times 4 \times 14 \times 14$
Pool4 ($2 \times 2 \times 2$)	$512 \times 2 \times 7 \times 7$
Conv5a ($3 \times 3 \times 3$)	$512 \times 2 \times 7 \times 7$
Conv5b ($3 \times 3 \times 3$)	$512 \times 2 \times 7 \times 7$
Pool5	$512 \times 1 \times 3 \times 3$
FC6	4096
FC7	4096
FC8	C

Sports-1M Top-5 Accuracy



Video Learning & Generation: **Motion & Temporal Dynamics**

- ▶ Motion as a primary cue for recognising actions in videos.
- ▶ Importance of separating the analysis of appearance and motion.
- ▶ Motion patterns often provide more discriminative information than static appearance.

- ▶ Computes a dense motion field between consecutive frames.
- ▶ Popular algorithms:
 - Farneback
 - TV-L1
- ▶ Optical flow is commonly used as input to Two-Stream Networks for action recognition.

- ▶ **Dense Motion Field:** Represents motion vectors for every pixel between two frames.
- ▶ **Temporal Coherence:** Assumes that motion is smooth and continuous over time.
- ▶ **Applications:** Used in action recognition, video segmentation, and object tracking.

Optical Flow: Key Concepts (cont.)

Image at frame t





Image at frame $t+1$

Optical flow gives a displacement field F between images I_t and I_{t+1}




Tells where each pixel will move in the next frame:

$$F(x, y) = (dx, dy)$$

$$I_{t+1}(x+dx, y+dy) = I_t(x, y)$$


Horizontal flow dx



Vertical Flow dy


- ▶ **Two-Stream Network:** Processes both RGB (appearance) and optical flow (motion) streams.
- ▶ Streams can be fused at various depths:
 - *Early fusion:* Combine features at initial layers.
 - *Late fusion:* Combine predictions or high-level features.
- ▶ Improves robustness to background and enhances motion understanding.

Two-Stream Network Architecture



- ▶ **RGB Stream:** Standard CNN (e.g., ResNet) for appearance features.
- ▶ **Optical Flow Stream:** Separate CNN for motion features.
- ▶ **Fusion:** Can be done at different stages:
 - Early: Concatenate features from both streams.
 - Late: Combine predictions from both streams.

Accuracy on UCF-101



Understanding complex actions in videos often requires analyzing long-term temporal structure, rather than relying solely on short clips. This involves capturing dependencies and patterns that span extended periods, which are crucial for recognizing actions composed of multiple stages or events.

- ▶ **Temporal Segmentation:** Divides a video into meaningful segments based on changes in activity.
- ▶ **Temporal Action Proposals:** Identifies candidate time intervals where actions may occur.


These techniques enable models to focus on relevant portions of the video and improve the recognition of complex, long-duration actions.

Several approaches have been developed to effectively model long-term temporal dependencies in videos:


- ▶ **Hierarchical RNNs and LSTMs:** Stack multiple recurrent layers to capture both short-term and long-term dependencies at different temporal scales.
- ▶ **Temporal Segment Networks (TSN):** Sample frames or segments sparsely across the entire video and aggregate their representations to model long-range structure.
- ▶ **Memory Networks:** Utilize external memory modules to store and retrieve information across hundreds of frames, enabling reasoning over extended temporal contexts.

These methods help in recognizing actions that unfold over long durations and involve multiple stages.


- ▶ So far, all our temporal CNNs only model local motion between frames in very short clips of approximately 2–5 seconds.
- ▶ What about long-term structure?




- ▶ So far, all our temporal CNNs only model local motion between frames in very short clips of approximately 2–5 seconds.
- ▶ What about long-term structure?
- ▶ **We know how to handle sequences!**
- ▶ How about **recurrent networks**?



- ▶ Process local features using recurrent network (e.g. LSTM)
- ▶ Many to many: one output per video frame



أكاديمية كاوست
KAUST ACADEMY




Each depends on
two inputs:

1. Same layer, previous timestep
2. Prev layer, same timestep

Use different weights at each layer, share weights across time


Ballas et al, "Delving Deeper into Convolutional Networks for Learning Video Representations", ICLR 2016

Normal 2D CNN:




Input features:
 $C \times H \times W$

2D Conv



Output features:
 $C \times H \times W$



Recall: Vanilla RNN


$$h_{t+1} = \tanh(W_h h_t + W_x x)$$

Replace all matrix multiply
with 2D convolution!


Modeling long-term temporal structure

RNN: Infinite
temporal extent
(fully-connected)

CNN: finite
temporal extent
(convolutional)




Recurrent CNN: Infinite
temporal extent
(convolutional)




Problem: RNNs are slow for long sequences (can't be parallelized)

RNN: Infinite temporal extent (fully-connected)

CNN: finite temporal extent (convolutional)



Recurrent CNN: Infinite temporal extent (convolutional)




Spatio-Temporal Self-Attention extends the Transformer architecture to video data by modeling dependencies across both spatial and temporal dimensions.

- ▶ **Transformers applied to video:** Video frames are treated as sequences, enabling the use of self-attention to capture relationships across space and time.
- ▶ **Factorized Attention (e.g., TimeSformer):** Attention is applied separately along spatial and temporal axes, reducing computational cost compared to full spatio-temporal attention.
- ▶ **Benefits:** Enables modeling of global context and long-range dependencies in videos.
- ▶ **Costs:** Self-attention has quadratic complexity with respect to sequence length, making it computationally expensive for long videos.

- ▶ **Self-Attention Mechanism:** Captures long-range dependencies in both spatial and temporal dimensions.
- ▶ **Multi-Head Attention:** Allows the model to focus on different parts of the input sequence simultaneously.

Spatio-Temporal Self-Attention (Nonlocal Block)




Spatio-Temporal Self-Attention (Nonlocal Block) (cont.)

Input clip




3D CNN



Nonlocal Block

3D CNN



Nonlocal Block

3D CNN

Running


- ▶ There has been a lot of work on architectures for images.
- ▶ Can we reuse image architectures for video?
- ▶ Idea: take a 2D CNN architecture.
- ▶ Replace each 2D $K_h \times K_w$ conv/pool layer with a 3D $K_t \times K_h \times K_w$ version.
- ▶ Can use weights of 2D conv to initialize 3D conv: copy K_t times in space and divide by K_t .
- ▶ This gives the same result as 2D conv given “constant” video input.

► Introduced by Carreira and Zisserman, CVPR 2017


► Key Ideas:

- **Inflation of 2D Filters:** Converts 2D convolutional filters into 3D by replicating them across time.
- **Temporal Modeling:** Captures motion information effectively by leveraging pre-trained 2D networks.
- **End-to-End Training:** Trained on large video datasets, allowing transfer learning to new tasks.
- **Performance Boost:** Significantly improves action recognition accuracy compared to previous methods.

Inflating 2D Networks to 3D (I3D) (cont.)



Top-1 Accuracy on Kinetics-400




set", CVPR 2017

All using Inception CNN


Vision Transformers (ViTs) adapt the Transformer architecture for video data by treating video frames as sequences of patches, enabling the capture of long-range dependencies across both spatial and temporal dimensions.

- ▶ **Patch Embedding:** Each video frame is divided into patches, which are then linearly embedded into a sequence.
- ▶ **Temporal Encoding:** Positional encodings are added to capture temporal information.
- ▶ **Self-Attention Mechanism:** Allows the model to focus on different parts of the video sequence simultaneously.
- ▶ **Benefits:** Captures global context and long-range dependencies effectively.
- ▶ **Costs:** Computationally expensive due to quadratic complexity with respect to sequence length.

Factorized attention: Attend over space / time



Pooling module: Reduce number of tokens




Bertasius et al, "Is Space-Time Attention All You Need for Video Understanding?", ICML 2021

Arnab et al, "ViViT: A Video Vision Transformer", ICCV 2021

Neimark et al, "Video Transformer Network", ICCV 2021

Fan et al, "Multiscale Vision Transformers", ICCV 2021
Li et al, "MViTv2: Improved Multiscale Vision Transformers for Classification and Detection", CVPR 2022

Top-1 Accuracy on Kinetics-400



Advanced Video Understanding

- ▶ Video understanding models are designed to capture both spatial and temporal information in videos.
- ▶ They often combine convolutional neural networks (CNNs) for spatial feature extraction with recurrent neural networks (RNNs) or attention mechanisms for temporal dynamics.
- ▶ These models can be used for tasks such as action recognition, video captioning, and video retrieval.



Problem Statement:

Given a long untrimmed video, the goal is to detect all people in both space and time, and classify the activities they are performing.


- ▶ **Input:** Untrimmed video sequence.
- ▶ **Output:** For each person, a spatio-temporal tube (bounding boxes across frames) and an activity label.

Example: AVA Dataset



The AVA (Atomic Visual Actions) dataset provides annotated videos with bounding boxes and action labels for each person in every frame.



clink glass → drink



open → close



grab (a person) → hug



look at phone → answer phone

- **Annotations:** Spatial (bounding boxes) and temporal (frame-level) localization of actions.

Spatio-temporal detection involves identifying and localizing objects or events in both space and time within video sequences. This is crucial for tasks such as action recognition, event detection, and video surveillance.

- ▶ **Spatio-Temporal Features:** These features capture both the spatial layout of objects and their temporal dynamics.
- ▶ **3D Convolutional Networks (3D CNNs):** Extend traditional CNNs by adding a temporal dimension, allowing them to learn spatio-temporal patterns directly from video data.
- ▶ **Challenges:** High computational cost, data sparsity, and the need for large annotated datasets.
- ▶ **Applications:** Surveillance, human-computer interaction, sports analytics.

Ego4D is a large-scale dataset designed to advance the understanding of egocentric (first-person) video. It consists of over 3,670 hours of egocentric video footage captured using head-mounted cameras.

- ▶ **Long Videos:** Each video ranges from *1 to 10 hours* in length.
- ▶ **Diversity:** Data collected by *14 teams* across *9 countries*, *74 locations*, involving *931 unique camera wearers*.
- ▶ **Natural-Language Narrations:** Contains *3.85 million* sentences of narrations.
- ▶ **Rich Annotations:** Supports *5 different tasks*:
 - Episodic Memory
 - Hands and Objects
 - Audio-Video Diarization
 - Social Interactions
 - Forecasting


Key Features of Ego4D:

- ▶ **First-Person Perspective:** Captures videos from the viewpoint of the person wearing the camera, providing a unique perspective on human activities.
- ▶ **Large Scale:** 3,670 hours of video data, making it one of the largest datasets for egocentric video understanding.
- ▶ **Diverse Activities and Participants:** Wide range of activities and a large, varied set of camera wearers, reflecting real-world scenarios.
- ▶ **Comprehensive Annotations:** Natural-language narrations and support for multiple tasks enable comprehensive model training and evaluation.

Ego4D: New Large-Scale Video Dataset (cont.)




- ▶ **Temporal Order:** Learning to predict or verify the correct temporal sequence of video frames as a self-supervised task.
- ▶ **Cycle Consistency:** Enforcing that transformations applied to video frames or clips can be reversed, ensuring consistency in learned representations.
- ▶ **Video Speedup:** Training models to recognize or reconstruct videos at different playback speeds, encouraging temporal understanding.
- ▶ **Video Colorization:** Using the task of colorizing grayscale video frames as a self-supervised signal for learning spatiotemporal features.



Training data: Shuffled video frames, original video frames


Pretext task: Predict if the frames are in the correct temporal order (binary classification task).




Objective: Learn temporal dependencies and motion patterns in videos.

- ▶ Given a sequence of video frames, randomly shuffle the order of frames.
- ▶ The model receives either the original or shuffled sequence.
- ▶ The objective is to classify whether the input sequence is temporally correct or not.
- ▶ This encourages the model to learn temporal dependencies and motion patterns in videos.

Frame Reordering (cont.)




Generating positive and negative examples



Triplet Siamese network for sequence verification

Transfer Learning: Fine-tune spatial stream for video classification.



Dataset	Initialization	Mean Accuracy
UCF101	Random	38.6
	(Ours) Tuple verification	50.2
HMDB51	Random	13.3
	UCF Supervised	15.2
	(Ours) Tuple verification	18.1

[Misra et. al., Shuffle and Learn: Unsupervised Learning using Temporal Order Verification, ECCV 2016]

Benefits:

- ▶ No need for labeled data, as the task is self-supervised.
- ▶ Helps the model learn temporal dynamics and motion patterns in videos.
- ▶ Can be used as a pre-training step before fine-tuning on specific video tasks.


Training data: Video frames, corresponding optical flow maps

Pretext task: Predict the optical flow between pairs of video frames.

Learning Correspondence:

- ▶ Match patches across frames
- ▶ Applications: tracking, correspondence learning

Ultimate Goal: Correspondence




[Wang and Efros, Learning Correspondence from the Cycle-consistency of Time, CVPR 2019]


Temporal Cycle Consistency is a self-supervised learning approach that leverages the temporal structure of videos to learn representations by ensuring that transformations applied to video frames can be reversed.

- ▶ **Cycle Consistency:** The model learns to predict the optical flow between pairs of video frames, ensuring that the transformation can be reversed.
- ▶ **Applications:** Useful for tasks like tracking and correspondence learning.
- ▶ **Goal:** To learn robust representations that capture the temporal dynamics of video data.

Temporal cycle consistency (cont.)



Dwibed et. al. Temporal Cycle-Consistency Learning, CVPR'19



Jabri et. al, Space time correspondence as Contrastive Random Walk, NeurIPS 2020


Learning Speediness is a self-supervised learning approach that focuses on understanding the temporal dynamics of videos by learning to recognize or reconstruct videos at different playback speeds.

- ▶ **Speed Variation:** The model learns to predict or reconstruct video frames at various speeds, enhancing its understanding of temporal relationships.
- ▶ **Applications:** Useful for tasks like action recognition, video summarization, and temporal segmentation.
- ▶ **Goal:** To learn robust representations that capture the dynamics of video data across different temporal scales.


Learning the Speediness in Videos (cont.)

Ultimate Goal: Watch video content faster by adaptively speeding up the video

Uniform Speed Up (2x)



Adaptive Speed Up (2x)



[Joint work with: Sagie Benaim, Ariel Ephrat, Oran Lang, Inbar Mosseri, Bill Freeman, Miki Rubinstein and Michal Irani, CVPR 2020]

Video Learning & Generation: **Summary**

- ▶ Video understanding evolves from single-frame analysis to capturing global context using convolution, recurrence, and attention mechanisms.
- ▶ Temporal modeling is essential for tasks like action recognition and future prediction.

Video Learning & Generation: **References**

- [1] D. Tran, L. Bourdev, R. Fergus, L. Torresani, and M. Paluri,
“Learning Spatiotemporal Features with 3D ConvNets,”
in *ICCV*, 2015.
arxiv.org/abs/1412.0767

- [2] J. Carreira and A. Zisserman,
“Quo Vadis, Action Recognition? A New Model and the Kinetics Dataset,”
in *CVPR*, 2017.
arxiv.org/abs/1705.07750

- [3] X. Wang, R. Girshick, A. Gupta, and K. He,
“SlowFast Networks for Video Recognition,”
in *ICCV*, 2019.
arxiv.org/abs/1812.03982

- [4] G. Bertasius, H. Wang, and L. Torresani,
“Is Space-Time Attention All You Need for Video Understanding?”
in *NeurIPS*, 2021.
arxiv.org/abs/2102.05095

- [5] H. Sun et al.,
“Ego4D: Around the World in 3,000 Hours of Egocentric Video,”
in *CVPR*, 2022.
ego4d-data.org

- [6] A. Radford et al.,
“Learning Transferable Visual Models From Natural Language Supervision,”
in *ICML*, 2021.
arxiv.org/abs/2103.00020

- [7] P. Esser, R. Rombach, and B. Ommer,
“Taming Transformers for High-Resolution Image Synthesis,”
in *CVPR*, 2021.
arxiv.org/abs/2012.09841

- [8] J. Ho, W. Chan, C. Saharia, et al.,
“Video Diffusion Models,”
in *NeurIPS*, 2022.
arxiv.org/abs/2204.03458

- [9] L. Yang et al.,
“VideoCrafter: Open Diffusion Models for High-Quality Video Generation,”
2023.
arxiv.org/abs/2309.08485

- [10] S. Khandelwal, A. Jain, S. Choudhury, et al.,
“TrajDiffuser: Diffusion for Trajectory Prediction,”
in *NeurIPS*, 2023.
arxiv.org/abs/2306.08694
- [11] F.-F. Li, Y. Li, and R. Gao,
“Stanford CS231n: Deep Learning for Computer Vision,”
cs231n.stanford.edu
- [12] A. Shocher, S. Bagon, M. Galun, and T. Dekel,
“WAIC DL4CV: Deep Learning for Computer Vision: Fundamentals and Applications,”
[WAIC-DL4CV](#)
- [13] J. Johnson,
“UMich EECS 498.008/598.008: Deep Learning for Computer Vision,”
[UMich DL4CV](#)