

**INTERNATIONAL INSTITUTE
OF
PROFESSIONAL STUDIES
DAVV, INDORE**

**SESSION :
2024-2025**

C++ ASSIGNMENT

SUBMITTED BY:	SUBMITTED TO:
KAUSTUBH PATEL	JASNEET KAUR
	MA'AM

ROLL NO. : IT-2K24-102

Q1. WAP to find a given number is even or odd.

```
#include<iostream>
using namespace std;
int main()
{
    cout<<"Enter a number to be checked";
    int n;
    cin>>n;
    if(n%2==0)
        cout<<n<<" is even.";
    else
        cout<<n<<" is odd.";
    return 0;
}
```

Q2. Write a program to find given number is prime or composite.

```
#include<iostream>
using namespace std;
int main()
{
    cout<<"Enter a number";
    int n,flag=0;
    cin>>n;
    for(int i=2;i<n/2;i++)
    {
        if(n%i==0)
        {
            flag=0;
        }
        else{
            flag=1;
        }
    }
    if (flag==0)
```

```
{  
    cout<<n<<" is prime";  
}  
else  
{  
    cout<<n<<" is composite";  
}  
return 0;  
}
```

Q3. Write a program to print table of a given number upto 'N' multiple.

```
#include <iostream>

using namespace std;

int main(){

    int num, n;

    cout<<"Enter a number: ";

    cin>>num;

    cout<<"Enter number of multiples: ";

    cin>>n;

    cout<<"Table of " <<num <<" up to " <<n <<"
multiples:" <<endl;

    for (int i = 1; i <= n; i++)
    {
        cout <<num <<" x " <<i <<" = " <<num * i <<endl;
    }

    return 0;

}
```

Q4. WAP to find:

i) Greater of two numbers

```
#include <iostream>

using namespace std;

int main()
{
    int num1, num2;
    cout<<"Enter first number: ";
    cin>>num1;
    cout<<"Enter second number: ";
    cin>>num2;
    if (num1 > num2)
    {
        cout<<num1 <<" is greater.";
    }
    else if (num2 > num1)
    {
```

```
        cout<<num2 <<" is greater.";
    } else
    {
        cout<<"Both numbers are equal.";
    }
    return 0;}
```

ii) greater of three numbers

```
int main() {
    int a, b, c;
    cout << "Enter first number (a): ";
    cin >> a;
    cout << "Enter second number (b): ";
    cin >> b;
    cout << "Enter third number (c): ";
    cin >> c;
    if (a > b && a > c) {
        cout << a << " is greater.";
```

```
} else if (b > a && b > c) {  
    cout << b << " is greater.";  
} else if (c > a && c > b) {  
    cout << c << " is greater.";  
} else {  
    cout << "At least two numbers are equal.";  
}  
return 0;  
}
```


Q5. WAP to find sum of first n natural numbers.

```
#include <iostream>
using namespace std;
int main()
{
    int n, sum = 0;
    cout << "Enter the value of n:";
    cin >> n;
    for (int i = 1; i <= n; i++)
    {
        sum += i;
    }
    cout << "The sum of the first " << n << " natural
numbers is: " << sum;
    return 0;
}
```

Q6. WAP to find factorial of a given number.

```
#include<iostream>

using namespace std;

int main(){

    int n,fact=1;

    cout<<"Enter a number: ";

    cin>>n;

    if(n==0 || n==1)

    {

        cout<<"Factorial of "<<n <<" is: 1";

    }

    else if(n<0)

        cout<<"Factorial cannot be calculated for negative numbers";

    else

    {

        for(int i=n;i>=2;i--)
```

```
{  
    fact=fact*i;  
}  
  
cout<<"Factorial of "<<n <<" is: "<<fact;  
}  
  
return 0;  
}
```

Q7. Write a program to find sum of digit of n digit natural number.

```
#include<iostream>

using namespace std;

int main()
{
    int num, sum = 0;
    cout << "Enter a number: ";
    cin >> num;
    while (num != 0)
    {
        sum += num % 10;
        num /= 10;
    }
    cout << "Sum of digits is: " << sum;
    return 0;
}
```

Q8. WAP to find reverse of a number.

```
#include <iostream>

using namespace std;

int main()
{
    int num, reverse = 0;
    cout << "Enter a number: ";
    cin >> num;
    while (num != 0)
    {
        reverse = reverse * 10 + num % 10;
        num /= 10;
    }
    cout << "Reverse of the number is: " << reverse;
    return 0;
}
```

Q9. WAP to determine given number is palindrome or not.

```
#include <iostream>

using namespace std;

int main()
{
    int num, reverse = 0, original;
    cout << "Enter a number: ";
    cin >> num;
    original = num;
    while (num != 0)
    {
        reverse = reverse * 10 + num % 10;
        num /= 10;
    }
    if (original == reverse)
    {
```

```
    cout << original << " is a palindrome.";
} else
{
    cout << original << " is not a palindrome.";
}
return 0;
}
```

Q10. WAP to print fibonacci series upto n terms.

```
#include <iostream>

using namespace std;

int main()
{
    int n, t1 = 0, t2 = 1;

    cout << "Enter the number of terms: ";
    cin >> n;

    cout << "Fibonacci Series: " << t1 << " " << t2 << " ";
    for (int i = 3; i <= n; i++)
    {
        int nextTerm = t1 + t2;
        t1 = t2;
        t2 = nextTerm;
        cout << nextTerm << " ";
    }

    return 0;}
```


Q11. Write a program to determine given n digit number is armstrong or not.

```
#include <iostream>
```

```
Using namespace std;
```

```
int main()
```

```
{
```

```
    int num, originalNum, remainder, result = 0;
```

```
    cout << "Enter a three-digit integer: ";
```

```
    cin >> num;
```

```
    originalNum = num;
```

```
    while (originalNum != 0)
```

```
{
```

```
        remainder = originalNum % 10;
```

```
        result += remainder * remainder * remainder;
```

```
        originalNum /= 10;
```

```
}
```

```
    if (result == num)
```

```
cout << num << " is an Armstrong number.";
```

```
else
```

```
cout << num << " is not an Armstrong number.";
```

```
return 0;
```

```
}
```

Q12. WAP to print all even numbers between 100 and 200.

```
#include <iostream>

using namespace std;

int main()
{
    cout << "Even numbers between 100 and 200: "
    for (int i = 100; i <= 200; i++)
    {
        if (i % 2 == 0)
        {
            cout << i << endl;
        }
    }
    return 0;
}
```

Q13. Write a program to print first 50 prime numbers

```
#include<iostream>

using namespace std;

int main()
{
    cout<<"First 50 prime number are:";
    int n=2,flag=0,count=1;
    while(count<=50)
    {
        for(int i=2;i<n/2;i++)
        {
            if(n%i==0)
            {
                flag=0;
            }
            else{
                flag=1;
            }
        }
    }
```

```
    }  
  
    }  
    if (flag==0)  
    {  
        cout<<n<<endl;  
        n++;  
  
    }  
    ++count;  
    }  
  
return 0;  
}
```

Q14. WAP to print all 4 digit Armstrong numbers.

```
#include <iostream>

using namespace std;

int main()
{
    cout << "Four-digit Armstrong numbers: " << endl;
    for (int i = 1000; i <= 9999; i++)
    {
        int temp = i;
        int sum = 0;
        while (temp != 0)
        {
            int digit = temp % 10;
            sum += digit * digit * digit * digit;
            temp /= 10;
        }
        if (sum == i)
```

```
{  
    cout << i << endl;  
}  
}  
return 0;  
}
```

Q15. WAP to print following patterns.

i) *

 **

```
#include <iostream>
using namespace std;
int main()
{
    for (int i = 1; i <= 5; i++)
    {
        for (int j = 1; j <= i; j++)
        {
            cout << "* ";
        }
        cout << endl;
    }
}
```



```
}  
  
return 0;  
  
}
```

ii) *****

**

*

```
#include <iostream>  
using namespace std;  
int main()  
{  
    for (int i = 5; i >= 1; i--)
```

```
{  
    for (int j = 1; j <= i; j++)  
    {  
        cout << "* ";  
    }  
    cout << endl;  
}  
return 0;  
}
```

iii)

```
      *  
    *  *  *  
  *  *  *  *  *
```

```
#include <iostream>  
using namespace std;  
int main()  
{  
for (int i=1;i <=3;i++)  
{  
    for (int j=3; j>i ;j--)  
    {  
        cout << "  ";  
    }  
    for (int k=1 ; k<=2*i-1 ; k++)  
    {  
        cout << "*";  
    }  
}
```

```
    }  
    cout << "\n";  
}  
return 0;  
}
```

iv) 1

2 2

3 3 3

4 4 4 4

```
#include <iostream>  
using namespace std;  
int main()  
{  
    for (int i = 1; i <= 4; i++)  
    {
```

```
    for (int j = 1; j >= i; j++)  
    {  
        cout << i;  
    }  
    cout << endl;  
}  
return 0;  
}
```

v) Pascals Triangle

```
#include<iostream>  
  
Using namespace std;  
  
int main() {  
    int rows,p;  
    int num=1;
```

```
cout <<" Enter the number of rows for Pascal's
Triangle: ";
cin >> rows;
for (int i = 0; i < rows; i++) {
p=num;
for (int j=0; j < rows-i-1; j++) {
cout << " ";
}
while(p!=0)
{
int r=p%10;
cout << r <<" ";
p=p/10;
}
num=num *11;
cout << endl;
}
```

```
return 0;  
}
```

vi) Flyodd's Triangle

```
#include <iostream>  
using namespace std;  
int main()  
{  
    int n;  
    cout << "Enter the number of rows: ";  
    cin >> n;  
    int num = 1;  
    for (int i = 1; i <= n; i++)  
    {  
        for (int j = 1; j <= i; j++)  
        {  
            cout << num << " ";  
            num++;  
        }  
        cout << "\n";  
    }  
}
```

```
        num++;  
    }  
    cout << endl;  
}  
return 0;  
}
```


Q16. Using functions write following c++ programs.

- i) To print all palindrome numbers from range 500 to 1000**

```
#include <iostream>
using namespace std;
void palindrome()
{
    for (int i = 500; i <= 1000; i++)
    {
        int num = i;
        int rev = 0;
        while (num != 0)
        {
            int digit = num % 10;
            rev = rev * 10 + digit;
            num /= 10;
        }
    }
}
```

```
        if (rev == i)
        {
            cout << i << endl;
        }
    }
}

int main() {
    palindrome ();
    return 0;
}
```

ii) To print first 100 odd numbers.

```
#include <iostream>
using namespace std;
void Odd()
{
    int n;
    for (n=1; n<=200;n++)
    {
        if (n%2!=0)
        {
            cout << "\n"<<n;
        }
    }
}
int main()
{
    Odd();
}
```

```
return 0;  
}
```

iii) To find binary, octal, hexadecimal equivalent of a given decimal number.

```
#include <iostream>  
using namespace std;  
void binary(int n)  
{  
    int org_num = n;  
    int factor = 1;  
    int bin = 0;  
    while (n != 0)  
    {  
        bin = bin + (n % 2) * factor;  
        n = n / 2;  
        factor = factor * 10;  
    }  
}
```

```
    cout << "The binary number for " << org_num << "
is " << bin << "\n";
```

```
}
```

```
void octal(int n)
```

```
{
```

```
    int org_num = n;
```

```
    int factor = 1;
```

```
    int oct = 0;
```

```
    while (n != 0)
```

```
    {
```

```
        oct = oct + (n % 8) * factor;
```

```
        n = n / 8;
```

```
        factor = factor * 10;
```

```
    }
```

```
    cout << "The octal number for " << org_num << " is
" << oct << "\n";
```

```
}
```

```
void hexadecimal(int n)
```

```
{  
    int org_num = n;  
    int factor = 1;  
    int hexa = 0;  
    while (n != 0)  
    {  
        hexa = hexa + (n % 16) * factor;  
        n = n / 16;  
        factor = factor * 10;  
    }  
    cout << "The hexadecimal number for " <<  
org_num << " is " << hexa << "\n";  
}  
int main()  
{  
    int num;  
    cout << "Enter a number:";
```

```
    cin >> num;

    binary(num);

    octal(num);

    hexadecimal(num);

    return 0;
}
```

iv) To find decimal equivalents for given binary, hexadecimal and octal numbers.

```
#include <iostream>

#include <cmath>

using namespace std;

void bin(int n)
{
    int org_num = n;
    int deci = 0;
    int power = 0;
    while (n != 0)
```

```
{  
    deci = deci + (n % 10) * pow(2, power);  
    n = n / 10;  
    power++;  
}  
  
cout << "The decimal number for binary " <<  
org_num << " is " << deci << "\n";  
}  
  
void oct(int n)  
{  
    int org_num = n;  
    int deci = 0;  
    int power = 0;  
    while (n != 0)  
    {  
        deci = deci + (n % 10) * pow(8, power);  
        n = n / 10;
```



```
        power++;
    }

    cout << "The decimal number for octal " <<
    org_num << " is " << deci << "\n";
}

void hex(int n)
{
    int org_num = n;
    int deci = 0;
    int power = 0;
    while (n != 0)
    {
        deci = deci + (n % 10) * pow(16, power);
        n = n / 10;
        power++;
    }

    cout << "The decimal number for hexadecimal " <<
    org_num << " is " << deci << "\n";
```

```
}  
  
int main()  
{  
    int num, choice = 0;  
    cout << "Enter 1 if number is binary, 2 if it is octal  
and 3 if it is hexadecimal:";  
    cin >> choice;  
    cout << "Enter a number:";  
    cin >> num;  
    if (choice == 1)  
    {  
        bin(num);  
    }  
    else if (choice == 2)  
    {  
        oct(num);  
    }  
}
```

```
else if (choice == 3)
{
    hex(num);
}
else
{
    cout << "Invalid choice.";
}
return 0;
}
```

v) To calculate geometric sum upto n terms.

```
#include <iostream>

using namespace std;

double geometricSum(double a, double r, int n) {

    double sum = 0;
    double term = a;
    for (int i = 0; i < n; i++) {
        sum += term;
        term *= r;
    }
    return sum;
}

int main() {
    double a, r;
    int n;

    cout << "Enter the first term (a): ";
    cin >> a;
```

```
cout << "Enter the common ratio (r): ";  
cin >> r;  
cout << "Enter the number of terms (n): ";  
cin >> n;  
double sum = geometricSum(a, r, n);  
cout << "Geometric sum up to " << n << " terms: " <<  
sum << endl;  
return 0;  
}
```

Q17. Using recursion write following c++ programs.

i) Print binary number for a decimal number

```
#include <iostream>

using namespace std;

void toBin(int n)
{
    if (n > 1)
    {
        toBin(n / 2);
    }
    cout << n % 2;
}

int main()
{
    int num;

    cout << "Enter the number:";

    cin >> num;
```

```
if (num == 0)
{
    cout << 0;
}
else
    toBin(num);
return 0;
}
```

ii) Print octal number for a decimal number.

```
#include <iostream>
using namespace std;
void toOct(int n)
{
    if (n > 1)
```

```
{
    toOct(n / 8);
}
cout << n % 8;
}
int main()
{
    int num;
    cout << "Enter the number:";
    cin >> num;
    if (num == 0)
    {
        cout << 0;
    }
    else
        toOct(num);
    return 0; }
```


iii) Print factorials for a given range.

```
#include <iostream>

using namespace std;

int factorial(int n)
{
    if (n == 0 || n == 1)
    {
        return 1;
    }
    else {
        return n * factorial(n - 1);
    }
}

int main() {
    int upper_limit, lower_limit;

    cout << "For range of factorials, enter lower limit:";
    cin >> lower_limit;
```

```
cout << "Enter upper limit:";
cin >> upper_limit;
for (int i = lower_limit; i <= upper_limit; i++) {
    int fact;
    fact = factorial(i);
    cout << "The factorial of " << i << " is " << fact <<
"\n";
}
return 0;
}
```

iv) Print first n terms of fibonacci series.

```
#include <iostream>
using namespace std;
int fibonacci(int n)
{
    if (n == 0)
    {
```

```
        return 0;
    }
    else if (n == 1) {
        return 1;
    }
    else {
        return fibonacci(n - 1) + fibonacci(n - 2);
    }
}

int main() {
    int n;

    cout << "Enter the number of terms for fibonacci
series:";

    cin >> n;

    cout << "Fibonacci series:\n";

    for (int i = 0; i < n; i++) {
        cout << fibonacci(i) << " ";
    }
}
```

```
}
```

```
return 0;
```

```
}
```

KAUSTUBH PATEL 102

Q18. WAP to find average of all the elements of 1D array.

```
#include <iostream>

using namespace std;

int main()
{
    int n;

    cout << "Enter the number of elements: ";

    cin >> n;

    int arr[n];

    cout << "Enter the elements: ";

    for (int i = 0; i < n; i++)
    {
        cin >> arr[i];
    }

    int sum = 0;

    for (int i = 0; i < n; i++)
```

```
{  
    sum += arr[i];  
}  
double average = (double)sum / n;  
cout << "Average: " << average << endl;  
return 0;  
}
```

Q19. WAP to find maximum and minimum value of a 1D numeric array.

```
#include <iostream>

using namespace std;

int main() {

    int n;

    cout << "Enter the number of elements: ";

    cin >> n;

    int arr[n];

    cout << "Enter the elements: ";

    for (int i = 0; i < n; i++) {

        cin >> arr[i];

    }

    int maxVal = arr[0];

    int minVal = arr[0];

    for (int i = 1; i < n; i++) {

        if (arr[i] > maxVal) {
```

```
        maxVal = arr[i];
    }
    if (arr[i] < minVal) {
        minVal = arr[i];
    }
}
cout << "Maximum value: " << maxVal << endl;
cout << "Minimum value: " << minVal << endl;
return 0;
}
```


Q20. Write a program to find transpose of a 2D matrix.

```
#include <iostream>

using namespace std;

int main()
{
    int rows, cols;

    cout << "Enter number of rows: ";
    cin >> rows;

    cout << "Enter number of columns: ";
    cin >> cols;

    int matrix[rows][cols];

    cout << "Enter matrix elements: " << endl;
    for (int i = 0; i < rows; i++)
    {
        for (int j = 0; j < cols; j++)
        {
```

```
        cin >> matrix[i][j];
    }
}

cout << "Original Matrix: " << endl;
for (int i = 0; i < rows; i++)
{
    for (int j = 0; j < cols; j++)
    {
        cout << matrix[i][j] << " ";
    }
    cout << endl;
}

cout << "Transpose Matrix: " << endl;
for (int i = 0; i < cols; i++)
{
    for (int j = 0; j < rows; j++)
    {
```

```
        cout << matrix[j][i] << " ";  
    }  
    cout << endl;  
}  
return 0;  
}
```

Q21. WAP to add two matrices.

```
#include <iostream>

using namespace std;

int main() {

    int rows, cols;

    cout << "Enter number of rows: ";

    cin >> rows;

    cout << "Enter number of columns: ";

    cin >> cols;

    int matrix1[rows][cols];

    int matrix2[rows][cols];

    cout << "Enter elements of Matrix 1: " << endl;

    for (int i = 0; i < rows; i++) {

        for (int j = 0; j < cols; j++) {

            cin >> matrix1[i][j];

        }

    }

}
```

```
cout << "Enter elements of Matrix 2: " << endl;
for (int i = 0; i < rows; i++) {
    for (int j = 0; j < cols; j++) {
        cin >> matrix2[i][j];
    }
}

cout << "Matrix 1: " << endl;
for (int i = 0; i < rows; i++) {
    for (int j = 0; j < cols; j++) {
        cout << matrix1[i][j] << " ";
    }
    cout << endl;
}

cout << "Matrix 2: " << endl;
for (int i = 0; i < rows; i++) {
    for (int j = 0; j < cols; j++) {
        cout << matrix2[i][j] << " ";
```

```
    }  
  
    cout << endl;  
  
}  
  
cout << "Sum of Matrix 1 and Matrix 2: " << endl;  
for (int i = 0; i < rows; i++) {  
    for (int j = 0; j < cols; j++) {  
        cout << matrix1[i][j] + matrix2[i][j] << " ";  
    }  
    cout << endl;  
}  
  
return 0;  
}
```

Q22. WAP to multiply 2D matrices.

```
#include <iostream>
using namespace std;
int main() {
    int rows1, cols1, rows2, cols2;
    cout << "Enter number of rows for Matrix 1: ";
    cin >> rows1;
    cout << "Enter number of columns for Matrix 1: ";
    cin >> cols1;
    cout << "Enter number of rows for Matrix 2: ";
    cin >> rows2;
    cout << "Enter number of columns for Matrix 2: ";
    cin >> cols2;
    if (cols1 != rows2) {
        cout << "Matrix multiplication is not possible."
<< endl;
        return 0;
    }
}
```

```
}  
  
int matrix1[rows1][cols1];  
int matrix2[rows2][cols2];  
int result[rows1][cols2];  
  
cout << "Enter elements of Matrix 1: " << endl;  
for (int i = 0; i < rows1; i++) {  
    for (int j = 0; j < cols1; j++) {  
        cin >> matrix1[i][j];  
    }  
}  
  
cout << "Enter elements of Matrix 2: " << endl;  
for (int i = 0; i < rows2; i++) {  
    for (int j = 0; j < cols2; j++) {  
        cin >> matrix2[i][j];  
    }  
}  
  
for (int i = 0; i < rows1; i++) {
```



```
    for (int j = 0; j < cols2; j++) {  
        result[i][j] = 0;  
        for (int k = 0; k < cols1; k++) {  
            result[i][j] += matrix1[i][k] * matrix2[k][j];  
        }  
    }  
}  
  
cout << "Matrix 1: " << endl;  
for (int i = 0; i < rows1; i++) {  
    for (int j = 0; j < cols1; j++) {  
        cout << matrix1[i][j] << " ";  
    }  
    cout << endl;  
}  
  
cout << "Matrix 2: " << endl;  
for (int i = 0; i < rows2; i++) {  
    for (int j = 0; j < cols2; j++) {
```

```
        cout << matrix2[i][j] << " ";  
    }  
    cout << endl;  
}  
cout << "Result of Matrix Multiplication: " << endl;  
for (int i = 0; i < rows1; i++) {  
    for (int j = 0; j < cols2; j++) {  
        cout << result[i][j] << " ";  
    }  
    cout << endl;  
}  
return 0;  
}
```

Q23. WAP to sort an array in ascending order.

```
#include <iostream>

using namespace std;

int main() {

    int n;

    cout << "Enter the number of elements: ";

    cin >> n;

    int arr[n];

    cout << "Enter the elements: ";

    for (int i = 0; i < n; i++) {

        cin >> arr[i];

    }

    cout << "Original array: ";

    for (int i = 0; i < n; i++) {

        cout << arr[i] << " ";

    }

    cout << endl;
```

```
for (int i = 0; i < n; i++) {  
    for (int j = i + 1; j < n; j++) {  
        if (arr[i] > arr[j]) {  
            int temp = arr[i];  
            arr[i] = arr[j];  
            arr[j] = temp;  
        }  
    }  
}  
cout << "Sorted array: ";  
for (int i = 0; i < n; i++) {  
    cout << arr[i] << " ";  
}  
cout << endl;  
return 0;  
}
```

Q24. Write a program to reverse a given string.

```
#include <iostream>

using namespace std;

int main() {
    string str, rev;

    cout << "Enter a string : ";

    cin>> str;

    for ( int i= str.length()-1; i >=0; i --)
    {
        rev+=str[i];
    }

    cout<< "\n Revsersed string : "<<rev;

    return 0;
}
```

Q25. Write a program to count all the vowels in a given string.

```
#include <iostream>

using namespace std;

int main()
{
    string str;
    cout << "Enter a string: ";
    cin >> str;
    int vowelCount = 0;
    for (int i = 0; i < str.length(); i++)
    {
        char ch = str[i];
        if (ch == 'a' || ch == 'e' || ch == 'i' || ch == 'o' || ch ==
'u' ||
            ch == 'A' || ch == 'E' || ch == 'I' || ch == 'O' || ch
== 'U')
        {
```

```
        vowelCount++;  
    }  
}  
  
    cout << "Number of vowels: " << vowelCount <<  
endl;  
  
    return 0;  
}
```

Q26. WAP to check if a given string is palindrome or not.

```
#include<iostream>
#include<string>
using namespace std;
int main(){
string st;
cout<<"Enter a string \n";
cin>>st;
int flag=0;
int len=st.size();
for (int i=0;i<len/2;i++){
if(st[i] != st[len-1-i])
{
flag=1;
}
}
```



```
if(flag==0)
cout<<"Entered string is Palindrome.";
else
cout<<" Entered string is not Palindrome.";
return 0;
}
```

Q27. WAP to check if a given string is anagram or not.

```
#include<iostream>

using namespace std;

int main(){

    int arr[26]={0};

    cout << "enter a size:";

    int size;

    cin >> size;

    cout << "s1:";

    char s1[size];

    for(int i=0;i<size;i++){

        cin >> s1[i];

    }

    char s2[size];

    cout << "s2:";

    for(int i=0;i<size;i++){

        cin >> s2[i];
```

```
}  
for(int i=0;i<size;i++){  
    int a = s1[i]-'a';  
    arr[a]=arr[a]+1;  
}  
for(int i=0;i<size;i++){  
    int a = s2[i]-'a';  
    arr[a]=arr[a]-1;;  
}  
int flag=0;  
for(int i=0;i<26;i++){  
    if(arr[i]!=0){  
        flag=1;  
        break;  
    }  
}
```

```
(flag==0)? cout << "true" : cout << "false";
```

```
return 0;
```

```
}
```

KAUSTUBH PATEL 102

Q28. Write a program to display the minimum, maximum, sum, search and average of elements of an array.

```
#include<iostream>
using namespace std;
//maximum
int maxarr(int a[],int n)
{
    int mx;
    mx=a[0];
    for(int i=0;i<n;i++)
    {
        if(a[i]>mx)
        {
            mx=a[i];
        }
    }
    return mx;
```

```
}
```

```
//minimum
```

```
int minarr(int a[],int n)
```

```
{
```

```
    int mm=a[0];
```

```
    for(int i=0;i<n;i++)
```

```
    {
```

```
        if(a[i]<mm)
```

```
        {
```

```
            mm=a[i];
```

```
        }
```

```
    }
```

```
    return mm;
```

```
}
```

```
//average
```

```
int avgarr(int sum, int n)
```

```
{  
    double avg;  
    avg=double(sum)/n;  
    cout<<"\nAverage of all elements of array: "<<avg;  
    return 0;  
}  
  
//sum of elements  
int sumarr(int a[],int n)  
{  
    int sum=0;  
    for(int i=0;i<n;i++)  
    {  
        sum=sum+a[i];  
    }  
    avgarr(sum,n);  
    return sum;  
}
```

//search function

void searcharr(int a[],int n)

{

int x,idf=1,count=0;

cout<<"\nEnter a search element";

cin>>x;

for(int i=0;i<n;i++)

{

if (x==a[i])

{

idf=0;

++count;

}

else{

idf=1;

}


```
}  
  
if(idf==0)  
  
    cout<<"\nEntered element is an array element and  
frequency is: "<<count;  
  
else  
  
    cout<<"\nEntered element is not array element."  
  
}  
  
int main(){  
  
    cout<<"Enter size of array\n";  
  
    int i,n;  
  
    cin>>n;  
  
    int arr[n];  
  
    cout<<"\nEnter elements of array: ";  
    for(i=0;i<n;i++)  
    {  
  
        cin>>arr[i];
```

```
}  
  
int max, min, sum;  
  
max=maxarr(arr,n);  
min=minarr(arr,n);  
sum=sumarr(arr,n);  
searcharr(arr,n);  
  
cout<<endl<<"Maximum elements of array is:  
"<<max;  
  
cout<<endl<<"Minimum element of array is: "<<min;  
cout<<endl<<"Sum of elements of array is: "<<sum;  
  
return 0;  
}
```

Q29. Define a class student with the following specification

Private members of class student

admno integer

sname 20 character

eng. math, science float

total float

Public member function of class student

ctotal() a function to calculate eng +
math + science with float return type.

Takedata() Function to accept values for
admno, sname, eng, science **Showdata()**
Function to display all the data members on the
screen

```
#include <iostream>
using namespace std;
class Student {
private:
```

```
int admno;

char sname[20];

float eng, math, science;

float total;

public:

    // Function to calculate total
    float ctotal() {
        total = eng + math + science;
        return total;
    }

    void takeData() {
        cout << "Enter admission number: ";
        cin >> admno;
        cout << "Enter student name: ";
        cin >> sname;
        cout << "Enter English marks: ";
```

```
    cin >> eng;

    cout << "Enter Math marks: ";

    cin >> math;

    cout << "Enter Science marks: ";

    cin >> science;

}

void showData() {

    cout << "Admission Number: " << admno << endl;

    cout << "Student Name: " << sname << endl;

    cout << "English Marks: " << eng << endl;

    cout << "Math Marks: " << math << endl;

    cout << "Science Marks: " << science << endl;

    cout << "Total Marks: " << ctotal() << endl;

}

};

int main() {

    Student student;
```

```
student.takeData();  
student.showData();  
return 0;
```

```
}
```

KAUSTUBH PATEL 102

Q30. Define a class in C++ with following description:

Private Members

A data member Flight number of type integer

A data member Destination of type string

A data member Distance of type float

A data member Fuel of type float

A member function CALFUEL() to calculate the value of Fuel as per the following criteria

Distance	Fuel
<=1000	500
more than 1000 and <=2000	1100
more than 2000	2200

Public Members

A function FEEDINFO() to allow user to enter values for Flight Number, Destination, Distance & call function CALFUEL() to calculate the quantity of Fuel.

A function SHOWINFO() to allow user to view the content of all the data members.

```
#include<iostream>  
  
using namespace std;  
  
class travel{
```

```
int flightNumber;

string destination;

int distance;

float fuel;

void calFuel(){

    if(distance<=1000) fuel=500;

    else if(distance>1000 && distance<=2000)
fuel=1100;

    else fuel=2200;

}

public :

void feedInfo(int fn,string des,int dist){

    flightNumber=fn;

    destination=des;

    distance=dist;

    calFuel();

}
```



```
void showInfo(){
    cout << "flight number:" << flightNumber << endl;
    cout << "destination:" << destination << endl;
    cout << "distance:" << distance << endl;
    cout << "fuel:" << fuel << endl;
}
};

int main(){
    travel t1;
    t1.feedInfo(265,"BANGALORE (BLR)",2200);
    t1.showInfo();
    return 0;
}
```

Q31. Write a menu driven program to perform following:

- a) Input a matrix
- b) Display matrix
- c) Add two matrix
- d) Multiply two matrix
- e) Transpose a matrix

```
#include<iostream>
using namespace std;
class matrix{
    int arr1[3][3];
    int arr2[3][3];
    public :
    void Switch(int button){
        switch (button){
            case 1 :
                inputdata();
                break;
```

case 2 :

displaydata();

break;

case 3 :

add();

break;

case 4:

multiply();

break;

case 5:

transpose();

break;

default:

printf("Default case is Matched.");

break;

}

}

```
void inputdata(){  
    cout << "array 1:";  
    for(int i=0;i<3;i++){  
        for(int j=0;j<3;j++) {  
            cin >> arr1[i][j];  
        }  
    }  
    cout << "array 2:";  
    for(int i=0;i<3;i++){  
        for(int j=0;j<3;j++){  
            cin >> arr2[i][j];  
        }  
    }  
}
```

```
void displaydata(){  
    cout << "array 1:";  
    for(int i=0;i<3;i++){
```

```
        for(int j=0;j<3;j++) {  
            cout << arr1[i][j] << " ";  
        }  
        cout << endl;  
    }  
    cout << "array 2:";  
    for(int i=0;i<3;i++){  
        for(int j=0;j<3;j++) {  
            cout << arr2[i][j] << " ";  
        }  
        cout << endl;  
    }  
}  
  
void add(){  
    cout << "sum of two matrix";  
    for(int i=0;i<3;i++){
```

```
        for(int j=0;j<3;j++){
            int r= arr1[i][j]+arr2[i][j];
            cout << r << " ";
        }
        cout << endl;
    }
}
```

```
void multiply(){
    printf("the resultant matrix\n");
    for(int i=0;i<3;i++){
        int d=0;
        for(int j=0;j<i;j++){
            d=arr2[i][j];
            arr2[i][j]=arr2[j][i];
            arr2[j][i]=d;
        }
    }
}
```

```

    }
}

int r=0;
for(int i=0;i<3;i++){
    for(int j=0;j<3;j++){
        for(int k=0;k<3;k++){
            r=arr1[i][k]*arr2[j][k]+r;
        }
        cout << r << " ";
    }
    cout << endl;
}

void transpose(){
    cout << "transpose of both matrix:";
    for(int i=0;i<3;i++){
        int d=0;

```

```
        for(int j=0;j<i;j++){
            d=arr1[i][j];
            arr1[i][j]=arr1[j][i];
            arr1[j][i]=d;
        }
    }
    for(int i=0;i<3;i++){
        int d=0;
        for(int j=0;j<i;j++){
            d=arr2[i][j];
            arr2[i][j]=arr2[j][i];
            arr2[j][i]=d;
        }
    }
    displaydata();
}
};
```



```
int main(){  
    matrix m1;  
    cout << "enter 1 for input matrix:" << endl;  
    cout << "enter 2 for output matrix:" << endl;  
    cout << "enter 3 for add two matrix:" << endl;  
    cout << "enter 4 for multiply two matrix:" << endl;  
    cout << "enter 5 for transpose of matrix:" << endl;  
    int button;  
    cout << "enter button:";  
    cin >> button;  
    m1.Switch(button);  
    cout << "enter button:";  
    cin >> button;  
    m1.Switch(button);  
    cout << "enter button:";  
    cin >> button;
```

```
m1.Switch(button);  
  
return 0;  
  
}
```

Q32. Define a class called Car with attributes such as make, model, and year. Include member functions to set and get these attributes. Create an object of the Car class and demonstrate the use of its member functions.

```
#include<iostream>  
  
using namespace std;  
  
class car{  
    string make;  
    string model;  
    int year;  
    public:  
    void setData(){  
        cout << "enter make:";
```

```
    cin >> make;
    cout << "enter model:";
    cin >> model;
    cout << "year:";
    cin >> year;
}
```

```
void getData(){
    cout << "make:" << make << endl;
    cout << "model:" << model << endl;
    cout << "year:" << year << endl;
}
```

```
};
```

```
int main(){
    car c1;
    c1.setData();
}
```

```
c1.getData();
```

```
return 0;
```

```
}
```

KAUSTUBH PATEL 102

Q33. Define a class called Address with attributes such as street, city, and zipCode. Create a class called Person that has an Address object as a member variable. Demonstrate composition by creating a Person object and accessing its Address attributes.

```
#include <iostream>
#include <string>
using namespace std;
class Address {
public:
    string street;
    string city;
    string zipCode;
    Address();
    Address(string s, string c, string z)
    {
        street = s;
```

```
        city = c;
        zipCode = z;
    }
};

class Person {
    private: string name;
    Address address;
public:

    Person(string n, string s, string c, string z) {
        name = n;
        address = Address(s, c, z); // Initialize Address
object
    }

    // Function to display Person details
    void displayDetails() {
```

```
    cout << "Name: " << name << endl;

    cout << "Address: " << address.street << ", " <<
address.city << " " << address.zipCode << endl;

}

};

int main() {

    Person person("John Doe", "123 Main St",
"Anytown", "12345");

    person.displayDetails();

    return 0;

}
```