

To get your white-label platform for **top5pct.com** running on the TALL stack with Lunar, you need to establish the "Tenant Context" first.

Below is the complete draft of the core files required to handle the multi-tenancy logic, the database structure, and the Lunar/Filament management integration.

1. The Database Migration

This table stores the "personality" of each virtual storefront.

PHP

```
// database/migrations/xxxx_xx_xx_create_stores_table.php
Schema::create('stores', function (Blueprint $table) {
    $table->id();
    $table->string('name');
    $table->string('subdomain')->unique(); // e.g., 'lincoln-high'
    $table->foreignId('lunar_channel_id'); // Link to Lunar Channel

    // Design & Branding
    $table->string('logo_path')->nullable();
    $table->string('font_family')->default('Inter');
    $table->string('nav_layout')->default('left');
    $table->json('colors'); // Stores primary, secondary, accent hex codes

    // Content & Features
    $table->json('events')->nullable(); // Repeater data
    $table->json('roster')->nullable(); // Repeater data
    $table->boolean('has_banner')->default(false);
    $table->string('banner_text')->nullable();

    $table->timestamps();
});
```

2. The Multi-Tenancy Middleware

This is the "Brain" that detects which store is being accessed based on the subdomain.

PHP

```

// app/Http/Middleware/IdentifyStore.php
namespace App\Http\Middleware;

use App\Models\Store;
use Closure;
use Illuminate\Support\Facades\View;
use Lunar\Facades\Channels;

class IdentifyStore
{
    public function handle($request, Closure $next)
    {
        $host = $request->getHost(); // e.g., lincoln-high.top5pct.com
        $subdomain = explode('.', $host)[0];

        // Fallback for main domain
        if ($subdomain === 'www' || $subdomain === 'top5pct') {
            return $next($request);
        }

        $store = Store::where('subdomain', $subdomain)->firstOrFail();

        // 1. Set Global Helper
        app()->instance('current_store', $store);

        // 2. Tell Lunar to scope products/prices to this channel
        Channels::setCurrent($store->channel->handle);

        // 3. Share with all Blade views
        View::share('currentStore', $store);

        return $next($request);
    }
}

```

3. The Global Blade Layout (Dynamic CSS)

This file uses the data from the Middleware to theme the site on the fly.

HTML

```

{{-- resources/views/layouts/store.blade.php --}}
<!DOCTYPE html>
<html lang="en">
<head>
    <title>{{ $currentStore->name }} | Powered by Top5Pct</title>
    <style>
        :root {
            --brand-primary: {{ $currentStore->colors['primary'] ?? '#000000' }};
            --brand-secondary: {{ $currentStore->colors['secondary'] ?? '#ffffff' }};
            --brand-accent: {{ $currentStore->colors['accent'] ?? '#ff0000' }};
        }
        body { font-family: '{{ $currentStore->font_family }}', sans-serif; }
        .bg-brand-primary { background-color: var(--brand-primary); }
        .text-brand-primary { color: var(--brand-primary); }
    </style>
    @vite(['resources/css/app.css', 'resources/js/app.js'])
</head>
<body>
    <x-store-nav />

    @if($currentStore->has_banner)
        <div class="bg-brand-accent text-white text-center py-2">
            {{ $currentStore->banner_text }}
        </div>
    @endif

    <main>
        {{ $slot }}
    </main>

    <x-store-footer />
</body>
</html>

```

4. Specialized Blade Components

The Navigation Bar (Logic-based Layout):

HTML

```

{{-- resources/views/components/store-nav.blade.php --}}
@php
    $layoutClasses = match($currentStore->nav_layout) {
        'center' => 'flex-col justify-center items-center',
        'right' => 'flex-row-reverse justify-between',
        default => 'flex-row justify-between',
    };
@endphp

<nav class="flex {{ $layoutClasses }} p-4 border-b">
    <div class="logo">
        
    </div>
    <div class="flex gap-6 items-center">
        <a href="/catalog">Catalog</a>
        <a href="/events">Events</a>
        <livewire:lunar.components.cart-icon />
    </div>
</nav>

```

The Event Countdown (Alpine.js):

HTML

```

{{-- resources/views/components/event-countdown.blade.php --}}
<div x-data="timer('{{ $eventDate }}')" class="grid grid-cols-3 gap-2 text-center">
    <div>
        <span class="block text-2xl font-bold" x-text="days"></span>
        <span class="text-xs uppercase">Days</span>
    </div>
    <div>
        <span class="block text-2xl font-bold" x-text="hours"></span>
        <span class="text-xs uppercase">Hrs</span>
    </div>
    <div>
        <span class="block text-2xl font-bold" x-text="minutes"></span>
        <span class="text-xs uppercase">Min</span>
    </div>
</div>

```

5. Managing it in Lunar (Filament Resource)

You will add this to your StoreResource.php inside the form() method.

PHP

```
// Partial for StoreResource.php
return $form->schema([
    Forms\Components\Section::make('Store Content')->schema([
        Forms\Components\Repeater::make('events')
            ->schema([
                Forms\Components\TextInput::make('name')->required(),
                Forms\Components\DateTimePicker::make('date')->required(),
            ]->createItemButtonLabel('Add Event'),

        Forms\Components\Repeater::make('roster')
            ->schema([
                Forms\Components\FileUpload::make('image')->image(),
                Forms\Components\TextInput::make('student_name'),
                Forms\Components\TextInput::make('grade'),
            ]->grid(2)
        ])
    ])
]);
```

Final Architecture Checklist:

1. **Lunar Channels:** Every time you create a new Store in your dashboard, you must also create a corresponding **Channel** in Lunar. This allows you to assign specific products to specific stores.

2. **Wildcard Routing:** In routes/web.php, wrap your storefront routes in a domain group:

PHP

```
Route::domain('{subdomain}.top5pct.com')->middleware(['identify.store'])->group(function () {
    Route::get('/', [StorefrontController::class, 'index']);
    Route::get('/product/{slug}', [ProductController::class, 'show']);
});
```

3. **SSL:** If you use Laravel Forge, ensure you select the **"Allow Wildcard Subdomains"** checkbox when creating the site. This ensures any-school.top5pct.com is instantly secured via HTTPS.