Status	Finished
Started	Wednesday, 21 October 2026, 1:37 PM
Completed	Wednesday, 21 October 2026, 1:41 PM
Duration	4 mins 10 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What is the purpose of the with statement in Python file handling?

- a. To automatically close the file after its suite finishes ✓
- b. To delete a file
- c. To write data to a file
- d. To read data from a file

The correct answer is: To automatically close the file after its suite finishes

Question **2**

Correct

Mark 1.00 out of 1.00

file_object.seek(offset [, reference_point])

What is the default, the value of reference_point?

- a. null
- b. 1
- c. garbage
- d. 2
- e. 0 ✓

The correct answer is:
0

Question **3**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
f = open("test.txt", "w")
f.write("Hello, world!")
f.close()
f = open("test.txt", "r")
print(f.read())
f.close()
```

a. An error is raised

b. world

c. Hello, world! ✓

d. Hello

The correct answer is: Hello, world!

Question **4**

Correct

Mark 1.00 out of 1.00

Which of the following methods is used to read a single line from a file?

a. readline() ✓

b. readline(size)

c. read()

d. readlines()

The correct answer is: readline()

Question **5**

Correct

Mark 1.00 out of 1.00

Which function is used to open a file in Python?

a. file()

b. open() ✓

c. open_file()

d. openfile()

The correct answer is: open()

Question **6**

Correct

Mark 1.00 out of 1.00

What does the flush() method do in file handling?

- a. Closes the file
- b. Flushes the internal buffer to the file ✓
- c. Moves the file cursor to the beginning
- d. Deletes the file content

The correct answer is: Flushes the internal buffer to the file

Question **7**

Correct

Mark 1.00 out of 1.00

What will be the output of the following code if the file "example.txt" contains "Python Programming"?

```
f = open("example.txt", "r")
print(f.read(6))
f.close()
```

- a. An error is raised
- b. Python ✓
- c. Program
- d. Python Programming

The correct answer is: Python

Question **8**

Correct

Mark 1.00 out of 1.00

What is the use of seek() method in files?

- a. sets the file's current position within the file
- b. sets the file's current position at the offset ✓
- c. sets the file's previous position at the offset
- d. none of the mentioned

The correct answer is:
sets the file's current position at the offset

Question **9**

Correct

Mark 1.00 out of 1.00

If the file is opened in write mode and already exists, it truncates the existing content and places the filehandle at the beginning of the file.

Select one:

- True ✓
- False

The correct answer is 'True'.

Question **10**

Correct

Mark 1.00 out of 1.00

What does the seek() method do in file handling?

- a. Deletes the file
- b. Writes data to the file
- c. Moves the file cursor to the specified position ✓
- d. Reads the file line by line

The correct answer is: Moves the file cursor to the specified position

Question **11**

Correct

Mark 1.00 out of 1.00

Which method is used to read file line by line

- a. read(1)
- b. readline() ✓
- c. readlines(1)
- d. line()

The correct answer is: readline()

Question **12**

Correct

Mark 1.00 out of 1.00

How do you check if a file is closed in Python?

- a. file.closed()
- b. file.closed ✓
- c. file.isclosed()
- d. file.is_closed()

The correct answer is: file.closed

Question **13**

Correct

Mark 1.00 out of 1.00

What does the mode attribute of a file object indicate?

- a. The current position of the file cursor
- b. The size of the file
- c. The name of the file
- d. The access mode in which the file was opened ✓

The correct answer is: The access mode in which the file was opened

Question **14**

Correct

Mark 1.00 out of 1.00

Which of the following modes opens a file for both reading and writing?

- a. r
- b. a
- c. r+ ✓
- d. w

The correct answer is: r+

Question **15**

Correct

Mark 1.00 out of 1.00

To open a file a.txt for reading, we use _____

a. infile = open(file, “a.txt”, “r”)

b. infile = open(“a.txt”, “r”) ✓

c. infile = open(file = “a.txt”, “r”)

d. infile = open(file = “a.txt”, “r”)

The correct answer is:
infile = open(“a.txt”, “r”)