

	A	B	C	D	E
	Reference	Description	Vendor	Part Number/ File Name	Quantity
1					
2	a1-a2	round tube aluminum, 6061-T6-drawn, ASTM-B210, 5/8" OD × 0.058" Wall × 0.509" ID, 6' long	onlinemetals.com	19596	2
3	b1-b4	round tube aluminum, 6061-T6-drawn, ASTM-B210, 1/2" OD × 0.065" Wall × 0.370" ID, 6' long	onlinemetals.com	1210	4
4	c	square tube aluminum, 6063-T52-extruded, ASTM-B221, 3/4" Height × 0.065" Wall, 6' long	onlinemetals.com	1191	1
5	d	clamp plate stainless steel 304, 0.074" thick	sendcutsend.com	clamp_plate.dxf	4
6	e	tube clamp Polycarbonate (FDM), 80% Gyroid infill, black	craftcloud.com	tube_clamp.stl	8
7	f	tube mounting plate stainless steel 304, 0.074" thick	sendcutsend.com	tube_mount.dxf	2
8	g	balun mounting plate ABS, 0.125" thick, black	sendcutsend.com	balun_mount.dxf	1
9	h	Balun 1:1 impedance ratio, 50 Ohm, 2-50 MHz 4" × 4" × 2" NEMA Type 6P PVC Box 1" terminal spacing, 1/4" terminal bolt	dxengineering.com	DXE-MC20-1-1	1
10	i	insulator bar chemical-resistant PVC, 1/4" thick, 1" wide, extruded, gray	mcmaster.com	8740K121	1
11	j	boom clamp stainless steel 304, 0.048" thick	sendcutsend.com	boom_clamp.dxf	3
12	k	tube terminal aluminum 5052-H32, 0.040" thick	sendcutsend.com	tube_terminal.dxf	2
13	l	balun terminal aluminum 5052-H32, 0.040" thick	sendcutsend.com	tube_terminal.dxf	2

	A	B	C	D	E
14	m	stiffening rod structural FRP fiberglass, 1/2" diameter, reinforcement: fiberglass fabric, resin: Polyester plastic, white, 5' long	mcmaster.com	8543K51	1
15	n	tap bolt stainless steel 18-8, #10-24, 3/4"	boltdepot.com	5623	4
16	o	machine screw Phillips pan head, stainless steel 18-8, #10-24, 2-1/4"	boltdepot.com	9655	8
17	p	machine screw Phillips pan head, stainless steel 18-8, #10-24, 1/2"	boltdepot.com	1356	2
18	q	machine screw Phillips flat head, stainless steel 18-8, #10-24, 1/2"	boltdepot.com	1258	2
19	r	machine screw Phillips pan head, stainless steel 18-8, #8-32, 3/4"	boltdepot.com	1348	4
20	s	machine screw Phillips pan head, stainless steel 18-8, #6-32, 3/4"	boltdepot.com	1338	4
21	w	tube end cap Polyethylene, 0.6" to 0.67" inside size, square, black	mcmaster.com	9565K5	2
22	x	spacer rod flame-retardant Garolite G-10/FR4, 5/16" diameter, reinforcement: fiberglass fabric, resin: epoxy, orange, 1' long	mcmaster.com	8669K569	2
23	y	hose clamp stainless-steel material 301, stainless- steel housing 301, stainless-steel screw 305, 7/16" to 25/32" range, 1/2" width, worm-drive	mcmaster.com	54155K11	4
24	-	hex nylon-insert lock nut stainless steel 18-8, #10-24	boltdepot.com	2552	14
25	-	hex nylon-insert lock nut stainless steel 18-8, #8-32	boltdepot.com	2551	4

	A	B	C	D	E
26	-	hex nylon-insert lock nut stainless steel 18-8, #6-32	boltdpot.com	2550	4
27	-	hex nut stainless steel 18-8, #10-24	boltdpot.com	2560	2
28	-	flat washer stainless steel 18-8, #10	boltdpot.com	2946	24
29	-	flat washer stainless steel 18-8, #8	boltdpot.com	2943	8
30	-	flat washer stainless steel 18-8, #6	boltdpot.com	2942	8
31	-	self-fusing electrical tape silicone rubber, 1" wide, 0.012" thick	mcmaster.com	7643A79	1
32	-	tube bender lever-style tube bender for soft metal, for tube OD: 1/2", bend radius: 1 1/2"	grainger.com	3KE42	1
33	-	hacksaw blade bi-metal blade, 24 TPI, 1/32" blade thickness, 1/2" blade width	grainger.com	24C982	1
34	-	tube cutter for aluminum and copper, 1/4" - 1 1/8" OD cutting capacity	grainger.com	6XW70	1
35	-	tubing reamer tube inner/outer reamer, copper/stainless steel, max. pipe OD: 1-1/4", min. pipe OD: 1/4"	grainger.com	3ARC7	1
36	-	drill bit guide for drill bit size 1/8", 9/64", 5/32", 11/64", 3/16", 13/64", 7/32", 15/64", 1/4", 17/64", 9/32", 19/64", 5/16", 21/64", 11/32", 23/64", 3/8"	mcmaster.com	9550T14	1