

Modelling language: documents

Angus Roberts, Senior Lecturer in Health Informatics Institute of Psychiatry, Psychology and Neuroscience King's College London




Representing language

- How can we represent meaning in language?
- Symbolic, rationalist approaches
- Empirical approaches to representing documents
 - Bag-of-words
 - TF-IDF





Symbolic, rationalist approaches



Symbolic NLP

- If we want to manipulate language computationally, we need to represent it in some way
- In rule-based, symbolic NLP, we can consider language to be represented as strings of characters
 - A string of characters has little inherent meaning
 - We match these strings with expressions (rules, grammars) that define some pattern of characters
 - These rules give meaning to our strings
 - The approach can be extended to POS and other features
- The thinking is that language can be reasoned about in some logical way, and that the structures of language could be can in to sets of rules
- Prolog, a logic programming language, is a typical approach



Prolog grammars

```
/* DOG GRAMMAR.PL */
s --> np, vp.
np --> n. np --> adj, n. np --> adj, adj, n.
np \longrightarrow det, n. np \longrightarrow det, adj, n. np \longrightarrow det, adj, adj, n.
vp --> v, np. vp --> v, pp.
pp --> p, np.
det \longrightarrow [the]. det \longrightarrow [a]. det \longrightarrow [an].
n \longrightarrow [dogs]. n \longrightarrow [fox]. n \longrightarrow [jumps].
adj \longrightarrow [quick]. adj \longrightarrow [brown]. adj \longrightarrow [lazy].
v \longrightarrow [jumps]. \quad v \longrightarrow [runs].
p --> [over].    p --> [onto].
p --> [in].    p --> [under].
```

Credit: John Coleman, http://www.phon.ox.ac.uk/coleman




Grammars

- How many rules does it take to represent "grammatical" English?
- Do we have the same problem for all languages?
- What about medical language?
- Can we write grammars that capture not the syntax, but the semantics of language? i.e. the real-world categories that words relate to, and the relationships between them?
 - e.g. diseases, medications, anatomy?



Semantic grammars



Collier et al (2015). PhenoMiner: From text to a database of phenotypes associated with OMIM diseases. Database. 2015. bav104. 10.1093/database/bav104.



Empiricism

- Empiricism is at the heart of current NLP
 - Statistical models of language
 - How often do words appear?
 - In what context do they appear?
 - How many of a particular word appear in a piece of text?
- Is it disturbing that counting words in a document outperforms reasoning about the language?



Rationalism vs Empiricism




FIGURE 1 The shift from Rationalism to Empiricism is striking (and no longer controversial). This plot is based on two independent surveys of ACL meetings by Bob Moore and Fred Jelinek (personal communication).

Church, LiLT Volume 2, Issue 4 May 2007








Empirical representations: bag-of-words




- Let's consider four sentences:
 - he is a smoker
 - she is alcoholic
 - he is anxious
 - he is diabetic and diet controlled
- We will plot these along 3 dimensions:
 - smoker
 - alcoholic
 - is






he is a smoker






- he is a smoker
- she is alcoholic






- he is a smoker
- she is alcoholic
- he is anxious





- he is a smoker
- she is alcoholic
- he is anxious
- she is diabetic and is diet controlled





- Works surprisingly well on some problems
- But...
 - No word order: loss of context
 - "is this cancer" vs "this is cancer"
 - The Curse of Dimensionality: the power of our classifier reduces as the number of dimensions increases
 - Over fitting: given a low number of training instances relative to number of features
 - Important but less frequent words can have less of an influence than less important but more frequent words






Term frequency and inverse document frequency



- The occurrence of a rare word like "smoker" or "alcoholic" has as much influence on the vector as the occurrence of a common word like "is"
- Lots of occurrences of a common word (such as two mentions of "is" in one sentence) has a bigger effect than a more discriminating rare word.
- Note that we are just using "is" as an example, Often, we would deal with such highly frequent, so-called stop words, by filtering them out. TFIDF is still relevant for other frequent words.






TFIDF

• We can scale our BoW **term frequencies**, multiplying each by a factor that accounts for how rare the term is – an **inverse document frequency (idf)**

$$idf for word = \frac{number of documents}{number of documents containing word}$$

- Usually this is scaled further by taking the log
- The rarer a word, the higher idf
- The more common a word, the lower idf
- tf x idf scales the influence of each term accordingly







```
smoker A
Document 1:
                      tfidf(smoker)
                                       = 1 * ln(4/1) = 1.4
                                                                  he is a
                                       = 1 * ln(4/4) = 0
                      tfidf(is)
                                                                  smoker
                                                                                                     alcoholic
                                                                 1
```




Document 1: fidf(smoker) = 1 * ln(4/1) = 1.4

tfidf(is) = 1 * ln(4/4) = 0

Document 2: fidf(alcoholic) = 1 * ln(4/1) = 1.4

tfidf(is) = 1 * ln(4/4) = 0




Document 1: fidf(smoker) = 1 * ln(4/1) = 1.4

tfidf(is) = 1 * ln(4/4) = 0

Document 2: fidf(alcoholic) = 1 * ln(4/1) = 1.4

tfidf(is) = 1 * ln(4/4) = 0






Document 1: fidf(smoker) = 1 * ln(4/1) = 1.4fidf(is) = 1 * ln(4/4) = 0

Document 2: tfidf(alcoholic) = 1 * ln(4/1) = 1.4

tfidf(is) = 1 * ln(4/4) = 0

Document 3: tfidf(is) = 1 * ln(4/4) = 0




Document 1: fidf(smoker) = 1 * ln(4/1) = 1.4

tfidf(is) = 1 * ln(4/4) = 0

Document 2: tfidf(alcoholic) = 1 * ln(4/1) = 1.4

tfidf(is) = 1 * ln(4/4) = 0

Document 3: tfidf(is) = 1 * ln(4/4) = 0



Document 1: tfidf(smoker) = 1 * ln(4/1) = 1.4


tfidf(is) = 1 * ln(4/4) = 0

Document 2: tfidf(alcoholic) = 1 * ln(4/1) = 1.4

tfidf(is) = 1 * ln(4/4) = 0

Document 3: fidf(is) = 1 * ln(4/4) = 0

Document 4: tfidf(is) = 2 * ln(4/4) = 0



Document 1: tfidf(smoker) = 1 * ln(4/1) = 1.4


tfidf(is) = 1 * ln(4/4) = 0

Document 2: tfidf(alcoholic) = 1 * ln(4/1) = 1.4

tfidf(is) = 1 * ln(4/4) = 0

Document 3: fidf(is) = 1 * ln(4/4) = 0

Document 4: fidf(is) = 2 * ln(4/4) = 0



Document 1: tfidf(smoker) = 1 * ln(4/1) = 1.4

tfidf(is) = 1 * ln(4/4) = 0


Document 2: tfidf(alcoholic) = 1 * ln(4/1) = 1.4

tfidf(is) = 1 * ln(4/4) = 0

Document 3: fidf(is) = 1 * ln(4/4) = 0

Document 4: fidf(is) = 2 * ln(4/4) = 0


- Influence of rare words increased
- Influence of common words decreased





BoW vs TFIDF

Projections on to two dimensions of BoW (left) and TFIDF (right) vector spaces for words in tweets about disasters, and tweets not about disasters



From: https://blog.insightdatascience.com/how-to-solve-90-of-nlp-problems-a-step-by-step-guide-fda605278e4e



More complex features

- Reduce dimensions and find the commonalities: increase ratio of instances to features
 - Lemmas
 - Parts of speech he, she → pronouns
 - Semantic classes mother, father → parent
- Introduce word order e.g by using n-grams
- Introduce context
 - dependencies between parts of the sentence e.g. subject, verb and object
 - contextual models: embeddings





Thank you.
Any questions?

angus.roberts@kcl.ac.uk

