

Name _____ Date _____

Craft _____ I.D.# _____

1. What is the purpose of the blue signal protection?
 - a. To protect track repairmen from moving equipment
 - b. To show workers which cars are under active repair
 - c. To protect workers from injury caused by movement of rolling equipment
 - d. To give movement instructions in a freight car servicing area
2. What information does the blue signal convey?
 - a. The limits of car repair track areas
 - b. That workers are on, under or between rolling equipment.
 - c. That a locomotive is ok to move
 - d. The route into a repair track
3. When a blue signal is displayed, which of the following is true?
 - a. Rolling equipment cannot move until the displayed signal has been removed
 - b. Workers are clear of the equipment and on their lunch break
 - c. Track speed is restricted to not more than 10 miles per hour
 - d. Rolling equipment is ok to be moved at any time
4. Who is the issuing authority for the blue signal rules?
 - a. Keolis
 - b. The National Transportation Safety Board
 - c. The Association of American Railroads
 - d. The Federal Railroad Administration

5. An Effective locking device accomplishes what of the following?
 - a. Eliminates the possibility of rolling equipment from being moved
 - b. Can be locked and unlocked by anyone
 - c. Locks the controls of the locomotive
 - d. Locks the switch or derail being used for protection in place

6. Which of the following is true once blue signal protection has been displayed?
 - a. Repair work will be completed before end of shift
 - b. It may be removed only by the Foreman
 - c. It may be removed only by the class, craft or group of workers who displayed it
 - d. It must be removed and renewed at the end of each shift

7. When workers are on, under or between rolling equipment, which of the following is true?
 - a. The equipment does not have to be protected
 - b. A blue signal must be displayed at least one end of the equipment
 - c. Access to the track that work is being done on must be locked and tagged with an effective locking device
 - d. Engines must be uncoupled from cars

8. If the speed in a locomotive servicing area is restricted to five (5) miles per hour, equipment may be protected by a derail if it is placed at least _____ feet from the end of the equipment being protected.
 - a. 25
 - b. 50
 - c. 100
 - d. 150

9. Specific location Blue Flag Procedures may be reviewed on Keolis information portals located around the railroad (i.e. on the computer)?
True False

10. Which of the following is true for remotely controlled switches?
 - a. Must be physically locked by a Foreman
 - b. Must have a derail installed
 - c. Must have all operating power removed from it
 - d. Must have control switch locked with an effective locking device

11. When should you expect rolling equipment to move?
- a. Only when switches are properly lined
 - b. When the signals are properly displayed
 - c. On any track, in either direction, at any time
12. Who is considered a “Worker” under the definition in CFR 218?
- a. Train and engine service employees
 - b. All non-railroad employees
 - c. Only railroad managers
 - d. A railroad employee assigned to inspect, test, repair, or service railroad rolling equipment
13. Who is **ultimately responsible** for your Blue Signal protection?
- a. Foreman
 - b. Coach cleaner
 - c. The employee about to perform the work on the equipment
 - d. The manager
14. When securing both ends of a track at night, only 1 Blue light is necessary
- True
- False
15. When a derail is in the non-derailing position, it must be locked.
- True
- False
16. When securing a trainset for service or repair you are required to?
- a. Apply or verify handbrakes are applied on both ends of equipment
 - b. Record the train number and estimate departure time
 - c. Test the brakes and remove the old paperwork
 - d. Inform your Foreman you are back from lunch and ready to work
17. If work is being performed in a Mechanical department facility and an Engineering department employee (i.e. B&B) needs to be on the equipment?
- a. Mechanical will provide the protection
 - b. Protection must be provided separately by each department
 - c. Engineering department will have to wait until Mechanical is finished
 - d. Engineering department does not require protection on a Mechanical track

18. Only one craft at a time may occupy a track under blue flag

True

False

19. In the normal servicing area at Pawtucket, BET S&I, RDV Yard, or SH S&I, which of the following is still considered incidental servicing and does NOT require Blue Signal Protection?

- a. Fueling a locomotive
- b. Filling a water tank
- c. Inspecting along-side equipment
- d. Dumping or topping off a toilet tank

20. If a blue light is on the locomotive and in clear view and is illuminated by an interior cab light, the blue light does not need to be flashing

True

False

Score (First Attempt): _____%

Score (After Review): _____%

By signing above, I acknowledge that I have reviewed my exam with my instructor and understand the questions I answered incorrectly.

(Note: This section is required only if the student does not pass the exam.)