

Assignment 12

KD1-Indrajeet-86641

Q1. Write a query that selects all customers whose ratings are equal to or greater than ANY of Serres'.

→ **select * from customers**

where rating >= any(select min rating from customers, salespeople

where customers.snum = salespeople.snum and sname = 'Serres');

```
KD1-Indrajeet-86641@>select * from customers where rating >= any(select rating from customers, salespeople
-> where customers.snum = salespeople.snum and sname = 'Serres');
+-----+-----+-----+-----+-----+
| cnum | cname | city | rating | snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome | 200 | 1003 |
| 2003 | Liu | San Jose | 200 | 1002 |
| 2004 | Grass | Berlin | 300 | 1002 |
| 2008 | Cisneros | San Jose | 300 | 1007 |
+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

Q2. Write a query using ANY or ALL that will find all salespeople who have no customers located in their city.

→ **select sname from salespeople, customers where salespeople.city**

NOT IN (select city from customers) and

salespeople.snum = customers.snum;

```
KD1-Indrajeet-86641@>select sname from salespeople, customers where salespeople.city
-> NOT IN ( select city from customers) and salespeople.snum = customers.snum;
+-----+
| sname |
+-----+
| Axelrod |
| Rifkin |
+-----+
2 rows in set (0.01 sec)
```

Q3. Write a query that selects all orders for amounts greater than any for the customers in London.

➔ **select * from orders where amt > ANY (SELECT amt FROM orders
WHERE cnum IN (SELECT cnum FROM customers WHERE city='London'));**

```
KD1-Indrajeet-86641@>select * from orders where amt > ANY ( SELECT amt FROM orders  
-> WHERE cnum IN ( SELECT cnum FROM customers WHERE city='London' ) );
```

onum	amt	odate	cnum	snum
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3008	4723.00	1990-10-04	2006	1001
3011	9891.88	1990-10-04	2006	1001

6 rows in set (0.00 sec)

Q4. Write the above query using MIN or MAX.

➔ **select * from orders where amt > (SELECT min(amt) FROM orders
WHERE cnum IN(SELECT cnum FROM customers WHERE city='London'));**

```
KD1-Indrajeet-86641@>select * from orders where amt > ( SELECT min(amt) FROM orders  
-> WHERE cnum IN( SELECT cnum FROM customers WHERE city='London' ) );
```

onum	amt	odate	cnum	snum
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3008	4723.00	1990-10-04	2006	1001
3011	9891.88	1990-10-04	2006	1001

6 rows in set (0.00 sec)