

ASSIGNMENT 15

Using Subqueries with DML Commands

KD1-86691-Harsh

QUESTION 1

```
KD1-86691-Harsh@>create table multicast as select * from salespeople
-> where snum in (select snum from customers group by snum having count(snum) > 1);
Query OK, 2 rows affected (0.05 sec)
Records: 2 Duplicates: 0 Warnings: 0
```

```
KD1-86691-Harsh@>table multicast;
+-----+-----+-----+-----+
| snum | sname | city   | comm |
+-----+-----+-----+-----+
| 1001 | Peel  | London | 0.12 |
| 1002 | Serres| San Jose | 0.13 |
+-----+-----+-----+-----+
2 rows in set (0.00 sec)
```

QUESTION 2

```
KD1-86691-Harsh@>delete from customers where cnum not in(select c
num from orders);
Query OK, 2 rows affected (0.01 sec)
```

```
KD1-86691-Harsh@>table customers;
+-----+-----+-----+-----+-----+
| cnum | cname   | city   | rating | snum |
+-----+-----+-----+-----+-----+
| 2001 | Hoffman | London | 100    | 1001 |
| 2002 | Giovanni| Rome   | 300    | 1003 |
| 2003 | Liu     | San Jose | 200    | 1002 |
| 2004 | Grass   | Berlin | 300    | 1002 |
| 2008 | Cisneros| San Jose | 300    | 1007 |
| 2007 | Pereira | Rome   | 200    | 1002 |
+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)
```

QUESTION 3

```
KD1-86691-Harsh@>update salespeople set comm = comm*1.2 where snum in (select snum from orders group by snum having sum(amt)>3000);
Query OK, 1 row affected, 1 warning (0.01 sec)
Rows matched: 1 Changed: 1 Warnings: 1
```

```
KD1-86691-Harsh@>table salespeople;
+-----+-----+-----+-----+
| snum | sname | city   | comm |
+-----+-----+-----+-----+
| 1001 | Peel  | London | 0.12 |
| 1002 | Serres| San Jose | 0.19 |
| 1004 | Motika | London | 0.11 |
| 1007 | Rifkin | Barcelona | 0.15 |
| 1003 | Axelrod | New York | 0.10 |
| 1100 | blanco | san jose | NULL |
+-----+-----+-----+-----+
6 rows in set (0.00 sec)
```