

## Assignment –6

### Using Special Operators in Conditions.

1) Write two different queries that would produce all orders taken on October 3<sup>rd</sup> or 4<sup>th</sup>, 1990.

```
select *from orders
-> where odate='1990-10-03' or odate='1990-10-04';
select *from orders
-> where odate in('1990-10-03','1990-10-04');
```

```
[KD2-86650-Shivali@>select *from orders
-> where odate='1990-10-03' or odate='1990-10-04';
+-----+-----+-----+-----+-----+
| Onum | Amt   | Odate   | Cnum | Snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75 | 1990-10-04 | 2004 | 1002 |
+-----+-----+-----+-----+-----+
7 rows in set (0.00 sec)

[KD2-86650-Shivali@>select *from orders
-> where odate in('1990-10-03','1990-10-04');
+-----+-----+-----+-----+-----+
| Onum | Amt   | Odate   | Cnum | Snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75 | 1990-10-04 | 2004 | 1002 |
+-----+-----+-----+-----+-----+
7 rows in set (0.01 sec)
```

2) Write a query that selects all of the customers serviced by Peel or Motika. (Hint: the snum field relates the two tables to one another).

```
select sname,cname from customers,salespeople where
customers.snum=salespeople.snum and sname in('peel','motika');
```

```
[KD2-86650-Shivali@>select *from customers where city='Rome'or rating>100;
+-----+-----+-----+-----+-----+
| Cnum | Cname   | City    | Rating | Snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome    | 200    | 1003 |
| 2003 | Liu      | San Jose | 200    | 1002 |
| 2004 | Grass    | Berlin  | 300    | 1002 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
| 2007 | Pereira  | Rome    | 100    | 1004 |
+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)

KD2-86650-Shivali@>
```

3) Write a query that will produce all the customers whose names begin with a letter from 'A' to 'G'.

```
[KD2-86650-Shivali@>select *from customers where cname between 'A'and'H';
+-----+-----+-----+-----+-----+
| Cnum | Cname   | City    | Rating | Snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome    | 200    | 1003 |
| 2004 | Grass    | Berlin  | 300    | 1002 |
| 2006 | Clemens  | London  | 100    | 1001 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

4) Write a query that selects all customers whose names begin with the letter 'C'.

```
[KD2-86650-Shivali@>select *from customers
-> where Cname between 'C' and 'D';
+-----+-----+-----+-----+-----+
| Cnum | Cname   | City    | Rating | Snum |
+-----+-----+-----+-----+-----+
| 2006 | Clemens  | London  | 100    | 1001 |
| 2008 | Cisneros | San Jose | 300    | 1007 |
+-----+-----+-----+-----+-----+
2 rows in set (0.00 sec)
```

5) Write a query that selects all orders except those with zeroes or NULLs in the amt field.

select \* from orders

-> where amt is not null or '0';

```
[KD2-86650-Shivali@>select *from orders
[  -> where amt is not null or '0';
+-----+-----+-----+-----+-----+
| Onum | Amt   | Odate   | Cnum | Snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69 | 1990-10-03 | 2008 | 1007 |
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45 | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23 | 1990-10-04 | 2002 | 1003 |
| 3007 | 75.75 | 1990-10-04 | 2004 | 1002 |
| 3008 | 4723.00 | 1990-10-05 | 2006 | 1001 |
| 3010 | 1309.95 | 1990-10-06 | 2004 | 1002 |
| 3011 | 9891.88 | 1990-10-06 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
10 rows in set (0.00 sec)
```