<u>Assignment – 15</u> Using Subqueries with DML Commands.

1) Assume there is a table called Multicust, with all of the same column definitions as Salespeople. Write a command that inserts all salespeople with more than one customer into this table.

```
KD2-87412-Abhishek@>CREATE TABLE Multicast AS
   -> SELECT *
   -> FROM salespeople
      WHERE snum IN
    ->
           (SELECT snum
            FROM customers
    ->
            GROUP BY snum
            HAVING count(snum)>1);
Query OK, 1 row affected (0.02 sec)
Records: 1
           Duplicates: 0 Warnings: 0
KD2-87412-Abhishek@>select * from multicast;
 Snum
         Sname
                 city
                          comm
 1001
        peel
                London
                         0.12
 row in set (0.00 sec)
```

2) Write a command that deletes all customers with no current orders.

```
KD2-87412-Abhishek@>delete from customers where cnum in (select cnum from orders
   -> group by cnum having count(cnum)=0);
Query OK, 0 rows affected (0.00 sec)
<D2-87412-Abhishek@>select * from customers;
                   City
 Cnum I
        Cname
                              Rating |
                                        Snum
        Hoffman
 2001
                    London
                                  100
                                        1001
 2002
        Gionavi
                    Rome
                                  300
                                        1003
                    Sanjose
 2003
         liu
                                  200
                                        1002
                    Berlin
 2004
         Grass
                                  200
                                        1002
 2006
         Celmens
                    London
                                  100
                                        1001
 2006
         Cisneros
                    SanJose
                                  300
                                        1007
 2007
        Pereira
                    Rome
                                  200
                                        NULL
 rows in set (0.00 sec)
```

3) Write a command that increases by twenty percent the commissions of all salespeople with total orders above Rs. 3,000.

```
KD2-87412-Abhishek@>UPDATE salespeople
    -> SET comm=comm*1.20
    -> WHERE snum IN
           (SELECT snum
            FROM orders
            WHERE amt>300);
Query OK, 4 rows affected (0.01 sec)
Rows matched: 4 Changed: 4 Warnings: 0
KD2-87412-Abhishek@> select * from salespeople;
 Snum | Sname
                 city
                               comm
                   London
                               0.144
 1001 | peel
         Blanco
                                NULL
  1100
                   San jose
  1004
         Motika
                   London
                               0.132
  1007
         Rifkin
                   Barcelona
                                0.18
       Aexlord
                   New york
                                0.12
  1003
 rows in set (0.00 sec)
```

Sameer Dehadrai

Page: 1