Write two different queries that would produce all orders taken on October 3rd or 4th, 1990.

```
KD2-87412-Abhishek@> select *
                                from orders where odate between '1990-10-03' and '1990-10-04';
        Amt
                   Odate
                                        Snum |
 Onum
                                 Cnum
                   1990-10-03
 3001
           18.69
                                 2008
                                         1007
 3003
          767.19
                   1990-10-03
                                 2001
                                         1001
 3002
         1900.10
                    1990-10-03
                                 2007
                                         1004
         5160.45
                   1990-10-03
 3005
                                 2003
                                         1002
 3006
         1098.16
                   1990-10-03
                                 2008
                                         1007
 3009
         1713.23
                   1990-10-04
                                         1003
                                 2002
 3007
           75.75
                   1990-10-04
                                 2004
                                        1002
 rows in set (0.02 sec)
(D2-87412-Abhishek@> select *
                                from orders where odate in ('1990-10-03', '1990-10-04');
        Amt
                   Odate
                                 Cnum
 Onum
                                        Snum |
 3001
           18.69
                   1990-10-03
                                 2008
                                        1007
 3003
          767.19
                   1990-10-03
                                 2001
                                         1001
         1900.10
                   1990-10-03
                                 2007
                                        1004
 3002
 3005
         5160.45
                   1990-10-03
                                 2003
                                        1002
 3006
         1098.16
                   1990-10-03
                                 2008
                                        1007
         1713.23
                    1990-10-04
  3009
                                 2002
                                         1003
                   1990-10-04
 3007
           75.75
                                 2004
                                        1002
 rows in set (0.00 sec)
```

Write a query that selects all of the customers serviced by Peel or Motika

Cnum	Cname	City	Rating	Snum
2001	Hoffman	London	100	1001
2002	Gionavi	Rome	200	1003
2003	liu	Sanjose	200	1002
2004	Grass	Berlin	200	1002
2006	Celmens	London	100	1001
2007	Pereira	Rome	100	1004

Write a query that will produce all the customers whose names begin with a letter from 'A' to 'G'.

```
KD2-87412-Abhishek@> select *
                                from customers where cname between 'A'and'H';
                    City
                                         Snum
  Cnum
         Cname
                               Rating
                                  200
  2002
         Gionavi
                                         1003
                     Rome
  2004
                                   200
                                         1002
         Grass
                     Berlin
  2006
         Celmens
                     London
                                   100
                                         1001
  2006
         Cisneros
                     SanJose
                                   300
                                         1007
 rows in set (0.00 sec)
```

Write a query that selects all customers whose names begin with the letter 'C'.

```
KD2-87412-Abhishek@> select *
                                from customers where cname like 'c%';
 Cnum
         Cname
                    City
                               Rating
                                        Snum
  2006
         Celmens
                    London
                                  100
                                        1001
  2006
         Cisneros
                     SanJose
                                  300
                                        1007
2 rows in set (0.00 sec)
```

Write a query that selects all orders except those with zeroes or NULLs in the amt field

```
KD2-87412-Abhishek@> select * from orders where amt>0 and amt is not null;
                   0date
 Onum
         Amt
                                 Cnum
                                         Snum
                    1990-10-03
 3001
           18.69
                                 2008
                                         1007
 3003
          767.19
                    1990-10-03
                                 2001
                                         1001
         1900.10
                                         1004
 3002
                    1990-10-03
                                 2007
 3005
         5160.45
                    1990-10-03
                                 2003
                                         1002
 3006
         1098.16
                    1990-10-03
                                 2008
                                         1007
 3009
         1713.23
                    1990-10-04
                                 2002
                                         1003
 3007
           75.75
                    1990-10-04
                                 2004
                                         1002
 3008
         4723.00
                    1990-10-05
                                 2006
                                         1001
         1309.95
 3010
                    1990-10-06
                                 2004
                                         1002
 3011
         9891.88
                   1990-10-06
                                 2006
                                         1001
10 rows in set (0.00 sec)
```