

Assignment No.7

1. Write a query that lists each order number followed by the name of the customer who made the order.

```
kd2_98837_sakshi> select o.onum,c.cname from orders o
-> inner join customers c on o.cnum=c.cnum;
```

onum	cname
3001	Cisneros
3003	Hoffman
3002	Pereira
3005	Liu
3006	Cisneros
3009	Giovanni
3007	Grass
3008	Clemens
3010	Grass
3011	Clemens

10 rows in set (0.00 sec)

2. Write a query that gives the names of both the salesperson and the customer for each order along with the order number.

```
kd2_98837_sakshi> select c.cname,s.sname,o.onum from customers c
-> inner join orders o on o.cnum=c.cnum
-> inner join salespeople s on s.snum=o.snum;
```

cname	sname	onum
Hoffman	Peel	3003
Giovanni	Axelrod	3009
Liu	Serres	3005
Grass	Serres	3010
Grass	Serres	3007
Clemens	Peel	3011
Clemens	Peel	3008
Cisneros	Rifkin	3006
Cisneros	Rifkin	3001
Pereira	Motika	3002

10 rows in set (0.00 sec)

3. Write a query that produces all customers serviced by salespeople with a commission above 12%. Display the customer's name, the salesperson's name, and the salesperson's rate of commission.

```
kd2_98837_sakshi> select c.cname,s.sname,s.comm from customers c
-> inner join salespeople s on s.snum=c.snum
-> where s.comm>0.12;
```

cname	sname	comm
Liu	Serres	0.13
Grass	Serres	0.13
Cisneros	Rifkin	0.15

3 rows in set (0.00 sec)

4. Write a query that calculates the commission earned by each salesperson for orders placed by customers with a rating above 100.

```
kd2_98837_sakshi> select distinct o.onum,s.comm,s.comm*o.amt total_comm from salespeople s
-> inner join orders o on o.snum=s.snum
-> inner join customers c on c.cnum=o.cnum
-> where c.rating>100;
```

onum	comm	total_comm
3010	0.13	40.2935
3007	0.13	9.8475
3005	0.13	670.8585
3006	0.15	164.7240
3001	0.15	2.8035
3009	0.10	171.3230

6 rows in set (0.00 sec)

5. Write a query that produces all pairs of salespeople who are living in the same city. Exclude combinations of salespeople with themselves as well as duplicate rows with the order reversed .

```
kd2_98837_sakshi> SELECT DISTINCT s1.sname AS sname1, s2.sname AS sname2, s1.city FROM salespeople s1
-> INNER JOIN salespeople s2 ON s1.city = s2.city
-> WHERE s1.sname < s2.sname
-> ORDER BY sname1;
```

sname1	sname2	city
Motika	Peel	London

1 row in set (0.00 sec)