

1. Write a query that lists each order number followed by the name of the customer who made the order.

```
KD2_SAURABH_98912>select o.onum,c.cname from orders o join customers c on o.snum=c.snum;
```

onum	cname
3001	Cisneros
3003	Clemens
3003	Hoffman
3002	Pereira
3005	Grass
3005	Liu
3006	Cisneros
3009	Giovanni
3007	Grass
3007	Liu
3008	Clemens
3008	Hoffman
3010	Grass
3010	Liu
3011	Clemens
3011	Hoffman

16 rows in set (0.00 sec)

2. Write a query that gives the names of both the salesperson and the customer for each order along with the order number.

```
KD2_SAURABH_98912>select o.onum,s.sname,c.cname from orders o join salespeople s on o.snum=s.snum join customers c on o.snum=c.snum;
```

onum	sname	cname
3001	Rifkin	Cisneros
3003	Peel	Clemens
3003	Peel	Hoffman
3002	Motika	Pereira
3005	Serres	Grass
3005	Serres	Liu
3006	Rifkin	Cisneros
3009	Axelrod	Giovanni
3007	Serres	Grass
3007	Serres	Liu
3008	Peel	Clemens
3008	Peel	Hoffman
3010	Serres	Grass
3010	Serres	Liu
3011	Peel	Clemens
3011	Peel	Hoffman

16 rows in set (0.00 sec)

3. Write a query that produces all customers serviced by salespeople with a commission above 12%. Display the customer's name, the salesperson's name, and the salesperson's rate of commission.

```
KD2_SAURABH_98912>select c.cname,s.sname,s.comm from customers c join salespeople s on c.snum=s.snum where comm>0.12;
```

cname	sname	comm
Liu	Serres	0.13
Grass	Serres	0.13
Cisneros	Rifkin	0.15

3 rows in set (0.00 sec)

4. Write a query that calculates the commission earned by each salesperson for orders placed by customers with a rating above 100.

```
KD2_SAURABH_98912>select s.sname,o.amt*s.comm as Commission from salespeople s join orders o on s.snum=o.snum join customers c on s.snum=c.snum where c.rating >100;
```

sname	Commission
Rifkin	2.8035
Serres	670.8585
Serres	670.8585
Rifkin	164.7240
Axelrod	171.3230
Serres	9.8475
Serres	9.8475
Serres	40.2935
Serres	40.2935

9 rows in set (0.01 sec)

5. Write a query that produces all pairs of salespeople who are living in the same city. Exclude combinations of salespeople with themselves as well as duplicate rows with the order reversed.

```
ERROR 1054 (42S22): Unknown column 's.city' in 'field list'
KD2_SAURABH_98912>select s1.city,s1.sname,s2.sname from salespeople s1 join salespeople s2 on s1.city=s2.city and s1.snum<s2.snum;
```

city	sname	sname
London	Peel	Motika

1 row in set (0.01 sec)