

1. Write a query that counts the number of salespeople registering orders for each day. (If a salesperson has more than one order on a given day, he or she should be counted only once.).

```
KD2_SAURABH_98912>select odate,count(distinct snum) as salesperson_count from orders group by odate ;
```

odate	salesperson_count
1990-10-03	4
1990-10-04	3

```
2 rows in set (0.00 sec)
```

2. Write a query on the Customers table that will find the highest rating in each city. Put the output in this form: For the city (city), the highest rating is: (rating).

```
ERROR 1063 (42000): Incorrect parameters in the call to native function 'concat'
KD2_SAURABH_98912>select concat("For the city ",city,"max rating is ",max(rating)) as City_wise_max_ra
ting from customers group by city;
```

City_wise_max_rating
For the city Londonmax rating is 100
For the city Romemax rating is 200
For the city San Josemax rating is 300
For the city Berlinmax rating is 300

```
4 rows in set (0.00 sec)
```

- 3 Write an SQL query to calculate the total order amount for each day and display the results in descending order of total orders.

```
KD2_SAURABH_98912>select odate,sum(amt) as total_order_amt from orders group by odate;
```

odate	total_order_amt
1990-10-03	8944.59
1990-10-04	16713.81

```
2 rows in set (0.00 sec)
```

4. Write a query that selects the total amount in orders for each salesperson for whom this total is greater than the average amount of the order in the table. (Note Use the average amount value directly →2565.84)

```
KD2_SAURABH_98912>select snum,sum(amt) as total_amt from orders group by snum having total_amt>2565.84;
```

snum	total_amt
1001	15382.07
1002	5546.15

```
2 rows in set (0.00 sec)
```

5. Write a query that selects the highest rating in each city.

```
KD2_SAURABH_98912>select city,max(rating) as max_rating from customers group by city;
```

city	max_rating
London	100
Rome	200
San Jose	300
Berlin	300

```
4 rows in set (0.00 sec)
```

6.Retrieve the maximum order amount for each salesperson from the orders table, including only those orders whose value exceeds Rs. 3000.

```
KD2_SAURABH_98912>select snum,max(amt) as max_order_amt from orders where amt>3000 group by snum ;
```

snum	max_order_amt
1002	5160.45
1001	9891.88

```
2 rows in set (0.00 sec)
```

7.Write an SQL query to find the smallest order placed by every customer .

```
KD2_SAURABH_98912>select cnum,min(amt) as min_val_order from orders group by cnum;
```

cnum	min_val_order
2008	18.69
2001	767.19
2007	1900.10
2003	5160.45
2002	1713.23
2004	75.75
2006	4723.00

```
7 rows in set (0.00 sec)
```