DBT ASSIGNMENT- 11

1) Create a view that shows all of the customers who have the highest ratings.

```
KD2_Digvijay_96215>CREATE VIEW highest_rating_customers AS
    -> SELECT *
    -> FROM customers
    -> WHERE rating = (SELECT MAX(rating) FROM customers);
Query OK, 0 rows affected (0.02 sec)

KD2_Digvijay_96215>SELECT * FROM highest_rating_customers;
+------+----------+----------+--------+------+
| cnum | cname    | city     | rating | snum |
+------+----------+----------+--------+------+
| 2004 | Grass    | Berlin   |    300 | 1002 |
| 2008 | Cisneros | San Jose |    300 | 1007 |
+------+----------+----------+--------+------+
2 rows in set (0.02 sec)
```

2) Create a view that shows the number of salespeople in each city.

```
KD2_Digvijay_96215>CREATE VIEW scity_count AS SELECT city, COUNT(*) from salespeople GROUP BY city;
Query OK, 0 rows affected (0.06 sec)

KD2_Digvijay_96215>SELECT * FROM scity_count;
+-----------+----------+
| city      | COUNT(*) |
+-----------+----------+
| London    |        2 |
| San Jose  |        1 |
| Barcelona |        1 |
| New York  |        1 |
+-----------+----------+
4 rows in set (0.01 sec)
```

3) Create a view that shows the average and total orders for each salesperson after his or her name. Assume all names are unique.

```
KD2_Digvijay_96215>CREATE VIEW salesperson_order_stats AS
    -> SELECT s.sname,
    ->        COUNT(o.onum) AS total_orders,
    ->        AVG(o.amt) AS avg_orders
    -> FROM salespeople s
    -> JOIN orders o ON s.snum = o.snum
    -> GROUP BY s.sname;
Query OK, 0 rows affected (0.04 sec)

KD2_Digvijay_96215>SELECT * FROM salesperson_order_states;
ERROR 1146 (42S02): Table 'sales.salesperson_order_states' doesn't exist
KD2_Digvijay_96215>SELECT * FROM salesperson_order_stats;
+---------+--------------+-------------+
| sname   | total_orders | avg_orders  |
+---------+--------------+-------------+
| Rifkin  |            2 |  558.425000 |
| Peel    |            3 | 5127.356667 |
| Motika  |            1 | 1900.100000 |
| Serres  |            3 | 1848.716667 |
| Axelrod |            1 | 1713.230000 |
+---------+--------------+-------------+
5 rows in set (0.02 sec)
```

4) Create a view that shows each salesperson with multiple customers.

```
KD2_Digvijay_96215>CREATE VIEW multi_customer_salespeople AS
    -> SELECT s.snum, s.sname, COUNT(c.cnum) AS total_customers
    -> FROM salespeople s
    -> INNER JOIN customers c ON s.snum = c.snum
    -> GROUP BY s.snum, s.sname
    -> HAVING COUNT(c.cnum) > 1;
Query OK, 0 rows affected (0.03 sec)

KD2_Digvijay_96215>SELECT * FROM multi_customer_salespeople;
+------+--------+-----------------+
| snum | sname  | total_customers |
+------+--------+-----------------+
| 1001 | Peel   |               2 |
| 1002 | Serres |               2 |
+------+--------+-----------------+
2 rows in set (0.01 sec)
```

5) Which of these views are updateable (will allow DML operations)?

#1 Create View Dailyorders as Select Distinct cnum, snum, onum, odate from Orders;

```
KD2_Digvijay_96215>CREATE VIEW Dailyorders
    -> AS SELECT DISTINCT cnum,snum,onum,odate FROM orders;
Query OK, 0 rows affected (0.07 sec)

KD2_Digvijay_96215>SELECT * FROM Dailyorders;
+------+------+------+------------+
| cnum | snum | onum | odate      |
+------+------+------+------------+
| 2008 | 1007 | 3001 | 1990-10-03 |
| 2001 | 1001 | 3003 | 1990-10-03 |
| 2007 | 1004 | 3002 | 1990-10-03 |
| 2003 | 1002 | 3005 | 1990-10-03 |
| 2008 | 1007 | 3006 | 1990-10-03 |
| 2002 | 1003 | 3009 | 1990-10-04 |
| 2004 | 1002 | 3007 | 1990-10-04 |
| 2006 | 1001 | 3008 | 1990-10-04 |
| 2004 | 1002 | 3010 | 1990-10-04 |
| 2006 | 1001 | 3011 | 1990-10-04 |
+------+------+------+------------+
10 rows in set (0.01 sec)
```

#2 Create View Custotals as Select cname, Sum (amt) Sum_Amt from Orders, Customers where Orders.cnum=Customers.cnum Group by cname;

```
KD2_Digvijay_96215>CREATE VIEW Custotals
    -> AS SELECT cname,sum(amt) SUM+AMT FROM orders, customers
    -> WHERE orders.cnum=Customers.cnum
    -> GROUP BY cname;^C
KD2_Digvijay_96215>
KD2_Digvijay_96215>CREATE VIEW Custotals
    -> AS SELECT cname,sum(amt) SUM_AMT FROM orders, customers
    -> WHERE orders.cnum=Customers.cnum
    -> GROUP BY cname;
Query OK, 0 rows affected (0.04 sec)

KD2_Digvijay_96215>SELECT * FROM Custotals;
+----------+----------+
| cname    | SUM_AMT  |
+----------+----------+
| Cisneros |  1116.85 |
| Hoffman  |   767.19 |
| Pereira  |  1900.10 |
| Liu      |  5160.45 |
| Giovanni |  1713.23 |
| Grass    |   385.70 |
| Clemens  | 14614.88 |
+----------+----------+
7 rows in set (0.01 sec)
```

#3 Create view Thirdorders as Select * from Dailyorders where odate='1990-10-03';

```
KD2_Digvijay_96215>CREATE VIEW Thirdorders
    -> AS SELECT * FROM Dailyorders WHERE
    -> odate ='1990=10=03';
Query OK, 0 rows affected (0.04 sec)

KD2_Digvijay_96215>SELECT * FROM Thirdorders;
+------+------+------+------------+
| cnum | snum | onum | odate      |
+------+------+------+------------+
| 2008 | 1007 | 3001 | 1990-10-03 |
| 2001 | 1001 | 3003 | 1990-10-03 |
| 2007 | 1004 | 3002 | 1990-10-03 |
| 2003 | 1002 | 3005 | 1990-10-03 |
| 2008 | 1007 | 3006 | 1990-10-03 |
+------+------+------+------------+
5 rows in set, 1 warning (0.02 sec)
```

#4 Create view Nullcities as Select snum, sname, city from Salespeople where city is NULL OR sname BETWEEN ‘A’ and ‘MZ’;

```
KD2_Digvijay_96215>CREATE VIEW Nullcities
    -> AS SELECT snum,sname,city
    -> FROM salespeople
    -> WHERE city is NULL
    -> OR sname BETWEEN 'A' and 'MZ';
Query OK, 0 rows affected (0.05 sec)

KD2_Digvijay_96215>SELECT * FROM Nullcities;
+------+---------+----------+
| snum | sname   | city     |
+------+---------+----------+
| 1004 | Motika  | London   |
| 1003 | Axelrod | New York |
+------+---------+----------+
2 rows in set (0.00 sec)
```

6) Create a view of the Salespeople table called Commissions. This view will include only the snum and comm fields. Through this view, someone could enter or change commissions, but only to values between .10 and .20.

```
KD2_Digvijay_96215>CREATE VIEW commision AS SELECT snum,comm FROM sale
speople WHERE comm BETWEEN 0.1 AND 0.20 WITH CHECK OPTION;
Query OK, 0 rows affected (0.03 sec)

KD2_Digvijay_96215>SELECT * FROM commission;
ERROR 1146 (42S02): Table 'sales.commission' doesn't exist
KD2_Digvijay_96215>SELECT * FROM commision;
+------+------+
| snum | comm |
+------+------+
| 1001 | 0.12 |
| 1002 | 0.13 |
| 1004 | 0.11 |
| 1007 | 0.15 |
| 1003 | 0.10 |
+------+------+
5 rows in set (0.01 sec)
```