Use appropriate joins to solve following queries.

Note: To solve below queries, use “sales” database.

1. Write a query that lists each order number followed by the name of the customer who made the order.

```
mysql> SELECT o.onum, c.cname FROM customers c INNER JOIN orders o ON o.cnum = c.cnum;
+------+----------+
| onum | cname    |
+------+----------+
| 3001 | Cisneros |
| 3003 | Hoffman  |
| 3002 | Pereira  |
| 3005 | Liu      |
| 3006 | Cisneros |
| 3009 | Giovanni |
| 3007 | Grass    |
| 3008 | Clemens  |
| 3010 | Grass    |
| 3011 | Clemens  |
+------+----------+
10 rows in set (0.001 sec)
```

2. Write a query that gives the names of both the salesperson and the customer for each order along with the order number.

```
mysql> SELECT o.onum, s.sname, c.cname FROM orders o INNER JOIN customers c ON c.cnum = o.cnum INNER JOIN salespeople s ON o.snum = s.snum;
+------+---------+----------+
| onum | sname   | cname    |
+------+---------+----------+
| 3003 | Peel    | Hoffman  |
| 3009 | Axelrod | Giovanni |
| 3005 | Serres  | Liu      |
| 3010 | Serres  | Grass    |
| 3007 | Serres  | Grass    |
| 3011 | Peel    | Clemens  |
| 3008 | Peel    | Clemens  |
| 3006 | Rifkin  | Cisneros |
| 3001 | Rifkin  | Cisneros |
| 3002 | Motika  | Pereira  |
+------+---------+----------+
10 rows in set (0.001 sec)
```

3. Write a query that produces all customers serviced by salespeople with a commission above 12%. Display the customer's name, the salesperson's name, and the salesperson's rate of commission.

```
mysql> SELECT c.cname, s.sname, s.comm FROM customers c INNER JOIN salespeople s ON c.snum = s.snum WHERE s.comm > 0.12;
+----------+--------+------+
| cname    | sname  | comm |
+----------+--------+------+
| Liu      | Serres | 0.13 |
| Grass    | Serres | 0.13 |
| Cisneros | Rifkin | 0.15 |
+----------+--------+------+
3 rows in set (0.001 sec)
```

4. Write a query that calculates the commission earned by each salesperson for orders placed by customers with a rating above 100.

```
mysql> SELECT o.onum, s.comm, o.amt * s.comm FROM orders o INNER JOIN salespeople s ON o.snum = s.snum INNER JOIN customers c ON c.cnum = o.cnum WHERE c.rating > 100;
+------+------+---------------+
| onum | comm | o.amt * s.comm |
+------+------+---------------+
| 3010 | 0.13 |       40.2935 |
| 3007 | 0.13 |        9.8475 |
| 3005 | 0.13 |      670.8585 |
| 3006 | 0.15 |      164.7240 |
| 3001 | 0.15 |        2.8035 |
| 3009 | 0.10 |      171.3230 |
+------+------+---------------+
6 rows in set (0.001 sec)
```

5. Write a query that produces all pairs of salespeople who are living in the same city. Exclude combinations of salespeople with themselves as well as duplicate rows with the order reversed .

```
mysql> SELECT s1.sname, s2.sname, s1.city FROM salespeople s1 INNER JOIN salespeople s2 ON s1.city = s2.city WHERE s1.sname < s2.sname;
+--------+-------+--------+
| sname  | sname | city   |
+--------+-------+--------+
| Motika | Peel  | London |
+--------+-------+--------+
1 row in set (0.001 sec)
```