ASSIGNMENT – 6 kd2_vaibhav_96218

1. Write a query that counts the number of salespeople registering orders for each day. (If a salesperson has more than one order on a given day, he or she should be counted only once.).

```
kd2_vaibhav_96218>SELECT odate, count(distinct snum) from orders group by odate;
+------------+----------------------+
| odate      | count(distinct snum) |
+------------+----------------------+
| 1990-10-03 |                    4 |
| 1990-10-04 |                    3 |
+------------+----------------------+
2 rows in set (0.032 sec)
```

2. Write a query on the Customers table that will find the highest rating in each city. Put the output in this form: For the city (city), the highest rating is: (rating).

```
kd2_vaibhav_96218>SELECT CONCAT('For the city ', city, ' the highest rating is: ', MAX(rating)) AS
formatted_output FROM CUSTOMERS GROUP BY CITY;
+-------------------------------------------------+
| formatted_output                                |
+-------------------------------------------------+
| For the city London the highest rating is: 100  |
| For the city Rome the highest rating is: 200    |
| For the city San Jose the highest rating is: 300 |
| For the city Berlin the highest rating is: 300  |
+-------------------------------------------------+
4 rows in set (0.009 sec)
```

3 Write an SQL query to calculate the total order amount for each day and display the results in descending order of total orders.

```
kd2_vaibhav_96218>SELECT odate, SUM(AMT) FROM ORDERS GROUP BY odate ORDER BY odate DESC;
+------------+----------+
| odate      | SUM(AMT) |
+------------+----------+
| 1990-10-04 | 16713.81 |
| 1990-10-03 |  8944.59 |
+------------+----------+
2 rows in set (0.035 sec)
```

4. Write a query that selects the total amount in orders for each salesperson for whom this total is greater than the average amount of the order in the table. (Note Use the average amount value directly →2565.84)

```
kd2_vaibhav_96218>SELECT s.snum, sum(o.amt) FROM orders o
    -> INNER JOIN salespeople s ON o.snum = s.snum
    -> GROUP BY  s.snum
    -> HAVING sum(o.amt) > 2565.84;
+------+------------+
| snum | sum(o.amt) |
+------+------------+
| 1001 |   15382.07 |
| 1002 |    5546.15 |
+------+------------+
2 rows in set (0.009 sec)
```

5. Write a query that selects the highest rating in each city.

```
kd2_vaibhav_96218>SELECT city, max(rating)
    -> FROM customers
    -> GROUP BY city;
+----------+-------------+
| city     | max(rating) |
+----------+-------------+
| London   |         100 |
| Rome     |         200 |
| San Jose |         300 |
| Berlin   |         300 |
+----------+-------------+
4 rows in set (0.010 sec)
```

6. Retrieve the maximum order amount for each salesperson from the orders table, including only those orders whose value exceeds Rs. 3000.

```
kd2_vaibhav_96218>SELECT s.snum, max(o.amt) FROM salespeople s
    -> RIGHT JOIN orders o ON s.snum = o.snum
    -> GROUP BY s.snum
    -> HAVING max(o.amt)>3000
    -> ORDER BY max(o.amt);
+------+------------+
| snum | max(o.amt) |
+------+------------+
| 1002 |    5160.45 |
| 1001 |    9891.88 |
+------+------------+
2 rows in set (0.017 sec)
```

7. Write an SQL query to find the smallest order placed by every customer.

```
kd2_vaibhav_96218>SELECT c.cnum, min(o.amt) from customers c left join orders o ON c.cnum =
 o.cnum GROUP BY c.cnum order by c.cnum;
+------+------------+
| cnum | min(o.amt) |
+------+------------+
| 2001 |     767.19 |
| 2002 |    1713.23 |
| 2003 |    5160.45 |
| 2004 |      75.75 |
| 2006 |    4723.00 |
| 2007 |    1900.10 |
| 2008 |      18.69 |
+------+------------+
7 rows in set (0.007 sec)
```