1. Write a query that lists each order number followed by the name of the customer who made the order.

```
kd2_vaibhav_96218>SELECT o.onum, c.cname FROM customers c
    -> RIGHT JOIN orders o ON  c.cnum = o.cnum;
+------+----------+
| onum | cname    |
+------+----------+
| 3001 | Cisneros |
| 3003 | Hoffman  |
| 3002 | Pereira  |
| 3005 | Liu      |
| 3006 | Cisneros |
| 3009 | Giovanni |
| 3007 | Grass    |
| 3008 | Clemens  |
| 3010 | Grass    |
| 3011 | Clemens  |
+------+----------+
10 rows in set (0.006 sec)
```

2 Write a query that gives the names of both the salesperson and the customer for each order along with the order number.

```
kd2_vaibhav_96218>SELECT onum, cname, sname FROM orders o
    -> LEFT JOIN salespeople s ON o.snum = s.snum
    -> INNER JOIN customers c ON o.cnum = c.cnum;
+------+----------+---------+
| onum | cname    | sname   |
+------+----------+---------+
| 3001 | Cisneros | Rifkin  |
| 3003 | Hoffman  | Peel    |
| 3002 | Pereira  | Motika  |
| 3005 | Liu      | Serres  |
| 3006 | Cisneros | Rifkin  |
| 3009 | Giovanni | Axelrod |
| 3007 | Grass    | Serres  |
| 3008 | Clemens  | Peel    |
| 3010 | Grass    | Serres  |
| 3011 | Clemens  | Peel    |
+------+----------+---------+
10 rows in set (0.010 sec)
```

3 Write a query that produces all customers serviced by salespeople with a commission above 12%. Display the customer's name, the salesperson's name, and the salesperson's rate of commission.

```
kd2_vaibhav_96218>SELECT cname, sname, comm FROM customers c
    -> INNER JOIN salespeople s ON c.snum = s.snum
    -> WHERE comm > 0.12;
+----------+--------+------+
| cname    | sname  | comm |
+----------+--------+------+
| Liu      | Serres | 0.13 |
| Grass    | Serres | 0.13 |
| Cisneros | Rifkin | 0.15 |
+----------+--------+------+
3 rows in set (0.012 sec)
```

4. Write a query that calculates the commission earned by each salesperson for orders placed by customers with a rating above 100.

```
kd2_vaibhav_96218>SELECT o.onum, s.comm, o.amt*s.comm FROM orders o
    -> INNER JOIN salespeople s ON o.snum = s.snum
    -> INNER JOIN customers c ON o.cnum = c.cnum
    -> WHERE c.rating > 100;
+------+------+--------------+
| onum | comm | o.amt*s.comm |
+------+------+--------------+
| 3010 | 0.13 |      40.2935 |
| 3007 | 0.13 |       9.8475 |
| 3005 | 0.13 |     670.8585 |
| 3006 | 0.15 |     164.7240 |
| 3001 | 0.15 |       2.8035 |
| 3009 | 0.10 |     171.3230 |
+------+------+--------------+
6 rows in set (0.015 sec)
```

5 Write a query that produces all pairs of salespeople who are living in the same city. Exclude combinations of salespeople with themselves as well as duplicate rows with the order reversed .

```
kd2_vaibhav_96218>SELECT s1.sname , s2.sname, s1.city FROM salespeople s1
    -> INNER JOIN salespeople s2
    -> ON s1.city = s2.city
    -> WHERE s1.sname != s2.sname
    -> AND s1.sname > s2.sname;
+-------+--------+--------+
| sname | sname  | city   |
+-------+--------+--------+
| Peel  | Motika | London |
+-------+--------+--------+
1 row in set (0.051 sec)
```