

Use appropriate joins to solve following queries.

Note: To solve below queries, use “sales” database.

1. Write a query that lists each order number followed by the name of the customer who made the order.

```
KD2-Vishwajeet-96150>select o.onum, c.cname from customers c
-> inner join orders o on o.cnum=c.cnum;
+-----+-----+
| onum | cname |
+-----+-----+
| 3001 | Cisneros |
| 3003 | Hoffman |
| 3002 | Pereira |
| 3005 | Liu |
| 3006 | Cisneros |
| 3009 | Giovanni |
| 3007 | Grass |
| 3008 | Clemens |
| 3010 | Grass |
| 3011 | Clemens |
+-----+-----+
10 rows in set (0.006 sec)

KD2-Vishwajeet-96150>=|
```

2. Write a query that gives the names of both the salesperson and the customer for each order along with the order number.

```
KD2-Vishwajeet-96150>select o.onum , s.sname, c.cname from orders o inner join customers c on o.cnum=c.cnum
-> inner join salespeople s on o.snum=s.snum;
+-----+-----+-----+
| onum | sname | cname |
+-----+-----+-----+
| 3003 | Peel | Hoffman |
| 3009 | Axelrod | Giovanni |
| 3005 | Serres | Liu |
| 3010 | Serres | Grass |
| 3007 | Serres | Grass |
| 3011 | Peel | Clemens |
| 3008 | Peel | Clemens |
| 3006 | Rifkin | Cisneros |
| 3001 | Rifkin | Cisneros |
| 3002 | Motika | Pereira |
+-----+-----+-----+
10 rows in set (0.016 sec)

KD2-Vishwajeet-96150>
```

3. Write a query that produces all customers serviced by salespeople with a commission above 12%. Display the customer's name, the salesperson's name, and the salesperson's rate of commission.

```
KD2-Vishwajeet-96150>Select c.cname, s.sname, s.comm from salespeople s inner join
-> customers c on c.snum=s.snum
-> where s.comm >.12;
+-----+-----+-----+
| cname | sname | comm |
+-----+-----+-----+
| Liu   | Serres | 0.13 |
| Grass | Serres | 0.13 |
| Cisneros | Rifkin | 0.15 |
+-----+-----+-----+
3 rows in set (0.011 sec)

KD2-Vishwajeet-96150>
```

4. Write a query that calculates the commission earned by each salesperson for orders placed by customers with a rating above 100.

```
KD2-Vishwajeet-96150>select o.onum, s.comm, s.comm * o.amt
-> from orders o inner join salespeople s
-> on o.snum = s.snum
-> inner join customers c
-> on c.cnum=o.cnum
-> where rating >100;
+-----+-----+-----+
| onum | comm | s.comm * o.amt |
+-----+-----+-----+
| 3010 | 0.13 | 40.2935 |
| 3007 | 0.13 | 9.8475 |
| 3005 | 0.13 | 670.8585 |
| 3006 | 0.15 | 164.7240 |
| 3001 | 0.15 | 2.8035 |
| 3009 | 0.10 | 171.3230 |
+-----+-----+-----+
6 rows in set (0.025 sec)

KD2-Vishwajeet-96150>
```

5. Write a query that produces all pairs of salespeople who are living in the same city. Exclude combinations of salespeople with themselves as well as duplicate rows with the order reversed.

```
KD2-Vishwajeet-96150>select s.sname,m.sname from salespeople s
->     inner join salespeople m
->     on s.city=m.city
->     where s.snum < m.snum;
+-----+-----+
| sname | sname |
+-----+-----+
| Peel  | Motika |
+-----+-----+
1 row in set (0.008 sec)
```